

**6006EH****Specifications**

|                         |                                 |
|-------------------------|---------------------------------|
| Weight                  | 1,670 lbs (757 kgs)             |
| Length                  | 13' 1" (3.98 m)                 |
| Width                   | 1' 9.75" (.55 m)                |
| Height                  | 2' 11.88" (.90 m)               |
| Base Plate Dimensions   | 16.75" x 16.75" (.43 m x .43 m) |
| Boom Down               | TBD                             |
| Boom Retract            | TBD                             |
| Full 360° Boom Rotation | 66-78 seconds                   |

\*Truck must be equipped with appropriate outriggers, minimum 75-amp alternator, minimum 100-minute reserve capacity H.D. maintenance-type battery with 500 cold cranking amp capacity.

**Lifting Capacities**

| Reach       | Manual/Power Boom Extension | 6006EH Load Chart                                                                                                                                                             |  |
|-------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 3' (.9 m)   | 6,000 lbs (2,722 kgs)       | <p><b>6006EH</b></p> <p>NOTE: WEIGHT OF LOAD HANDLING DEVICES ARE PART OF THE LOAD AND MUST BE DEDUCTED FROM THE CAPACITY</p> <p>ATTENTION! OVER 3000 LBS USE DOUBLE LINE</p> |  |
| 4' (1.22 m) | 6,000 lbs (2,722 kgs)       |                                                                                                                                                                               |  |
| 5' (1.5 m)  | 6,000 lbs (2,722 kgs)       |                                                                                                                                                                               |  |
| 6' (1.8 m)  | 6,000 lbs (2,722 kgs)       |                                                                                                                                                                               |  |
| 7' (2.1 m)  | 5,140 lbs (2,332 kgs)       |                                                                                                                                                                               |  |
| 8' (2.4 m)  | 4,500 lbs (2,041 kgs)       |                                                                                                                                                                               |  |
| 9' (2.7 m)  | 4,000 lbs (1,814 kgs)       |                                                                                                                                                                               |  |
| 10' (3.0 m) | 3,600 lbs (1,633 kgs)       |                                                                                                                                                                               |  |
| 11' (3.3 m) | 3,270 lbs (1,483 kgs)       |                                                                                                                                                                               |  |
| 12' (3.7 m) | 3,000 lbs (1,361 kgs)       |                                                                                                                                                                               |  |
| 13' (3.9 m) | 2,770 lbs (1,256 kgs)       |                                                                                                                                                                               |  |
| 14' (4.3 m) | 2,570 lbs (1,166 kgs)       |                                                                                                                                                                               |  |
| 15' (4.6 m) | 2,400 lbs (1,089 kgs)       |                                                                                                                                                                               |  |
| 16' (4.9 m) | 2,250 lbs (1,021 kgs)       |                                                                                                                                                                               |  |
| 17' (5.2 m) | 2,120 lbs (962 kgs)         |                                                                                                                                                                               |  |
| 18' (5.5 m) | 2,000 lbs (907 kgs)         |                                                                                                                                                                               |  |
| 19' (5.8 m) | 1,895 lbs (860 kgs)         |                                                                                                                                                                               |  |
| 20' (6.1 m) | 1,800 lbs (816 kgs)         |                                                                                                                                                                               |  |



Auto Crane Company / 4707 N. Mingo Rd. Tulsa, OK 74117  
918-836-0463 / [AutoCrane.com](http://AutoCrane.com)

