



HT-30



COMANSA HT-30

- 30 M RADIUS
- 2,2 M TAIL SWING
- MAX LOAD: 1.000/4.000 KG
- 22 M UNDER HOOK
- BASE OPTIONS: 3,8/4,3 M
- TOWABLE FULLY BALLASTED
- SUPER-RAPID ERECTION
- FAST, SAFE DISTRIBUTION



COMANSA



TRANSPORT



Thanks to the folding counterweight system, the weight is evenly transmitted to the axles to permit transport of the crane **FULLY BALLASTED**.

SELF-LEVELLING



No external equipment necessary; the HT-30 is quickly and safely levelled using the central hydraulic system of the crane.

SELF-BALLASTING

When not possible to transport the crane fully ballasted, the ballast blocks can be self-loaded, using the main hoist of the crane and the tower folding system, to pick up or set down the standard blocks at up to 5 m radius and through 360°.

HT-30





INSTALLATION

All-hydraulic erection of the HT-30 is simple, fast and in any direction, unfolding the jib once the mast is fully extended. All movements protected by automatic safety cut-outs.





HT-30 WORKS WITH FOLDED JIB

The HT-30 can remain out of service with the jib folded, or even work with a maximum load up to 3.600 Kg. at 12,5 m.



CONTROL SYSTEMS

The ample control cupboard is completely numbered and equipped with interchangeable components from world-class suppliers. The slewing control system is capable of varying the tension to both the motor and the eddy-current brake, thus automatically ensuring smooth, loadswing-free slewing, with the corresponding increase in productivity, as well as a substantial increase in motor life.



CONVERTIBLE BASE

Optionally, the HT-30, according to site conditions, can be erected without base ballast, with 4,3 m between screw jacks, or, with base ballast, only 3,8 m, in both cases with a tail swing of just 2,2 m.



AUTOMATIC CHANGE SR/DR

Changeover from two falls (SR) to four falls (DR) or vice versa, is automatic, from the control console, with the hook/trolley *at any radius*.



Construcciones Metálicas COMANSA S.A.

Polígono Industrial de Areta

E-31620 HUARTE - PAMPLONA (SPAIN)

Tel: 34 948 335 020 - Fax: 34 948 330 810

e-mail: export@comansa.com

www.comansa.com

