


340.00




EFFER
340.00

Standard



Optional



3S

	13200	7870	5270	3920	3140	kg
	2.27	4.06	5.97	7.97	10.04	m
3615 kg	29100	17350	11615	8640	6920	lb
7965 lb	7'5"	13'3"	19'7"	26'1"	32'11"	ft

4S

	12800	7520	5020	3710	2860	2380	kg
	2.27	4.16	6.06	8.06	10.14	12.31	m
3810 kg	28215	16575	11065	8175	6305	5245	lb
8395 lb	7'5"	13'7"	19'10"	26'5"	33'3"	40'4"	ft

5S

	12650	7250	4820	3490	2680	2160	1790	kg
	2.27	4.30	6.20	8.20	10.28	12.45	14.68	m
4005 kg	27885	15980	10625	7690	5905	4760	3945	lb
8825 lb	7'5"	14'1"	20'4"	26'10"	33'8"	40'10"	48'1"	ft

4S+JIB 3S

	1270	1110	1000	900	kg
	15.17	16.77	18.43	20.12	m
4595 kg	2795	2445	2200	1980	lb
10130 lb	49'9"	55'	60'5"	66'	ft

	1860	1475	1200	1000	kg
	5.85	7.45	9.14	10.83	m
	4100	3250	2645	2200	lb
	19'2"	24'5"	29'11"	35'6"	ft

4S+JIB 4S

	1200	1030	900	810	735	kg
	15.25	16.85	18.51	20.20	21.90	m
4680 kg	2645	2270	1980	1785	1620	lb
10315 lb	50'	55'3"	60'8"	66'3"	71'10"	ft

	1740	1365	1090	940	810	kg
	5.93	7.53	9.22	10.91	12.60	m
	3835	3005	2400	2070	1785	lb
	19'5"	24'8"	30'2"	35'9"	41'4"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
3S	32,27	407	2450	2500	1230	6400	26
4S	31,51	407	2450	2500	1230	6400	26
5S	31,44	407	2450	2550	1230	6400	26
4S+JIB 3S	31,51	407	2550	2550	1320	6400	26
4S+JIB 4S	31,51	407	2550	2550	1320	6400	26

MODEL							
	lb*ft	(°)	in	in	in	in	lb
3S	233490	407	96	98	48	252	57300
4S	227990	407	96	98	48	252	57300
5S	227480	407	96	100	48	252	57300
4S+JIB 3S	227990	407	100	100	52	252	57300
4S+JIB 4S	227990	407	100	100	52	252	57300