

Loaded Boom Angle	PRELIMINARY JIB CHART @ 75%							
	TRACKS EXTENDED FULLY EXTENDED BOOM							
	Firm level Ground 360° Rating							
	fixed jib		telescopic jib					
°	26 ft	8 m	°	26 ft	8 m	°	46 ft	14 m
79°	5,600 lbs.	2,55 t	79°	5,400 lbs	2,46 t			
77°	5,300 lbs.	2,41 t	77°	5,100 lbs	2,32 t	79°	3,400 lbs	1,55 t
75°	4,960 lbs.	2,26 t	75°	4,700 lbs	2,14 t	77°	3,300 lbs	1,50 t
72°	4,490 lbs.	2,04 t	72°	4,230 lbs	1,92 t	76°	3,200 lbs	1,46 t
70°	4,080 lbs.	1,86 t	70°	3,820 lbs	1,74 t	74°	3,040 lbs	1,38 t
67°	3,710 lbs.	1,69 t	67°	3,440 lbs	1,57 t	72°	2,800 lbs	1,28 t
65°	3,380 lbs.	1,54 t	65°	3,100 lbs	1,41 t	69°	2,670 lbs	1,22 t
62°	3,080 lbs.	1,40 t	62°	2,810 lbs	1,28 t	67°	2,480 lbs	1,13 t
59°	2,820 lbs.	1,28 t	59°	2,540 lbs	1,16 t	65°	2,310 lbs	1,05 t
56°	2,470 lbs.	1,13 t	56°	2,180 lbs	0,99 t	63°	2,110 lbs	0,96 t
53°	2,070 lbs.	0,94 t	53°	1,770 lbs	0,81 t	60°	1,940 lbs	0,89 t
50°	1,720 lbs.	0,79 t	50°	1,430 lbs	0,65 t	58°	1,770 lbs	0,81 t
46°	1,420 lbs.	0,65 t	46°	1,130 lbs	0,52 t	55°	1,580 lbs	0,72 t
42°	1,160 lbs.	0,53 t	42°	870 lbs	0,40 t	52°	1,320 lbs	0,60 t
38°	930 lbs.	0,43 t	38°	640 lbs	0,30 t	49°	1,080 lbs	0,50 t
Information: Load ratings above the heavy line are Structurally limited capacities. Load ratings below the heavy line are stability limited capacities and do not exceed 75% of tipping.						46°	870 lbs	0,40 t
						43°	690 lbs	0,32 t

Meets ANSI/ASME B 30.5 and DIN 15018 DIN 15019 Requirements



Crawler crane FFC 25T

Dimensions

