



# Self-Propelled Scissor Lifts

## GS™ -2032, GS-2632 & GS-3232

### Specifications

| Models                                  | GS-2032     |        | GS-2632     |        | GS-3232      |         |
|-----------------------------------------|-------------|--------|-------------|--------|--------------|---------|
| Measurements                            | US          | Metric | US          | Metric | US           | Metric  |
| Working height maximum*                 | 26 ft       | 8.10 m | 32 ft       | 9.92 m | 38 ft        | 11.75 m |
| <b>A</b> Platform height maximum        | 20 ft       | 6.10 m | 26 ft       | 7.92 m | 32 ft        | 9.75 m  |
| <b>B</b> Platform height stowed         | 3 ft 4.5 in | 1.03 m | 3 ft 9.5 in | 1.16 m | 4 ft 2.75 in | 1.29 m  |
| <b>C</b> Platform length - outside      | 7 ft 5 in   | 2.26 m | 7 ft 5 in   | 2.26 m | 7 ft 5 in    | 2.26 m  |
| extended                                | 10 ft 5 in  | 3.18 m | 10 ft 5 in  | 3.18 m | 10 ft 5 in   | 3.18 m  |
| Slide-out platform extension deck       | 3 ft        | .91 m  | 3 ft        | .91 m  | 3 ft         | .91 m   |
| <b>D</b> Platform width - outside       | 2 ft 8 in   | .81 m  | 2 ft 8 in   | .81 m  | 2 ft 8 in    | .81 m   |
| Guardrail height: fixed rails           | 3 ft 3 in   | .99 m  | —           | —      | —            | —       |
| fold down rails (CE)                    | 3 ft 7 in   | 1.10 m | 3 ft 7 in   | 1.10 m | 3 ft 7 in    | 1.10 m  |
| Toeboard height                         | 6 in        | .15 m  | 6 in        | .15 m  | 6 in         | .15 m   |
| <b>E</b> Height - stowed                |             |        |             |        |              |         |
| fixed rails                             | 6 ft 8 in   | 2.03 m | —           | —      | —            | —       |
| folding guardrails (CE)                 | 7 ft        | 2.13 m | 7 ft 5 in   | 2.26 m | 8 ft         | 2.43 m  |
| rails folded                            | 5 ft 9 in   | 1.75 m | 6 ft 3 in   | 1.91 m | 6 ft 8 in    | 2.03 m  |
| <b>F</b> Length - stowed                | 8 ft        | 2.44 m | 8 ft        | 2.44 m | 8 ft         | 2.43 m  |
| Length - extended                       | 10 ft 11 in | 3.33 m | 10 ft 11 in | 3.33 m | 10 ft 11 in  | 3.33 m  |
| <b>G</b> Width                          | 2 ft 8 in   | .81 m  | 2 ft 8 in   | .81 m  | 2 ft 8 in    | .81 m   |
| <b>H</b> Wheelbase                      | 6 ft 1 in   | 1.85 m | 6 ft 1 in   | 1.85 m | 6 ft 1 in    | 1.85 m  |
| <b>I</b> Ground clearance - center      | 3.5 in      | .09 m  | 3.5 in      | .09 m  | 3.5 in       | .09 m   |
| <b>J</b> - with pothole guards deployed | .75 in      | .02 m  | .75 in      | .02 m  | .75 in       | .02 m   |

### Productivity

|                              |                  |                 |                  |                 |                  |                 |
|------------------------------|------------------|-----------------|------------------|-----------------|------------------|-----------------|
| Maximum platform occupancy** | 2                | 2               | 2                | 2               | 2                | 2               |
| Lift capacity                | 800 lbs          | 363 kg          | 500 lbs          | 227 kg          | 500 lbs          | 227 kg          |
| Extension deck capacity      | 250 lbs          | 113 kg          | 250 lbs          | 113 kg          | 250 lbs          | 113 kg          |
| Drive height                 | full height      |                 | full height      |                 | 22 ft            | 6.71 m          |
| Drive speed - stowed         | 2.2 mph          | 3.5 km/h        | 2.2 mph          | 3.5 km/h        | 2.2 mph          | 3.5 km/h        |
| Drive speed - raised         | 0.5 mph          | 0.8 km/h        | 0.5 mph          | 0.8 km/h        | 0.5 mph          | 0.8 km/h        |
| Gradeability - stowed***     | 30%              |                 | 25%              |                 | 25%              |                 |
| Maximum outrigger leveling:  |                  |                 |                  |                 |                  |                 |
| front to back                | —                | —               | —                | —               | 3°               |                 |
| Maximum outrigger leveling:  |                  |                 |                  |                 |                  |                 |
| side to side                 | —                | —               | —                | —               | 5°               |                 |
| Turning radius - inside      | zero             | zero            | zero             | zero            | zero             | zero            |
| Turning radius - outside     | 7 ft             | 2.13 m          | 7 ft             | 2.13 m          | 7 ft             | 2.13 m          |
| Raise / lower speed          | 30 / 34 sec      | 30 / 34 sec     | 30 / 40 sec      | 30 / 40 sec     | 57 / 40 sec      | 57 / 40 sec     |
| Controls                     | proportional     |                 | proportional     |                 |                  |                 |
| Drive                        | dual front wheel |                 | dual front wheel |                 | dual front wheel |                 |
| Multiple disc brakes         | dual rear wheel  |                 | dual rear wheel  |                 | dual rear wheel  |                 |
| Tires - solid non-marking    | 15 x 5 x 11 in   | 38 x 13 x 28 cm | 15 x 5 x 11 in   | 38 x 13 x 28 cm | 15 x 5 x 11 in   | 38 x 13 x 28 cm |

### Power

|                           |                                       |        |                                       |        |                                       |        |
|---------------------------|---------------------------------------|--------|---------------------------------------|--------|---------------------------------------|--------|
| Power source              | 24 V DC<br>(four 6V 225 Ah batteries) |        | 24 V DC<br>(four 6V 225 Ah batteries) |        | 24 V DC<br>(four 6V 225 Ah batteries) |        |
| Hydraulic system capacity | 3.75 gal                              | 14.2 L | 3.75 gal                              | 14.2 L | 3.75 gal                              | 14.2 L |

### Weight\*\*\*\*

|           |           |          |           |          |           |          |
|-----------|-----------|----------|-----------|----------|-----------|----------|
| ANSI, CSA | 3,574 lbs | 1,621 kg | 4,413 lbs | 2,002 kg | 5,185 lbs | 2,352 kg |
| CE, AUS   | 4,024 lbs | 1,825 kg | 4,313 lbs | 1,956 kg | 5,185 lbs | 2,352 kg |

### Standards Compliance

 ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* CE/AUS markets: GS-2632 and GS-3232 indoor use only. GS-2032 outdoor use-one person maximum occupancy.

\*\*\* Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

\*\*\*\* Weight will vary depending on options and/or country standards.



# Self-Propelled Scissor Lifts

GS™-2032, GS-2632 & GS-3232

## Features

### Standard Features

#### Measurements

##### GS-2032

- 26 ft (8.10 m) working height
- Up to 800 lbs (363 kg) lift capacity

##### GS-2632

- 32 ft (9.92 m) working height
- Up to 500 lbs (227 kg) lift capacity

##### GS-3232

- 38 ft (11.75 m) working height
- Up to 500 lbs (227 kg) lift capacity

#### Productivity

- 89 x 32 in (2.26 x .81 m) steel platform
- 36 in (.91 m) extension deck
- Fixed rail with chain entry gate (standard GS™-2032)
- Folding rails with half-height swing gate (standard on all CE, GS™-2632, GS™-3232)
- Automatic leveling outriggers (GS™-3232 only)
- Dual front wheel drive
- Universal 20 amp smart charger
- Rear recessed charger receptacle
- SmartLink™ - 2 speed lift and proportional drive
- Platform control with battery charge indicator and diagnostic display
- On-board diagnostic system
- AC power to platform
- Lanyard attachment points
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Rear wheel multiple disc brakes
- Front wheel hydraulic dynamic braking
- Brake release
- Swing-out component trays
- Solid non-marking tires
- Pothole guards
- Tilt level sensor with audible alarm
- Descent alarm
- Electronic horn
- Hour meter

#### Power

- 24 V DC (four 6 V 225 Ah batteries)

### Options & Accessories

#### Productivity Options

- Folding rails with half-height swing gate (GS™-2032)
- Platform swing gate, half-height (GS™-2032)
- Air line to platform
- Dual flashing beacons
- Motion alarm
- Automotive horn
- Biodegradable hydraulic fluid

#### Power Options

- Power Inverter (120 V/60 Hz)
- EE rating
- AGM maintenance-free batteries



### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

### Distributed By:

Effective Date: January, 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2014 Terex Corporation.