



Custom Built Marine & Offshore Cranes

SPECIFICATIONS

HLRM 80-3S

OVERALL DIMENSIONS DIMENSIONI DI INGOMBRO

1" (inch) = 25,40 mm

(*) Variable dimension
Quota variabile

TECHNICAL DATA DATI TECNICI	
Hydraulic extensions	Sfili idraulici
Net lifting moment	Momento nominale
Slewing torque	Coppia di rotazione
Slewing angle (continuous)	Angolo di rotazione (continuo)
Pump capacity	Portata della pompa
Max working pressure	Pressione massima di esercizio
Empty weight of the crane	Peso gru a vuoto
Recommended amount of oil	Quantità di olio consigliata
Slewing speed	Velocità di rotazione
Main boom liftin time	Tempo di sollevamento 1° braccio
Secondary boom articulation time	Tempo di articolazione 2° braccio
Boom element extension time	Tempo di estensione sfili braccio

OPTIONALS A RICHIESTA	
5000 kg direct pull winch rope Ø18	Argano da 5000 kg in tiro diretto fune Ø18
Winch limit switch	Finecorsa argano
Slewing limit switch (450°)	Finecorsa rotazione (450°)
Cabin with windows and wipers	Cabina con vetri e tergicristalli
Size 7 electrohydraulic power pack (45 kW)	Taglia 7 centralina elettroidraulica (45 kW)
Control panel out of the crane	Comandi distributore fuori macchina



Custom Built Marine & Offshore Cranes

HLRM 80-3S

WORKING DIAGRAM
(ONLY FOR USE WITH HOOK - SEA STATE - 0 - OR HARBOUR CONDITION)

I dati contenuti in questa scheda sono puramente indicativi. • The technical data contained in this card are only indicative.

