MODEL 1000JBT-RATED LIFTING CAPACITIES IN POUNDS

	OAD	444		BOOM L	ENGTH I	N FEET				
RADIUS		22.6	28	34	40	46	52	56		
T	5	20000							ļ	
F	10	12000	11500	10750	10000	9000	-7500			
F	15	8200	8000	7600	7200	6800	6400	5800		
F	20	5900	5800	5600	5400	5300	5200	5000	ı	
١	25	3.00	4200	4200	4200	4100	4000	3900		
	30			3200	3100	3100	3000	3000		
V	35				2600	2500	2500	2500		
	40		R THE R. P. LEWIS CO.			2100	2100	2100		
	45					1700	1700	1700		
	50						1400	1400		
	5							1200		

PERMISSIBLE LINE PULL

NUMBER PARTS LINE	9/16" DIA. (200') 6X37 IWR IPS CLASS	9/16" DIA. (200') DYFORM 18 HSLR
SINGLE	8400 LBS.	7400 LBS.
TWO	16800 LBS.	14800 LBS.
THREE	20000 LBS.	20000 LBS.

DO NOT OPERATE THIS CRANE UNLESS YOU KNOW THE DIAMETER AND TYPE ROPE CURRENTLY INSTALLED ON THE CRANE. DO NOT EXCEED PERMISSIBLE LINE PULL OF ROPE INSTALLED ON THIS CRANE. DO NOT USE 3 PART LINE WITH BOOM LENGTH OVER 34 FEET.

702830