



KATO

メインブーム【通常伸縮】 定格総荷重表

メインブーム(アウトリガ9.4m)

作業半径 (m)	13.6mブーム						18.15mブーム						22.7mブーム						31.8mブーム					
	性能区分						性能区分						性能区分						性能区分					
	A1	B1	C1	D1	E1	F1	A1	B1	C1	D1	E1	F1	A1	B1	C1	D1	E1	F1	A1	B1	C1	D1	E1	F1
3.0	150.0	150.0	150.0	150.0	150.0	150.0																		
3.5	150.0	150.0	150.0	150.0	150.0	150.0	120.0	120.0	120.0	120.0	120.0	120.0												
4.0	150.0	150.0	150.0	150.0	150.0	146.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0						
4.5	150.0	150.0	150.0	145.3	137.8	131.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0						
5.0	150.0	149.3	140.1	133.2	125.7	116.7	120.0	120.0	120.0	120.0	120.0	115.0	120.0	120.0	120.0	120.0	120.0	113.7	70.0	70.0	70.0	70.0	70.0	70.0
6.0	136.9	127.9	119.9	113.9	102.1	94.6	120.0	120.0	118.6	112.4	100.4	92.9	120.0	120.0	117.6	111.1	99.1	91.6	70.0	70.0	70.0	70.0	70.0	70.0
7.0	119.4	111.4	104.3	95.5	85.2	78.8	118.0	110.0	103.0	93.8	83.6	77.1	117.0	109.0	102.0	92.6	82.3	75.9	70.0	70.0	70.0	70.0	70.0	70.0
8.0	105.4	98.3	90.6	81.6	72.6	67.0	104.1	96.9	88.9	79.9	70.9	65.3	103.0	95.9	87.7	78.7	69.7	64.1	70.0	70.0	70.0	70.0	70.0	66.7
9.0	94.1	87.7	78.8	70.8	62.8	57.1	92.7	86.2	77.1	69.1	61.1	54.9	91.7	85.2	75.9	67.9	59.9	53.3	70.0	70.0	70.0	70.0	62.5	56.5
10.0	84.8	78.8	69.4	62.2	55.0	45.6	83.3	77.2	67.7	60.5	53.3	43.6	82.3	76.0	66.4	59.3	52.1	42.1	70.0	70.0	69.0	61.8	54.6	45.2
11.0	76.9	70.4	61.7	55.2	46.3	37.3	75.4	68.7	60.0	53.4	44.4	35.2	74.4	67.4	58.7	52.2	43.0	33.7	70.0	69.9	61.2	54.7	45.8	36.8
12.0							68.7	61.5	53.5	47.5	37.2	28.7	67.6	60.3	52.3	46.3	35.9	27.3	65.8	62.7	54.8	48.8	38.6	30.1
14.0							57.7	50.3	43.5	36.9	27.0	19.9	56.5	49.1	42.2	35.6	25.7	18.6	56.6	51.5	44.6	38.0	28.2	21.2
16.0							41.6	41.6	36.0	28.7	20.2	14.3	47.2	40.7	34.7	27.5	18.8	13.0	49.5	43.0	37.1	29.7	21.2	15.4
18.0													40.0	34.2	28.5	21.7	14.1	9.0	42.2	36.5	30.7	23.8	16.3	11.4
20.0													34.3	29.1	23.4	17.3	10.7		36.4	31.3	25.4	19.3	12.7	8.3
22.0																			31.7	27.0	21.3	15.8	9.9	5.5
24.0																			27.8	23.4	18.0	13.0	7.5	3.4
26.0																			24.4	20.5	15.4	10.8	5.4	
28.0																			21.6	17.9	13.2	8.9	3.6	
30.0																								
32.0																								
34.0																								
36.0																								
38.0																								
40.0																								
42.0																								
44.0																								
46.0																								
掛数	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	7	7	7	7	7	7
危険角度(°)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	33
フック種類	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)

メインブーム(アウトリガ9.4m)

作業半径 (m)	40.9mブーム						45.5mブーム						50.0mブーム					
	性能区分						性能区分						性能区分					
	A1	B1	C1	D1	E1	F1	A1	B1	C1	D1	E1	F1	A1	B1	C1	D1	E1	F1
3.0																		
3.5																		
4.0																		
4.5																		
5.0																		
6.0																		
7.0	60.0	60.0	60.0	60.0	60.0	60.0												
8.0	60.0	60.0	60.0	60.0	60.0	60.0	47.0	47.0	47.0	47.0	47.0	47.0	35.0	35.0	35.0	35.0	35.0	35.0
9.0	60.0	60.0	60.0	60.0	60.0	52.9	47.0	47.0	47.0	47.0	47.0	47.0	35.0	35.0	35.0	35.0	35.0	35.0
10.0	60.0	60.0	60.0	60.0	55.4	43.8	47.0	47.0	47.0	47.0	47.0	42.3	35.0	35.0	35.0	35.0	35.0	35.0
11.0	60.0	60.0	60.0	55.8	47.1	36.8	47.0	47.0	47.0	47.0	46.4	35.8	35.0	35.0	35.0	35.0	35.0	35.0
12.0	60.0	60.0	55.9	49.9	39.8	31.4	47.0	47.0	47.0	47.0	40.1	30.6	35.0	35.0	35.0	35.0	35.0	30.3
14.0	52.1	52.1	45.8	39.2	29.4	22.4	47.0	47.0	46.1	39.5	29.8	22.7	35.0	35.0	35.0	35.0	30.4	22.9
16.0	45.4	44.1	38.2	30.8	22.3	16.5	42.9	42.9	38.5	31.1	22.6	16.8	35.0	35.0	35.0	31.6	23.2	17.4
18.0	40.0	37.6	31.7	24.8	17.4	12.4	38.2	37.9	31.9	25.1	17.7	12.7	35.0	35.0	32.4	25.6	18.2	13.3
20.0	35.7	32.3	26.3	20.3	13.7	9.4	34.2	32.6	26.6	20.6	14.0	9.7	31.4	31.4	27.1	21.1	14.5	10.2
22.0	32.0	28.0	22.2	16.8	10.9	6.8	30.8	28.3	22.5	17.0	11.2	7.2	28.3	28.3	22.9	17.5	11.6	7.8
24.0	28.8	24.5	18.9	13.9	8.7	4.6	27.8	24.8	19.2	14.2	8.9	5.0	25.7	25.3	19.6	14.7	9.4	5.6
26.0	25.4	21.5	16.3	11.6	6.6		25.2	21.7	16.5	11.9	6.9		23.4	22.2	16.9	12.3	7.5	3.7
28.0	22.6	18.9	14.0	9.8	4.8		22.9	19.2	14.3	10.0	5.1		21.5	19.7	14.7	10.4	5.6	
30.0	20.1	16.7	12.2	8.1	3.2		20.4	16.9	12.4	8.4	3.6		19.8	17.4	12.8	8.8	4.1	
32.0	18.0	14.7	10.6	6.5			18.2	15.0	10.8	6.8			18.3	15.5	11.1	7.3		
34.0	16.1	13.1	9.2	5.1			16.3	13.3	9.4	5.4			16.8	13.7	9.7	5.9		
36.0	14.5	11.6	7.9	3.9			14.7	11.8	8.1	4.2			15.1	12.2	8.5	4.6		
38.0	12.3	10.3	6.6				13.2	10.5	6.8	3.1			13.6	10.8	7.2	3.5		
40.0							11.9	9.3	5.7				12.2	9.6	6.1			
42.0							10.7	8.3	4.7				11.0	8.5	5.0			
44.0													9.9	7.6	4.1			
46.0													8.9	6.7	3.3			
掛数	6	6	6	6	6	6	4	4	4	4	4	4	4	4	4	4	4	4
危険角度(°)	-	-	-	-	36	47	-	-	-	23	43	52	6	7	11	32	47	56
フック種類	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)



メインブーム【通常伸縮】定格総荷重表

メインブーム(アウトリガ8.4m)

作業半径 (m)	13.6mブーム						18.15mブーム						22.7mブーム						31.8mブーム					
	性能区分						性能区分						性能区分						性能区分					
	A2	B2	C2	D2	E2	F2	A2	B2	C2	D2	E2	F2	A2	B2	C2	D2	E2	F2	A2	B2	C2	D2	E2	F2
3.0	150.0	150.0	150.0	150.0	150.0	150.0																		
3.5	150.0	150.0	150.0	150.0	150.0	150.0	120.0	120.0	120.0	120.0	120.0	120.0												
4.0	150.0	150.0	150.0	150.0	150.0	146.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0						
4.5	150.0	150.0	150.0	145.3	137.8	131.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0						
5.0	150.0	149.3	140.1	133.2	125.7	116.7	120.0	120.0	120.0	120.0	120.0	115.0	120.0	120.0	120.0	120.0	120.0	113.7	70.0	70.0	70.0	70.0	70.0	70.0
6.0	136.9	127.9	119.9	113.9	102.1	94.6	120.0	120.0	118.6	112.4	100.4	92.9	120.0	120.0	117.6	111.1	99.1	91.6	70.0	70.0	70.0	70.0	70.0	70.0
7.0	119.4	111.4	104.3	95.5	85.2	78.8	118.0	110.0	103.0	93.8	83.6	77.1	117.0	109.0	102.0	92.6	82.3	75.9	70.0	70.0	70.0	70.0	70.0	70.0
8.0	105.4	98.3	90.6	81.6	72.6	61.8	104.1	96.9	88.9	79.9	70.9	59.3	103.0	95.9	87.7	78.7	69.7	57.4	70.0	70.0	70.0	70.0	70.0	56.0
9.0	94.1	87.7	78.8	70.8	59.5	46.6	92.7	86.2	77.1	69.1	57.3	44.3	91.7	85.2	75.9	67.9	55.6	42.7	70.0	70.0	70.0	70.0	58.6	44.9
10.0	84.8	78.8	69.4	62.2	47.4	36.7	83.3	77.2	67.7	60.5	45.3	34.6	82.3	76.0	66.4	59.3	43.8	33.1	70.0	70.0	69.0	61.8	46.9	36.2
11.0	76.9	70.4	61.7	53.0	38.8	29.7	75.4	68.7	60.0	51.0	36.8	27.7	74.4	67.4	58.7	49.6	35.4	26.3	70.0	69.9	61.2	52.4	38.3	29.1
12.0							68.7	61.5	53.5	42.9	30.5	22.6	67.6	60.3	52.3	41.5	29.2	21.2	65.8	62.7	54.8	44.2	31.9	23.9
14.0							57.7	50.3	41.5	31.7	21.8	15.5	56.5	49.1	40.2	30.4	20.6	14.2	56.6	51.5	42.7	32.9	23.0	16.7
16.0							41.6	41.6	32.5	24.3	16.2	10.9	47.2	40.7	31.2	23.1	14.9	9.6	49.5	43.0	33.5	25.4	17.2	11.9
18.0													40.0	34.2	24.9	17.9	10.9	5.6	42.2	36.3	27.0	20.0	13.0	8.5
20.0													34.3	28.3	20.2	14.1	7.5		36.4	30.3	22.2	16.1	10.0	5.4
22.0																			31.7	25.6	18.4	13.0	7.3	3.0
24.0																			27.8	21.9	15.4	10.6	5.0	
26.0																			24.4	18.9	13.0	8.5	3.1	
28.0																			21.6	16.4	11.0	6.5		
30.0																								
32.0																								
34.0																								
36.0																								
38.0																								
40.0																								
42.0																								
44.0																								
46.0																								
掛数	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	7	7	7	7	7	7
危険角度(°)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	24	-	-	-	-	25	41
フック種類	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)

メインブーム(アウトリガ8.4m)

作業半径 (m)	40.9mブーム						45.5mブーム						50.0mブーム					
	性能区分						性能区分						性能区分					
	A2	B2	C2	D2	E2	F2	A2	B2	C2	D2	E2	F2	A2	B2	C2	D2	E2	F2
3.0																		
3.5																		
4.0																		
4.5																		
5.0																		
6.0																		
7.0	60.0	60.0	60.0	60.0	60.0	60.0												
8.0	60.0	60.0	60.0	60.0	60.0	51.9	47.0	47.0	47.0	47.0	47.0	47.0	35.0	35.0	35.0	35.0	35.0	35.0
9.0	60.0	60.0	60.0	60.0	54.9	42.2	47.0	47.0	47.0	47.0	47.0	40.7	35.0	35.0	35.0	35.0	35.0	35.0
10.0	60.0	60.0	60.0	60.0	46.1	35.0	47.0	47.0	47.0	47.0	44.7	33.9	35.0	35.0	35.0	35.0	35.0	33.4
11.0	60.0	60.0	60.0	53.8	39.3	29.4	47.0	47.0	47.0	47.0	38.2	28.7	35.0	35.0	35.0	35.0	35.0	28.4
12.0	60.0	60.0	55.9	45.5	33.1	25.0	47.0	47.0	47.0	45.8	33.1	24.4	35.0	35.0	35.0	35.0	32.7	24.3
14.0	52.1	52.1	43.8	34.0	24.2	17.8	47.0	47.0	44.1	34.3	24.5	18.0	35.0	35.0	35.0	34.9	25.1	18.1
16.0	45.4	44.1	34.6	26.4	18.3	13.0	42.9	42.9	34.9	26.7	18.5	13.3	35.0	35.0	35.0	27.3	19.1	13.7
18.0	40.0	37.3	28.0	21.0	14.1	9.6	38.2	37.6	28.3	21.3	14.3	9.8	35.0	35.0	28.8	21.8	14.9	10.3
20.0	35.7	31.2	23.1	17.0	10.9	6.7	34.2	31.5	23.4	17.3	11.2	7.1	31.4	31.4	23.9	17.8	11.7	7.7
22.0	32.0	26.5	19.3	13.9	8.5	4.3	30.8	26.8	19.6	14.2	8.8	4.7	28.3	27.3	20.1	14.6	9.2	5.3
24.0	28.8	22.8	16.3	11.5	6.2		27.8	23.0	16.6	11.7	6.6		25.7	23.5	17.0	12.1	7.1	
26.0	25.4	19.7	13.9	9.4	4.3		25.2	20.0	14.1	9.7	4.6		23.4	20.4	14.5	10.1	5.2	
28.0	22.6	17.2	11.8	7.6			22.9	17.4	12.1	8.0	3.1		21.5	17.9	12.5	8.4	3.6	
30.0	20.1	15.1	10.1	5.9			20.4	15.3	10.3	6.3			19.8	15.7	10.7	6.8		
32.0	18.0	13.3	8.7	4.5			18.2	13.5	8.9	4.8			18.3	13.9	9.2	5.3		
34.0	16.1	11.7	7.2	3.3			16.3	11.9	7.5	3.5			16.8	12.3	7.9	4.0		
36.0	14.5	10.4	5.9				14.7	10.5	6.2				15.1	10.9	6.6			
38.0	12.3	9.2	4.8				13.2	9.4	5.0				13.6	9.7	5.4			
40.0							11.9	8.3	4.0				12.2	8.6	4.3			
42.0							10.7	7.2	3.1				11.0	7.5	3.4			
44.0													9.9	6.5				
46.0													8.9	5.6				
掛数	6	6	6	6	6	6	4	4	4	4	4	4	4	4	4	4	4	4
危険角度(°)	-	-	-	22	43	53	-	-	-	33	48	58	6	7	20	39	52	61
フック種類	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)



KATO

メインブーム【通常伸縮】定格総荷重表

メインブーム(アウトリガ7.4m)

作業半径 (m)	13.6mブーム						18.15mブーム						22.7mブーム						31.8mブーム					
	性能区分						性能区分						性能区分						性能区分					
	A3	B3	C3	D3	E3	F3	A3	B3	C3	D3	E3	F3	A3	B3	C3	D3	E3	F3	A3	B3	C3	D3	E3	F3
3.0	150.0	150.0	150.0	150.0	150.0	150.0																		
3.5	150.0	150.0	150.0	150.0	150.0	150.0	120.0	120.0	120.0	120.0	120.0	120.0												
4.0	150.0	150.0	150.0	150.0	150.0	146.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0						
4.5	150.0	150.0	150.0	145.3	137.8	131.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0						
5.0	150.0	149.3	140.1	133.2	125.7	116.7	120.0	120.0	120.0	120.0	120.0	115.0	120.0	120.0	120.0	120.0	120.0	113.7	70.0	70.0	70.0	70.0	70.0	70.0
6.0	136.9	127.9	119.9	113.9	102.1	90.8	120.0	120.0	118.6	112.4	100.4	87.9	120.0	120.0	117.6	111.1	99.1	80.9	70.0	70.0	70.0	70.0	70.0	70.0
7.0	119.4	111.4	104.3	95.5	76.7	60.1	118.0	110.0	103.0	93.8	74.3	57.8	117.0	109.0	102.0	92.6	72.5	56.0	70.0	70.0	70.0	70.0	70.0	55.2
8.0	105.4	98.3	90.6	76.2	56.4	43.7	104.1	96.9	88.9	74.1	54.3	41.6	103.0	95.9	87.7	72.6	52.8	40.1	70.0	70.0	70.0	70.0	56.0	43.3
9.0	94.1	87.7	75.9	59.8	43.8	33.5	92.7	86.2	73.9	57.9	41.9	31.6	91.7	85.2	72.6	56.5	40.5	30.2	70.0	70.0	70.0	59.4	43.4	33.1
10.0	84.8	78.8	62.2	48.7	35.2	26.6	83.3	77.2	60.4	46.9	33.4	24.8	82.3	76.0	59.1	45.6	32.1	23.5	70.0	70.0	61.8	48.3	34.8	26.1
11.0	76.9	67.8	52.3	40.6	29.0	21.5	75.4	66.0	50.5	38.9	27.3	19.8	74.4	64.8	49.3	37.7	26.1	18.6	70.0	67.3	51.8	40.2	28.6	21.1
12.0							68.7	56.7	43.1	32.9	22.6	16.0	67.6	55.5	41.9	31.7	21.4	14.9	65.8	57.9	44.3	34.0	23.8	17.2
14.0							55.0	43.5	32.5	24.3	16.0	10.7	53.9	42.4	31.4	23.2	14.9	9.6	56.1	44.6	33.6	25.4	17.1	11.8
16.0							41.6	34.7	25.5	18.6	11.7	7.2	43.2	33.6	24.4	17.5	10.5	5.8	45.2	35.6	26.4	19.5	12.6	8.1
18.0													35.5	27.2	19.3	13.4	7.4		37.4	29.1	21.2	15.3	9.3	5.3
20.0													29.7	22.5	15.5	10.3			31.5	24.3	17.3	12.1	6.9	
22.0																			26.9	20.5	14.3	9.6	4.6	
24.0																			23.3	17.4	11.8	7.7		
26.0																			20.3	14.9	9.9	6.0		
28.0																			17.8	12.9	8.2	4.2		
30.0																								
32.0																								
34.0																								
36.0																								
38.0																								
40.0																								
42.0																								
44.0																								
46.0																								
掛数	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	7	7	7	7	7	7
危険角度(°)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	14	37	-	-	-	-	36	47
フック種類	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)

メインブーム(アウトリガ7.4m)

作業半径 (m)	40.9mブーム						45.5mブーム						50.0mブーム					
	性能区分						性能区分						性能区分					
	A3	B3	C3	D3	E3	F3	A3	B3	C3	D3	E3	F3	A3	B3	C3	D3	E3	F3
3.0																		
3.5																		
4.0																		
4.5																		
5.0																		
6.0																		
7.0	60.0	60.0	60.0	60.0	60.0	50.6												
8.0	60.0	60.0	60.0	60.0	53.3	40.4	47.0	47.0	47.0	47.0	47.0	38.8	35.0	35.0	35.0	35.0	35.0	35.0
9.0	60.0	60.0	60.0	60.0	44.1	33.0	47.0	47.0	47.0	47.0	42.7	31.9	35.0	35.0	35.0	35.0	35.0	31.3
10.0	60.0	60.0	60.0	49.5	36.0	27.3	47.0	47.0	47.0	47.0	36.1	26.5	35.0	35.0	35.0	35.0	35.0	26.2
11.0	60.0	60.0	53.0	41.3	29.7	22.2	47.0	47.0	47.0	41.6	30.0	22.3	35.0	35.0	35.0	35.0	30.5	22.2
12.0	60.0	59.0	45.4	35.1	24.9	18.3	47.0	47.0	45.7	35.4	25.2	18.6	35.0	35.0	35.0	35.0	25.8	18.8
14.0	52.1	45.6	34.6	26.4	18.1	12.8	47.0	45.9	34.9	26.6	18.4	13.1	35.0	35.0	35.0	27.2	18.9	13.6
16.0	45.4	36.5	27.3	20.4	13.5	9.1	42.9	36.8	27.6	20.7	13.8	9.4	35.0	35.0	28.1	21.2	14.3	9.9
18.0	38.3	30.0	22.1	16.2	10.2	6.4	38.2	30.3	22.4	16.4	10.5	6.7	35.0	30.8	22.8	16.9	11.0	7.1
20.0	32.4	25.1	18.2	13.0	7.8		32.6	25.4	18.4	13.2	8.0		31.4	25.8	18.9	13.7	8.5	
22.0	27.8	21.3	15.1	10.5	5.8		28.0	21.5	15.4	10.7	6.1		28.3	22.0	15.8	11.1	6.5	
24.0	24.1	18.2	12.7	8.5	3.8		24.3	18.5	12.9	8.7	4.1		24.7	18.9	13.3	9.1	4.7	
26.0	21.0	15.7	10.6	6.8			21.3	15.9	10.9	7.1			21.6	16.3	11.3	7.5		
28.0	18.5	13.6	9.0	5.3			18.7	13.8	9.2	5.7			19.1	14.2	9.6	6.1		
30.0	16.4	11.9	7.6	3.8			16.6	12.1	7.8	4.2			16.9	12.4	8.1	4.7		
32.0	14.5	10.4	6.4				14.7	10.6	6.6				15.1	10.9	6.9	3.3		
34.0	13.0	9.1	5.1				13.2	9.2	5.4				13.5	9.6	5.8			
36.0	11.6	7.9	4.0				11.8	8.1	4.2				12.1	8.4	4.7			
38.0	10.4	7.0					10.6	7.1	3.2				10.8	7.4	3.6			
40.0							9.5	6.2					9.7	6.5				
42.0							8.6	5.4					8.8	5.7				
44.0													7.9	4.7				
46.0													7.1	3.9				
掛数	6	6	6	6	6	6	4	4	4	4	4	4	4	4	4	4	4	4
危険角度(°)	-	-	-	33	48	59	-	-	22	40	53	63	7	9	31	45	58	66
フック種類	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)



メインブーム【通常伸縮】定格総荷重表

メインブーム(アウトリガ6.4m)

作業半径 (m)	13.6mブーム					18.15mブーム					22.7mブーム					31.8mブーム				
	性能区分					性能区分					性能区分					性能区分				
	B4	C4	D4	E4	F4	B4	C4	D4	E4	F4	B4	C4	D4	E4	F4	B4	C4	D4	E4	F4
3.0	150.0	150.0	150.0	150.0	150.0															
3.5	150.0	150.0	150.0	150.0	150.0	120.0	120.0	120.0	120.0	120.0										
4.0	150.0	150.0	150.0	150.0	146.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0					
4.5	150.0	150.0	145.3	137.8	131.4	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	105.2					
5.0	149.3	140.1	133.2	125.7	104.6	120.0	120.0	120.0	120.0	96.9	120.0	120.0	120.0	110.7	84.4	70.0	70.0	70.0	70.0	70.0
6.0	127.9	119.9	110.4	81.8	63.5	120.0	118.6	107.9	79.4	61.1	120.0	117.6	106.1	77.6	58.5	70.0	70.0	70.0	70.0	54.3
7.0	111.4	99.6	78.5	57.5	44.0	110.0	97.5	76.5	55.5	42.0	109.0	96.0	74.9	53.9	40.4	70.0	70.0	70.0	55.7	41.4
8.0	98.3	76.6	60.0	43.4	32.7	96.9	74.8	58.1	41.5	30.8	95.6	73.4	56.8	40.1	29.4	70.0	70.0	59.6	43.0	32.3
9.0	80.0	61.6	47.9	34.1	25.2	78.3	59.9	46.1	32.3	23.5	77.0	58.6	44.9	31.1	22.2	70.0	61.3	47.5	33.7	24.9
10.0	66.7	51.1	39.3	27.6	20.0	65.1	49.4	37.6	25.9	18.4	63.9	48.2	36.5	24.7	17.2	66.3	50.7	38.9	27.2	19.6
11.0	56.9	43.2	33.0	22.7	16.2	55.2	41.6	31.4	21.1	14.5	54.1	40.5	30.2	20.0	13.4	56.4	42.8	32.5	22.3	15.7
12.0						47.7	35.6	26.5	17.4	11.6	46.6	34.5	25.4	16.3	10.5	48.8	36.7	27.6	18.5	12.7
14.0						36.8	26.9	19.5	12.1	7.4	35.7	25.8	18.4	11.0	6.0	37.8	27.9	20.5	13.1	8.4
16.0						29.3	21.0	14.8	8.5		28.2	19.9	13.7	7.4		30.2	21.9	15.6	9.4	5.1
18.0											22.8	15.6	10.2			24.7	17.5	12.1	6.7	
20.0											18.8	12.4	7.7			20.5	14.2	9.4	4.1	
22.0																17.2	11.5	7.3		
24.0																14.5	9.4	5.3		
26.0																12.4	7.7	3.5		
28.0																10.6	6.2			
30.0																				
32.0																				
34.0																				
36.0																				
38.0																				
40.0																				
42.0																				
44.0																				
46.0																				
掛数	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	7	7	7	7	7
危険角度(°)	-	-	-	-	-	-	-	-	-	13	-	-	-	30	46	-	-	22	44	55
フック種類	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	83t	83t	83t	83t	83t
フック質量(t)	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.0	1.0	1.0	1.0	1.0

(単位 : ton)

メインブーム(アウトリガ6.4m)

作業半径 (m)	40.9mブーム					45.5mブーム					50.0mブーム				
	性能区分					性能区分					性能区分				
	B4	C4	D4	E4	F4	B4	C4	D4	E4	F4	B4	C4	D4	E4	F4
3.0															
3.5															
4.0															
4.5															
5.0															
6.0															
7.0	60.0	60.0	60.0	51.5	38.4										
8.0	60.0	60.0	59.4	41.9	30.7	47.0	47.0	47.0	40.4	29.5	35.0	35.0	35.0	35.0	29.0
9.0	60.0	60.0	48.7	34.7	24.9	47.0	47.0	47.0	33.6	24.1	35.0	35.0	35.0	33.1	23.8
10.0	60.0	51.8	40.0	28.3	20.5	47.0	47.0	40.3	28.4	19.9	35.0	35.0	35.0	28.1	19.8
11.0	57.5	43.9	33.6	23.4	16.8	47.0	44.1	33.9	23.7	16.5	35.0	35.0	34.5	24.0	16.6
12.0	49.8	37.7	28.6	19.6	13.7	47.0	38.0	28.9	19.8	13.7	35.0	35.0	29.5	20.4	13.9
14.0	38.7	28.9	21.5	14.1	9.3	39.0	29.1	21.7	14.3	9.4	35.0	29.6	22.3	14.9	9.7
16.0	31.1	22.8	16.6	10.3		31.4	23.1	16.8	10.6		31.8	23.5	17.3	11.0	
18.0	25.6	18.4	13.0	7.6		25.8	18.6	13.2	7.8		26.3	19.1	13.7	8.3	
20.0	21.3	15.0	10.2	5.4		21.6	15.2	10.5	5.7		22.0	15.7	10.9	6.2	
22.0	18.0	12.4	8.1			18.2	12.6	8.3			18.7	13.0	8.7		
24.0	15.3	10.2	6.4			15.6	10.4	6.6			16.0	10.8	7.0		
26.0	13.1	8.5	4.7			13.4	8.7	5.0			13.7	9.1	5.5		
28.0	11.3	7.0	3.1			11.5	7.2	3.4			11.9	7.6	3.9		
30.0	9.7	5.7				9.9	6.0				10.3	6.3			
32.0	8.4	4.3				8.6	4.6				8.9	5.1			
34.0	7.3	3.1				7.4	3.4				7.8	3.9			
36.0	6.3					6.4					6.7				
38.0	5.2					5.4					5.8				
40.0						4.4					4.8				
42.0						3.6					3.9				
44.0											3.0				
46.0															
掛数	6	6	6	6	6	4	4	4	4	4	4	4	4	4	4
危険角度(°)	-	23	41	55	65	-	33	47	59	68	15	39	50	63	70
フック種類	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)



メインブーム【通常伸縮】 定格総荷重表

メインブーム(アウトリガ5.4m)

作業半径 (m)	13.6mブーム				18.15mブーム				22.7mブーム				31.8mブーム			
	性能区分				性能区分				性能区分				性能区分			
	C5	D5	E5	F5	C5	D5	E5	F5	C5	D5	E5	F5	C5	D5	E5	F5
3.0	150.0	150.0	150.0	150.0												
3.5	150.0	150.0	150.0	150.0	120.0	120.0	120.0	120.0								
4.0	150.0	150.0	150.0	121.0	120.0	120.0	120.0	104.6	120.0	120.0	118.9	89.4				
4.5	150.0	145.3	109.6	84.6	120.0	120.0	106.9	81.9	120.0	120.0	95.8	71.3				
5.0	140.1	114.2	83.6	64.1	120.0	111.8	81.3	61.8	120.0	110.1	79.4	58.4	70.0	70.0	70.0	53.2
6.0	97.8	76.6	55.3	41.7	95.9	74.6	53.4	39.7	94.5	73.2	51.9	38.3	70.0	70.0	53.9	39.2
7.0	72.8	56.5	40.1	29.7	71.1	54.8	38.4	28.0	69.8	53.5	37.2	26.7	70.0	56.2	39.8	29.4
8.0	57.2	44.0	30.7	22.2	55.6	42.4	29.1	20.6	54.5	41.2	28.0	19.5	56.9	43.6	30.4	21.9
9.0	46.6	35.4	24.3	17.1	45.1	33.9	22.8	15.6	44.0	32.8	21.7	14.6	46.3	35.1	24.0	16.8
10.0	38.9	29.3	19.6	13.5	37.4	27.8	18.2	12.0	36.4	26.8	17.1	11.0	38.5	28.9	19.3	13.1
11.0	33.1	24.6	16.1	10.7	31.6	23.2	14.7	9.3	30.6	22.2	13.7	8.3	32.7	24.2	15.8	10.3
12.0					27.1	19.5	12.0	7.1	26.1	18.5	11.0	6.2	28.1	20.5	13.0	8.1
14.0					20.4	14.2	8.0		19.5	13.2	7.0		21.3	15.1	8.9	
16.0					15.8	10.5			14.8	9.6			16.6	11.3	6.1	
18.0									11.5	6.9			13.1	8.5	3.6	
20.0									8.9				10.5	6.4		
22.0													8.4	4.6		
24.0													6.7			
26.0													5.3			
28.0													3.8			
30.0																
32.0																
34.0																
36.0																
38.0																
40.0																
42.0																
44.0																
46.0																
掛数	14	14	14	14	12	12	12	12	12	12	12	12	7	7	7	7
危険角度(°)	-	-	-	-	-	-	-	34	-	12	41	53	5	35	51	62
フック種類	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	150t	83t	83t	83t	83t
フック質量(t)	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.0	1.0	1.0	1.0

(単位 : ton)

メインブーム(アウトリガ5.4m)

作業半径 (m)	40.9mブーム				45.5mブーム				50.0mブーム			
	性能区分				性能区分				性能区分			
	C5	D5	E5	F5	C5	D5	E5	F5	C5	D5	E5	F5
3.0												
3.5												
4.0												
4.5												
5.0												
6.0												
7.0	60.0	56.9	39.3	28.0								
8.0	58.0	44.7	31.5	22.3	47.0	45.0	30.9	21.5	35.0	35.0	30.3	21.2
9.0	47.3	36.1	25.0	17.8	47.0	36.4	25.3	17.3	35.0	35.0	25.4	17.2
10.0	39.5	29.9	20.3	14.1	39.8	30.2	20.5	14.0	35.0	30.7	21.1	14.0
11.0	33.6	25.2	16.7	11.3	33.9	25.4	16.9	11.3	34.4	25.9	17.5	11.5
12.0	29.0	21.4	13.9	9.0	29.2	21.7	14.1	9.1	29.7	22.2	14.6	9.3
14.0	22.2	16.0	9.8		22.4	16.2	10.0		22.9	16.7	10.4	
16.0	17.4	12.2	6.9		17.7	12.4	7.1		18.1	12.8	7.5	
18.0	13.9	9.3			14.2	9.6			14.6	10.0		
20.0	11.2	7.2			11.5	7.4			11.9	7.8		
22.0	9.1	5.5			9.3	5.7			9.7	6.1		
24.0	7.4	3.9			7.6	4.2			8.0	4.7		
26.0	6.0				6.2				6.5			
28.0	4.8				5.0				5.3			
30.0	3.4				3.7				4.2			
32.0												
34.0												
36.0												
38.0												
40.0												
42.0												
44.0												
46.0												
掛数	6	6	6	6	4	4	4	4	4	4	4	4
危険角度(°)	35	48	62	70	42	52	65	72	46	57	68	74
フック種類	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t	83t
フック質量(t)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

(単位 : ton)