




KRØLL CRANES



→ 18 tonnes Max Load

F.E.M 1.001-A3/E3




HIGH TOP
TOWER CRANE

K320
18 tonnes Max



KRØLL CRANES

JIB CONFIGURATIONS










KRØLL CRANES

LOAD CHARTS

Radius	Jib Length															
	75.0 m		69.2 m		63.4 m		57.6 m		51.8 m		46.0 m		40.2 m		34.4 m	
	4 parts	2 parts	4 parts	2 parts	4 parts	2 parts	4 parts	2 parts	4 parts	2 parts	4 parts	2 parts	4 parts	2 parts	4 parts	2 parts
[m]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]
18.0	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000
19.0	16,980	9,000	17,480	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000	18,000	9,000
20.0	16,000	9,000	16,480	9,000	16,970	9,000	17,390	9,000	17,650	9,000	17,650	9,000	17,640	9,000	17,640	9,000
21.0	15,130	9,000	15,580	9,000	16,050	9,000	16,450	9,000	16,690	9,000	16,690	9,000	16,690	9,000	16,690	9,000
22.0	14,340	9,000	14,770	9,000	15,210	9,000	15,590	9,000	15,820	9,000	15,820	9,000	15,820	9,000	15,820	9,000
23.0	13,620	9,000	14,030	9,000	14,460	9,000	14,820	9,000	15,040	9,000	15,040	9,000	15,040	9,000	15,040	9,000
24.0	12,970	9,000	13,360	9,000	13,770	9,000	14,110	9,000	14,320	9,000	14,320	9,000	14,320	9,000	14,320	9,000
25.0	12,370	9,000	12,750	9,000	13,140	9,000	13,470	9,000	13,670	9,000	13,670	9,000	13,670	9,000	13,670	9,000
26.0	11,820	9,000	12,180	9,000	12,560	9,000	12,870	9,000	13,070	9,000	13,070	9,000	13,070	9,000	13,070	9,000
27.0	11,320	9,000	11,660	9,000	12,020	9,000	12,330	9,000	12,510	9,000	12,510	9,000	12,510	9,000	12,510	9,000
28.0	10,850	9,000	11,180	9,000	11,530	9,000	11,820	9,000	12,000	9,000	12,000	9,000	12,000	9,000	12,000	9,000
29.0	10,420	9,000	10,740	9,000	11,070	9,000	11,350	9,000	11,520	9,000	11,520	9,000	11,520	9,000	11,520	9,000
30.0	10,010	9,000	10,320	9,000	10,640	9,000	10,920	9,000	11,080	9,000	11,080	9,000	11,080	9,000	11,080	9,000
31.0	9,640	9,000	9,930	9,000	10,240	9,000	10,510	9,000	10,670	9,000	10,670	9,000	10,670	9,000	10,670	9,000
32.0	9,280	9,000	9,570	9,000	9,870	9,000	10,130	9,000	10,280	9,000	10,280	9,000	10,280	9,000	10,280	9,000
33.0	8,960	8,960	9,230	9,000	9,520	9,000	9,770	9,000	9,920	9,000	9,920	9,000	9,920	9,000	9,920	9,000
34.0	8,650	8,650	8,920	8,920	9,200	9,000	9,440	9,000	9,580	9,000	9,580	9,000	9,580	9,000	9,580	9,000
34.4	8,530	8,530	8,790	8,790	9,070	9,000	9,310	9,000	9,450	9,000	9,450	9,000	9,450	9,000	9,450	9,000
35.0	8,350	8,350	8,620	8,620	8,890	8,890	9,120	9,000	9,270	9,000	9,260	9,000	9,260	9,000		
36.0	8,080	8,080	8,330	8,330	8,600	8,600	8,830	8,830	8,960	8,960	8,960	8,960	8,960	8,960		
37.0	7,820	7,820	8,070	8,070	8,330	8,330	8,550	8,550	8,680	8,680	8,680	8,680	8,680	8,680		
38.0	7,580	7,580	7,820	7,820	8,070	8,070	8,280	8,280	8,410	8,410	8,410	8,410	8,410	8,410		
39.0	7,350	7,350	7,580	7,580	7,820	7,820	8,030	8,030	8,160	8,160	8,160	8,160	8,160	8,160		
40.0	7,130	7,130	7,350	7,350	7,590	7,590	7,800	7,800	7,920	7,920	7,920	7,920	7,920	7,920		
40.2	7,080	7,080	7,310	7,310	7,550	7,550	7,750	7,750	7,870	7,870	7,870	7,870	7,870	7,870		
41.0	6,920	6,920	7,140	7,140	7,370	7,370	7,570	7,570	7,690	7,690	7,690	7,690				
42.0	6,720	6,720	6,940	6,940	7,160	7,160	7,360	7,360	7,470	7,470	7,470	7,470				
43.0	6,530	6,530	6,740	6,740	6,960	6,960	7,150	7,150	7,270	7,270	7,260	7,260				
44.0	6,350	6,350	6,560	6,560	6,770	6,770	6,960	6,960	7,070	7,070	7,070	7,070				
45.0	6,180	6,180	6,380	6,380	6,590	6,590	6,770	6,770	6,880	6,880	6,880	6,880				
46.0	6,020	6,020	6,210	6,210	6,420	6,420	6,590	6,590	6,700	6,700	6,700	6,700				
47.0	5,860	5,860	6,050	6,050	6,250	6,250	6,420	6,420	6,530	6,530						
48.0	5,710	5,710	5,900	5,900	6,090	6,090	6,260	6,260	6,370	6,370						
49.0	5,570	5,570	5,750	5,750	5,940	5,940	6,110	6,110	6,210	6,210						
50.0	5,430	5,430	5,610	5,610	5,800	5,800	5,960	5,960	6,060	6,060						
51.0	5,300	5,300	5,470	5,470	5,660	5,660	5,820	5,820	5,910	5,910						
51.8	5,190	5,190	5,370	5,370	5,550	5,550	5,710	5,710	5,800	5,800						
52.0	5,170	5,170	5,340	5,340	5,520	5,520	5,680	5,680								
53.0	5,050	5,050	5,220	5,220	5,390	5,390	5,550	5,550								
54.0	4,930	4,930	5,100	5,100	5,270	5,270	5,420	5,420								
55.0	4,820	4,820	4,980	4,980	5,150	5,150	5,300	5,300								
56.0	4,710	4,710	4,870	4,870	5,040	5,040	5,180	5,180								
57.0	4,600	4,600	4,760	4,760	4,930	4,930	5,070	5,070								
57.6	4,540	4,540	4,700	4,700	4,860	4,860	5,000	5,000								
58.0	4,500	4,500	4,660	4,660	4,820	4,820										
59.0	4,400	4,400	4,560	4,560	4,710	4,710										
60.0	4,310	4,310	4,460	4,460	4,620	4,620										
61.0	4,220	4,220	4,360	4,360	4,520	4,520										
62.0	4,130	4,130	4,270	4,270	4,430	4,430										
63.0	4,040	4,040	4,190	4,190	4,340	4,340										
63.4	4,010	4,010	4,150	4,150	4,300	4,300										
64.0	3,960	3,960	4,100	4,100												
65.0	3,880	3,880	4,020	4,020												
66.0	3,800	3,800	3,940	3,940												
67.0	3,730	3,730	3,860	3,860												
68.0	3,660	3,660	3,790	3,790												
69.0	3,580	3,580	3,710	3,710												
69.2	3,570	3,570	3,700	3,700												
70.0	3,520	3,520														
71.0	3,450	3,450														
72.0	3,380	3,380														
73.0	3,320	3,320														
74.0	3,260	3,260														
75.0	3,200	3,200														



DRIVES

HOIST WINCH MOTOR 55 kW	2-PARTS		4-PARTS				
							
	Load	Max. Speed	Load	Max. Speed			
	0 - 1.0 t	128 m/min	0 - 2.0 t	64 m/min			
	1.0 - 3.5 t	72 m/min	2.0 - 7.0 t	36 m/min			
	3.5 - 9.0 t	32 m/min	7.0 - 18.0 t	16 m/min			
	HOIST DRUM			HOIST WIRE			
	CAPACITY 430 m / 6 Layers			Diameter	18 mm		
				Safety Factor	5		
				MBL	220 kN		
	TROLLEY WINCH			TROLLEY DRUM			
	MOTOR 7 kW			CAPACITY 75 m / 1 Layer			
TROLLEY SPEEDS			TROLLEY WIRE				
	0 - 18 t		0 - 70 m/min		Diameter	9 mm	
					Safety Factor	6	
					MBL	65 kN	
	SLEW DRIVE			POWER			
	Motor 2 x 7 kW			SUPPLY 400 - 480 V, 50/60 Hz			
SLEW SPEEDS				Consumption		100 kVA	
	0 - 18 t			0 - 0.6 rpm		Main Fuse	100 A
						Recommended Generator Size	250 kVA
	UNDERCARRIAGE			SUPPLY CABLE			
	Motor 4 x 7 kW			Cable Length	Cable Type		
TRAVEL SPEEDS				0 - 175 m		4 x 25 mm ²	
	0 - 18 t			0 - 25 m/min		175 - 250 m	4 x 35 mm ²
<i>All motion controls are completely stepless ensuring smooth and jerk-free operation. Creeping speed down to 0.5% of maximum speed.</i>				<i>All specifications shown in the tables are for the standard version of K320. For special requirements regarding load charts or drive speeds, please contact Krøll Cranes A/S.</i>			

F.E.M 1.001-A3/E3

EN 14439:2009-C25



All data is subject to alteration.



KRØLL CRANES

CONTACTS



KRØLL CRANES



KRØLL CRANES A/S
Nordkranvej 2
DK-3540 Lynge
Denmark

Tel: +45 48 18 74 00
Mail: info@krollcranes.dk
Web: www.krollcranes.dk



**FAELLE
FAVCO**

THE MUHIBBAH GROUP