



Capacity: Max. 200 T					NOTE: 85% LOAD CHART * Over rear. ** 8.65x6.30m outrigger base. Lifting Capacitues > 140 T require additional equipment. - Fly jib is available (+10m, +17m, +24m, +31m, +38m)						
Crane: KRUPP KMK 6200											
Boom Type: Standard											
Counterweight: 60 T											
Radius	Boom Length										
m	14.8m*	14.8m	19.6m	24.4m	29.2m	34.0m	40.5m	43.4m	47.1m	50.0m	53.0m
3.m	220. T**	187. T**									
4.m	187. T**	157. T**	149.0 T	132.0 T							
5.m	156. T**	135. T**	130.0 T	117.0 T	99.0 T	88.0 T					
6.m	130. T**	118. T**	114.0 T	104.0 T	89.5 T	79.5 T					
7.m	111. T**	102.0 T	101.0 T	94.0 T	81.5 T	72.5 T	59.6 T				
8.m	97. T**	92.0 T	90.5 T	85.0 T	74.0 T	66.0 T	51.0 T	42.0 T			
9.m	85. T**	83.0 T	81.5 T	78.0 T	68.0 T	60.0 T	47.5 T	42.0 T			
10.m	75. T**	75.5 T	74.0 T	72.0 T	63.0 T	55.5 T	41.5 T	42.0 T	41.0 T	34.0 T	27.0 T
12.m			58.5 T	59.0 T	54.5 T	47.5 T	36.0 T	40.0 T	37.0 T	33.5 T	27.0 T
14.m			47.5 T	48.0 T	47.0 T	41.0 T	32.0 T	36.0 T	34.0 T	30.5 T	26.0 T
16.m			39.0 T	39.5 T	39.0 T	7.0 T	29.0 T	32.0 T	30.5 T	28.0 T	24.0 T
18.m					33.5 T	32.5 T	335.0 T	26.5 T	29.0 T	27.5 T	25.0 T
20.m					28.5 T	27.5 T	30.5 T	24.0 T	6.5 T	25.0 T	23.0 T
22.m							23.0 T	27.5 T	22.0 T	24.0 T	22.5 T
24.m							19.6 T	23.5 T	18.8 T	22.0 T	20.0 T
26.m									20.5 T	16.9 T	18.8 T
28.m											18.3 T
30.m											17.0 T
32.m											15.1 T
34.m											15.9 T
36.m											18.1 T
38.m											16.0 T
40.m											16.9 T
42.m											16.0 T
44.m											15.0 T
46.m											14.2 T
48.m											13.3 T
											13.0 T
											11.6 T
											12.8 T
											4.2 T
											11.6 T
											12.8 T
											10.3 T
											10.6 T
											9.3 T
											9.0 T
											8.2 T
											7.9 T
											6.9 T
											7.2 T
											8.2 T
											6.2 T
											7.2 T
											5.4 T
											4.7 T