





picture 1



+/-		boom extended		axle 1		axle 2		axle 3		axle 4		axle 5		axle 6,7		axle 8		total weight	
		[m]	[ft-inch]	[t]	[lbs]	[t]	[lbs]	[t]	[lbs]	[t]	[lbs]	[t]	[lbs]	[t]	[lbs]	[t]	[lbs]	[t]	[lbs]
Ⓐ	T-16.4 (40/0/0/0/0)	3,79	12'- 5"	7,42	16350	7,65	16860	7,28	16060	7,49	16520	7,33	16150	10,22	22540	3,50	7730	50,89	112200
+	3-axle dolly			/	/	/	/	/	/	/	/	/	/	+ 2,59	+ 5700	+ 1,72	+ 3800	+ 4,31	+ 9500
+	tyres 20.5 R 25 XGC			+ 0,1	+ 220	+ 0,1	+ 220	+ 0,1	+ 220	+ 0,1	+ 220	+ 0,1	+ 220	/	/	/	/	+ 0,5	+ 1100
+	drive 10x8			+ 0,29	+ 640	+ 0,09	+ 190	0	0	0	0	0	0	/	/	/	/	+ 0,38	+ 830
+	eddy-current brake			0	0	0	0	0	0	0	0	+ 0,23	+ 510	/	/	/	/	+ 0,23	+ 510
+	second winch			+ 1,30	+ 2870	+ 1,29	+ 2840	+ 0,13	+ 280	+ 0,12	+ 270	+ 0,12	+ 270	/	/	/	/	+ 2,96	+ 6520
+	hose reel for hyd. jib			0	0	0	0	0	0	0	0	0	0	+ 0,24	+ 530	+ 0,08	+ 180	+ 0,32	+ 710
+	mech. fly jib incl. support			+ 0,11	+ 240	+ 0,11	+ 240	+ 0,08	+ 180	+ 0,08	+ 180	+ 0,08	+ 180	+ 1,0	+ 2200	+ 0,34	+ 750	+ 1,81	+ 3980
+	hyd. fly jib incl. support			+ 0,11	+ 240	+ 0,11	+ 240	+ 0,08	+ 180	+ 0,08	+ 180	+ 0,08	+ 180	+ 1,10	+ 2430	+ 0,38	+ 830	+ 1,95	+ 4290
+	hookblock 1 sheave			- 0,06	- 130	- 0,06	- 130	- 0,04	- 100	- 0,04	- 100	- 0,04	- 100	+ 0,52	+ 1150	+ 0,18	+ 390	+ 0,45	+ 990
+	hookblock 3 sheave			- 0,09	- 200	- 0,09	- 200	- 0,07	- 150	- 0,07	- 150	- 0,07	- 150	+ 0,81	+ 1790	+ 0,28	+ 610	+ 0,70	+ 1540
+	hookblock 5 sheave			- 0,12	- 260	- 0,12	- 260	- 0,09	- 200	- 0,09	- 200	- 0,09	- 200	+ 1,04	+ 2300	+ 0,36	+ 790	+ 0,90	+ 1980

LTM 1130-5.1
USA/Florida

with: * 1 persons
* tyres 16.00 R-25
* drive 10x6
* air conditioning
* pin pullers

without: *eddy-current brake
*trailer coupling
*spare wheel
*toolbox rear
*second winch or repl. CWGT
*folding jib incl. support and hose reel
*rooster sheave
*hookblock
*counterweight

Blatt 01 von 02

SKA182032-002

LWE_CAD

16.10.2008 KNY

crane weighed
182L TM1130-5-1A0Do01

subject to technical modification

125 HIT DOLLY USA
LTM 1130-5.1

SKA 182032 -002
9872 737 08