


Specifications

Lattice Boom Truck Crane

HC-218H

125 Ton (113 metric ton)



General dimensions	feet	meters
Overall width, outriggers extended, (over floats)	23' 6"	7.16
Overall width, outriggers extended, (c/l of jacks)	21' 0"	6.40
Overall width, outriggers retracted	11' 0"	3.35
Vehicle clearance circle over outside of front bumper	104' 2"	31.73
Vehicle clearance circle over outside of front bumper counterweight	105' 10"	32.25
Minimum ground clearance (at bottom of front bogie beams)	11"	.28
Counterweight tailswing (at corners)	15' 9"	4.80
Overall cab width (upper)	11' 0"	3.35
Radius of boom hinge pin	35-7/16"	.90
Height of boom hinge pin	6' 9"	1.98
Ground clearance under counterweight	5' 2"	1.58

**Axle Loads — Calculated**

Based on standard HC-218H revolving upperstructure equipped with Isuzu engine, power load lowering on front and rear load hoist drums, no counterweight, mounted on 260" (6.60 m) wheelbase, 8 x 4 drive carrier, 11' 0" (3.35 m) wide, equipped with GM 8V-92 TAC DDEC diesel engine, front center hydraulic jack, and full fuel.	Basic Machine Gross Weight			Upper facing front				Upper facing rear			
	**	lbs	kg	lbs.	kg	lbs.	kg	lbs.	kg	lbs.	kg
	A	34,340		-510		34,850		12,130		22,210	
	B	42,430		20,745		21,685		20,745		21,685	
C	76,770		20,235		56,535		32,875		43,895		
	Component Weights			Front axle		Rear axle		Front axle		Rear axle	
Adjust axle weights for adding following components.	lbs.	kg	lbs.	kg	lbs.	kg	lbs.	kg	lbs.	kg	
Upperstructure —											
Add for boomhoist rope and live mast :											
folded to rear of upper	5,590	2 536	-2,455	1 114	8,045	3 649	4,345	1 971	1,245	565	
-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	
folded forward of boomfoot	5,590	2 536	3,470	1 574	2,120	962	-1,575	-714	7,165	3 250	
Rear drum wire rope —1,000' (305 m) of 1" (25 mm) Type "P"	770	349	-115	-52	885	401	375	170	395	179	
Front drum wire rope —1,000' (305 m) of 1-1/8" (29 mm) Type "N"	1,350	612	50	23	1,300	590	410	186	940	426	
Counterweight "A"	23,000	10 433	10,850	4 922	33,580	15 232	18,365	8 330	4,635	2 102	
-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	-or-	
Counterweight "AB"	42,330	19 201	20,635	9 360	62,965	28 561	34,960	15 858	7,370	3 343	
Carrier—											
Front outrigger box, beams and jacks	7,600	3 447	4,970	2 254	2,630	1 193	4,970	2 254	2,630	1 193	
Rear outrigger box, beams and jacks	7,600	3 447	-2,220	-1 007	9,820	4 454	-2,220	-1 007	9,820	4 454	
Hydraulic pin pullers	430	195	80	36	350	159	80	36	350	159	
5 jack floats	315	143	270	122	410	186	270	122	410	186	
Bumper counterweight "A"	13,500	6 124	17,810	8 079	-4,310	-1 955	17,810	8 079	4,310	1 955	
Cummins NTC diesel engine	n/a	n.a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
Attachment—											
20' (6.10 m) tubular boom base section with hydraulic boomfoot pins — horizontal	3,380	1 533					-1,465	-665	4,845	2 198	

* A—Upper, B—Carrier C—Total



Carrier

Type

260" (6.60 m) wheelbase, 8 x 4 drive.
11' 0" (3.35 m) wide.

Frame — Main members heat treated alloy steel, triple-box construction. Machined mounting surface for turntable bearing.

Turntable bearing — Inner race, with integral internal tooth swing (ring) gear, bolted to machined surface on carrier deck.

Outriggers

Full width, double box, front and rear pin connected to carrier frame. Hydraulically operated beams and jack cylinders individually controlled from each side of carrier. Hydraulic power supplied by belt-driven hydraulic pump. Check valve at each jack cylinder.

Optional - Hydraulic outrigger box pin puller.

Front center hydraulic jack with float
Standard- Single hydraulic jack, with float, mounted at front of the carrier. Jack/float assembly required for handling 360° swing rated capacities.

Floats — Low profile, alloy steel; 30" (0.76 m) square base.

Trailer hitch — *Optional* - Includes air and electric connections at rear of carrier for trailer lights and air brakes.

Axles

Front- Tubular; bogie beam mounted tandem axles, single wheels. 105" (2.67 m) track.

Rear- Planetary type, bogie mounted tandem axles, dual wheels. 100" (2.54 m) track.

Suspension — Hendrickson bronze bushed equalizer beams with rubber bushed torque rods.

Wheels and rims — Front; disc-type. Rear; integral with planetary hubs.

Tag axle — *Optional* - Consult factory.

Tires

Single tires on front axles, dual tires on rear axles.

Standard — 14.0 x 24-J (20-ply rating) transport type tread.

Optional — Consult factory.

Brakes

Air brake system

Service — Dual circuit with modulated emergency brakes. Bendix dual circuit 8 wheel air brakes with service chambers on 4 front wheels and spring applied, air released emergency, parking, service chambers on 4 rear wheels. Air dryer standard.

Size

Rear wheels; 20-1/4" x 7" (0.51 x 0.18 m)

Front wheels; 16-1/2" x 6" (0.42 x 0.15 m)

Steering — Sheppard full integral hydraulic power with one master gear, one slave gear and one hydraulic pump for each axle. Steering mounted high on side of frame to minimize exposure to hazards. Separate master and slave for each axle eliminates transfer of steering force from entire system into one axle which could overload and damage linkage. Steering wheel is mechanically connected to axles to allow steering (with increased steering input effort) in the event of hydraulic system failure. Multiple pumps minimize possibility of total hydraulic system failure and only require increase in steering input effort sufficient to compensate for that portion of system that failed. High speed, high power system to maximize maneuverability both on the job site and on the road.

Engines

Diesel; 12/24-volt alternator, starter, pressure lubrication, hydraulic pump, dry type air cleaner, and 24 c.f.m. (.68 m³/min) air compressor.

Standard - Detroit Diesel 8V-92 TAC diesel, 8 cylinder. See page 4 for details.

Optional - Cummins. See page 4 for details.

Clutch — Lipe-Rollway 15-1/2" (0.39 m) 2 plate, dry disc.

Transmissions

Main — Eaton RTX 14708LL; ten speeds forward, three reverse.

Auxiliary — Spicer P-1241-C; 4-speed, midship mounting.

Bumper Counterweight

"A" counterweight — 13,500 lbs.
(6 124 kg).

Carrier Cab

One-man, offset, fully enclosed. Air suspension mounted bucket seat with seat belt. Noise absorbing insulation with vinyl covering, sound reduction headliner, rubber floor mat; isolated from engine compartment rubber mounted for sound level reduction. Instrument panel and dash includes speedometer, odometer, voltmeter, and gauges for fuel, engine temperature, air and oil pressures. Low air pressure warning buzzer, key locking switch, starter, tachometer, fire extinguisher, heater and defroster, 2-speed electric windshield wiper, and windshield washer.

Electrical System

12-volt, including dual sealed beam headlights, directional signals with 4-way flashing system, stop and tail lights, clearance lights, horn, lighting of instrument panel, dome light, headlight dimmer switch, and four 12-volt, group 31 batteries. Individual switches provide circuit control for hydraulic outrigger solenoid valves; one control station on each side of carrier.

Fuel Tank

One 85 gallon (322 liter) capacity tank; side mounted on carrier frame.

Standard auxiliary equipment — West Coast type rear view mirrors, lug wrench, 2-way reading bubble levels. High pressure lube fittings at all bearing points. Hand grab rails, carrier deck access ladder, back-up alarm, skid-resistant finish on carrier deck



Engine Specifications	Detroit Diesel 8V-92 TAC DDEC	Cummins NTC
Number of cylinders	8	6
Bore	4.84" (0.12 m)	5.5" (0.15 m)
Stroke	5" (0.13 m)	6" (0.15 m)
Piston Displacement	736 cu. in. (12 061 cm ³)	855 cu. in. (14 011 cm ³)
Max. brake h.p. @ r.p.m.	450 (335.56 kw) @ 2,100	(Consult factory)
Governed load speed r.p.m.	2,100	(Consult factory)
Peak torque @ r.p.m.	1,425 ft. lbs. (1 932 j) @ 1,200	(Consult factory)
Electrical system	12-volt charging/24-volt starting	12-volt charging/24-volt starting
Batteries	Four 12-volt	Four 12-volt
Air compressor	Bendix TU-FLO 1000	Cummins 30 cfm

Carrier Speeds —

Main — Eaton RTX 14708LL			Auxiliary — Spicer P-1241-C							
			4th		3rd		2nd		1st	
Gear	Ratio		m.p.h.	km/hr	m.p.h.	km/hr	m.p.h.	km/hr	m.p.h.	km/hr
High	8th	.74	48.0	77.2	47.4	76.3	38.2	61.5	20.0	32.2
	7th	1.00	43.2	69.5	35.1	56.5	28.3	45.5	14.8	23.8
	6th	1.36	31.8	51.2	25.8	41.5	20.8	33.5	10.9	17.5
	5th	1.83	23.6	38.0	19.2	30.9	15.5	24.9	8.1	13.0
Low	4th	2.53	17.1	27.5	13.9	22.4	11.5	18.5	5.9	9.5
	3rd	3.40	12.7	20.4	10.3	16.6	8.3	13.4	4.4	7.1
	2nd	4.63	9.3	15.0	7.6	12.2	6.1	9.8	3.2	5.1
	1st	6.24	6.9	11.1	5.6	9.0	4.5	7.2	2.4	3.9
	L	9.42	4.6	7.4	3.7	6.0	3.0	4.8	1.6	2.6
Deep reduction	LL	14.56	3.0	4.8	2.4	3.9	1.9	3.1	1.0	1.6
Hi Rev.	-	2.89	15.0	24.1	12.1	19.5	9.8	15.8	5.1	8.2
Lo Rev.	-	9.85	4.4	7.1	3.6	5.8	2.9	4.7	1.5	2.4
Deep Rev. Creep	-	15.22	2.8	4.5	2.3	3.7	1.9	3.1	1.0	1.6
Deep 1st @ 1,200 rpm	-	-	1.7	2.7	1.4	2.3	1.1	1.8	.6	1.0
Deep Rev. @ 1,200 rpm	-	-	1.6	2.6	1.3	2.1	1.0	1.6	.6	1.0



HC-218H Load Hoisting Performance

Available line speed and line pull - based on ISUZU 6SA1T at 2100 rpm full load speed.

Line pulls are not based on wire rope strength. See wire rope chart for maximum permissible single part of line working loads.

Front and Rear Drum: Line speeds and pulls

16-3/4" (.43 m) Root Dia. - 7/8" (22 mm) dia. rope													
Single line pull		First layer speed				Fourth layer speed				Seventh layer speed			
		Front Drum		Rear Drum		Front Drum		Rear Drum		Front Drum		Rear Drum	
lbs	kgs	fpm	m/min	fpm	m/min	fpm	m/min	fpm	m/min	fpm	m/min	fpm	m/min
1,000	454	224	68	363	111	291	89	471	144	357	109	579	176
5,000	2 268	224	68	363	111	291	89	471	144	357	109	579	176
10,000	4 536	224	68	332	101	291	89	341	104	331	101	353	108
15,000	6 804	219	67	233	71	227	69	238	73	233	71	-	-
20,000	9 072	171	52	180	55	176	54	-	-	180	55	-	-
22,000	9 979	140	43	-	-	140	43	-	-	140	43	-	-

Wire rope: size, type and working strength

Wire rope application	Size: diameter		Type	Max. permissible load	
	inches	mm		lbs	kg
Boom hoist	7/8	22	W	22,700	10 297
Main load hoist	7/8	22	N	22,700	10 297
Auxiliary hoist	7/8	22	P	13,000	5 896
Boom pendants	1-1/4	32	N	53,200	24 100

Wire rope: types available

- Type "N" - 6 X 25 (6 X 19 class), filler wire, extra improved plow steel, preformed, independent wire rope center, right lay, regular lay.
- Type "W" - 6 X 26 (6 X 19 class), extra improved plow steel, preformed, independent wire rope center, right lay, alternate lay.
- Type "P" - 19 X 7 non-rotating, extra improved plow steel, preformed, wire strand core.



Upperstructure



Frame

All-welded, precision machined unit;



Fuel tank

76 gallon (290 L) capacity



Power transmission

All functions hydraulically powered allowing positive, precise control, with independent or simultaneous operation of all crane functions.

Engine Specifications

Isuzu 6SA1T with oil filter, oil cooler, air cleaner, fuel filter, water separator, hour meter, tachometer and electrical shutdown.

Number of cylinders	6
Bore and stroke - inch	4 - 17/32 X 5 - 5/16
- (mm)	(115 X 135)
Piston displacement	513
- (in ³)	(8413)
- (cm ³)	
Engine rpm at full load speed	2100
Hi-idle rpm	2350
Net engine horsepower at full load speed, (HP)	195 (145 kw)
Peak torque - foot pounds	513
- (joule)	696
Peak torque - rpm	1400
Electrical system	24 volt
Batteries	2 - 12 volt



Hydraulic System



Hydraulic pumps

Two variable displacement piston pumps operating at 4000 PSI powers travel, main drum, auxiliary drum, and boomhoist functions. One fixed displacement gear pump operating at 3000 PSI powers swing functions. One fixed displacement gear pump operating at 1210 PSI powers pilot control system, clutches, brakes and pump controls.



Hydraulic reservoir

78 US gallon (295 L), equipped with sight level gauge.



Relief valves

Each function is equipped with relief valves to protect the circuit from overload or shock.



Hydraulic filtration

Ten micron, full flow line filter furnished in control circuit. All oil is filtered prior to return to sump tank.



Hydraulic motors

Main hoist drum, auxiliary hoist drum, boomhoist, and swing are powered by axial piston motors.



Counterbalance valves

Hoist motors are equipped with counterbalance valves to provide positive load lowering and prevent accidental load drop when hydraulic power is suddenly reduced.

Principal Operating Functions



Control system



Remote controlled hydraulic servo for main drum and auxiliary drum. Mechanical linkage controls swing. Function speed is proportional to lever movement. Levers are adjustable for operator comfort.



Load hoisting and lowering

Main and auxiliary hoist drums are driven by individual axial piston motors and reduction gearing. Load hoisting or lowering is provided by actuating or reversing a hydraulic motor. Smooth, precise, power load lowering is attained with automatic hydraulic brake. The control lever provides two speeds for hoisting and lowering. Hoisting or lowering speeds are proportional to lever movement.



Load hoist drums

Main (front) and auxiliary (rear) hoist drums are 16-3/4" (43 mm) root diameter grooved for 7/8" (22 mm) wire rope. Mounted on anti-friction bearings.



Drum clutches

Speed-o-Matic® power hydraulic two-shoe clutches, internal expanding, lined shoes. Clutch spiders are splined to shafts; clutch drums are integral with hoist drums.

Load hoist clutches - Front and rear main drums - clutch drums 20" diameter, 5" face width. Swept area is 314 square inches



Drum brakes

External contracting band type; operated by foot pedal equipped with a locking latch. Operator may select automatic brake mode (spring applied, hydraulically released), which will apply brakes when the hoist control lever is in the neutral position.



Drum rotation indicators

Standard for front and rear drums. Audible-type indicators.



Drum locking pawl

Standard for front and rear drums; electrically actuated and prevents drum rotation in a lowering direction.



Anti two-block system

Standard: A switch mounted on the boom peak activates a buzzer to warn the operator of a two-block condition and simultaneously disengages hoist function while applying the hoist brakes.



Link-Belt

CONSTRUCTION EQUIPMENT

Swing system

Independent, hydraulic swing is driven; by an axial piston motor through a gear reduction system.

Swing brake - Spring applied, hydraulically released; controlled by button on swing control lever.

Swing lock - Mechanically controlled, 360° locking mechanism.

Swing speed - 0 to 2.2 r.p.m.

Boomhoist / lowering system

Independent, hydraulic boomhoist is driven by an axial piston motor through a gear reduction system. Boom hoisting or lowering is performed by actuating or reversing the motor.

Boomhoist drum

Single grooved lagging 10-11/16" (.27 m) root diameter.

Boomhoist drum locking pawl

Electrically operated.

Boomhoist brake

Spring applied, hydraulically released, multiple disc type brake. Brake is automatically applied when control lever is in neutral position.

Boomhoist limiting device - Restricts hoisting boom beyond recommended minimum radius.

Electrical system

24 volt negative ground system, with two 12-volt batteries. Standard lighting system includes: two 70 watt headlights mounted on machine front and one interior cab light.

Operator's cab

Full vision, modular compartment with safety glass panels. The completely independent cab is insulated against noise and vibration. Sliding operator's door, swing up roof window. Standard equipment includes: heater, defroster, windshield wiper, dry chemical fire extinguisher, sun visor, bubble-type level, fuel gauge, tachometer, hydraulic temperature gauge, engine oil pressure gauge, coolant temperature gauge and service monitor system.

Machinery cab

Hinged doors (one on right side, two on left side) for machinery access. Equipped with roof-top access ladder, electric warning horn and skid resistant finish on roof.

Catwalks

Standard on operator side. Catwalks remove for reduced travel width.

Bail

Pinned to revolving frame. Six sheaves are provided for 14-part boomhoist wire rope reeving. Sheaves mounted on anti-friction bearings, sealed for lifetime lubrication.

Counterweight

Counterweight "A" - 23,000 lbs. (10,433 kg)

Counterweight "B" - 20,000 lbs. (9,072 kg)

We are constantly improving our products and therefore reserve the right to change designs and specifications. © Link-Belt is a registered trademark.

Link-Belt Construction Equipment Company Lexington, Kentucky

A unit of Sumitomo Construction Machinery Co., Ltd.