



NEW



Mini Crawler Crane

MC-305C-2

Lifting Capacity : **2.98ton × 2.5m**

Maximum Working Radius : **12.16m × 0.26t**

Dimensions (L × W × H) : 4285 × 1280 × 1695mm

Outrigger Safety System

4Fall/2Fall Hook Block

Two Way Remote Controller



Moment Limiter Display



with electric motor spec





MAEDA Mini Crawler Crane MC-305C-2

Specifications


Model		MC-305CRMS(E)-2
Crane capacity	t × m	2.98t × 2.5m
Max. working radius	m × t	12.16m × 0.26t
Max. lifting height (on the ground)	m	12.52m
Max. lifting height (underground)	m	-16.09m
Winch system	Hook speed	m/min
	Hoist wire rope	φ × m
Telescoping system	Type	Fully automatic 5-section pentagonal telescopic boom
	Boom length	m
	Boom telescoping stroke / time	m/sec
Boom hoist system	Hoist angle / time	deg / sec
Swing system	swing angle / time	deg / rpm
Outrigger system	Type	Extended Hydraulic cylinder direct acting Setting up Hydraulic cylinder direct acting
	Max. extended width	mm
Travel system	Type	Hydraulic motor driven, stepless speed changer
	Travel speed	km/h
	Gradability	deg
	Crawler ground length × width	mm
Engine	Ground pressure	kpa [kgf/cm ²]
	Model	YANMAR 3TNV76
	Displacement	L [cc]
	Rated output	kw/min ⁻¹ [ps/rpm]
	Starting method	Electric starting
Motor (MC-305CRMSE-2)	Fuel / Fuel tank capacity	L
	Motor type	Totally enclosed fan-cooled motor 5.5kw, 4P 200V or 380V
Remote control system	Starting system	Inverter system (30Hz-60Hz)
	Type	Cable remote controller
	Micro/High speed mode	Available
	Load display for transmitter	Available
	Outrigger operation	Available
Overall length × width × height	mm	4,285 × 1,280 × 1,695
	Machine weight	kg
Safety device		Overwind protection, Load indicator, Hydraulic safety valve, Wire rope latch, Level, Machine body inclination alarm, EMO switch, Travel lock lever, Outrigger interlock device Moment limiter, Rotary lamp
	Options	White rubber track, Single fall hook Searcher hook

Total Rated Load Chart (4 falls)



Total Rated Load Chart with outrigger extended to maximum							
5.945m Boom		8.145m Boom		10.315m Boom		12.485m Boom	
Working radius (m)	Total rated load (kg)	Working radius (m)	Total rated load (kg)	Working radius (m)	Total rated load (kg)	Working radius (m)	Total rated load (kg)
2.5 or less	2980	2.7	2270	4.0	1080	4.5 or less	790
3.0	2390	3.0	2120	4.5	985	5.0	660
3.5	1990	3.5	1680	5.0	880	6.0	520
4.0	1710	4.0	1440	6.0	770	7.0	430
4.5	1490	4.5	1260	7.0	670	8.0	380
5.0	1340	5.0	1110	8.0	570	9.0	340
5.62	1160	5.5	990	9.0	500	10.0	310
		6.0	880	9.99	435	11.0	280
		7.0	730			12.16	260
		7.82	630				

* The Total Rated Load Chart is based on actual working radius with the bending of boom attributable to load reflected and is shown with the mass of hook (30kg) included.

Working Range (4 falls)



Dimensions



Before use, please read the Operation Manual

Due to improvements, the specifications are subject to change without notice.



MAEDA SEISAKUSHO CO.,LTD.

No.1095, Onbegawa, Shinonoi, Nagano-City, Nagano-Pref. 388-8522 Japan
Head office TEL: 026-292-2228 FAX: 026-293-5590
URL: <http://www.maesei.co.jp/> E-mail: maedasp@maesei.co.jp