



3577C

STANDARD COMPONENTS INCLUDE:

Boom, boom hoist cylinder, 2-speed winch, load line and 5 ton (4,5 mt) overhaul ball, turret, pedestal, sub-frame, dual operator control stations, LMI & ATB protection systems, load chart for multiple spread outriggers, out-down outriggers, out-down rear stabilizers, hydraulic reservoir and boom rest.

HYDRAULICS

- 8-Bolt direct mounted PTO with SAE-C output
- Three-section vane pump, SAE-C input

Pump Section	2000 RPM	2000 RPM
Shaft End Pump:	38.4 GPM @ 100 PSI	145 LPM @ 100 PSI
Center Pump:	27.4 GPM @ 100 PSI	104 LPM @ 100 PSI
Cover End Pump:	11.2 GPM @ 100 PSI	42 LPM @ 100 PSI

- Hydraulic reservoir - 115 gallon (435 liter) capacity

WARNING SYSTEMS

- Wireless LMI with display and crane function shut-offs for overload protection
- Wireless anti-two block system
- Back-up alarm

OPTIONS

- Wired LMI and ATB system
- 22' (6,7 m) Flatbed - wood or 1/8" steel deck
- 22' (6,7 m) Heavy hauler flatbed - 3/16" steel deck w/rub rails
- 24" (610 mm) Bulkhead
- Wire rope type 6 x 25 EIPS IWRC
- Load block - 1 or 3 sheave options
- Auxiliary sheave block for up to 8-part line reeve
- Front center stabilizer for 360° work area
- Gear pump
- Hydraulic oil cooler
- Hose reel - boom mounted
- Toolboxes
 - 24" L x 20" W x 18" H (610 mm x 508 mm x 457 mm)
 - 48" L x 18" W x 18" H (1220 mm x 457 mm x 457 mm)
- 2-Person gravity leveled non-rotating basket - 600 lb (272 kg) capacity
- 2-Person gravity leveled rotating (manual) basket - 1,200 lb (544 kg) capacity
- 4-Function radio remote crane control system



BOOM

- 35 Ton (31,8 mt) capacity @ 6' (1,8 m) radius
- 3-Section 77' (23,5 m) proportional boom
- 5-Sheave quick reeve boom point


HOIST

- Maximum theoretical line speed 453 fpm (138 mpm)
- Maximum theoretical bottom-layer line pull 14,500 lb (6,577 kg)
- Wire Rope – 380' (115,8 m) 5/8" (16 mm) diameter, rotation resistant

In order to ensure continuous improvement, Manitex reserves the right to change design and specifications without notice.



RETRACTED SPREAD



INTERMEDIATE SPREAD


CHASSIS DATA	3577C
Wheelbase (WB)	271" 6 883 mm
Cab to Axel (CA)	202" 4 887 mm
After Frame (AF)	114" 2 896 mm
Frame Section Modulus for 360° Rotation (Minimum)*	30 in ³ 125,000 psi 861 875 kPa
Front Axle Gross Weight Rating	20,000 lb 8 165 kg
Rear Axle Gross Weight Rating	40,000 lb 18 144 kg
Minimum Truck Axle Weight - Front**	8,450 lb 3 674 kg
Minimum Truck Axle Weight - Back**	8,300 lb 3 765 kg
Nominal Frame Width	34" 864 mm

*Also applies to front frame extensions for single front stabilizer.

Chassis data is general-not for engineering. Some dimensions depend on truck selection.

WEIGHTS	3577C
Total Crane - Standard	27,450 lb 12 451 kg
22' (6,71 m) Flat Bed	2,000 lb 907 kg

MAXIMUM TIP HEIGHT (A)	3577C
Configuration	Boom 77' 23,5 m
Extended Boom	87'-11" 26.8 m



FULL SPREAD