

MODEL CENTURY T200 - 20 TON HYDRAULIC CRANE LOAD

OPERATING RADIUS FEET		29 FT. RATED LOAD POUNDS		40 FT. RATED LOAD POUNDS		48 FT. RATED LOAD POUNDS		56 FT. RATED LOAD POUNDS		64 FT. RATED LOAD POUNDS		70.3 FT. RATED LOAD POUNDS		OPERATING RADIUS FEET	
POWERED BOOM LENGTH IN FEET - MANUAL RETRACTED		29 FT.		40 FT.		48 FT.		56 FT.		64 FT.		70.3 FT.			
		RATED LOAD POUNDS		RATED LOAD POUNDS		RATED LOAD POUNDS		RATED LOAD POUNDS		RATED LOAD POUNDS		RATED LOAD POUNDS			
		SIDE	REAR	SIDE	REAR	SIDE	REAR	SIDE	REAR	SIDE	REAR	SIDE	REAR		
10	63	40000		71	40000	75	40000							10	
12	58	40000		68	40000	72	40000							12	
15	50	36400		63	36400	68	35800	72	33200	75	31000			15	
20	34	25900		54	25900	62	25900	67	22900	70	25900	73	23500	20	
25				44	18000	54	18000	61	18000	65	18000	68	18000	25	
30				32	12500	46	12500	54	12500	60	12500	64	12500	30	
35						36	9200	47	9200	54	9200	59	9200	35	
40						23	6900	39	6900	48	6900	53	6900	40	
45								30	8200	42	5200	48	5200	45	
50								13	4000	34	4000	42	4000	50	
55										23	3000	34	3000	55	
60												25	2200	60	
65												8	1500	65	
70														70	
75														75	
80														80	
85														85	

INFORMATION:

