

**PK 12000 Performance****Technical Data****PK 12000 Performance**

Max. lifting moment	113.8 kNm	
Max. lifting capacity (CE)	6790 kg	14970 lbs
Max. lifting capacity	6790 kg	14970 lbs
Max. hydraulic outreach	14.6 m	47' 11"
Max. mechanical outreach	16.6 m	54' 6"
Max. outreach (with fly jib)	- m	0' -0"
Slewing angle	420 °	

Standard Crane

Slewing angle	13.7 kNm	
Outreach	6.2 m	20' 4"
Stabilizer spread standard	4.6 m	15' 1"
Stabilizer spread max.	6.6 m	21' 8"
Fitting space required (min.)	0.78 m	2' 7"
Fitting space required (max.)	0.95 m	3' 1"
Width folded	2.5 m	8' 2"
Operating pressure	300 bar	4350 psi
Recommended pump capacity	50 l/min	
Dead weight standard crane	1380 kg	3040 lbs

PK 12000 A*hydraulic*

Outreach	Capacity	
1.8 m 5' 11"	6680 kg	14730 lbs
4,5 m 14' 9"	2510 kg	5530 lbs
6,1 m 20' 0"	1820 kg	4010 lbs
8,1 m 26' 7"	1360 kg	3000 lbs

PK 12000 B*Manual*

Outreach	Capacity	
12.3 m 40' 4"	770 kg	1700 lbs
14,3 m 46' 11"	620 kg	1370 lbs
16.4 m 53' 10"	380 kg	840 lbs

Hydraulic

Outreach	Capacity	
1.8 m 5' 11"	6560 kg	14460 lbs
4,5 m 14' 9"	2420 kg	5340 lbs
6,1 m 20' 0"	1720 kg	3790 lbs
8,1 m 26' 7"	1260 kg	2780 lbs
10,2 m 33' 6"	980 kg	2160 lbs

**PK 12000 C***manual*

Outreach		Capacity	
14,2 m	46 ' 7 "	590 kg	1300 lbs
16,3 m	53 ' 6 "	380 kg	840 lbs

hydraulic

Outreach		Capacity	
1,8 m	5 ' 11 "	6460 kg	14240 lbs
4,5 m	14 ' 9 "	2350 kg	5180 lbs
6,1 m	20 ' 0 "	1640 kg	3620 lbs
8,1 m	26 ' 7 "	1170 kg	2580 lbs
10,2 m	33 ' 6 "	890 kg	1960 lbs
12,2 m	40 ' 0 "	720 kg	1590 lbs

PK 12000 D*manual*

Outreach		Capacity	
16,4 m	53 ' 10 "	380 kg	840 lbs

hydraulic

Outreach		Capacity	
1,8 m	5 ' 11 "	6360 kg	14020 lbs
4,5 m	14 ' 9 "	2280 kg	5030 lbs
6,1 m	20 ' 0 "	1570 kg	3460 lbs
8,1 m	26 ' 7 "	1090 kg	2400 lbs
10,2 m	33 ' 6 "	800 kg	1760 lbs
12,2 m	40 ' 0 "	640 kg	1410 lbs
14,3 m	46 ' 11 "	530 kg	1170 lbs