



| RADIUS<br>FEET | BOOM<br>ANGLE | OVER<br>REAR | OVER<br>SIDE | OVER<br>FRONT | BOOM<br>ANGLE | OVER<br>REAR | OVER<br>SIDE | OVER<br>FRONT | BOOM<br>ANGLE | OVER<br>REAR | OVER<br>SIDE | OVER<br>FRONT |
|----------------|---------------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|
| 27 FT. BOOM    |               |              |              |               | 47 FT. BOOM   |              |              |               |               | 67 FT. BOOM  |              |               |
| 6              | 79            | 59,200       | 59,200       | 59,200        |               |              |              |               |               |              |              |               |
| 8              | 74            | 49,070       | 49,070       | 49,070        |               |              |              |               |               |              |              |               |
| 10             | 70            | 42,790       | 42,790       | 42,790        | 80            | 35,860       | 35,860       | 35,860        |               |              |              |               |
| 12             | 65            | 36,070       | 36,070       | 29,560        | 77            | 31,290       | 31,290       | 30,060        |               |              |              |               |
| 15             | 57            | 28,000       | 28,000       | 17,000        | 73            | 26,640       | 26,640       | 17,500        | 80            | 20,930       | 20,930       | 17,620        |
| 18             | 49            | 22,500       | 22,500       | 10,810        | 69            | 21,790       | 21,790       | 11,300        | 77            | 17,490       | 17,490       | 11,440        |
| 20             | 43            | 19,710       | 19,710       | 8,300         | 66            | 19,330       | 19,330       | 8,800         | 75            | 15,700       | 15,700       | 8,900         |
| 25             | 20            | 14,600       | 14,600       | 4,550         | 59            | 14,840       | 14,840       | 5,050         | 70            | 12,340       | 12,340       | 5,180         |
| 30             |               |              |              |               | 52            | 11,810       | 11,810       | 3,380         | 66            | 10,020       | 10,020       | 3,480         |
| 35             |               |              |              |               | 43            | 9,620        | 8,670        | 2,350         | 61            | 8,300        | 8,300        | 2,460         |
| 40             |               |              |              |               | 32            | 7,960        | 6,460        | 1,190         | 55            | 6,980        | 6,800        | 1,270         |
| 45             |               |              |              |               | 15            | 6,640        | 4,400        | 590           | 50            | 5,970        | 4,840        | 680           |
| 50             |               |              |              |               |               |              |              |               | 43            | 5,140        | 3,820        | 340           |
| 55             |               |              |              |               |               |              |              |               | 36            | 4,460        | 2,970        | 0             |
| 60             |               |              |              |               |               |              |              |               | 28            | 3,860        | 2,120        | 0             |
| 65             |               |              |              |               |               |              |              |               | 13            | 3,370        | 1,610        | 0             |

| PART<br>LINE | MAXIMUM<br>LOAD |
|--------------|-----------------|
| 1            | 7,400           |
| 2            | 14,800          |
| 3            | 22,200          |
| 4            | 29,600          |
| 5            | 37,000          |
| 6            | 44,400          |

| PART<br>LINE | MAXIMUM<br>LOAD |
|--------------|-----------------|
| 1            | 7,400           |
| 2            | 14,800          |
| 3            | 22,200          |
| 4            | 29,600          |
| 5            | 37,000          |
| 6            | 44,400          |

MODEL NUMBER

5967S

# RATED LIFTING CAPACITIES OUTRIGGERS FULLY EXTENDED

SERIAL NUMBER

1002973549



18071 MT. WASHINGTON ST.  
FOUNTAIN VALLEY, CA 92708  
(714) 754-0337

1. DEDUCTION FROM RATED LIFTING CAPACITIES MUST BE MADE FOR THE WEIGHT OF LOAD BLOCK, SLINGS, OR ANY OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED.
2. LOADS MUST BE FREELY SUSPENDED, DO NOT EXCEED LOAD BLOCK OR PARTS OF LINE RATINGS.
3. BOOM ANGLES REFLECT CORRECTED ANGLE AFTER LOAD APPLIED.
4. LOADS ABOVE DASHED LINE ARE BASED ON STRUCTURAL LIMITS, BELOW LINE ON STABILITY.
5. READ AND UNDERSTAND OWNERS MANUAL BEFORE OPERATING.