



RATED LIFTING CAPACITIES

QLP 25F

360°

23' JIB

SN: 0517912688

RADIUS IN FEET	26' BOOM	43' BOOM	60' BOOM		RADIUS IN FEET	83' BOOM		
8	14,800				20	8,400		
10	14,800				25	6,700		
12	14,800	14,800			30	5,500		
15	14,800	12,600	11,900		35	4,700		
20	12,400	9,700	9,000		40	4,000		
25	9,200	8,000	7,300		45	3,500		
30		6,800	6,100		50	3,100		
35		5,500	5,200		55	2,800		
40		4,300	4,600		60	2,500		
45			4,000		65	2,100		
50			3,300		70	1,700		
55			2,700		75	1,400	PARTS OF LINE	MAXIMUM LOAD
60			2,200		80	1,200	1	7,400
					83	1,000	2	14,800

1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED.
2. LOAD RATINGS ARE FOR ZERO DEGREES OF LIST.
3. LOADS MUST BE FREELY SUSPENDED.
4. DO NOT EXCEED LOAD BLOCK OR PARTS OF LINE RATINGS.

