



- Accurate to the millimeter
- Multifunctional
- Radio control of all features
- Large lifting capacity
- Secure suction hold with two vacuum circuits

As Sky Lifter is radio-controlled, there are no limits to working height. The range of the remote control is 100 metres. The lifted item is very resistant to wind/ gusts as Sky Lifter is mounted on the parent machine.

Sky Lifter also handles the architect's creative and lopsided solutions where high installations under overhangs or oblique angles may be a challenge.



Sky Lifter runs non-stop with extra batteries (optional extra) which are easy to replaced without the need for tools.

Sky Lifter handles high lifts for installations in highrises such as these.

N.A. Christensensvej 39 DK-7900 Nykøbing Mors Tel.: +45 9772 2911

E-mail: smart@smartlift.dk

www.smartlift.dk






and tip take place in soft, stepless movements.


Sky Lifter is easy to install on the telescopic loader using an adapter for Quick release.

Sky Lifter's smooth pattern of movement is repeated in the yoke where rotation, tilt

Dimensions 690 mm 300 mm



Sky Lifter SL 400



Technical data

Description	Value *
Weight	350 kg
Height	690 mm
Width (min/max)	880/1020 mm
Length (min/max)	1115/1415 mm
Extension of arm	300 mm
Speedregulation	Stepless
Vacuum system	2-circuits
Suction pads	4 x Ø 300 mm
Chargingvoltage	230 volt, 5 Amp

External charger included Battery E-bike 24 volt, 20,25 Ah

Chargingtime 75% 2 hours Chargingtime 100% 4 hours

Runningperiod Approx. 8 hours ** Battery replacement Approx. 15 sec.


1000 Charging cycles Sky Lifter can be partially charged


Lifting capacity 400 kg

*All measurements are without adaptor for Quick release

**With normal use, Sky Lifter can easily last an 8-hour working day without charging. Battery capacity with continuous operation and maximum load is 4 hours. With additional battery, the operating period is limitless.

The six degrees of freedom





Workpieces/items

Sky Lifter handles a wide range of items from plasterboard to fire doors and wall panels.



Table tops

Fire doors

Wood/plasterboard



Rubber panels

Stone/concrete panels

Parent machines

Sky Lifter is a small, light and flexible electric manipulator which, with the right adapter, can be mounted on any hydraulic telescopic loader, crane etc.



Telescopic loaders



Lorry cranes



Mini loaders



Forklift trucks



Spider cranes

N.A. Christensensvej 39 DK-7900 Nykøbing Mors Tlf.: +45 97722911

E-mail: smart@smartlift.dk

www.smartlift.dk

