




Gru a torre “Flat Top”
“Flat Top” Tower Crane • Grue à tour “Flat Top”
“Flat Top” Turmdrehkran • Grua torre “Flat Top”



CE FEM 1.001 A3
(A2 )

THE **ULTIMATE** CRANE™

Dati illustrativi non impegnativi
Con riserva di modifica senza preavviso

Angaben und Beschreibung unverbindlich
Änderungen vorbehalten ohne weitere Mitteilung

Specifications and data not binding
Subject to modification without notice

Dibujos y datos sin compromiso
Modificaciones reservadas sin preaviso

Données techniques seulement indicatives
Modifications réservées sans préavis

UTEDOC. REV.002 09_2002

CTT 561-24 HD23



CTT 561-24

Diagramma di portata
Load Diagram

I
GB

Curbes de charges
Lastkurven

F
D

Curvas de cargas

E



12 t	-	23.1 m
24 t	-	12.2 m
12 t	-	28.0 m
24 t	-	14.6 m
12 t	-	33.2 m
24 t	-	17.4 m
12 t	-	38.2 m
24 t	-	19.9 m
12 t	-	41.0 m
24 t	-	21.2 m
12 t	-	44.4 m
24 t	-	22.7 m
12 t	-	49.9 m
24 t	-	25.4 m
12 t	-	50.0 m
24 t	-	25.9 m
12 t	-	40.0 m
24 t	-	26.7 m

CTT 561-24														
m	20	25	30	35	40	45	50	55	60	65	70	75	80	85
t	12	10.95	8.89	7.43	6.35	5.51	4.84	4.30	3.85	3.47	3.14	2.86	2.62	2.40
t	13.29	10.10	8.02	6.54	5.45	4.60	4.93	3.38	2.92	2.54	2.21	1.93	1.68	1.50
t	12	12	11.12	9.35	8.03	7.02	6.21	5.55	5	4.54	4.14	3.80	3.50	
t	16.67	12.83	10.30	8.52	7.20	6.18	5.36	4.70	4.15	3.68	3.29	2.94	2.70	
t	12	12	12	11.31	9.74	8.53	7.57	6.78	6.13	5.58	5.11	4.70		
t	20.48	15.84	12.80	10.65	9.06	7.82	6.84	6.04	5.38	4.82	4.34	4		
t	12	12	12	12	11.42	10.03	8.92	8.02	7.27	6.64	6.10			
t	23.81	18.52	15.05	12.60	10.78	9.37	8.25	7.34	6.58	5.94	5.50			
t	12	12	12	12	12	10.85	9.66	8.69	7.88	7.20				
t	24	19.93	16.21	13.59	11.65	10.14	8.94	7.97	7.16	6.60				
t	12	12	12	12	12	11.81	10.52	9.47	8.60					
t	24	21.56	17.60	14.81	12.73	11.12	9.84	8.80	8.10					
t	12	12	12	12	12	12	11.98	10.80						
t	24	24	19.98	16.84	14.50	12.69	11.26	10.30						
t	12	12	12	12	12	12	12							
t	24	24	20.45	17.24	14.85	13	11.80							
t	12	12	12	12	12									
t	24	24	21.14	17.82	15.80									

Altre installazioni
Other configurations

I
GB

Autres implantations
Aufstellmöglichkeiten


F
D

Otras implantaciones

E



HD23 22.6		
m		
A min	2	2
C min	14	16
H max	44	50
x	2,95	
y	2,42	



HD23 R1		HD23 R2
		m
A min/max	36/60	36/72
B min/max	24/42	
C max	48	
H max	i	

i Consultateci

I Consult us

GB Nous consulter

F Consultarnos

E Auf Anfrage


D




CTT 561-24

Torre **I** Mast **GB** Mât **F** Turm **D** Mástil **E**


HD23




R1	1681 kN ●	1513 kN ◆
R2		121 kN ◆
	125 t	




R1	1487 kN ●	1605 kN ◆
R2		134 kN ◆
	145 t	



R1	1814 kN ●	2195 kN ◆
R2		269 kN ◆
	165 t	



R1	3651 kN ●	4263 kN ◆
R2	2806 kN ●	3547 kN ◆
	115 t	



R1	4188 kN ●	6033 kN ◆
R2	3238 kN ●	5218 kN ◆
	135 t	

* (75 m - 80 m - 85 m)

H	Altezza massima sotto gancio	I
●	In servizio	
◆	Fuori servizio	
	A vuoto, senza zavorra, braccio max., altezza max.	
H	Max. under hook height	GB
●	In service	
◆	Out of service	
	Without load, without ballast, max. jib and max. height	
H	Hauteur maxi. sous crochet	F
●	En service	
◆	Hors service	
	A vide, sans lest, avec flèche et hauteur maximum	
H	Höchste Hackenhöhe	D
●	In Betrieb	
◆	Alternativlösung	
	Ohne Last und Ballast, mit Maximalausleger und Maximalhöhe	
H	Maxima altura bajo gancho	E
●	En servicio	
◆	Fuera de servicio	
	Sin carga, sin lastre, con pluma y altura máxima	



CTT 561-24

Meccanismi Mechanisms	I GB	Mécanismes Antriebe	F D	Mecanismos E
216 * kVA	400 V - 50 Hz / 460 V - 60 Hz	CE 87/405		

* Gru senza traslazione / Crane without travelling equipment / Grue sans translation / Krane ohne Schienenfahren / Grúa sin traslación

			m/min	↑	kW	
	110 AWL 120 LLC		0 ⇄ 40	12	110	630 m
			0 ⇄ 55	8.6		
			0 ⇄ 75	6		
			0 ⇄ 102	4.2		
			0 ⇄ 116	0.6		
			0 ⇄ 20	24		
			0 ⇄ 27.5	17.2		
			0 ⇄ 37.5	12		
			0 ⇄ 51	8.4		
			0 ⇄ 58	1.2		

		400 V - 50 Hz	
	DCC 5 112	0 ⇨ 95 m/min	11 kW
	SSR 4 4 80	0.73 r.p.m.	4 × 80 Nm
 	▲ TSR 2RG 4M8	12 ⇨ 24 m/min	4 × 80 Nm
	● TSR 4RG 4M8		
			

	▲	●
	Max. H [m]	
T ₁	54	> 54
T ₂	66	> 66
T ₃	-	90

	Sollevamento	I	Hoisting	GB	Levage	F	Heben	D	Elevación	E
	Traslazione carrello		Trolleying		Distribution		Katzfahren		Distribución	
	Rotazione		Slewing		Orientation		Schwenken		Orientación	
	Traslazione		Travelling		Translation		Schienenfahren		Traslación	
	Direttiva sul livello acustico		Directive on noise level		Directive sur le niveau acoustique		Richtlinie für den Schall-Leistungspegel		Directiva sobre el nivel acustico	
	Consultateci		Consult us		Nous consulter		Auf Anfrage		Consultarnos	
	Potenza totale richiesta		Power requirements		Puissance totale nécessaire		Geforderte Stromstärke		Potencia necesaria	
	Alimentazione		Power supply		Alimentation		Stromversorgung		Alimentación	

Gru Comedil s.r.l.

A Terex Company

Via S. Egidio 42/A, 33074 Fontanafredda (PN) - Italy
Tel. (+39) 0434 567 311 - Telefax (+39) 0434 998631

Internet e-mail: info@comedil.com
Internet home page: http://www.comedil.com

Divisione Automontanti

Via Alessandrina, 25 - 20095 Cusano Milanino (MI) - Italy
Tel. (+39) 02 613 16011 - Telefax (+39) 02 613 16034

Internet e-mail: info.CBR@comedil.com



Terex Internet home page: http://www.terex.com