



AC 500-2 | All Terrain Crane 600 t Lifting Capacity



AC 500-2




ALL TERRAIN CRANE



TEREX | DEMAG

AC 500-2 HIGHLIGHTS

- ▶ Enhanced Demag ovaloid boom design ensures excellent lifting capacities
- ▶ Exceptional capacity enhancements due to new Sideways Superlift
- ▶ The shortest 8-axle crane with a carrier length of just 56.1 ft
- ▶ Star-type outriggers giving enhanced stability
- ▶ Short rigging time and optimal transport weights for all configurations
- ▶ Innovative crane control provides high operating comfort





ALL TERRAIN CRANE
AC 500-2


CONTENTS

	Page:	
Specifications		
Dimensions	4	1
Specifications	6	
Main boom		
Working ranges with / without SSL	7	2
Lifting capacities	8, 12	
Lifting capacities with SSL	10, 13	
Main boom extension		
Working ranges with / without SSL	15	3
Lifting capacities	16	
Lifting capacities with SSL 0°	17	
Lifting capacities with SSL 30°	18	
Fixed fly jib		
Working ranges with / without SSL	19	4
Lifting capacities	20, 22, 24	
Lifting capacities with SSL	21, 23	
Luffing fly jib		
Working ranges with / without SSL	25	5
Lifting capacities	26-30, 32, 34, 36, 38	
Lifting capacities with SSL	31, 33, 35, 37, 39	
Technical description		
Carrier · Superstructure · Optional equipment	40	6
Overview		
of standard duty charts	42	7




TEREX | DEMAG

DIMENSIONS




ALL TERRAIN CRANE AC 500-2

DIMENSIONS



* Tail swing above ground



Duties with reduced outrigger base on request



SPECIFICATIONS

AXLE LOADS

Crane with main boom, outriggers and hook block	
Axles	8 x 26,500 lb
Total weight	212,000 lb

WORKING SPEEDS (INFINITELY VARIABLE)

Mechanisms	Normal speed	Max. permissible line pull	Rope length
Hoist I	max. 423.7 ft / min	28,100 lb	1,969 ft
Hoist II	max. 505.3 ft / min	28,100 lb	2,362 ft
Slewing			max. 0.8 1/min.
Telescoping speed			48.2 – 183.7 ft: ~ 420 sec.
Boom elevation			–0.5° – +83°: 85 sec.

CARRIER PERFORMANCE


Travel speed	0 . . 40 mph
--------------	--------------

HOOK BLOCK / HEAVY-LIFT ATTACHMENT

Type	Possible load	Number of sheaves	Weight	„D“	Number of lines	Heavy-lift attachment
320	491,500 lb	11	7,100 lb	14.8 ft	20	2 add'l. sheaves
250	469,200 lb	9	5,700 lb	14.8 ft	19	2 add'l. sheaves
200	390,300 lb	7	5,100 lb	9.8 ft	15	
160	291,900 lb	5	4,200 lb	9.8 ft	11	
100	189,400 lb	3	4,000 lb	9.8 ft	7	
40	82,900 lb	1	1,700 lb	8.9 ft	3	
12.5	27,800 lb	Single line hook	1,100 lb	6.6 ft	1	

ALL TERRAIN CRANE
AC 500-2

WORKING RANGES MAIN BOOM WITH / WITHOUT SSL





TEREX | DEMAG

LIFTING CAPACITIES MAIN BOOM

 **352,700 lb**

 **360°**

85 %

Radius	Main boom														Radius
	ft	48.2 ¹⁾	48.2	63.3 ¹⁾	63.3	78.7 ¹⁾	78.7	93.8	108.9	124.3	139.4	154.9	169.9	183.7	
ft	1,000 lb														ft
10	1200.0*	566.6	-	-	-	-	-	-	-	-	-	-	-	-	10
12	840.0*	566.6	566.6	566.6	566.6	-	-	-	-	-	-	-	-	-	12
13	762.8*	566.6	566.6	566.6	566.6	540.1	540.1	-	-	-	-	-	-	-	13
15	698.9*	566.6	566.6	566.6	566.6	540.1	540.1	-	-	-	-	-	-	-	15
16	646.0*	557.8	566.6	555.6	540.1	540.1	463.0	-	-	-	-	-	-	-	16
20	566.6	493.8	549.0	493.8	513.7	493.8	432.1	366.0	-	-	-	-	-	-	20
23	509.3	443.1	487.2	443.1	465.2	443.1	405.7	343.9	313.1	-	-	-	-	-	23
26	456.4	401.2	436.5	401.2	421.1	401.2	377.0	321.9	295.4	257.9	-	-	-	-	26
30	405.7	366.0	396.8	366.0	383.6	366.0	352.7	304.2	275.6	242.5	210.1	182.8	-	-	30
33	363.8	337.3	363.8	337.3	350.5	335.1	328.5	286.6	260.1	229.3	198.2	173.3	147.3	-	33
39	302.0	288.8	299.8	288.8	295.4	286.6	284.4	253.5	227.1	206.1	177.3	156.5	134.9	-	39
46	-	-	253.5	246.9	253.5	244.7	244.7	224.9	200.8	185.4	159.8	142.0	123.5	-	46
53	-	-	219.4	214.3	219.8	211.4	213.4	199.5	178.4	167.1	145.3	129.4	112.9	-	53
59	-	-	167.3	170.9	192.5	185.0	187.0	177.5	160.5	151.0	132.7	118.4	103.4	-	59
66	-	-	-	-	170.6	163.6	165.6	159.8	145.7	136.9	121.5	108.9	95.0	-	66
72	-	-	-	-	141.8	142.0	147.9	145.9	132.7	124.6	111.8	100.3	87.5	-	72
79	-	-	-	-	-	-	132.5	134.5	121.3	113.8	103.0	92.8	80.9	-	79
85	-	-	-	-	-	-	119.7	122.8	110.9	104.3	95.2	86.2	75.2	-	85
92	-	-	-	-	-	-	-	111.8	101.9	96.1	88.6	80.2	70.1	-	92
98	-	-	-	-	-	-	-	102.3	93.7	89.1	82.9	75.0	65.7	-	98
105	-	-	-	-	-	-	-	66.6	87.5	83.3	78.0	70.5	61.9	-	105
112	-	-	-	-	-	-	-	-	81.1	77.6	73.4	66.1	58.0	-	112
118	-	-	-	-	-	-	-	-	63.3	72.8	69.7	62.8	54.7	-	118
125	-	-	-	-	-	-	-	-	-	67.9	65.7	59.3	51.4	-	125
131	-	-	-	-	-	-	-	-	-	63.3	62.2	56.4	48.7	-	131
138	-	-	-	-	-	-	-	-	-	-	58.6	53.6	45.9	-	138
144	-	-	-	-	-	-	-	-	-	-	54.9	50.9	43.7	-	144
151	-	-	-	-	-	-	-	-	-	-	38.6	48.5	41.2	-	151
158	-	-	-	-	-	-	-	-	-	-	-	46.1	39.2	-	158
164	-	-	-	-	-	-	-	-	-	-	-	-	37.5	-	164
171	-	-	-	-	-	-	-	-	-	-	-	-	35.7	-	171

Remarks

¹⁾ 396,800 lb counterweight, additional central outriggers, double hook block required

* over rear

ALL TERRAIN CRANE

AC 500-2

LIFTING CAPACITIES MAIN BOOM												
 264,600 lb		 360°									85 %	
Radius	Main boom										Radius	
	ft	48.2	63.3	78.7	93.8	108.9	124.3	139.4	154.9	169.9		183.7
ft						1,000 lb						ft
10		566.6	-	-	-	-	-	-	-	-	-	10
12		566.6	566.6	-	-	-	-	-	-	-	-	12
13		566.6	566.6	540.1	-	-	-	-	-	-	-	13
15		566.6	566.6	540.1	-	-	-	-	-	-	-	15
16		544.5	542.3	540.1	463.0	-	-	-	-	-	-	16
20		482.8	482.8	480.6	432.1	366.0	-	-	-	-	-	20
23		432.1	434.3	432.1	405.7	343.9	313.1	-	-	-	-	23
26		392.4	392.4	390.2	377.0	321.9	295.4	257.9	-	-	-	26
30		357.1	357.1	357.1	352.7	304.2	275.6	242.5	210.1	182.8	-	30
33		321.9	321.9	319.7	321.9	286.6	260.1	229.3	198.2	173.3	147.3	33
39		264.6	264.6	262.4	264.6	253.5	227.1	206.1	177.3	156.5	134.9	39
46		-	224.9	222.7	224.9	224.9	200.8	185.4	159.8	142.0	123.5	46
53		-	191.8	190.5	191.8	195.1	178.4	167.1	145.3	129.4	112.9	53
59		-	166.0	168.7	166.2	169.3	160.5	151.0	132.7	118.4	103.4	59
66		-	-	146.4	143.1	146.8	144.4	136.9	121.5	108.9	95.0	66
72		-	-	126.5	123.0	126.8	124.3	124.3	111.8	100.3	87.5	72
79		-	-	-	107.1	110.5	108.0	108.0	103.0	92.8	80.9	79
85		-	-	-	99.2	97.2	94.8	94.6	95.2	86.2	75.2	85
92		-	-	-	-	86.2	83.8	83.8	85.1	80.2	70.1	92
98		-	-	-	-	77.2	75.2	74.5	76.1	75.0	65.7	98
105		-	-	-	-	66.6	70.8	66.8	68.1	70.1	61.9	105
112		-	-	-	-	-	64.2	60.2	61.3	63.3	58.0	112
118		-	-	-	-	-	58.4	54.5	55.6	57.5	54.7	118
125		-	-	-	-	-	-	51.4	50.5	52.2	51.4	125
131		-	-	-	-	-	-	48.5	45.9	47.8	47.8	131
138		-	-	-	-	-	-	-	42.5	43.7	43.9	138
144		-	-	-	-	-	-	-	40.6	39.9	39.9	144
151		-	-	-	-	-	-	-	38.6	36.6	36.6	151
158		-	-	-	-	-	-	-	-	33.5	33.5	158
164		-	-	-	-	-	-	-	-	-	30.6	164
171		-	-	-	-	-	-	-	-	-	28.2	171

**TEREX | DEMAG****LIFTING CAPACITIES MAIN BOOM WITH SSL** **396,800 lb** **360°****85 %**

Radius	Main boom						Radius
	ft	108.9	124.3	139.4	154.9	169.9	
ft					1,000 lb		ft
20		412.3	-	-	-	-	20
23		399.0	366.0	328.5	-	-	23
26		383.6	354.9	321.9	275.6	-	26
30		357.1	343.9	315.3	269.0	266.8	30
33		326.3	321.9	308.6	264.6	253.5	33
39		275.6	273.4	271.2	251.3	222.7	39
46		240.3	235.9	233.7	233.7	203.0	46
53		210.5	209.0	206.6	205.7	193.1	53
59		183.0	185.6	184.1	183.4	182.8	59
66		166.0	163.6	166.7	165.1	164.7	66
72		154.3	145.3	154.8	149.9	149.7	72
79		141.1	130.1	140.0	134.5	136.9	79
85		128.1	117.1	127.0	121.5	123.9	85
92		117.1	106.0	115.7	110.5	112.7	92
98		103.2	96.6	106.3	100.8	103.0	98
105		-	88.2	97.7	92.4	94.6	105
112		-	78.5	90.4	84.9	87.1	112
118		-	-	83.8	78.3	80.2	118
125		-	-	76.1	72.3	74.3	125
131		-	-	55.6	66.8	69.0	131
138		-	-	-	61.3	63.9	138
144		-	-	-	51.6	59.5	144
151		-	-	-	-	55.1	151
158		-	-	-	-	47.4	158
164		-	-	-	-	-	164
171		-	-	-	-	-	171
177		-	-	-	-	-	177

 **264,600 lb** **360°****85 %**

Radius	Main boom						Radius
	ft	108.9	124.3	139.4	154.9	169.9	
ft					1,000 lb		ft
20		412.3	-	-	-	-	20
23		399.0	366.0	328.5	-	-	23
26		379.2	354.9	321.9	275.6	-	26
30		343.9	343.9	315.3	269.0	266.8	30
33		310.9	313.1	308.6	264.6	253.5	33
39		253.5	255.7	257.9	251.3	222.7	39
46		213.2	215.8	217.8	220.5	203.0	46
53		188.7	184.5	190.5	189.4	191.8	53
59		169.5	158.7	168.7	163.4	165.8	59
66		149.0	138.0	148.2	142.9	145.1	66
72		131.4	118.2	130.1	123.7	126.5	72
79		114.9	101.9	113.8	107.4	110.0	79
85		101.4	88.4	100.1	93.9	96.6	85
92		90.2	77.2	88.8	82.5	85.1	92
98		80.5	67.9	79.1	73.0	75.4	98
105		-	59.5	71.0	64.8	67.2	105
112		-	52.5	63.9	57.8	60.4	112
118		-	-	58.0	51.4	54.0	118
125		-	-	52.7	45.9	48.5	125
131		-	-	38.1	41.0	43.4	131
138		-	-	-	36.6	39.0	138
144		-	-	-	32.8	35.1	144
151		-	-	-	-	31.7	151
158		-	-	-	-	28.7	158
164		-	-	-	-	-	164
171		-	-	-	-	-	171
177		-	-	-	-	-	177

ALL TERRAIN CRANE

AC 500-2

NOTES TO LIFTING CAPACITY

Ratings are in compliance with ISO 4305 and DIN 15019.2 (test load = 1.25 x suspended load + 0.1 x dead weight of boom head).
Weight of hook blocks and slings is part of the load, and is to be deducted from the capacity ratings.

Crane operation with main boom is permissible up to a

wind pressure of: 1.25 lb/ft²
wind speed of: 21.9 mph

Consult operation manual for further details.

Note: Data published herein is intended as a guide only and shall not be construed to warrant applicability for lifting purposes.
Crane operation is subject to the computer charts and operation manual both supplied with the crane.

**LIFTING CAPACITIES MAIN BOOM**

132,300 lb		360°										85 %
Main boom												
Radius	ft	48.2	63.3	78.7	93.8	108.9	124.3	139.4	154.9	169.9	183.7	Radius
ft	1,000 lb											ft
10	566.6	-	-	-	-	-	-	-	-	-	-	10
12	566.6	566.6	-	-	-	-	-	-	-	-	-	12
13	566.6	566.6	540.1	-	-	-	-	-	-	-	-	13
15	560.0	557.8	540.1	-	-	-	-	-	-	-	-	15
16	524.7	524.7	522.5	463.0	-	-	-	-	-	-	-	16
20	465.2	465.2	463.0	432.1	366.0	-	-	-	-	-	-	20
23	403.4	403.4	401.2	403.4	343.9	313.1	-	-	-	-	-	23
26	348.3	348.3	350.5	348.3	321.9	295.4	257.9	-	-	-	-	26
30	304.2	304.2	306.4	304.2	304.2	275.6	242.5	210.1	182.8	-	-	30
33	269.0	269.0	271.2	269.0	269.0	251.3	229.3	198.2	173.3	147.3	-	33
39	186.5	187.2	191.1	197.1	192.5	189.2	185.0	177.3	156.5	134.9	-	39
46	-	138.0	147.0	145.7	141.3	144.0	138.7	140.7	142.0	123.5	-	46
53	-	112.9	114.9	113.5	117.5	114.4	113.3	114.0	111.6	111.8	-	53
59	-	91.3	92.8	95.5	95.2	95.2	94.8	91.9	89.5	89.9	-	59
66	-	-	76.9	80.7	79.1	79.8	78.5	75.8	73.6	73.9	-	66
72	-	-	67.7	68.3	68.6	67.5	66.1	63.5	61.3	61.7	-	72
79	-	-	-	58.6	59.3	57.8	56.7	54.0	51.8	52.0	-	79
85	-	-	-	50.9	51.4	49.8	48.7	46.3	43.9	44.3	-	85
92	-	-	-	-	45.0	43.4	42.3	39.7	37.3	37.5	-	92
98	-	-	-	-	39.7	38.1	36.8	34.0	31.5	32.0	-	98
105	-	-	-	-	35.3	33.3	32.0	29.3	26.9	27.1	-	105
112	-	-	-	-	-	29.3	28.0	25.1	22.7	22.9	-	112
118	-	-	-	-	-	26.0	24.5	21.6	19.2	19.4	-	118
125	-	-	-	-	-	-	21.4	18.5	16.1	16.3	-	125
131	-	-	-	-	-	-	18.7	15.9	13.4	13.7	-	131
138	-	-	-	-	-	-	-	13.4	11.0	11.2	-	138
144	-	-	-	-	-	-	-	11.5	9.0	9.0	-	144
151	-	-	-	-	-	-	-	9.9	7.1	7.1	-	151
158	-	-	-	-	-	-	-	-	5.5	5.5	-	158

 0 lb		 360°										85 %
	Main boom											
Radius	ft	48.2	63.3	78.7	93.8	108.9	124.3	139.4	154.9	169.9	183.7	Radius
ft	1,000 lb											ft
10	566.6	-	-	-	-	-	-	-	-	-	-	10
12	566.6	566.6	-	-	-	-	-	-	-	-	-	12
13	566.6	566.6	540.1	-	-	-	-	-	-	-	-	13
15	524.7	524.7	522.5	-	-	-	-	-	-	-	-	15
16	465.2	465.2	429.9	359.4	-	-	-	-	-	-	-	16
20	346.1	295.4	269.0	231.5	198.2	184.5	-	-	-	-	-	20
23	215.6	204.6	185.8	174.2	155.9	143.7	130.3	-	-	-	-	23
26	134.9	149.0	143.3	133.2	124.3	112.9	103.2	92.2	-	-	-	26
30	90.8	103.0	111.1	106.0	99.9	91.3	84.0	75.0	67.0	-	-	30
33	65.5	76.1	83.1	84.4	82.5	75.4	69.4	61.9	55.1	52.5	-	33
39	37.7	46.1	52.0	53.1	54.0	52.2	49.4	43.4	38.1	36.4	-	39
46	-	30.2	35.3	36.2	37.0	35.5	34.2	30.6	25.6	24.0	-	46
53	-	20.3	24.9	25.6	26.5	24.9	23.8	19.8	15.4	14.3	-	53
59	-	13.4	17.6	18.5	19.2	17.6	16.5	12.3	8.2	7.3	-	59
66	-	-	12.6	13.2	13.9	12.3	11.0	6.8	-	-	-	66
72	-	-	7.9	8.6	9.5	7.7	6.4	-	-	-	-	72
79	-	-	-	5.1	5.7	-	-	-	-	-	-	79

ALL TERRAIN CRANE

AC 500-2

LIFTING CAPACITIES MAIN BOOM WITH SSL								
 176,400 lb		 360°					85 %	
Main boom								
Radius	ft	108.9	124.3	139.4	154.9	169.9	183.7	Radius
ft	1,000 lb							ft
20	412.3	-	-	-	-	-	-	20
23	399.0	366.0	328.5	-	-	-	-	23
26	357.1	354.9	321.9	275.6	-	-	-	26
30	315.3	317.5	315.3	269.0	266.8	198.0	-	30
33	280.0	284.4	286.6	264.6	253.5	229.3	-	33
39	224.9	227.1	229.3	229.3	222.7	204.6	-	39
46	194.4	178.6	193.1	185.6	183.6	179.0	-	46
53	153.9	138.0	152.6	144.8	148.4	148.8	-	53
59	124.8	110.0	123.7	116.4	119.5	120.2	-	59
66	103.8	89.5	102.5	95.7	98.5	99.0	-	66
72	87.7	73.9	86.4	79.8	82.7	83.1	-	72
79	75.2	61.3	74.1	67.5	70.1	70.5	-	79
85	65.0	50.9	63.9	57.1	60.2	60.6	-	85
92	56.9	42.5	55.6	48.5	51.6	52.0	-	92
98	49.8	35.3	48.3	41.2	44.1	44.5	-	98
105	-	29.5	42.1	35.1	37.9	38.4	-	105
112	-	24.5	36.8	29.8	32.6	32.8	-	112
118	-	-	32.2	25.1	28.0	28.2	-	118
125	-	-	28.2	21.2	23.8	24.3	-	125
131	-	-	15.0	17.9	20.3	20.7	-	131
138	-	-	-	14.8	17.2	17.4	-	138
144	-	-	-	12.1	14.3	14.6	-	144
151	-	-	-	-	11.9	12.1	-	151
158	-	-	-	-	9.7	9.9	-	158
164	-	-	-	-	-	7.9	-	164
171	-	-	-	-	-	6.2	-	171
177	-	-	-	-	-	-	-	177



NOTES TO LIFTING CAPACITY

Ratings are in compliance with ISO 4305 and DIN 15019.2 (test load = 1.25 x suspended load + 0.1 x dead weight of boom head).
Weight of hook blocks and slings is part of the load, and is to be deducted from the capacity ratings.

Crane operation with main boom is permissible up to a

wind pressure of: 1.25 lb/ft²
wind speed of: 21.9 mph


Consult operation manual for further details.

Note: Data published herein is intended as a guide only and shall not be construed to warrant applicability for lifting purposes.
Crane operation is subject to the computer charts and operation manual both supplied with the crane.



ALL TERRAIN CRANE
AC 500-2

WORKING RANGES MAIN BOOM EXTENSION WITH / WITHOUT SSL





TEREX | DEMAG

LIFTING CAPACITIES MAIN BOOM EXTENSION

308,600 lb 360° 85 %

183.7 ft Main boom

Radius	19.7 ft	39.4 ft			Extension			78.7 ft			98.4 ft			Radius
	0°	0°	20°	40°*	0°	20°	40°*	0°	20°	40°*	0°	20°	40°	
ft							1,000 lb							ft
39	106.7	-	-	-	-	-	-	-	-	-	-	-	-	39
46	97.4	82.7	-	-	68.6	-	-	-	-	-	-	-	-	46
53	89.1	75.6	-	-	63.5	-	-	55.3	-	-	-	-	-	53
59	82.0	69.4	59.7	-	59.1	-	-	51.6	-	-	45.0	-	-	59
66	75.6	63.9	56.4	49.4	54.9	43.7	-	48.1	-	-	41.9	-	-	66
72	69.9	59.1	53.1	47.2	51.1	41.7	-	45.0	-	-	39.2	-	-	72
79	65.0	54.9	50.0	45.2	47.8	39.7	34.2	42.1	33.3	-	36.8	-	-	79
85	60.6	51.1	47.2	43.2	44.8	37.9	33.1	39.5	31.7	-	34.6	-	-	85
92	56.9	48.1	44.5	41.2	42.1	36.2	32.0	37.3	30.2	-	32.6	25.6	-	92
98	53.4	45.2	42.1	39.2	39.5	34.6	30.9	35.1	28.9	24.9	30.6	24.5	-	98
105	50.0	42.5	39.9	37.3	37.5	33.1	29.8	33.3	27.8	24.0	29.1	23.4	-	105
112	47.0	40.1	37.9	35.5	35.3	31.5	28.7	31.3	26.5	23.4	27.6	22.5	19.4	112
118	44.3	37.9	35.9	34.0	33.5	30.0	27.6	29.8	25.4	22.7	26.0	21.6	18.7	118
125	41.7	35.7	34.2	32.2	31.7	28.7	26.7	28.2	24.5	22.0	24.7	20.7	18.1	125
131	39.2	34.0	32.4	30.6	30.0	27.6	25.8	26.9	23.4	21.4	23.6	19.8	17.4	131
138	37.0	32.0	30.9	29.1	28.4	26.2	24.9	25.6	22.5	20.5	22.3	19.0	16.8	138
144	35.1	30.2	29.5	28.0	27.1	25.1	24.0	24.3	21.6	19.8	21.2	18.3	16.3	144
151	33.1	28.7	28.2	26.7	25.6	24.0	23.1	22.9	20.7	19.2	20.3	17.4	15.7	151
158	31.5	27.3	26.9	25.6	24.5	23.1	22.5	21.8	20.1	18.7	19.2	16.8	15.2	158
164	30.0	25.8	25.6	-	23.1	22.0	21.6	20.7	19.2	18.1	18.3	16.1	14.8	164
177	27.3	23.6	23.4	-	20.9	20.3	20.1	18.5	17.9	16.8	16.5	14.8	13.9	177
190	-	21.6	21.4	-	19.0	18.5	-	16.8	16.3	15.7	14.8	13.4	13.0	190
203	-	19.8	-	-	17.2	16.8	-	15.0	15.0	-	13.2	12.1	12.1	203
217	-	-	-	-	15.7	15.2	-	13.4	13.4	-	11.9	11.0	11.2	217
230	-	-	-	-	-	-	-	12.1	12.1	-	10.4	9.9	-	230
243	-	-	-	-	-	-	-	10.8	-	-	9.0	8.6	-	243
256	-	-	-	-	-	-	-	-	-	-	7.7	7.5	-	256

88,200 lb 360° 85 %

183.7 ft Main boom

Radius	19.7 ft	39.4 ft			Extension			78.7 ft			98.4 ft			Radius
	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
ft							1,000 lb							ft
39	106.7	-	-	-	-	-	-	-	-	-	-	-	-	39
46	97.4	82.7	-	-	68.6	-	-	-	-	-	-	-	-	46
53	81.6	75.6	-	-	63.5	-	-	55.3	-	-	-	-	-	53
59	65.0	63.7	59.7	-	59.1	-	-	51.6	-	-	45.0	-	-	59
66	52.7	51.4	56.4	49.4	50.9	43.7	-	48.1	-	-	41.9	-	-	66
72	43.0	41.9	47.6	47.2	41.7	41.7	-	41.4	-	-	39.2	-	-	72
79	35.3	34.2	39.5	43.9	34.2	39.7	34.2	34.2	33.3	-	34.4	-	-	79
85	28.9	28.0	32.6	36.6	28.0	35.1	33.1	28.0	31.7	-	28.4	-	-	85
92	23.6	22.9	27.1	30.4	22.9	29.1	32.0	23.1	30.2	-	23.6	25.6	-	92
98	19.0	18.5	22.3	25.4	18.7	24.3	29.3	19.0	26.2	24.9	19.4	24.5	-	98
105	15.2	15.0	18.3	20.9	15.0	20.3	24.7	15.2	22.0	24.0	15.9	23.4	-	105
112	11.9	11.7	14.8	17.0	11.9	16.5	20.7	12.1	18.5	23.4	12.8	20.5	19.4	112
118	9.0	8.6	11.5	13.4	9.3	13.4	17.2	9.5	15.2	20.5	10.1	17.2	18.7	118
125	6.4	6.2	8.6	10.4	6.8	10.8	14.1	7.1	12.3	17.2	7.7	14.3	18.1	125
131	-	-	6.2	7.7	4.6	8.4	11.0	5.1	9.9	14.3	5.7	11.9	17.4	131
138	-	-	-	5.3	-	6.2	8.6	-	7.7	11.7	-	9.5	14.8	138
144	-	-	-	-	-	-	6.2	-	5.7	9.3	-	7.5	12.3	144
151	-	-	-	-	-	-	-	-	-	7.3	-	5.7	10.1	151
158	-	-	-	-	-	-	-	-	-	5.3	-	-	7.9	158
164	-	-	-	-	-	-	-	-	-	-	-	-	6.2	164
177	-	-	-	-	-	-	-	-	-	-	-	-	-	177

Remarks

* 264,600 lb Counterweight


ALL TERRAIN CRANE
AC 500-2
LIFTING CAPACITIES MAIN BOOM EXTENSION WITH SSL 0°

396,800 lb		 360°												85 %	
183.7 ft Main boom															
Extension															
	19.7 ft	39.4 ft			59.1 ft			78.7 ft			98.4 ft				
Radius	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	Radius	
ft	1,000 lb													ft	
30	110.2	-	-	-	-	-	-	-	-	-	-	-	-	30	
33	110.2	-	-	-	-	-	-	-	-	-	-	-	-	33	
39	110.2	100.8	-	-	82.5	-	-	-	-	-	-	-	-	39	
46	110.2	99.4	-	-	81.8	-	-	66.8	-	-	55.3	-	-	46	
53	110.2	97.7	85.1	-	80.7	-	-	63.9	-	-	53.1	-	-	53	
59	110.2	95.5	82.2	67.9	79.1	59.1	-	61.1	-	-	50.9	-	-	59	
66	107.6	92.8	79.1	65.7	77.4	56.4	-	58.4	-	-	48.9	-	-	66	
72	104.7	90.2	76.3	63.5	75.2	54.0	-	55.8	39.2	-	46.7	-	-	72	
79	101.9	87.1	73.2	61.5	72.8	51.8	41.2	53.1	37.9	-	44.8	-	-	79	
85	98.8	83.8	70.1	59.5	70.1	49.8	40.1	50.7	36.4	-	43.0	30.9	-	85	
92	95.7	80.7	67.0	57.8	67.2	47.8	39.2	48.5	35.3	28.9	41.0	29.8	-	92	
98	92.4	77.4	64.2	56.2	64.6	46.1	38.1	46.1	34.0	28.2	39.2	28.7	-	98	
105	89.1	74.3	61.3	54.7	61.7	44.5	37.5	44.1	33.1	27.6	37.5	27.6	22.3	105	
112	85.8	71.0	58.6	53.1	59.1	43.0	36.6	42.1	32.0	27.1	35.9	26.7	21.8	112	
118	82.0	68.1	56.4	51.8	56.7	41.7	35.9	40.3	31.1	26.7	34.4	25.8	21.2	118	
125	76.1	65.3	54.2	50.5	54.0	40.3	35.1	38.6	30.2	26.0	32.8	24.9	20.7	125	
131	70.5	62.6	52.5	49.2	51.8	39.2	34.4	37.0	29.5	25.6	31.5	24.3	20.3	131	
138	65.8	60.1	50.9	48.2	49.6	38.3	33.8	35.7	28.8	25.2	30.3	23.6	19.8	138	
144	61.1	57.5	49.4	47.2	47.4	37.3	33.3	34.4	28.0	24.9	29.1	22.9	19.4	144	
151	57.0	55.2	48.1	46.3	45.6	36.4	33.0	33.3	27.3	24.6	28.0	22.3	19.1	151	
158	52.9	52.9	46.7	45.4	43.9	35.5	32.6	32.2	26.7	24.3	26.9	21.6	18.7	158	
164	49.5	49.5	45.6	-	42.2	34.7	32.3	31.2	26.1	23.9	26.1	21.1	18.4	164	
177	42.9	43.2	42.9	-	39.2	33.4	31.7	29.4	25.1	23.4	24.6	20.1	17.9	177	
190	-	37.8	38.6	-	36.8	32.4	-	28.1	24.3	22.9	23.1	19.2	17.3	190	
203	-	32.0	-	-	34.0	31.7	-	26.9	23.5	-	22.0	18.3	17.1	203	
217	-	-	-	-	29.4	30.6	-	25.8	22.7	-	20.9	17.6	16.8	217	
230	-	-	-	-	-	-	-	24.8	22.3	-	20.0	17.2	-	230	
243	-	-	-	-	-	-	-	-	-	-	19.0	16.8	-	243	
256	-	-	-	-	-	-	-	-	-	-	17.9	16.5	-	256	

220,500 lb		 360°												85 %	
19.7 ft		39.4 ft			59.1 ft			78.7 ft			98.4 ft				
ft	1,000 lb													ft	
30	110.2	-	-	-	-	-	-	-	-	-	-	-	-	30	
33	110.2	-	-	-	-	-	-	-	-	-	-	-	-	33	
39	110.2	100.8	-	-	82.5	-	-	-	-	-	-	-	-	39	
46	110.2	99.4	-	-	81.8	-	-	66.8	-	-	55.3	-	-	46	
53	110.2	97.7	85.1	-	80.7	-	-	63.9	-	-	53.1	-	-	53	
59	110.2	95.5	82.2	67.9	79.1	59.1	-	61.1	-	-	50.9	-	-	59	
66	107.6	92.8	79.1	65.7	77.4	56.4	-	58.4	-	-	48.9	-	-	66	
72	104.7	90.2	76.3	63.5	75.2	54.0	-	55.8	39.2	-	46.7	-	-	72	
79	93.5	87.1	73.2	61.5	72.8	51.8	41.2	53.1	37.9	-	44.8	-	-	79	
85	81.4	81.8	70.1	59.5	70.1	49.8	40.1	50.7	36.4	-	43.0	30.9	-	85	
92	71.2	71.7	67.0	57.8	67.2	47.8	39.2	48.5	35.3	28.9	41.0	29.8	-	92	
98	62.8	63.3	64.2	56.2	64.6	46.1	38.1	46.1	34.0	28.2	39.2	28.7	-	98	
105	55.6	56.0	59.5	54.7	57.3	44.5	37.5	44.1	33.1	27.6	37.5	27.6	22.3	105	
112	49.2	49.6	52.9	53.1	50.9	43.0	36.6	42.1	32.0	27.1	35.9	26.7	21.8	112	
118	43.4	43.9	47.2	49.4	45.2	41.7	35.9	40.3	31.1	26.7	34.4	25.8	21.2	118	
125	38.6	38.8	41.9	44.1	40.1	40.3	35.1	38.6	30.2	26.0	32.8	24.9	20.7	125	
131	34.0	34.4	37.3	39.0	35.7	39.2	34.4	37.0	29.5	25.6	31.5	24.3	20.3	131	
138	30.3	30.6	33.2	34.7	32.0	35.5	33.8	33.4	28.8	25.2	30.3	23.6	19.8	138	
144	26.7	26.9	29.1	30.4	28.2	31.7	33.3	29.8	28.0	24.9	29.1	22.9	19.4	144	
151	23.6	23.8	25.9	27.0	25.1	28.4	30.3	26.7	27.3	24.6	27.1	22.3	19.1	151	
158	20.5	20.7	22.7	23.6	22.0	25.1	27.3	23.6	26.7	24.3	25.1	21.6	18.7	158	
164	18.1	18.3	20.0	-	19.5	22.4	24.3	21.1	24.4	23.9	22.6	21.1	18.4	164	
177	13.6	13.7	15.0	-	14.9	17.3	18.5	16.3	19.6	22.0	17.9	20.1	17.9	177	
190	-	9.8	10.8	-	11.0	12.9	-	12.3	15.2	17.1	13.8	17.5	17.3	190	
203	-	6.4	-	-	7.7	9.1	-	9.0	11.5	-	10.4	13.7	15.5	203	
217	-	-	-	-	4.9	6.0	-	6.2	7.9	-	7.3	10.1	11.9	217	
230	-	-	-	-	-	-	-	-	5.1	-	4.9	7.1	-	230	



LIFTING CAPACITIES MAIN BOOM EXTENSION WITH SSL 30°

 396,800 lb		 360°		85 %	
183.7 ft Main boom					
Extension					
Radius	39.4 ft	59.1 ft	78.7 ft	98.4 ft	Radius
ft	0°	0°	0°	0°	ft
39	108.0	92.4	-	-	39
46	104.7	88.2	72.8	63.1	46
53	101.2	84.2	67.5	58.4	53
59	97.2	80.2	62.8	54.2	59
66	93.0	76.3	58.6	50.5	66
72	88.6	72.5	54.9	47.2	72
79	84.2	69.0	51.6	44.3	79
85	79.8	65.5	48.7	41.7	85
92	75.4	62.2	46.1	39.2	92
98	71.2	59.1	43.7	37.3	98
105	67.2	56.2	41.9	35.5	105
112	63.3	53.4	39.9	33.7	112
118	60.0	50.7	38.4	32.4	118
125	56.7	48.3	36.8	31.1	125
131	53.8	46.1	35.3	29.8	131
138	51.1	44.1	34.1	28.7	138
144	48.5	42.1	32.8	27.6	144
151	46.1	40.3	31.7	26.6	151
158	43.7	38.6	30.6	25.6	158
164	41.6	37.0	29.5	24.7	164
177	37.4	34.0	27.6	23.0	177
190	33.3	31.0	25.9	21.6	190
203	-	28.1	24.3	20.2	203
217	-	24.8	22.5	19.0	217
230	-	-	20.9	18.0	230
243	-	-	-	16.8	243
256	-	-	-	15.7	256

 220,500 lb		 360°		85 %	
183.7 ft Main boom					
Extension					
Radius	39.4 ft	59.1 ft	78.7 ft	98.4 ft	Radius
ft	0°	0°	0°	0°	ft
39	108.0	92.4	-	-	39
46	104.7	88.2	72.8	63.1	46
53	101.2	84.2	67.5	58.4	53
59	97.2	80.2	62.8	54.2	59
66	93.0	76.3	58.6	50.5	66
72	88.6	72.5	54.9	47.2	72
79	84.2	69.0	51.6	44.3	79
85	79.8	65.5	48.7	41.7	85
92	71.7	62.2	46.1	39.2	92
98	63.3	59.1	43.7	37.3	98
105	56.0	56.2	41.9	35.5	105
112	49.6	50.9	39.9	33.7	112
118	43.9	45.2	38.4	32.4	118
125	38.8	40.1	36.8	31.1	125
131	34.4	35.7	35.3	29.8	131
138	30.6	32.0	32.5	28.7	138
144	26.9	28.2	29.8	27.6	144
151	23.8	25.1	26.7	26.3	151
158	20.7	22.0	23.6	25.1	158
164	18.3	19.5	21.1	22.6	164
177	13.7	14.9	16.3	17.9	177
190	9.8	11.0	12.3	13.8	190
203	-	7.6	9.0	10.4	203
217	-	4.9	6.2	7.3	217
230	-	-	-	4.9	230





ALL TERRAIN CRANE
AC 500-2

WORKING RANGES FIXED FLY JIB WITH / WITHOUT SSL

OFFSET FIXED FLY JIB

A	B	C 0° / 20° / 40°
86.6 ft	48.9 ft	37.7 ft
106.3 ft	48.9 ft	57.4 ft
126.0 ft	68.6 ft	57.4 ft
145.7 ft	68.6 ft	77.0 ft
165.4 ft	88.2 ft	77.0 ft
185.0 ft	88.2 ft	96.8 ft
204.7 ft	107.9 ft	96.8 ft

(27.6 ft, 47.2 ft + 66.9 ft only 0°)





TEREX | DEMAG

LIFTING CAPACITIES FIXED FLY JIB

 360° 85 %

183.4 ft Main boom

Fly jib													
Radius	27.6 ft	47.2 ft	66.9 ft	86.6 ft			106.3 ft			126.0 ft			Radius
	0°	0°	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
ft	1,000 lb												ft
46	90.6	76.9	-	-	-	-	-	-	-	-	-	-	46
53	82.2	70.3	62.6	52.7	-	-	-	-	-	-	-	-	53
59	74.7	64.4	58.0	48.7	-	-	43.0	-	-	-	-	-	59
66	68.3	59.1	53.8	45.2	40.6	-	39.9	-	-	35.1	-	-	66
72	62.6	54.2	49.8	41.9	37.9	-	37.0	-	-	32.4	-	-	72
79	58.1	50.3	46.5	39.1	35.5	33.5	34.6	30.4	-	30.2	-	-	79
85	53.6	46.3	43.2	36.4	33.3	31.7	32.2	28.7	-	28.0	25.6	-	85
92	49.9	43.1	40.3	34.1	31.3	30.0	30.1	26.9	25.1	26.1	24.0	-	92
98	46.3	39.9	37.5	31.7	29.5	28.2	28.0	25.4	23.8	24.3	22.5	21.4	98
105	43.5	37.4	35.2	29.8	28.0	26.9	26.3	24.0	22.7	22.7	21.2	20.3	105
112	40.8	34.8	32.8	27.8	26.5	25.4	24.7	22.7	21.4	21.2	19.8	19.2	112
118	38.4	32.7	31.0	26.2	25.1	24.3	23.3	21.4	20.5	19.8	18.7	18.1	118
125	35.9	30.6	29.1	24.7	23.8	22.9	21.8	20.3	19.4	18.5	17.6	17.2	125
131	34.0	28.9	27.4	23.4	22.5	21.8	20.6	19.2	18.5	17.5	16.5	16.1	131
144	30.3	25.7	24.5	20.8	20.3	19.8	18.4	17.4	16.8	15.5	14.8	14.6	144
158	27.2	22.9	21.9	18.5	18.3	18.1	16.4	15.7	15.2	13.7	13.2	13.0	158
171	24.4	20.5	19.7	16.4	16.4	16.5	14.6	14.1	13.9	12.0	11.8	11.7	171
184	21.5	18.4	18.0	14.7	14.8	14.9	12.9	12.8	12.7	10.6	10.6	10.5	184
197	18.6	16.5	16.5	13.2	13.1	13.2	11.4	11.5	11.5	9.3	9.4	9.3	197
210	-	14.7	15.0	11.7	11.7	-	10.1	10.3	10.4	8.2	8.3	8.4	210
223	-	-	13.7	10.6	10.6	-	9.0	9.0	-	7.1	7.3	7.4	223
236	-	-	12.4	9.5	9.5	-	7.9	8.2	-	6.2	6.4	-	236
249	-	-	-	8.6	-	-	7.1	7.3	-	5.3	5.5	-	249
263	-	-	-	-	-	-	6.4	6.4	-	4.4	4.6	-	263
276	-	-	-	-	-	-	5.7	-	-	-	-	-	276

145.7 ft				165.4 ft			185.0 ft			204.7 ft			
ft							1,000 lb						ft
72	29.3	-	-	25.8	-	-	-	-	-	-	-	-	72
79	27.3	-	-	24.0	-	-	21.2	-	-	-	-	-	79
85	25.4	-	-	22.3	-	-	19.8	-	-	-	17.2	-	85
92	23.7	-	-	20.7	-	-	18.5	-	-	-	16.0	-	92
98	22.0	20.1	-	19.2	17.9	-	17.2	-	-	-	14.8	-	98
105	20.6	19.0	-	17.9	16.8	-	16.0	-	-	-	13.7	-	105
112	19.2	17.9	16.8	16.5	15.7	-	14.8	13.7	-	-	12.6	-	112
118	18.0	16.8	15.9	15.4	14.8	14.3	13.7	12.8	-	-	11.6	11.0	118
125	16.8	15.9	15.0	14.3	13.9	13.4	12.6	11.9	-	-	10.6	10.4	125
131	15.8	14.8	14.3	13.3	13.0	12.6	11.7	11.2	-	-	9.7	9.5	131
144	13.9	13.2	12.8	11.6	11.2	11.2	10.0	9.7	9.7	-	7.9	8.2	144
158	12.2	11.7	11.5	10.0	9.9	9.9	8.5	8.4	8.4	-	6.4	6.8	158
171	10.8	10.4	10.3	8.7	8.6	8.7	7.2	7.2	7.4	-	5.2	5.6	171
184	9.5	9.3	9.1	7.6	7.5	7.6	6.1	6.2	6.3	-	-	4.4	184
197	8.2	8.2	8.2	6.5	6.5	6.6	5.1	5.1	5.3	-	-	-	197
210	7.2	7.2	7.3	5.5	5.5	5.7	-	-	4.4	-	-	-	210
223	6.2	6.2	6.4	4.6	4.6	4.9	-	-	-	-	-	-	223
236	5.3	5.5	5.6	-	-	-	-	-	-	-	-	-	236
249	4.4	4.6	4.9	-	-	-	-	-	-	-	-	-	249

Remarks

Counterweight 88,200 lb 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES FIXED FLY JIB WITH SSL**

360°85 %														
183.4 ft Main boom														
Fly jib														
	27.6 ft	47.2 ft	66.9 ft	86.6 ft			106.3 ft			126.0 ft				
Radius	0°	0°	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	Radius	
ft	1,000 lb													ft
39	159.0	95.7	-	-	-	-	-	-	-	-	-	-	39	
46	146.4	123.2	103.6	58.6	-	-	-	-	-	-	-	-	46	
53	134.7	113.1	95.2	81.8	-	-	70.8	-	-	41.9	-	-	53	
59	124.1	104.3	88.0	75.4	57.1	-	65.7	-	-	57.8	-	-	59	
66	114.4	96.3	81.6	69.9	54.0	-	60.8	-	-	53.6	-	-	66	
72	105.6	89.5	76.1	64.8	50.9	43.9	56.7	40.6	-	49.8	-	-	72	
79	97.8	83.7	71.4	60.7	48.3	41.9	53.0	38.6	-	46.6	35.1	-	79	
85	91.5	77.8	66.8	56.7	45.6	40.1	49.4	36.6	31.3	43.4	33.3	-	85	
92	87.0	73.1	63.2	53.4	43.4	38.6	46.4	34.8	30.4	40.7	31.5	27.3	92	
98	82.5	68.3	59.5	50.0	41.2	36.8	43.4	33.1	29.3	37.9	30.0	26.2	98	
105	78.5	64.8	56.7	47.4	39.5	35.5	41.1	31.5	28.2	35.7	28.7	25.4	105	
112	74.5	61.5	53.8	44.8	37.5	34.0	38.8	30.0	27.3	33.5	27.1	24.3	112	
118	71.3	58.8	51.3	42.7	35.9	32.8	36.8	28.7	26.2	31.7	25.8	23.4	118	
125	68.1	56.0	48.7	40.6	34.4	31.5	34.8	27.3	25.4	30.0	24.7	22.5	125	
131	64.0	53.6	46.2	38.7	33.1	30.4	33.3	26.0	24.3	28.5	23.6	21.6	131	
144	55.7	49.2	41.3	35.2	30.6	28.2	30.4	23.8	22.5	25.9	21.4	20.1	144	
158	47.6	45.4	37.8	32.0	28.2	26.5	27.9	21.8	20.7	23.6	19.6	18.5	158	
171	40.8	41.2	35.2	29.0	26.2	24.7	25.7	20.3	19.2	21.6	18.1	17.2	171	
184	35.1	36.0	32.8	26.2	24.5	23.4	23.7	19.0	17.9	19.8	16.8	15.9	184	
197	27.3	31.1	30.9	23.7	22.9	-	21.8	17.9	16.8	18.3	15.4	14.8	197	
210	-	25.2	29.2	22.3	21.6	-	20.1	17.0	15.9	16.8	14.3	13.7	210	
223	-	-	25.8	20.9	20.3	-	18.4	16.1	-	15.4	13.4	12.8	223	
236	-	-	19.4	19.8	18.5	-	16.8	15.4	-	14.1	12.6	-	236	
249	-	-	-	16.8	-	-	15.4	14.8	-	12.8	11.7	-	249	
263	-	-	-	-	-	-	14.6	13.4	-	12.0	10.8	-	263	
276	-	-	-	-	-	-	11.0	-	-	11.2	9.9	-	276	
289	-	-	-	-	-	-	-	-	-	9.0	-	-	289	

145.7 ft				165.4 ft				185.0 ft				204.7 ft				
ft							1,000 lb									ft
59	33.1	-	-	27.3	-	-	-	-	-	-	-	-	-	-	-	59
66	47.2	-	-	27.1	-	-	22.7	-	-	-	-	-	-	-	-	66
72	44.1	-	-	39.0	-	-	34.8	-	-	-	17.4	-	-	-	-	72
79	41.2	-	-	36.6	-	-	32.6	-	-	-	28.9	-	-	-	-	79
85	38.4	26.7	-	34.2	-	-	30.4	-	-	-	26.9	-	-	-	-	85
92	36.0	25.8	-	32.1	24.0	-	28.5	-	-	-	25.2	-	-	-	-	92
98	33.7	24.7	-	30.0	22.7	-	26.7	-	-	-	23.6	-	-	-	-	98
105	31.7	23.6	20.1	28.1	21.6	-	25.0	19.2	-	-	22.0	-	-	-	-	105
112	29.8	22.7	19.4	26.2	20.5	18.1	23.4	18.3	-	-	20.5	15.4	-	-	-	112
118	28.2	21.8	18.7	24.8	19.6	17.2	22.0	17.4	-	-	19.2	14.8	-	-	-	118
125	26.7	20.7	18.3	23.4	18.5	16.5	20.7	16.5	-	-	17.9	14.1	-	-	-	125
131	25.4	19.8	17.6	22.0	17.6	15.9	19.5	15.7	13.9	-	16.8	13.4	-	-	-	131
144	22.9	18.3	16.5	19.7	16.1	14.6	17.3	14.1	12.8	-	14.7	12.1	11.2	-	-	144
158	20.8	16.8	15.4	17.9	14.6	13.2	15.4	12.6	11.7	-	12.9	10.8	10.1	-	-	158
171	19.0	15.2	14.3	16.2	13.2	12.1	13.9	11.2	10.6	-	11.5	9.5	9.0	-	-	171
184	17.4	14.1	13.4	14.7	11.9	11.2	12.6	9.9	9.5	-	10.1	8.2	7.7	-	-	184
197	16.1	13.0	12.6	13.2	10.8	10.4	11.4	8.8	8.4	-	9.0	6.8	6.6	-	-	197
210	14.8	12.1	11.7	12.1	9.9	9.5	10.3	7.7	7.3	-	8.0	5.3	5.5	-	-	210
223	13.6	11.2	11.0	11.0	9.0	8.8	9.1	6.6	6.4	-	7.2	-	-	-	-	223
236	12.3	10.6	10.4	10.1	8.2	8.2	8.2	5.7	5.3	-	6.4	-	-	-	-	236
249	11.4	9.9	-	9.0	7.3	7.5	7.5	4.9	4.4	-	5.6	-	-	-	-	249
263	10.3	9.3	-	8.3	6.6	7.1	6.6	-	-	-	4.9	-	-	-	-	263
276	9.3	8.8	-	7.5	5.7	-	6.0	-	-	-	-	-	-	-	-	276
289	8.6	8.2	-	6.6	5.1	-	5.2	-	-	-	-	-	-	-	-	289
302	8.0	-	-	5.7	-	-	-	-	-	-	-	-	-	-	-	302
315	4.6	-	-	4.9	-	-	-	-	-	-	-	-	-	-	-	315
328	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	328

Remarks: see page 20

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb



TEREX | DEMAG

LIFTING CAPACITIES FIXED FLY JIB

 360° 85 %

169.9 ft Main boom

Fly jib														
	27.6 ft	47.2 ft	66.9 ft	86.6 ft			106.3 ft			126.0 ft				
Radius	0°	0°	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	Radius	
ft	1,000 lb													ft
39	117.7	-	-	-	-	-	-	-	-	-	-	-	39	
46	106.0	89.1	76.1	-	-	-	-	-	-	-	-	-	46	
53	96.1	81.6	70.1	60.6	-	-	-	-	-	-	-	-	53	
59	87.5	75.0	64.6	56.0	-	-	48.5	-	-	42.8	-	-	59	
66	80.0	69.0	59.7	51.6	45.2	-	45.0	-	-	39.7	-	-	66	
72	73.6	63.7	55.3	47.8	42.3	39.5	41.7	-	-	36.8	-	-	72	
79	68.6	59.3	51.7	44.5	39.7	37.3	38.8	34.2	-	34.3	30.6	-	79	
85	63.5	54.9	48.1	41.2	37.3	35.3	35.9	32.0	-	31.7	28.7	-	85	
92	59.5	51.3	45.3	38.7	35.1	33.3	33.7	30.2	28.0	29.7	26.9	25.6	92	
98	55.6	47.6	42.5	36.2	33.1	31.5	31.5	28.4	26.7	27.6	25.4	24.0	98	
105	52.1	44.9	40.3	34.1	31.3	30.0	29.7	26.9	25.4	25.9	24.0	22.9	105	
112	48.7	42.1	38.1	32.0	29.5	28.4	27.8	25.4	24.3	24.3	22.5	21.6	112	
118	45.9	39.7	36.3	30.3	28.2	27.1	26.2	24.3	23.1	22.8	21.2	20.5	118	
125	43.0	37.3	34.4	28.7	26.7	26.0	24.7	22.9	22.0	21.4	20.1	19.4	125	
131	40.6	35.3	32.7	27.3	25.6	24.9	23.5	21.8	20.9	20.2	19.0	18.5	131	
144	36.0	31.7	29.7	24.8	23.4	22.7	21.2	19.8	19.2	18.0	17.0	16.8	144	
158	32.3	28.8	26.9	22.5	21.4	21.2	19.2	18.1	17.6	16.1	15.4	15.2	158	
171	29.3	26.1	24.5	20.5	19.6	19.5	17.4	16.5	16.3	14.4	13.9	13.7	171	
184	26.8	23.9	22.5	18.7	18.1	18.1	15.8	15.2	15.1	12.9	12.6	12.5	184	
197	-	21.6	20.7	17.3	16.8	-	14.6	14.0	14.0	11.8	11.4	11.5	197	
210	-	-	19.3	15.9	15.5	-	13.4	12.9	-	10.6	10.4	10.6	210	
223	-	-	17.8	14.6	14.3	-	12.3	11.9	-	9.7	9.5	9.7	223	
236	-	-	-	13.4	-	-	11.2	11.1	-	8.8	8.7	-	236	
249	-	-	-	-	-	-	10.4	10.4	-	8.0	7.9	-	249	
263	-	-	-	-	-	-	9.6	-	-	7.4	7.4	-	263	
276	-	-	-	-	-	-	-	-	-	6.7	-	-	276	
289	-	-	-	-	-	-	-	-	-	-	-	-	289	

145.7 ft				165.4 ft			185.0 ft			204.7 ft				
ft							1,000 lb							ft
66	35.7	-	-	-	-	-	-	-	-	-	-	-	-	66
72	33.3	-	-	29.5	-	-	26.5	-	-	-	-	-	-	72
79	31.1	-	-	27.6	-	-	24.7	-	-	-	21.6	-	-	79
85	28.9	-	-	25.6	-	-	22.9	-	-	-	20.1	-	-	85
92	27.0	24.0	-	23.8	-	-	21.4	-	-	-	18.6	-	-	92
98	25.1	22.7	-	22.0	20.5	-	19.8	-	-	-	17.2	-	-	98
105	23.5	21.4	-	20.6	19.2	-	18.4	17.0	-	-	16.0	-	-	105
112	21.8	20.1	19.0	19.2	18.1	-	17.0	15.9	-	-	14.8	14.1	-	112
118	20.5	19.0	18.1	18.0	17.0	16.3	15.9	15.0	-	-	13.7	13.2	-	118
125	19.2	17.9	17.2	16.8	15.9	15.4	14.8	14.1	-	-	12.6	12.3	-	125
131	18.1	17.0	16.3	15.7	15.0	14.6	13.8	13.2	12.8	-	11.7	11.5	-	131
144	16.1	15.2	14.8	13.7	13.2	13.0	11.9	11.5	11.2	-	9.9	9.9	9.9	144
158	14.3	13.7	13.2	12.1	11.7	11.7	10.3	10.1	9.9	-	8.4	8.4	8.6	158
171	12.8	12.2	12.0	10.8	10.4	10.4	8.9	8.8	8.9	-	7.1	7.2	7.4	171
184	11.5	11.1	10.9	9.6	9.1	9.1	7.8	7.7	7.8	-	5.8	6.1	6.3	184
197	10.3	10.0	9.9	8.3	8.2	8.2	6.8	6.7	6.8	-	4.9	5.1	5.3	197
210	9.3	9.0	9.0	7.3	7.3	7.3	6.0	5.8	6.0	-	-	-	4.4	210
223	8.4	8.2	8.2	6.4	6.4	6.4	5.2	5.1	5.1	-	-	-	-	223
236	7.5	7.3	7.5	5.6	5.6	5.7	-	-	4.4	-	-	-	-	236
249	6.7	6.6	-	4.9	4.9	5.0	-	-	-	-	-	-	-	249
263	6.1	6.1	-	-	-	-	-	-	-	-	-	-	-	263
276	5.5	5.5	-	-	-	-	-	-	-	-	-	-	-	276
289	5.1	5.1	-	-	-	-	-	-	-	-	-	-	-	289
302	4.6	-	-	-	-	-	-	-	-	-	-	-	-	302
315	-	-	-	-	-	-	-	-	-	-	-	-	-	315

Remarks

Counterweight 88,200 lb 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb

Max. capacities with minimum counterweight · Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES FIXED FLY JIB WITH SSL**

360°															85 %	
169.9 ft Main boom																
Fly jib																
Radius	27.6 ft	47.2 ft	66.9 ft	86.6 ft			106.3 ft			126.0 ft			Radius			
	0°	0°	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°				
ft	1,000 lb															ft
33	179.5	-	-	-	-	-	-	-	-	-	-	-	-	33		
39	166.0	145.9	126.8	73.9	-	-	-	-	-	-	-	-	-	39		
46	153.4	134.5	116.0	97.0	-	-	80.7	-	-	-	-	-	-	46		
53	141.5	124.1	106.5	89.7	-	-	75.0	-	-	66.1	-	-	-	53		
59	130.7	114.6	97.9	83.1	63.3	-	70.1	-	-	61.9	-	-	-	59		
66	120.8	106.0	90.4	77.4	59.5	51.1	65.5	47.4	-	58.0	-	-	-	66		
72	115.1	98.3	83.8	72.1	56.0	48.7	61.3	45.0	-	54.5	40.8	-	-	72		
79	109.7	91.6	78.3	67.6	52.9	46.5	57.7	42.5	-	51.3	38.8	-	-	79		
85	104.3	86.9	72.8	63.1	50.0	44.5	54.0	40.3	35.3	48.1	36.6	31.7	-	85		
92	99.4	82.3	68.9	59.4	47.4	42.5	51.0	38.4	34.0	45.3	34.8	30.4	-	92		
98	94.6	77.8	65.3	55.8	45.2	40.8	48.1	36.4	32.8	42.5	32.8	29.3	-	98		
105	88.8	74.0	61.9	52.8	43.0	39.2	45.6	34.6	31.5	40.3	31.3	28.2	-	105		
112	83.1	70.1	58.6	49.8	41.0	37.5	43.2	32.8	30.4	38.1	29.8	26.9	-	112		
118	76.8	66.8	55.8	47.3	39.2	36.2	41.1	31.3	29.1	36.2	28.2	26.0	-	118		
125	70.5	63.5	52.9	44.8	37.5	34.6	39.0	29.8	28.0	34.2	26.9	24.9	-	125		
131	65.4	60.6	50.5	42.7	36.2	33.5	37.3	28.4	26.9	32.6	25.6	23.8	-	131		
144	55.9	55.2	46.2	38.7	33.3	31.1	34.0	25.8	24.7	29.7	23.4	22.0	-	144		
158	48.0	49.1	42.7	35.1	30.6	28.9	31.0	23.8	22.7	27.0	21.2	20.3	-	158		
171	41.2	42.3	39.7	31.9	28.4	27.1	28.3	22.3	20.9	24.7	19.6	18.7	-	171		
184	32.6	36.4	37.3	28.9	26.7	25.4	25.8	20.7	19.6	22.5	18.1	17.2	-	184		
197	-	30.0	34.4	27.6	24.9	-	23.6	19.6	18.5	20.7	16.8	15.9	-	197		
210	-	-	30.2	26.1	23.4	-	21.5	18.7	-	19.0	15.4	14.8	-	210		
223	-	-	23.4	24.5	21.8	-	20.1	17.9	-	17.4	14.6	-	-	223		
236	-	-	-	20.6	-	-	19.1	17.0	-	15.8	13.4	-	-	236		
249	-	-	-	-	-	-	17.9	16.3	-	14.6	12.3	-	-	249		
263	-	-	-	-	-	-	13.9	-	-	13.7	11.5	-	-	263		
276	-	-	-	-	-	-	-	-	-	12.0	-	-	-	276		

145.7 ft				165.4 ft			185.0 ft			204.7 ft			
ft							1,000 lb						ft
53	40.8	-	-	-	-	-	-	-	-	-	-	-	53
59	54.2	-	-	47.6	-	-	-	-	-	-	-	-	59
66	50.9	-	-	45.0	-	-	28.9	-	-	23.4	-	-	66
72	47.8	-	-	42.8	-	-	39.0	-	-	22.9	-	-	72
79	45.1	-	-	40.5	-	-	36.5	-	-	32.6	-	-	79
85	42.3	29.8	-	38.1	28.0	-	34.2	-	-	30.4	-	-	85
92	40.0	28.7	-	36.2	26.5	-	32.1	-	-	28.5	-	-	92
98	37.7	27.3	-	34.2	25.1	-	30.0	-	-	26.7	-	-	98
105	35.6	26.2	22.7	32.3	23.8	20.9	28.2	21.4	-	25.0	17.9	-	105
112	33.5	25.1	21.8	30.4	22.5	20.1	26.5	20.3	-	23.4	17.0	-	112
118	31.9	24.0	21.2	28.8	21.4	19.2	24.9	19.2	-	21.9	16.3	-	118
125	30.2	22.9	20.3	27.1	20.3	18.3	23.4	18.1	16.3	20.5	15.4	-	125
131	28.7	21.8	19.6	25.6	19.2	17.4	22.0	17.2	15.7	19.3	14.8	13.9	131
144	25.9	19.8	18.3	22.8	17.2	15.9	19.6	15.4	14.1	17.0	13.2	12.6	144
158	23.5	18.1	17.0	20.4	15.7	14.6	17.6	13.7	12.8	15.1	11.7	11.2	158
171	21.3	16.5	15.9	18.2	14.1	13.2	16.0	12.3	11.5	13.6	10.4	9.9	171
184	19.4	15.2	14.8	16.5	12.8	12.1	14.6	11.0	10.4	12.1	9.0	8.6	184
197	17.7	14.1	13.7	14.9	11.7	11.2	13.2	9.7	9.3	10.8	7.7	7.3	197
210	16.2	13.0	12.8	13.6	10.6	10.4	12.0	8.6	8.2	9.6	6.4	6.0	210
223	14.8	12.1	11.9	12.3	9.7	9.5	10.8	7.5	7.1	8.6	5.1	4.6	223
236	13.6	11.5	11.0	11.4	9.0	8.8	9.9	6.6	6.2	7.7	-	-	236
249	12.3	10.8	-	10.4	8.2	8.2	9.0	5.5	5.1	6.8	-	-	249
263	11.2	10.1	-	9.5	7.5	-	8.2	4.6	-	6.0	-	-	263
276	10.3	9.5	-	8.6	6.8	-	7.3	-	-	5.3	-	-	276
289	9.6	-	-	7.7	6.0	-	6.6	-	-	4.6	-	-	289
302	-	-	-	6.8	5.1	-	5.7	-	-	-	-	-	302
315	-	-	-	5.7	-	-	5.0	-	-	-	-	-	315

Remarks: see page 22

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb



LIFTING CAPACITIES FIXED FLY JIB

 360°															85 %	
139.4 ft Main boom																
Fly jib																
27.6 ft		47.2 ft		66.9 ft		86.6 ft			106.3 ft			126.0 ft				
Radius	0°	0°	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	Radius
ft	1,000 lb															ft
33	172.6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	33
39	152.3	137.8	107.6	-	-	-	-	-	-	-	-	-	-	-	-	39
46	135.1	122.4	101.0	97.0	-	-	-	-	-	-	-	-	-	-	-	46
53	121.0	109.6	94.6	88.6	-	-	-	76.7	-	-	-	-	67.0	-	-	53
59	109.1	98.5	88.2	81.1	68.3	-	-	72.1	-	-	-	-	63.1	-	-	59
66	99.2	89.3	82.2	74.5	65.3	56.7	-	67.5	50.3	-	-	-	59.5	-	-	66
72	91.1	81.6	76.5	68.6	62.2	54.7	-	63.1	47.8	-	-	-	56.0	46.3	-	72
79	84.4	75.5	71.2	63.6	59.1	52.7	-	59.1	45.6	39.5	-	-	52.8	43.9	-	79
85	77.8	69.4	65.9	58.6	55.8	50.9	-	55.1	43.7	38.1	-	-	49.6	41.7	38.1	85
92	72.6	64.8	61.3	54.8	52.9	48.7	-	51.5	41.7	37.0	-	-	46.6	39.7	36.6	92
98	67.5	60.2	56.7	50.9	49.8	46.7	-	47.8	39.7	35.7	-	-	43.7	37.7	35.3	98
105	63.2	56.3	53.0	47.8	47.0	44.8	-	44.8	37.9	34.6	-	-	41.1	35.9	34.0	105
112	58.9	52.5	49.4	44.8	44.1	42.8	-	41.7	36.2	33.3	-	-	38.6	34.4	32.6	112
118	55.4	49.3	46.4	42.1	41.7	40.8	-	39.0	34.6	32.2	-	-	36.3	32.8	31.5	118
125	52.0	46.1	43.4	39.5	39.2	38.8	-	36.4	33.1	31.1	-	-	34.0	31.5	30.4	125
131	49.1	43.5	41.2	37.3	37.0	36.8	-	34.3	31.5	30.0	-	-	32.1	30.2	29.3	131
144	43.4	39.0	37.3	33.2	33.1	33.3	-	30.4	28.7	27.8	-	-	28.5	27.6	27.1	144
158	37.9	35.3	34.0	29.8	29.8	30.0	-	27.3	26.0	25.6	-	-	25.4	25.1	25.1	158
171	-	32.1	31.2	27.0	26.8	-	-	24.7	23.6	23.6	-	-	22.8	22.8	22.9	171
184	-	-	28.7	24.6	24.0	-	-	22.7	21.5	21.6	-	-	20.5	20.5	20.7	184
197	-	-	-	22.5	21.4	-	-	20.9	19.6	-	-	-	18.5	18.4	18.4	197
210	-	-	-	20.7	-	-	-	19.2	18.1	-	-	-	16.9	16.5	-	210
223	-	-	-	-	-	-	-	17.6	16.8	-	-	-	15.4	14.8	-	223
236	-	-	-	-	-	-	-	-	-	-	-	-	14.0	13.5	-	236
249	-	-	-	-	-	-	-	-	-	-	-	-	12.6	-	-	249

145.7 ft				165.4 ft			185.0 ft			204.7 ft			
ft							1,000 lb						ft
59	55.8	-	-	48.1	-	-	-	-	-	-	-	-	59
66	52.2	-	-	44.8	-	-	39.7	-	-	-	-	-	66
72	48.9	-	-	41.9	-	-	37.0	-	-	-	32.2	-	72
79	46.1	-	-	39.2	-	-	34.7	-	-	-	30.1	-	79
85	43.2	33.7	-	36.6	31.3	-	32.4	-	-	-	28.0	-	85
92	40.7	32.6	-	34.4	29.8	-	30.4	-	-	-	26.1	-	92
98	38.1	31.3	26.5	32.2	28.4	-	28.4	23.8	-	-	24.3	-	98
105	36.0	30.2	26.2	30.5	27.3	25.8	26.8	22.7	-	-	22.7	21.2	105
112	34.0	29.3	26.0	28.9	26.0	24.7	25.1	21.8	-	-	21.2	20.1	112
118	32.1	28.2	25.6	27.3	24.9	23.6	23.8	20.9	-	-	20.0	19.2	118
125	30.2	27.3	25.1	25.8	23.8	22.5	22.5	20.1	19.4	-	18.7	18.1	125
131	28.7	26.2	24.5	24.7	22.9	21.6	21.3	19.4	18.5	-	17.6	17.2	131
144	25.7	24.5	23.4	22.5	20.9	19.8	19.1	17.9	17.0	-	15.5	15.7	144
158	23.1	22.7	21.8	20.5	19.4	18.1	17.2	16.3	15.7	-	13.9	14.1	158
171	20.7	20.7	20.3	18.7	17.7	16.6	15.5	15.0	14.3	-	12.6	12.8	171
184	18.7	19.0	18.7	17.0	16.2	15.2	14.0	13.7	13.2	-	11.4	11.6	184
197	17.0	17.2	17.0	15.3	14.7	14.0	12.6	12.5	12.0	-	10.3	10.6	197
210	15.2	15.4	15.5	13.7	13.2	12.8	11.3	11.2	10.9	-	9.3	9.6	210
223	13.7	13.7	-	12.2	11.7	11.6	10.1	9.9	9.8	-	8.4	8.6	223
236	12.2	12.1	-	10.7	10.4	-	9.0	8.7	8.8	-	7.5	7.7	236
249	10.9	10.8	-	9.2	9.1	-	7.6	7.6	7.9	-	6.5	6.7	249
263	9.5	-	-	7.8	7.9	-	6.4	6.6	-	-	5.2	5.5	263
276	-	-	-	6.2	7.1	-	5.1	5.7	-	-	-	-	276
289	-	-	-	4.8	-	-	-	-	-	-	-	-	289
302	-	-	-	-	-	-	-	-	-	-	-	-	302

Remarks

Counterweight

88,200 lb

132,300 lb

176,400 lb

220,500 lb

264,600 lb

308,600 lb

352,700 lb


Max. capacities with minimum counterweight

Further counterweight configurations on request



ALL TERRAIN CRANE
AC 500-2

WORKING RANGES LUFFING FLY JIB, MAIN BOOM 83° TO 65° WITH / WITHOUT SSL



**LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°**

360°85 %																					
48.2 ft + 13.1 ft Main boom + adapter																					
Fly jib																					
		78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius		83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft		1,000 lb																		ft	
46		257.9	-	-	224.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	46	
53		235.9	-	-	216.1	-	-	188.5	-	-	151.5	-	-	-	-	-	-	-	-	53	
59		213.4	-	-	206.1	-	-	185.2	-	-	151.5	-	-	119.9	-	-	-	-	-	59	
66		191.8	-	-	190.7	-	-	181.9	-	-	151.5	-	-	119.9	-	-	108.0	-	-	66	
72		173.7	167.1	-	172.8	165.8	-	171.1	-	-	151.5	-	-	119.9	-	-	108.0	-	-	72	
79		158.7	152.6	-	157.6	151.5	-	155.9	149.5	-	149.3	-	-	119.9	-	-	108.0	-	-	79	
85		119.0	140.2	135.8	144.8	139.1	-	143.3	137.1	-	141.5	-	-	119.5	-	-	108.0	-	-	85	
92		-	129.6	125.7	134.0	128.5	124.3	132.3	126.5	-	130.5	124.8	-	114.9	-	-	108.0	-	-	92	
98		-	-	116.8	116.8	119.3	115.5	122.8	117.5	-	121.0	115.7	-	110.2	113.3	-	106.9	-	-	98	
105		-	-	-	-	111.3	107.6	114.4	109.3	105.6	112.7	107.6	-	105.6	108.9	-	105.2	104.5	-	105	
112		-	-	-	-	104.3	100.8	100.1	102.3	98.8	105.4	100.5	-	101.0	101.6	-	103.4	100.1	-	112	
118		-	-	-	-	-	94.8	83.1	96.1	92.6	98.8	94.1	90.8	95.9	95.5	-	98.5	93.7	-	118	
125		-	-	-	-	-	-	-	90.4	87.3	90.8	88.6	85.3	91.1	89.7	86.4	92.6	88.2	-	125	
131		-	-	-	-	-	-	-	85.5	82.2	78.7	83.6	80.5	86.0	84.7	81.4	87.3	83.1	-	131	
138		-	-	-	-	-	-	-	-	77.8	65.9	78.9	75.8	80.9	80.0	76.9	82.5	78.5	75.4	138	
144		-	-	-	-	-	-	-	-	-	-	74.7	71.9	74.7	75.8	73.0	78.0	74.3	71.2	144	
151		-	-	-	-	-	-	-	-	-	-	70.8	68.1	65.5	71.9	69.2	74.1	70.3	67.5	151	
158		-	-	-	-	-	-	-	-	-	-	-	64.6	55.3	67.9	65.5	68.6	66.8	64.2	158	
164		-	-	-	-	-	-	-	-	-	-	-	-	-	64.6	62.2	61.1	63.3	60.8	164	
177		-	-	-	-	-	-	-	-	-	-	-	-	-	-	56.2	45.4	57.3	54.9	177	
190		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50.0	190	
		196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft				
ft		1,000 lb																		ft	
72		92.6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72	
79		92.6	-	-	74.1	-	-	62.8	-	-	-	-	-	-	-	-	-	-	-	79	
85		92.6	-	-	73.6	-	-	62.6	-	-	52.5	-	-	-	-	-	-	-	-	85	
92		92.6	-	-	73.2	-	-	62.4	-	-	51.8	-	-	41.7	-	-	-	-	-	92	
98		92.6	-	-	72.5	-	-	61.9	-	-	51.4	-	-	41.2	-	-	34.2	-	-	98	
105		91.7	-	-	72.1	-	-	61.7	-	-	50.9	-	-	40.6	-	-	33.5	-	-	105	
112		90.8	-	-	71.7	-	-	61.5	-	-	50.5	-	-	39.9	-	-	33.1	-	-	112	
118		89.5	84.9	-	71.0	-	-	61.1	-	-	49.8	-	-	39.2	-	-	32.4	-	-	118	
125		88.4	84.9	-	70.1	68.3	-	60.8	-	-	49.4	-	-	38.8	-	-	31.7	-	-	125	
131		86.6	82.2	-	69.4	67.9	-	60.2	-	-	48.7	-	-	38.1	-	-	31.3	-	-	131	
138		81.8	77.6	-	68.8	67.5	-	59.5	61.3	-	48.1	-	-	37.5	-	-	30.6	-	-	138	
144		77.4	73.4	-	68.1	67.2	-	59.1	60.6	-	47.4	49.2	-	36.8	-	-	30.0	-	-	144	
151		73.4	69.7	66.8	67.2	66.8	-	58.4	60.0	-	46.5	48.5	-	36.2	37.9	-	29.5	-	-	151	
158		69.7	66.1	63.5	65.7	64.4	61.5	58.0	59.3	-	45.9	47.8	-	35.5	37.0	-	28.9	-	-	158	
164		66.1	62.8	60.2	63.9	61.1	58.4	57.3	58.6	-	45.0	47.2	-	34.6	36.4	-	28.2	29.5	-	164	
177		57.1	56.7	54.2	58.2	55.1	52.7	55.6	53.6	50.9	43.4	45.6	-	33.3	34.6	-	27.1	28.2	-	177	
190		45.0	51.6	49.4	51.6	50.0	47.8	51.6	48.5	46.3	41.9	44.3	44.5	32.0	32.8	-	26.0	27.1	-	190	
203		-	47.2	45.0	41.9	45.4	43.4	46.3	44.1	41.9	40.1	43.0	41.7	30.6	31.3	32.4	24.9	25.8	26.9	203	
217		-	-	41.4	30.9	41.7	39.7	38.1	40.1	38.1	38.4	39.9	37.9	29.3	30.2	31.1	24.0	24.7	25.8	217	
230		-	-	-	-	-	36.4	29.5	36.8	35.1	35.5	36.6	34.6	28.2	29.1	29.8	23.1	23.8	24.7	230	
243		-	-	-	-	-	-	34.0	32.2	28.9	33.5	31.7	27.1	27.1	28.0	28.7	22.0	22.9	23.8	243	
256		-	-	-	-	-	-	-	-	-	-	30.9	29.1	26.2	27.1	27.6	21.2	21.8	22.7	256	
269		-	-	-	-	-	-	-	-	-	-	-	26.7	20.9	26.5	26.5	20.5	21.2	21.8	269	
282		-	-	-	-	-	-	-	-	-	-	-	-	-	24.9	24.3	19.6	20.5	21.2	282	
295		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	20.1	20.5	295	
308		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	19.6	308	
322		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	322	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°**

360°85 %																				
63.3 ft + 13.1 ft Main boom + adapter																				
Fly jib																				
78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft					
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft	1,000 lb																			ft
46	244.7	-	-	213.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	46	
53	229.3	-	-	203.9	-	-	172.6	-	-	-	-	-	-	-	-	-	-	-	53	
59	211.6	-	-	194.4	-	-	171.3	-	-	139.6	-	-	-	-	-	-	-	-	59	
66	189.8	-	-	185.0	-	-	170.0	-	-	139.6	-	-	114.6	-	-	102.5	-	-	66	
72	172.0	163.4	-	170.9	-	-	167.3	-	-	139.6	-	-	114.6	-	-	102.1	-	-	72	
79	157.2	149.0	-	156.1	147.7	-	154.3	-	-	139.6	-	-	114.6	-	-	101.6	-	-	79	
85	143.1	136.9	-	143.3	135.8	-	141.8	133.8	-	134.9	-	-	114.6	-	-	101.2	-	-	85	
92	-	126.5	121.3	132.5	125.4	-	130.7	123.5	-	129.2	-	-	112.4	-	-	100.8	-	-	92	
98	-	117.7	112.7	123.0	116.4	111.3	121.3	114.4	-	119.7	112.7	-	108.9	-	-	100.3	-	-	98	
105	-	-	105.2	100.5	108.5	103.8	113.1	106.7	-	111.3	104.7	-	105.6	106.0	-	99.6	-	-	105	
112	-	-	-	-	101.6	97.0	105.8	99.6	95.0	104.1	97.9	-	102.3	99.0	-	99.2	97.4	-	112	
118	-	-	-	-	95.5	91.3	92.2	93.5	89.1	97.7	91.7	-	97.7	92.8	-	97.4	91.3	-	118	
125	-	-	-	-	-	86.0	71.2	88.0	83.8	91.7	86.2	81.8	93.0	87.3	-	91.5	85.8	-	125	
131	-	-	-	-	-	-	-	83.1	79.1	86.0	81.1	77.2	87.7	82.5	-	86.2	80.7	-	131	
138	-	-	-	-	-	-	-	78.7	74.7	73.2	76.7	72.8	82.9	77.8	73.9	81.6	76.3	-	138	
144	-	-	-	-	-	-	-	-	71.0	57.1	72.5	69.0	78.0	73.6	69.9	77.2	72.1	68.1	144	
151	-	-	-	-	-	-	-	-	-	-	69.0	65.3	71.7	69.9	66.4	73.2	68.3	64.6	151	
158	-	-	-	-	-	-	-	-	-	-	65.3	61.9	61.5	66.1	62.8	69.2	64.8	61.3	158	
164	-	-	-	-	-	-	-	-	-	-	-	58.6	-	62.8	59.5	65.7	61.5	58.2	164	
177	-	-	-	-	-	-	-	-	-	-	-	-	-	-	54.0	50.0	55.6	52.5	177	
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50.5	47.8	190	
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43.7	203	
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	217	

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft					
ft	1,000 lb																			ft
72	86.6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72	
79	86.4	-	-	69.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79	
85	86.2	-	-	68.6	-	-	60.8	-	-	-	-	-	-	-	-	-	-	-	85	
92	85.8	-	-	68.1	-	-	60.6	-	-	47.8	-	-	-	-	-	-	-	-	92	
98	85.5	-	-	67.7	-	-	60.4	-	-	47.8	-	-	39.0	-	-	-	-	-	98	
105	85.1	-	-	67.0	-	-	60.2	-	-	47.6	-	-	38.6	-	-	31.7	-	-	105	
112	84.7	-	-	66.6	-	-	60.0	-	-	47.4	-	-	38.1	-	-	31.3	-	-	112	
118	84.0	-	-	66.1	-	-	59.5	-	-	47.4	-	-	37.7	-	-	30.9	-	-	118	
125	83.3	80.0	-	65.9	-	-	59.3	-	-	47.2	-	-	37.0	-	-	30.4	-	-	125	
131	82.7	80.0	-	65.5	65.5	-	58.9	-	-	46.7	-	-	36.6	-	-	29.8	-	-	131	
138	80.9	75.4	-	65.0	64.8	-	58.4	60.2	-	46.5	-	-	36.2	-	-	29.3	-	-	138	
144	76.5	71.4	-	64.6	64.2	-	57.8	59.5	-	45.9	-	-	35.5	-	-	28.9	-	-	144	
151	72.5	67.7	-	64.2	63.7	-	57.3	59.1	-	45.4	47.0	-	35.1	-	-	28.4	-	-	151	
158	68.8	64.2	60.6	63.3	62.4	-	56.9	58.6	-	44.8	46.3	-	34.4	35.7	-	27.8	-	-	158	
164	65.3	60.8	57.5	62.4	59.1	-	56.4	57.3	-	44.3	45.9	-	33.7	35.1	-	27.3	28.4	-	164	
177	58.9	54.9	52.0	57.5	53.6	50.3	55.3	51.8	-	43.2	45.0	-	32.6	34.0	-	26.5	27.3	-	177	
190	48.9	49.8	47.2	52.0	48.3	45.6	50.7	47.0	43.9	41.7	44.1	43.2	31.5	32.8	-	25.6	26.5	-	190	
203	-	45.6	43.0	45.2	44.1	41.4	46.1	42.5	39.7	40.1	42.3	39.5	30.4	31.5	32.8	24.5	25.4	-	203	
217	-	-	39.5	34.4	40.3	37.7	41.0	38.8	36.2	38.4	38.6	35.7	29.3	30.4	31.5	23.6	24.3	25.4	217	
230	-	-	-	-	37.0	34.6	32.4	35.5	33.1	36.4	35.3	32.6	28.2	29.3	30.2	22.7	23.6	24.3	230	
243	-	-	-	-	-	32.0	-	32.6	30.2	31.5	32.2	29.8	27.1	28.2	29.1	21.8	22.7	23.4	243	
256	-	-	-	-	-	-	-	-	27.6	23.4	29.8	27.1	26.5	27.3	26.9	20.9	22.0	22.5	256	
269	-	-	-	-	-	-	-	-	-	27.3	24.9	27.3	23.4	26.5	24.5	20.3	21.2	21.8	269	
282	-	-	-	-	-	-	-	-	-	-	-	22.7	-	24.7	22.5	19.6	20.7	21.2	282	
295	-	-	-	-	-	-	-	-	-	-	-	-	-	-	20.5	15.9	20.3	19.6	295	
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	19.8	18.1	308	
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	322	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°**

360°85 %																				
78.7 ft + 13.1 ft Main boom + adapter																				
Fly jib																				
78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft					
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft	1,000 lb																			ft
53	217.8	-	-	192.2	-	-	159.8	-	-	-	-	-	-	-	-	-	-	-	53	
59	203.7	-	-	183.4	-	-	158.3	-	-	130.7	-	-	-	-	-	-	-	-	59	
66	188.3	-	-	174.6	-	-	156.7	-	-	130.7	-	-	109.8	-	-	-	-	-	66	
72	170.4	-	-	166.0	-	-	155.2	-	-	130.7	-	-	109.8	-	-	96.8	-	-	72	
79	155.6	145.9	-	154.5	-	-	150.1	-	-	130.7	-	-	109.8	-	-	96.3	-	-	79	
85	143.1	134.0	-	142.0	132.9	-	140.2	-	-	129.4	-	-	109.8	-	-	95.7	-	-	85	
92	-	123.9	-	131.2	122.6	-	129.4	120.8	-	125.2	-	-	109.6	-	-	95.2	-	-	92	
98	-	115.1	109.1	121.9	113.8	-	120.2	112.0	-	118.4	-	-	107.1	-	-	94.6	-	-	98	
105	-	-	101.6	113.1	106.0	100.3	112.0	104.1	-	110.2	102.3	-	104.5	-	-	94.1	-	-	105	
112	-	-	95.2	-	99.2	93.9	104.7	97.4	-	103.0	95.5	-	102.1	96.8	-	93.7	-	-	112	
118	-	-	-	-	93.3	88.0	98.3	91.3	86.0	96.6	89.5	-	97.9	90.6	-	93.0	87.7	-	118	
125	-	-	-	-	-	82.9	80.2	85.8	80.9	90.8	84.0	-	92.2	85.3	-	90.6	83.6	-	125	
131	-	-	-	-	-	78.3	-	80.9	76.3	85.5	79.1	74.3	86.9	80.2	-	85.3	78.7	-	131	
138	-	-	-	-	-	-	-	76.7	72.1	78.9	74.7	70.1	82.2	75.8	-	80.7	74.3	-	138	
144	-	-	-	-	-	-	-	-	68.3	64.4	70.8	66.4	77.8	71.9	67.5	76.3	70.1	-	144	
151	-	-	-	-	-	-	-	-	64.6	-	67.0	62.8	73.6	68.1	63.9	72.3	66.6	62.2	151	
158	-	-	-	-	-	-	-	-	-	-	63.5	59.5	66.1	64.6	60.6	68.6	63.3	58.9	158	
164	-	-	-	-	-	-	-	-	-	-	-	56.4	54.5	61.3	57.3	65.0	60.0	56.0	164	
177	-	-	-	-	-	-	-	-	-	-	-	-	-	55.3	51.8	54.0	54.0	50.5	177	
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	47.2	-	49.2	45.9	190	
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	41.9	203	
196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft					
ft	1,000 lb																			ft
79	82.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79	
85	81.4	-	-	63.9	-	-	57.3	-	-	-	-	-	-	-	-	-	-	-	85	
92	80.9	-	-	63.5	-	-	56.9	-	-	46.3	-	-	-	-	-	-	-	-	92	
98	80.5	-	-	63.3	-	-	56.7	-	-	46.3	-	-	36.6	-	-	-	-	-	98	
105	80.0	-	-	62.8	-	-	56.4	-	-	46.1	-	-	36.2	-	-	31.1	-	-	105	
112	79.6	-	-	62.4	-	-	56.2	-	-	45.9	-	-	35.9	-	-	30.6	-	-	112	
118	79.1	-	-	61.9	-	-	56.0	-	-	45.6	-	-	35.7	-	-	30.2	-	-	118	
125	78.7	-	-	61.5	-	-	55.8	-	-	45.4	-	-	35.5	-	-	29.8	-	-	125	
131	78.3	75.8	-	61.3	-	-	55.3	-	-	45.2	-	-	35.3	-	-	29.3	-	-	131	
138	77.8	73.4	-	60.8	61.5	-	55.1	-	-	45.2	-	-	35.1	-	-	28.9	-	-	138	
144	75.6	69.4	-	60.4	60.8	-	54.9	52.9	-	44.8	-	-	34.6	-	-	28.2	-	-	144	
151	71.7	65.7	-	60.0	60.4	-	54.5	52.5	-	44.3	-	-	34.2	-	-	27.8	-	-	151	
158	68.1	62.4	-	59.5	60.0	-	54.2	52.2	-	43.9	44.1	-	33.7	-	-	27.3	-	-	158	
164	64.6	59.3	55.1	59.1	57.5	-	54.0	51.8	-	43.4	43.9	-	33.1	34.4	-	26.9	-	-	164	
177	58.2	53.6	49.8	56.9	52.0	48.1	53.4	50.0	-	42.8	43.2	-	32.2	33.5	-	26.0	27.1	-	177	
190	52.9	48.5	45.2	51.6	47.0	43.4	50.0	45.4	41.7	41.7	42.8	-	31.1	32.6	-	24.9	26.2	-	190	
203	38.4	44.3	41.2	47.0	42.8	39.5	45.6	41.2	37.7	40.1	41.0	37.3	30.2	31.5	-	24.0	25.1	-	203	
217	-	40.8	37.7	37.3	39.0	35.9	41.7	37.5	34.2	38.6	37.3	33.7	29.1	30.6	31.7	23.1	24.3	-	217	
230	-	-	34.8	-	35.9	33.1	35.9	34.4	31.1	37.0	34.0	30.9	28.2	29.5	30.4	22.5	23.4	24.5	230	
243	-	-	-	-	-	30.2	-	31.5	28.4	33.7	31.1	28.0	27.1	28.7	27.6	21.8	22.7	23.6	243	
256	-	-	-	-	-	-	-	28.9	25.8	25.8	28.4	25.4	26.5	27.6	25.1	20.9	22.0	22.7	256	
269	-	-	-	-	-	-	-	-	23.8	-	26.0	23.1	25.4	25.8	22.9	20.3	21.4	22.0	269	
282	-	-	-	-	-	-	-	-	-	-	-	21.2	-	23.6	20.7	19.8	20.7	19.8	282	
295	-	-	-	-	-	-	-	-	-	-	-	-	-	21.8	19.0	17.6	20.3	18.1	295	
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	17.4	-	19.2	16.5	308	
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	15.0	322	
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	335	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°**

360°85 %																					
93.8 ft + 13.1 ftMain boom + adapter																					
Fly jib																					
		78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius		83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft		1,000 lb																			ft
53	188.7	-	-		166.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	53	
59	178.1	-	-		160.1	-	-	139.3	-	-	-	-	-	-	-	-	-	-	-	59	
66	168.4	-	-		154.1	-	-	137.1	-	-	115.5	-	-	98.3	-	-	-	-	-	66	
72	159.0	-	-		147.7	-	-	134.7	-	-	114.9	-	-	98.1	-	-	86.6	-	-	72	
79	151.2	-	-		141.3	-	-	131.8	-	-	114.2	-	-	97.9	-	-	86.0	-	-	79	
85	142.0	124.3	-		134.9	-	-	127.0	-	-	113.3	-	-	97.7	-	-	85.5	-	-	85	
92	-	116.0	-		130.1	114.0	-	122.4	-	-	110.2	-	-	97.4	-	-	84.9	-	-	92	
98	-	109.3	-		121.0	106.9	-	117.7	101.9	-	106.9	-	-	96.3	-	-	84.2	-	-	98	
105	-	105.2	95.5		112.9	101.4	-	111.1	96.6	-	103.8	93.7	-	94.8	-	-	83.8	-	-	105	
112	-	-	89.7		-	95.9	88.6	103.8	91.5	-	100.5	89.3	-	93.0	-	-	83.1	-	-	112	
118	-	-	85.5		-	91.5	83.8	97.4	87.5	-	95.7	84.9	-	91.5	84.7	-	82.7	-	-	118	
125	-	-	-		-	86.2	78.9	87.7	83.8	75.4	89.9	80.5	-	89.7	81.1	-	82.0	76.9	-	125	
131	-	-	-		-	-	75.6	-	79.4	71.9	84.9	77.2	-	86.2	77.4	-	81.4	73.9	-	131	
138	-	-	-		-	-	72.1	-	75.2	68.3	80.2	73.2	67.0	81.4	73.9	-	79.8	71.0	-	138	
144	-	-	-		-	-	-	-	71.2	65.7	70.1	69.2	63.9	77.2	70.3	-	75.6	67.9	-	144	
151	-	-	-		-	-	-	-	-	62.8	-	65.7	60.6	73.0	66.8	61.9	71.7	64.8	-	151	
158	-	-	-		-	-	-	-	-	59.5	-	62.2	57.8	69.2	63.3	58.9	67.9	61.7	-	158	
164	-	-	-		-	-	-	-	-	-	-	59.1	54.7	59.3	60.0	55.8	64.4	58.6	54.0	164	
177	-	-	-		-	-	-	-	-	-	-	-	49.4	-	54.2	50.3	58.2	52.9	48.7	177	
190	-	-	-		-	-	-	-	-	-	-	-	-	-	-	45.6	-	48.1	44.3	190	
203	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	43.9	40.3	203	
217	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	37.0	217	
230	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	230	

		196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft				
ft		1,000 lb																		ft	
79	75.4	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79	
85	74.7	-	-		58.6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85	
92	74.3	-	-		58.4	-	-	51.6	-	-	-	-	-	-	-	-	-	-	-	92	
98	73.9	-	-		58.2	-	-	51.4	-	-	41.7	-	-	-	-	-	-	-	-	98	
105	73.2	-	-		58.0	-	-	51.1	-	-	41.7	-	-	34.2	-	-	28.0	-	-	105	
112	72.8	-	-		57.8	-	-	50.9	-	-	41.4	-	-	34.0	-	-	27.8	-	-	112	
118	72.1	-	-		57.5	-	-	50.7	-	-	41.4	-	-	33.7	-	-	27.6	-	-	118	
125	71.7	-	-		57.1	-	-	50.5	-	-	41.4	-	-	33.3	-	-	27.3	-	-	125	
131	71.0	-	-		56.9	-	-	50.0	-	-	41.2	-	-	33.1	-	-	27.1	-	-	131	
138	70.5	66.6	-		56.7	-	-	49.8	-	-	41.2	-	-	32.8	-	-	26.9	-	-	138	
144	69.9	64.4	-		56.4	54.0	-	49.6	-	-	41.0	-	-	32.6	-	-	26.7	-	-	144	
151	69.2	62.4	-		56.2	53.1	-	49.4	49.2	-	40.8	-	-	32.2	-	-	26.5	-	-	151	
158	67.5	60.2	-		56.0	52.2	-	49.2	48.3	-	40.6	-	-	32.0	-	-	26.2	-	-	158	
164	63.9	58.0	-		55.8	51.1	-	48.9	47.4	-	40.3	40.6	-	31.7	-	-	25.8	-	-	164	
177	57.8	52.2	48.1		55.3	49.4	-	48.3	45.4	-	39.7	40.1	-	31.1	32.0	-	25.1	-	-	177	
190	52.5	47.4	43.7		50.9	45.9	41.9	48.1	43.7	-	39.2	39.5	-	30.6	31.5	-	24.5	25.6	-	190	
203	41.7	43.2	39.7		46.5	41.7	37.9	45.2	40.1	35.9	38.4	39.0	-	30.0	31.1	-	23.8	24.7	-	203	
217	-	39.7	36.4		40.8	38.1	34.6	41.2	36.6	32.6	37.5	36.2	32.2	29.1	30.4	-	23.1	23.8	-	217	
230	-	-	33.3		-	34.8	31.3	37.7	33.3	29.5	36.6	33.1	29.1	28.0	29.8	28.9	22.5	23.1	-	230	
243	-	-	-		-	32.2	28.7	27.6	30.4	26.9	34.4	30.0	26.5	27.1	28.7	26.0	21.8	22.5	23.8	243	
256	-	-	-		-	-	26.2	-	28.0	24.5	27.6	27.3	24.0	26.5	27.1	23.6	21.2	21.8	22.7	256	
269	-	-	-		-	-	-	-	-	22.3	-	25.1	21.8	25.8	24.9	21.4	20.5	21.4	20.5	269	
282	-	-	-		-	-	-	-	-	-	-	22.9	19.8	19.2	22.7	19.4	19.8	20.7	18.5	282	
295	-	-	-		-	-	-	-	-	-	-	-	18.1	-	20.7	17.6	19.2	20.1	16.8	295	
308	-	-	-		-	-	-	-	-	-	-	-	-	-	-	16.1	-	18.3	15.2	308	
322	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	16.8	13.9	322	
335	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	12.6	335	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



TEREX | DEMAG

LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°

 360° **85 %**

108.9 ft + 13.1 ft Main boom + adapter

Fly jib																				
78.7 ft				98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft	1,000 lb																			ft
59	160.5	-	-	144.2	-	-	128.8	-	-	-	-	-	-	-	-	-	-	-	59	
66	151.2	-	-	138.2	-	-	124.8	-	-	105.4	-	-	-	-	-	-	-	-	66	
72	141.8	-	-	132.3	-	-	121.0	-	-	103.8	-	-	90.2	-	-	-	-	-	72	
79	134.5	-	-	126.3	-	-	117.1	-	-	102.3	-	-	89.5	-	-	76.9	-	-	79	
85	129.2	-	-	120.6	-	-	112.7	-	-	100.8	-	-	88.8	-	-	76.1	-	-	85	
92	125.0	103.8	-	115.7	100.1	-	108.0	-	-	98.5	-	-	88.2	-	-	75.4	-	-	92	
98	-	97.4	-	111.8	94.6	-	103.6	-	-	95.5	-	-	87.3	-	-	74.7	-	-	98	
105	-	92.6	-	108.9	89.3	-	100.3	85.1	-	92.2	-	-	85.8	-	-	73.9	-	-	105	
112	-	87.7	-	100.8	84.2	-	97.2	81.1	-	89.1	77.2	-	84.2	-	-	73.0	-	-	112	
118	-	-	74.1	-	80.5	-	94.6	77.2	-	86.4	73.9	-	82.7	-	-	71.9	-	-	118	
125	-	-	69.9	-	76.7	68.8	91.1	73.4	-	84.0	70.3	-	81.1	70.5	-	70.8	-	-	125	
131	-	-	-	-	75.0	65.5	71.2	70.5	62.6	81.6	67.2	-	79.4	67.7	-	69.9	64.6	-	131	
138	-	-	-	-	-	61.9	-	67.9	59.7	79.4	63.9	-	77.6	64.6	-	68.8	62.2	-	138	
144	-	-	-	-	-	60.0	-	66.6	57.1	75.4	61.7	55.3	75.6	61.9	-	67.7	59.7	-	144	
151	-	-	-	-	-	-	-	65.0	54.7	57.5	59.3	52.7	72.5	59.3	-	66.6	57.1	-	151	
158	-	-	-	-	-	-	-	-	52.9	-	57.8	50.5	68.8	57.3	50.5	65.3	54.9	-	158	
164	-	-	-	-	-	-	-	-	51.1	-	56.2	48.3	63.5	55.6	48.3	63.9	52.5	-	164	
177	-	-	-	-	-	-	-	-	-	-	-	44.8	-	52.0	44.5	57.8	49.4	42.8	177	
190	-	-	-	-	-	-	-	-	-	-	-	-	-	48.5	41.2	40.3	46.1	39.5	190	
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	39.7	-	43.0	36.6	203	
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	34.8	217	

196.9 ft				216.5 ft				236.2 ft				255.9 ft				275.6 ft				295.3 ft				
ft	1,000 lb																			ft				
85	68.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85			
92	67.7	-	-	53.8	-	-	45.6	-	-	-	-	-	-	-	-	-	-	-	-	-	92			
98	67.0	-	-	53.6	-	-	45.4	-	-	38.4	-	-	-	-	-	-	-	-	-	-	98			
105	66.4	-	-	53.4	-	-	45.2	-	-	38.1	-	-	31.1	-	-	-	-	-	-	-	105			
112	65.7	-	-	53.1	-	-	45.0	-	-	38.1	-	-	30.9	-	-	24.7	-	-	-	-	112			
118	65.0	-	-	52.9	-	-	45.0	-	-	37.9	-	-	30.9	-	-	24.5	-	-	-	-	118			
125	64.4	-	-	52.7	-	-	44.8	-	-	37.9	-	-	30.6	-	-	24.5	-	-	-	-	125			
131	63.9	-	-	52.2	-	-	44.5	-	-	37.7	-	-	30.6	-	-	24.3	-	-	-	-	131			
138	63.3	-	-	51.8	-	-	44.3	-	-	37.5	-	-	30.4	-	-	24.0	-	-	-	-	138			
144	62.6	57.5	-	51.6	-	-	44.3	-	-	37.5	-	-	30.4	-	-	24.0	-	-	-	-	144			
151	61.9	55.6	-	51.1	47.8	-	44.1	-	-	37.3	-	-	30.2	-	-	23.8	-	-	-	-	151			
158	61.1	53.4	-	50.7	46.7	-	44.1	42.5	-	37.3	-	-	30.0	-	-	23.6	-	-	-	-	158			
164	60.0	51.4	-	50.3	45.4	-	43.9	41.4	-	37.3	-	-	30.0	-	-	23.6	-	-	-	-	164			
177	57.3	47.4	-	49.6	43.0	-	43.7	39.5	-	37.0	34.6	-	29.8	29.5	-	23.1	-	-	-	-	177			
190	52.0	44.5	38.8	48.7	40.6	36.8	43.2	37.5	-	36.8	33.7	-	29.5	29.3	-	22.9	23.4	-	-	-	190			
203	44.8	41.9	35.7	46.1	38.1	33.7	42.5	35.5	32.2	36.4	32.8	-	29.3	29.3	-	22.7	23.1	-	-	-	203			
217	-	38.8	33.3	42.1	35.9	31.1	40.8	33.5	29.5	35.9	31.7	28.7	28.7	29.1	-	22.5	22.9	-	-	-	217			
230	-	35.9	31.5	27.8	34.2	28.9	37.3	31.5	27.1	35.5	30.2	26.2	28.0	28.9	25.8	21.8	22.7	-	-	-	230			
243	-	-	29.5	-	31.3	27.1	30.0	29.5	25.1	34.2	28.4	24.0	27.3	27.3	23.8	21.4	22.3	22.7	-	-	243			
256	-	-	-	-	-	25.1	-	27.1	23.1	29.3	26.7	22.5	26.7	25.8	21.8	20.9	21.8	20.9	-	-	256			
269	-	-	-	-	-	-	-	24.9	21.2	18.1	24.3	20.7	26.0	24.0	20.3	20.3	21.2	19.4	-	-	269			
282	-	-	-	-	-	-	-	-	19.4	-	22.3	18.7	20.9	21.8	18.3	19.8	20.7	17.4	-	-	282			
295	-	-	-	-	-	-	-	-	-	-	-	17.0	-	20.1	16.8	19.4	19.2	15.7	-	-	295			
308	-	-	-	-	-	-	-	-	-	-	-	-	-	18.5	15.2	-	17.4	14.1	-	-	308			
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.7	-	16.1	12.8	-	-	322			
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11.5	-	-	335			
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	348			

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES LUFFING FLY JIB WITH SSL, MAIN BOOM 83°-65°**

360° 85 %																
108.9 ft + 13.1 ft Main boom + adapter																
Fly jib																
98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius
ft	1,000 lb															ft
53	198.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	53
59	195.6	-	-	170.0	-	-	-	-	-	-	-	-	-	-	-	59
66	181.9	-	-	179.2	-	-	143.5	-	-	-	-	-	-	-	-	66
72	164.5	-	-	162.7	-	-	161.2	-	-	136.2	-	-	-	-	-	72
79	150.1	-	-	148.4	-	-	146.6	-	-	131.2	-	-	-	-	-	79
85	137.8	-	-	136.0	-	-	134.5	-	-	126.1	-	-	-	118.2	-	85
92	127.2	113.8	-	125.4	-	-	123.9	-	-	121.0	-	-	-	114.6	-	92
98	118.2	105.6	-	116.4	-	-	114.6	-	-	116.0	-	-	-	112.7	-	98
105	110.2	98.3	-	108.5	96.3	-	106.7	-	-	108.2	-	-	-	106.5	-	105
112	99.4	91.9	-	101.4	89.9	-	99.6	88.0	-	101.2	-	-	-	99.4	-	112
118	-	86.2	78.0	95.0	84.2	-	93.3	82.2	-	94.8	-	-	-	93.3	-	118
125	-	81.1	73.4	89.5	79.1	-	87.7	77.2	-	89.1	78.5	-	-	87.5	-	125
131	-	76.7	69.2	70.1	74.5	67.0	82.7	72.8	-	84.0	73.9	-	-	82.5	72.1	131
138	-	-	65.5	-	70.3	63.3	78.0	68.6	-	79.4	69.7	-	-	77.8	67.9	138
144	-	-	61.9	-	66.8	59.7	74.1	64.8	57.8	75.2	65.9	-	-	73.6	64.2	144
151	-	-	-	-	63.5	56.7	56.4	61.3	54.7	71.4	62.6	-	-	69.9	60.8	151
158	-	-	-	-	-	53.8	-	58.2	51.8	67.9	59.5	52.9	-	66.4	57.8	158
164	-	-	-	-	-	51.4	-	55.3	49.2	62.8	56.4	50.3	63.3	54.9	-	164
177	-	-	-	-	-	-	-	-	44.5	-	51.4	45.6	57.5	49.6	43.9	177
190	-	-	-	-	-	-	-	-	-	-	47.2	41.7	39.7	45.4	39.7	190
203	-	-	-	-	-	-	-	-	-	-	-	38.1	-	41.7	36.4	203
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	33.3	217
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	230

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			
ft	1,000 lb															ft		
85	91.1	-	-	68.8	-	-	-	-	-	-	-	-	-	-	-	-	85	
92	89.1	-	-	73.9	-	-	56.7	-	-	-	-	-	-	-	-	-	92	
98	87.3	-	-	71.9	-	-	61.3	-	-	48.7	-	-	-	-	-	-	98	
105	85.5	-	-	69.9	-	-	60.4	-	-	48.1	-	-	39.2	-	-	-	105	
112	83.6	-	-	68.1	-	-	59.7	-	-	47.4	-	-	38.6	-	-	32.0	112	
118	81.8	-	-	66.1	-	-	58.9	-	-	46.5	-	-	38.1	-	-	31.3	118	
125	79.8	-	-	64.2	-	-	58.2	-	-	45.9	-	-	37.5	-	-	30.9	125	
131	78.0	-	-	62.6	-	-	57.3	-	-	45.2	-	-	37.0	-	-	30.2	131	
138	76.3	67.2	-	61.3	-	-	56.4	-	-	44.5	-	-	36.4	-	-	29.8	138	
144	73.0	63.5	-	60.0	-	-	55.3	-	-	43.9	-	-	35.9	-	-	29.3	144	
151	69.2	60.0	-	58.6	56.2	-	54.5	-	-	43.0	-	-	35.3	-	-	28.7	151	
158	65.7	56.9	-	57.1	55.1	-	53.4	45.0	-	42.1	-	-	34.6	-	-	28.2	158	
164	62.4	54.0	-	55.8	52.2	-	52.2	44.5	-	41.0	35.9	-	33.7	-	-	27.6	164	
177	56.7	48.9	43.0	54.0	47.0	-	50.0	43.7	-	39.2	35.5	-	32.0	31.7	-	26.5	177	
190	51.8	44.5	38.8	50.0	42.5	37.0	48.3	40.8	-	37.7	34.8	-	30.6	30.6	-	25.1	190	
203	44.1	40.8	35.5	45.9	38.8	33.5	44.1	36.8	31.5	37.0	34.4	-	29.3	29.5	-	23.8	203	
217	-	37.5	32.4	41.9	35.5	30.4	40.3	33.5	28.4	36.4	33.3	28.0	28.4	28.4	-	22.7	217	
230	-	34.6	29.8	27.1	32.6	27.8	37.0	30.6	25.8	35.7	30.2	25.4	27.6	27.6	24.9	22.0	230	
243	-	-	27.6	-	30.0	25.4	29.1	28.0	23.4	33.7	27.6	22.9	26.7	26.9	22.5	21.2	243	
256	-	-	-	-	-	23.4	-	25.8	21.4	29.3	25.1	20.7	26.0	24.9	20.5	20.5	256	
269	-	-	-	-	-	-	-	23.8	19.4	-	23.1	19.0	25.6	22.7	18.5	19.8	269	
282	-	-	-	-	-	-	-	-	17.6	-	21.2	17.2	20.9	20.9	16.8	19.4	282	
295	-	-	-	-	-	-	-	-	-	-	-	15.7	-	19.2	15.2	18.7	295	
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.7	-	308	
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	12.3	-	322	
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	335	
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	348	

Remarks

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°** 360° **85 %****124.3 ft + 13.1 ft Main boom + adapter**

Fly jib																					
78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft						
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius		
ft	1,000 lb																				ft
59	140.7	-	-	125.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59		
66	132.5	-	-	120.6	-	-	107.1	-	-	-	-	-	-	-	-	-	-	-	66		
72	125.0	-	-	115.3	-	-	103.8	-	-	89.9	-	-	77.6	-	-	-	-	-	72		
79	117.7	-	-	110.5	-	-	100.5	-	-	88.0	-	-	76.3	-	-	66.6	-	-	79		
85	112.9	-	-	105.6	-	-	97.0	-	-	85.8	-	-	75.0	-	-	65.9	-	-	85		
92	108.2	-	-	100.8	-	-	93.5	-	-	83.6	-	-	73.6	-	-	65.3	-	-	92		
98	-	86.6	-	97.4	84.9	-	89.9	-	-	81.1	-	-	72.3	-	-	64.4	-	-	98		
105	-	81.6	-	94.6	79.8	-	86.9	-	-	78.5	-	-	71.0	-	-	63.7	-	-	105		
112	-	76.5	-	91.5	75.0	-	84.0	71.4	-	76.1	-	-	69.7	-	-	62.8	-	-	112		
118	-	73.4	-	-	71.0	-	81.6	67.7	-	73.9	65.5	-	68.1	-	-	61.7	-	-	118		
125	-	-	61.7	-	67.2	-	79.1	63.9	-	71.7	62.4	-	66.8	-	-	60.8	-	-	125		
131	-	-	58.6	-	64.8	57.3	77.4	61.3	-	69.7	59.3	-	65.5	60.0	-	59.7	-	-	131		
138	-	-	-	-	62.2	54.0	-	58.4	-	67.7	56.2	-	64.2	57.3	-	58.6	55.1	-	138		
144	-	-	-	-	-	51.6	-	56.2	48.3	66.1	53.8	-	63.1	54.7	-	57.8	52.7	-	144		
151	-	-	-	-	-	48.9	-	54.2	45.6	64.8	51.4	44.8	61.9	52.0	-	56.7	50.5	-	151		
158	-	-	-	-	-	-	-	53.4	43.7	-	49.2	42.3	61.1	50.0	-	55.6	48.3	-	158		
164	-	-	-	-	-	-	-	-	41.9	-	47.2	40.1	60.2	48.1	41.9	54.7	45.9	-	164		
177	-	-	-	-	-	-	-	-	-	-	45.4	36.8	-	44.5	37.9	52.7	42.5	36.8	177		
190	-	-	-	-	-	-	-	-	-	-	-	34.4	-	42.5	35.1	45.4	39.2	33.3	190		
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	32.6	-	37.0	30.6	203		
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	35.9	28.4	217		
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	26.9	230		
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	243		

196.9 ft				216.5 ft				236.2 ft				255.9 ft				275.6 ft				295.3 ft				
ft	1,000 lb																			ft				
85	59.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85			
92	58.6	-	-	46.1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92			
98	57.8	-	-	45.9	-	-	40.8	-	-	-	-	-	-	-	-	-	-	-	-	-	98			
105	57.1	-	-	45.6	-	-	40.3	-	-	33.1	-	-	-	-	-	-	-	-	-	-	105			
112	56.2	-	-	45.2	-	-	40.1	-	-	33.1	-	-	26.9	-	-	21.8	-	-	-	-	112			
118	55.6	-	-	45.0	-	-	39.9	-	-	33.1	-	-	26.9	-	-	21.8	-	-	-	-	118			
125	54.7	-	-	44.5	-	-	39.7	-	-	32.8	-	-	26.9	-	-	21.6	-	-	-	-	125			
131	54.0	-	-	44.3	-	-	39.2	-	-	32.8	-	-	26.7	-	-	21.4	-	-	-	-	131			
138	53.1	-	-	44.1	-	-	39.0	-	-	32.8	-	-	26.7	-	-	21.4	-	-	-	-	138			
144	52.5	-	-	43.7	-	-	38.8	-	-	32.6	-	-	26.7	-	-	21.2	-	-	-	-	144			
151	51.6	47.8	-	43.4	-	-	38.6	-	-	32.6	-	-	26.5	-	-	21.2	-	-	-	-	151			
158	50.9	46.1	-	43.2	40.8	-	38.1	-	-	32.6	-	-	26.5	-	-	20.9	-	-	-	-	158			
164	50.0	44.3	-	42.8	39.5	-	37.9	34.8	-	32.4	-	-	26.5	-	-	20.9	-	-	-	-	164			
177	48.7	40.6	-	42.1	37.3	-	37.5	33.3	-	32.4	30.2	-	26.2	-	-	20.7	-	-	-	-	177			
190	47.2	37.7	33.5	41.7	35.1	-	36.8	31.7	-	32.2	29.1	-	26.0	24.7	-	20.3	-	-	-	-	190			
203	46.3	35.1	30.2	41.0	32.6	28.7	36.4	30.4	-	32.0	28.0	-	25.8	24.5	-	20.1	19.4	-	-	-	203			
217	-	32.6	27.8	40.3	30.4	25.8	35.7	28.4	24.7	32.0	26.9	-	25.8	24.3	-	19.8	19.2	-	-	-	217			
230	-	31.7	25.6	31.7	28.0	23.6	35.3	26.5	22.3	31.7	25.4	21.8	25.6	24.0	-	19.6	18.7	-	-	-	230			
243	-	-	24.3	-	27.1	21.6	32.0	24.3	20.1	31.7	23.6	19.6	25.4	22.9	19.6	19.4	18.5	-	-	-	243			
256	-	-	-	-	26.2	20.3	-	23.1	18.3	30.9	21.8	17.6	25.1	21.4	17.6	19.2	17.9	14.6	-	-	256			
269	-	-	-	-	-	19.4	-	22.5	17.0	20.9	20.5	16.1	25.1	19.8	15.7	19.0	17.0	13.4	-	-	269			
282	-	-	-	-	-	-	-	-	16.1	-	19.8	14.6	22.7	18.3	14.3	18.7	16.1	12.3	-	-	282			
295	-	-	-	-	-	-	-	-	-	-	19.2	13.9	-	17.6	13.0	18.5	15.2	11.2	-	-	295			
308	-	-	-	-	-	-	-	-	-	-	-	13.0	-	17.2	12.1	14.1	14.8	10.4	-	-	308			
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11.5	-	14.6	9.7	-	-	322			
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.4	9.3	-	-	335			
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	8.8	-	-	348			

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES LUFFING FLY JIB WITH SSL, MAIN BOOM 83°-65°**

360°85 %																
124.3 ft + 13.1 ft Main boom + adapter																
Fly jib																
98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius
ft	1,000 lb															ft
59	181.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59
66	170.6	-	-	166.9	-	-	-	-	-	-	-	-	-	-	-	66
72	160.5	-	-	157.2	-	-	150.4	-	-	-	-	-	-	-	-	72
79	148.8	-	-	147.0	-	-	142.4	-	-	130.5	-	-	95.9	-	-	79
85	136.7	-	-	134.9	-	-	133.4	-	-	125.9	-	-	108.2	-	-	85
92	126.1	-	-	124.6	-	-	122.8	-	-	121.3	-	-	106.7	-	-	92
98	117.1	103.4	-	115.3	-	-	113.8	-	-	115.3	-	-	104.9	-	-	98
105	109.1	96.1	-	107.4	-	-	105.8	-	-	107.4	-	-	103.4	-	-	105
112	102.3	89.9	-	100.3	88.0	-	98.8	-	-	100.3	-	-	98.5	-	-	112
118	-	84.2	-	94.1	82.2	-	92.4	80.5	-	93.9	-	-	92.4	-	-	118
125	-	79.4	-	88.6	77.4	-	86.9	75.4	-	88.4	-	-	86.6	-	-	125
131	-	74.7	66.8	79.4	72.8	-	81.8	71.0	-	83.3	72.1	-	81.6	-	-	131
138	-	71.0	63.1	-	68.8	60.8	77.4	66.8	-	78.7	68.1	-	77.2	66.4	-	138
144	-	-	59.7	-	65.0	57.5	73.2	63.1	-	74.5	64.4	-	73.0	62.6	-	144
151	-	-	56.7	-	61.7	54.5	64.4	59.7	52.5	70.8	61.1	-	69.2	59.3	-	151
158	-	-	-	-	58.9	51.8	-	56.7	49.8	67.2	58.0	-	65.7	56.2	-	158
164	-	-	-	-	-	49.2	-	54.0	47.2	64.2	55.1	48.3	62.6	53.4	-	164
177	-	-	-	-	-	-	-	49.2	42.8	-	50.0	43.7	56.9	48.3	41.9	177
190	-	-	-	-	-	-	-	-	38.8	-	45.9	39.9	44.8	44.1	37.9	190
203	-	-	-	-	-	-	-	-	-	-	-	36.6	-	40.3	34.6	203
217	-	-	-	-	-	-	-	-	-	-	-	-	-	37.3	31.7	217
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	29.1	230
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	243

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			
ft	1,000 lb															ft		
85	85.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85	
92	84.2	-	-	70.3	-	-	-	-	-	-	-	-	-	-	-	-	92	
98	82.7	-	-	69.0	-	-	57.5	-	-	-	-	-	-	-	-	-	98	
105	81.4	-	-	67.5	-	-	57.3	-	-	46.5	-	-	34.6	-	-	-	105	
112	79.8	-	-	66.1	-	-	56.9	-	-	45.9	-	-	37.0	-	-	26.9	112	
118	78.5	-	-	64.8	-	-	56.7	-	-	45.4	-	-	36.6	-	-	30.0	118	
125	76.9	-	-	63.3	-	-	56.2	-	-	45.0	-	-	36.4	-	-	29.5	125	
131	75.6	-	-	61.9	-	-	55.8	-	-	44.3	-	-	35.9	-	-	29.3	131	
138	74.1	-	-	60.6	-	-	55.6	-	-	43.9	-	-	35.5	-	-	28.9	138	
144	72.3	61.7	-	59.3	-	-	54.7	-	-	43.2	-	-	35.1	-	-	28.7	144	
151	68.3	58.4	-	58.0	-	-	53.6	-	-	42.5	-	-	34.8	-	-	28.2	151	
158	65.0	55.3	-	56.9	49.8	-	52.7	-	-	41.7	-	-	34.2	-	-	27.8	158	
164	61.7	52.5	-	55.6	49.2	-	51.6	40.1	-	40.8	-	-	33.5	-	-	27.6	164	
177	56.2	47.4	-	53.6	45.6	-	49.6	39.5	-	39.0	33.1	-	32.0	-	-	26.2	177	
190	51.4	43.2	37.0	49.4	41.2	-	47.6	38.8	-	37.3	32.8	-	30.4	28.2	-	24.9	190	
203	47.2	39.5	33.7	45.2	37.5	31.7	43.4	35.7	-	35.9	32.6	-	28.9	27.6	-	23.8	203	
217	-	36.2	30.9	41.4	34.4	28.9	39.7	32.4	26.7	34.8	32.0	-	27.8	26.9	-	22.5	217	
230	-	33.5	28.2	30.9	31.3	26.2	36.4	29.5	24.3	33.7	29.1	23.8	26.7	26.2	-	21.6	230	
243	-	-	25.8	-	28.9	23.8	32.0	26.9	21.8	33.1	26.5	21.4	25.8	25.6	20.9	20.7	243	
256	-	-	-	-	26.7	21.8	-	24.7	19.8	30.6	24.3	19.4	25.1	23.8	19.0	19.8	256	
269	-	-	-	-	-	20.1	-	22.7	17.9	20.9	22.0	17.4	24.7	21.8	17.0	19.2	269	
282	-	-	-	-	-	-	-	-	16.3	-	20.3	15.9	22.7	19.8	15.4	18.7	282	
295	-	-	-	-	-	-	-	-	-	-	18.5	14.3	-	18.3	13.9	18.5	295	
308	-	-	-	-	-	-	-	-	-	-	-	12.8	-	16.8	12.3	14.1	308	
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11.2	-	322	
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9.0	335
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	7.9	348

Remarks

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



TEREX | DEMAG

LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°

 360° **85 %**

139.4 ft + 13.1 ft Main boom + adapter

Fly jib																				
78.7 ft				98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft	1,000 lb																			ft
59	-	-	-	101.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59	
66	109.1	-	-	97.2	-	-	88.0	-	-	-	-	-	-	-	-	-	-	-	66	
72	103.2	-	-	93.5	-	-	84.7	-	-	73.9	-	-	-	-	-	-	-	-	72	
79	97.7	-	-	89.5	-	-	81.6	-	-	71.7	-	-	64.2	-	-	-	-	-	79	
85	92.8	-	-	85.8	-	-	78.3	-	-	69.4	-	-	62.8	-	-	55.6	-	-	85	
92	88.8	-	-	82.0	-	-	75.8	-	-	67.0	-	-	61.3	-	-	54.2	-	-	92	
98	-	-	-	78.9	-	-	73.2	-	-	65.0	-	-	60.0	-	-	53.1	-	-	98	
105	-	67.5	-	76.5	65.7	-	71.0	-	-	63.3	-	-	58.6	-	-	52.0	-	-	105	
112	-	63.1	-	73.9	61.7	-	68.6	-	-	61.3	-	-	57.3	-	-	50.9	-	-	112	
118	-	60.2	-	-	58.4	-	66.8	55.6	-	59.7	-	-	56.2	-	-	49.8	-	-	118	
125	-	-	-	-	54.9	-	64.8	52.7	-	58.0	49.4	-	54.9	-	-	48.7	-	-	125	
131	-	-	-	-	52.2	-	63.5	50.0	-	56.7	47.0	-	53.8	-	-	47.8	-	-	131	
138	-	-	-	-	49.8	44.3	-	47.4	-	55.3	44.5	-	52.7	45.6	-	46.7	-	-	138	
144	-	-	-	-	-	41.9	-	45.4	-	54.2	42.3	-	51.8	43.4	-	45.9	41.7	-	144	
151	-	-	-	-	-	39.7	-	43.7	37.7	53.4	40.1	-	50.9	41.4	-	45.0	39.7	-	151	
158	-	-	-	-	-	38.1	-	42.8	35.9	-	38.6	-	50.0	39.5	-	44.3	37.9	-	158	
164	-	-	-	-	-	-	-	-	34.2	-	37.0	32.4	49.2	37.7	-	43.7	35.9	-	164	
177	-	-	-	-	-	-	-	-	31.5	-	34.8	29.3	-	35.1	30.6	42.3	32.6	-	177	
190	-	-	-	-	-	-	-	-	-	-	-	26.9	-	32.8	27.8	41.7	30.4	26.5	190	
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25.8	-	28.0	23.8	203	
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	24.3	-	27.3	21.8	217	
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	20.5	230	
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	243	

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft				
ft	1,000 lb																		ft
92	48.3	-	-	39.9	-	-	-	-	-	-	-	-	-	-	-	-	-	92	
98	47.6	-	-	39.5	-	-	33.1	-	-	-	-	-	-	-	-	-	-	98	
105	46.7	-	-	38.8	-	-	32.6	-	-	28.4	-	-	-	-	-	-	-	105	
112	46.1	-	-	38.4	-	-	32.4	-	-	28.2	-	-	22.5	-	-	-	-	112	
118	45.2	-	-	37.9	-	-	32.2	-	-	28.0	-	-	22.3	-	-	17.4	-	118	
125	44.5	-	-	37.3	-	-	31.7	-	-	27.8	-	-	22.3	-	-	17.4	-	125	
131	43.7	-	-	36.8	-	-	31.5	-	-	27.6	-	-	22.3	-	-	17.4	-	131	
138	43.0	-	-	36.4	-	-	31.3	-	-	27.3	-	-	22.0	-	-	17.4	-	138	
144	42.3	-	-	35.9	-	-	30.9	-	-	27.1	-	-	22.0	-	-	17.2	-	144	
151	41.4	-	-	35.5	-	-	30.6	-	-	26.9	-	-	22.0	-	-	17.2	-	151	
158	40.8	37.3	-	35.3	-	-	30.2	-	-	26.7	-	-	21.8	-	-	17.2	-	158	
164	40.1	35.5	-	34.8	33.1	-	30.0	-	-	26.5	-	-	21.8	-	-	17.2	-	164	
177	39.0	32.2	-	34.0	30.2	-	29.3	26.9	-	26.0	-	-	21.6	-	-	17.0	-	177	
190	37.9	29.3	-	33.3	27.3	-	28.7	24.7	-	25.6	22.9	-	21.6	19.4	-	17.0	-	190	
203	37.3	27.1	23.6	32.6	24.7	-	28.4	22.7	-	25.1	21.4	-	21.4	18.5	-	16.8	14.8	203	
217	-	25.1	21.2	32.2	22.9	19.4	28.0	20.7	-	24.9	19.6	-	21.2	17.6	-	16.8	14.3	217	
230	-	24.0	19.4	31.7	21.2	17.2	27.8	19.2	15.9	24.5	18.1	-	21.2	17.0	-	16.8	14.1	230	
243	-	-	18.1	-	19.8	15.9	27.3	17.6	13.9	24.0	16.8	13.4	20.9	15.9	-	16.5	13.7	243	
256	-	-	17.2	-	19.4	14.3	-	16.3	12.6	23.8	15.2	11.7	20.7	14.8	11.7	16.5	13.0	256	
269	-	-	-	-	-	13.7	-	15.9	11.2	23.1	13.9	10.6	20.7	13.4	10.1	16.3	12.1	269	
282	-	-	-	-	-	-	-	-	10.4	-	13.4	9.3	20.5	12.3	9.0	16.3	11.0	282	
295	-	-	-	-	-	-	-	-	9.9	-	13.0	8.4	-	11.7	7.9	16.1	10.1	295	
308	-	-	-	-	-	-	-	-	-	-	-	7.9	-	11.2	7.1	15.9	9.3	308	
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.6	-	9.0	322	
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.0	-	8.8	335	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES LUFFING FLY JIB WITH SSL, MAIN BOOM 83°-65°**

360°85 %																
139.4 ft + 13.1 ft Main boom + adapter																
Fly jib																
98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius	
83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°		
ft	1,000 lb															ft
59	153.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59
66	164.2	-	-	131.4	-	-	-	-	-	-	-	-	-	-	-	66
72	154.3	-	-	147.5	-	-	111.3	-	-	-	-	-	-	-	-	72
79	144.2	-	-	138.9	-	-	130.5	-	-	97.0	-	-	-	-	-	79
85	135.6	-	-	130.3	-	-	124.3	-	-	117.3	-	-	98.3	-	-	85
92	125.2	-	-	122.8	-	-	117.9	-	-	112.7	-	-	96.3	-	-	92
98	116.2	-	-	114.4	-	-	111.8	-	-	108.0	-	-	94.4	-	-	98
105	108.2	94.1	-	106.5	-	-	104.9	-	-	103.4	-	-	92.4	-	-	105
112	101.2	88.0	-	99.4	-	-	97.9	-	-	99.0	-	-	90.4	-	-	112
118	-	82.5	-	93.3	80.5	-	91.7	-	-	93.0	-	-	88.0	-	-	118
125	-	77.6	-	87.7	75.6	-	86.0	73.6	-	87.5	-	-	85.5	-	-	125
131	-	73.2	-	82.9	71.0	-	81.1	69.2	-	82.5	70.5	-	80.9	-	-	131
138	-	69.2	60.8	-	67.0	-	76.5	65.3	-	78.0	66.6	-	76.3	-	-	138
144	-	-	57.5	-	63.5	-	72.5	61.5	-	73.9	62.8	-	72.3	61.1	-	144
151	-	-	54.7	-	60.2	52.5	68.8	58.2	-	70.1	59.5	-	68.6	57.8	-	151
158	-	-	52.0	-	57.3	49.8	-	55.3	47.6	66.6	56.4	-	65.0	54.7	-	158
164	-	-	-	-	-	47.2	-	52.5	45.2	63.5	53.8	-	61.9	51.8	-	164
177	-	-	-	-	-	43.0	-	47.6	40.8	-	48.7	41.9	56.2	47.0	-	177
190	-	-	-	-	-	-	-	-	37.0	-	44.5	38.1	48.5	42.8	36.2	190
203	-	-	-	-	-	-	-	-	-	-	-	34.8	-	39.0	32.8	203
217	-	-	-	-	-	-	-	-	-	-	-	32.0	-	35.9	30.0	217
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	27.6	230
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	243

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft		
ft	1,000 lb															ft	
92	80.0	-	-	54.9	-	-	-	-	-	-	-	-	-	-	-	92	
98	78.7	-	-	63.9	-	-	46.5	-	-	-	-	-	-	-	-	98	
105	77.4	-	-	63.1	-	-	55.8	-	-	38.4	-	-	-	-	-	105	
112	76.1	-	-	61.9	-	-	55.3	-	-	43.7	-	-	35.5	-	-	112	
118	74.5	-	-	61.1	-	-	54.9	-	-	43.4	-	-	35.3	-	-	118	
125	73.2	-	-	60.2	-	-	54.5	-	-	43.0	-	-	34.8	-	-	125	
131	71.9	-	-	59.1	-	-	54.2	-	-	42.8	-	-	34.6	-	-	131	
138	70.3	-	-	58.2	-	-	53.8	-	-	42.3	-	-	34.4	-	-	138	
144	69.0	-	-	57.3	-	-	53.1	-	-	42.1	-	-	34.2	-	-	144	
151	67.7	54.7	-	56.4	-	-	52.5	-	-	41.7	-	-	34.0	-	-	151	
158	64.4	53.6	-	55.3	43.2	-	51.6	-	-	41.0	-	-	33.5	-	-	158	
164	61.1	51.1	-	54.5	42.8	-	50.7	-	-	40.3	-	-	33.1	-	-	164	
177	55.6	46.1	-	52.7	41.4	-	48.9	35.5	38.6	30.6	-	-	31.7	-	-	177	
190	50.7	41.9	-	48.9	40.1	-	47.2	34.8	37.0	30.2	-	-	30.2	23.8	-	190	
203	46.5	38.4	32.0	44.8	36.4	-	43.0	34.2	-	35.5	30.0	-	28.9	23.6	-	203	
217	-	35.1	29.1	41.0	33.1	27.1	39.2	31.3	25.1	34.6	29.5	-	27.6	23.6	-	217	
230	-	32.4	26.7	34.6	30.4	24.7	35.9	28.4	22.7	33.5	28.0	22.3	26.7	23.4	-	230	
243	-	-	24.5	-	27.8	22.5	33.1	25.8	20.3	32.4	25.6	20.1	25.6	23.1	18.5	243	
256	-	-	22.5	-	25.6	20.3	-	23.6	18.3	30.2	23.1	17.9	24.7	22.9	17.4	256	
269	-	-	-	-	-	18.5	-	21.6	16.5	23.1	21.2	16.1	24.0	20.7	15.7	269	
282	-	-	-	-	-	-	-	-	15.0	-	19.4	14.6	23.4	19.0	14.1	282	
295	-	-	-	-	-	-	-	-	13.7	-	17.6	13.0	-	17.2	12.6	295	
308	-	-	-	-	-	-	-	-	-	-	-	11.7	-	15.9	11.2	308	
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9.9	322	
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	8.8	335	
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.8	348
361	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	361

Remarks

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°** 360° **85 %****154.9 ft + 13.1 ft Main boom + adapter**

Fly jib																					
78.7 ft				98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft		
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°			
1,000 lb																					
66	88.6	-	-	78.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	66	
72	84.2	-	-	75.4	-	-	68.8	-	-	-	-	-	-	-	-	-	-	-	-	72	
79	80.7	-	-	72.5	-	-	66.6	-	-	57.1	-	-	52.2	-	-	-	-	-	-	79	
85	77.4	-	-	70.1	-	-	64.4	-	-	55.3	-	-	51.1	-	-	45.6	-	-	-	85	
92	74.7	-	-	67.7	-	-	62.4	-	-	53.6	-	-	50.0	-	-	44.8	-	-	-	92	
98	71.9	-	-	65.5	-	-	60.4	-	-	52.0	-	-	48.9	-	-	43.9	-	-	-	98	
105	-	-	-	63.5	-	-	58.4	-	-	50.7	-	-	47.8	-	-	42.8	-	-	-	105	
112	-	53.1	-	61.7	50.0	-	56.4	-	-	49.4	-	-	46.7	-	-	41.9	-	-	-	112	
118	-	50.3	-	60.6	47.2	-	55.1	-	-	48.1	-	-	45.6	-	-	41.0	-	-	-	118	
125	-	47.4	-	-	44.3	-	53.6	42.1	-	46.7	-	-	44.8	-	-	40.1	-	-	-	125	
131	-	-	-	-	42.3	-	52.2	39.9	-	45.6	38.1	-	43.7	-	-	39.2	-	-	-	131	
138	-	-	-	-	40.3	-	51.1	37.7	-	44.8	36.2	-	42.8	-	-	38.6	-	-	-	138	
144	-	-	-	-	39.0	34.0	-	36.2	-	43.7	34.2	-	41.9	35.3	-	37.7	-	-	-	144	
151	-	-	-	-	-	32.2	-	34.6	-	42.8	32.2	-	41.2	33.5	-	36.8	31.7	-	-	151	
158	-	-	-	-	-	30.4	-	33.5	28.2	42.3	30.9	-	40.3	32.0	-	36.2	30.2	-	-	158	
164	-	-	-	-	-	28.9	-	32.2	26.9	-	29.5	-	39.7	30.2	-	35.7	28.7	-	-	164	
177	-	-	-	-	-	-	-	-	24.5	-	27.1	22.5	38.8	28.0	-	34.4	25.8	-	-	177	
190	-	-	-	-	-	-	-	-	-	-	-	20.3	-	25.8	21.4	33.7	23.6	-	-	190	
203	-	-	-	-	-	-	-	-	-	-	-	18.7	-	24.7	19.6	-	21.8	17.6	-	203	
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	18.1	-	20.5	16.1	-	217	
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	14.6	-	230	
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.7	-	243	
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256	

196.9 ft				216.5 ft				236.2 ft				255.9 ft				275.6 ft				295.3 ft				
ft										1,000 lb												ft		
92	39.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92		
98	38.8	-	-	31.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	98		
105	38.1	-	-	31.1	-	-	26.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	105		
112	37.5	-	-	30.4	-	-	25.8	-	-	21.2	-	-	-	-	-	-	-	-	-	-	-	112		
118	36.8	-	-	30.0	-	-	25.6	-	-	20.9	-	-	18.1	-	-	13.9	-	-	-	-	-	118		
125	36.2	-	-	29.5	-	-	25.1	-	-	20.7	-	-	18.1	-	-	13.9	-	-	-	-	-	125		
131	35.5	-	-	29.1	-	-	24.9	-	-	20.5	-	-	17.9	-	-	13.7	-	-	-	-	-	131		
138	34.8	-	-	28.7	-	-	24.5	-	-	20.3	-	-	17.6	-	-	13.7	-	-	-	-	-	138		
144	34.2	-	-	28.2	-	-	24.3	-	-	20.1	-	-	17.4	-	-	13.7	-	-	-	-	-	144		
151	33.7	-	-	27.8	-	-	23.8	-	-	19.8	-	-	17.2	-	-	13.7	-	-	-	-	-	151		
158	33.1	29.3	-	27.6	-	-	23.6	-	-	19.6	-	-	17.2	-	-	13.7	-	-	-	-	-	158		
164	32.4	28.0	-	27.1	-	-	23.4	-	-	19.4	-	-	17.0	-	-	13.4	-	-	-	-	-	164		
177	31.3	25.4	-	26.2	23.1	-	22.7	20.5	-	19.2	-	-	16.8	-	-	13.4	-	-	-	-	-	177		
190	30.2	22.7	-	25.6	20.7	-	22.3	18.5	-	18.7	17.0	-	16.5	-	-	13.4	-	-	-	-	-	190		
203	29.5	20.9	17.2	24.9	18.5	-	21.8	16.8	-	18.3	15.4	-	16.3	12.6	-	13.2	-	-	-	-	-	203		
217	29.3	19.2	15.4	24.3	17.0	13.4	21.4	14.8	-	18.1	13.9	-	16.1	11.9	-	13.2	-	-	-	-	-	217		
230	-	17.9	13.9	24.0	15.4	11.7	20.9	13.4	10.1	17.9	12.3	-	15.9	11.2	-	13.2	-	-	-	-	-	230		
243	-	17.4	12.6	-	14.1	10.4	20.5	12.3	8.6	17.6	11.2	-	15.7	10.6	-	13.2	-	-	-	-	-	243		
256	-	-	11.7	-	13.7	9.3	20.1	11.0	7.3	17.4	10.1	-	15.4	9.5	-	13.0	-	-	-	-	-	256		
269	-	-	-	-	-	8.4	-	10.4	6.4	17.4	9.0	-	15.2	8.6	-	13.0	-	-	-	-	-	269		
282	-	-	-	-	-	7.7	-	9.9	5.5	-	8.4	-	15.2	7.5	-	13.0	-	-	-	-	-	282		
295	-	-	-	-	-	-	-	-	4.9	-	7.9	-	14.3	6.8	-	12.8	-	-	-	-	-	295		
308	-	-	-	-	-	-	-	-	-	-	-	-	-	6.4	-	12.8	-	-	-	-	-	308		
322	-	-	-	-	-	-	-	-	-	-	-	-	-	6.2	-	-	-	-	-	-	-	322		
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	335		

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



ALL TERRAIN CRANE

AC 500-2

LIFTING CAPACITIES LUFFING FLY JIB WITH SSL, MAIN BOOM 83°-65°

360°85 %																
154.9 ft + 13.1 ft Main boom + adapter																
Fly jib																
98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius
ft	1,000 lb															ft
66	138.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	66
72	127.9	-	-	121.5	-	-	-	-	-	-	-	-	-	-	-	72
79	121.9	-	-	113.8	-	-	110.2	-	-	84.7	-	-	-	-	-	79
85	117.9	-	-	106.0	-	-	103.6	-	-	101.2	-	-	71.9	-	-	85
92	114.0	-	-	100.8	-	-	97.0	-	-	95.9	-	-	87.3	-	-	92
98	109.8	-	-	97.7	-	-	90.4	-	-	90.6	-	-	83.8	-	-	98
105	104.5	-	-	94.6	-	-	85.8	-	-	85.5	-	-	80.2	-	-	105
112	99.4	86.2	-	91.7	-	-	81.4	-	-	80.5	-	-	76.9	-	-	112
118	94.1	80.7	-	88.8	78.0	-	79.1	-	-	77.2	-	-	73.6	-	-	118
125	-	75.8	-	86.0	73.9	-	76.9	-	-	73.6	-	-	70.3	-	-	125
131	-	71.4	-	82.0	69.4	-	75.2	67.5	-	70.1	-	-	67.2	-	-	131
138	-	67.7	-	66.8	65.5	-	73.4	63.7	-	67.7	63.5	-	64.4	-	-	138
144	-	64.2	55.6	-	61.9	-	71.2	60.0	-	66.4	61.3	-	61.5	-	-	144
151	-	-	52.7	-	58.6	-	68.1	56.9	-	65.0	58.2	-	58.4	53.1	-	151
158	-	-	50.0	-	55.8	47.8	54.5	53.8	-	63.7	55.1	-	56.9	51.8	-	158
164	-	-	47.6	-	53.1	45.4	-	51.1	-	62.4	52.5	-	55.3	50.5	-	164
177	-	-	-	-	-	41.0	-	46.3	39.0	46.1	47.6	40.1	53.1	45.6	-	177
190	-	-	-	-	-	-	-	-	35.3	-	43.4	36.4	50.9	41.4	34.4	190
203	-	-	-	-	-	-	-	-	32.2	-	39.9	33.3	-	37.9	31.3	203
217	-	-	-	-	-	-	-	-	-	-	-	30.4	-	34.8	28.4	217
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	26.0	230
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	23.8	243
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			ft	
ft	1,000 lb															ft			
92	58.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92		
98	69.2	-	-	48.7	-	-	-	-	-	-	-	-	-	-	-	-	98		
105	67.5	-	-	59.1	-	-	48.3	-	-	-	-	-	-	-	-	-	105		
112	65.7	-	-	57.8	-	-	47.6	-	-	40.1	-	-	24.5	-	-	-	112		
118	63.9	-	-	56.4	-	-	47.2	-	-	39.9	-	-	31.7	-	-	18.7	118		
125	62.2	-	-	55.1	-	-	46.5	-	-	39.7	-	-	31.5	-	-	25.4	125		
131	60.6	-	-	53.8	-	-	46.1	-	-	39.5	-	-	31.5	-	-	25.1	131		
138	58.9	-	-	52.5	-	-	45.4	-	-	39.2	-	-	31.3	-	-	24.9	138		
144	57.1	-	-	51.1	-	-	44.8	-	-	39.0	-	-	31.1	-	-	24.7	144		
151	55.3	-	-	50.0	-	-	44.1	-	-	38.8	-	-	30.9	-	-	24.7	151		
158	53.8	45.0	-	48.7	-	-	43.2	-	-	38.4	-	-	30.6	-	-	24.5	158		
164	52.0	44.1	-	47.6	37.5	-	42.3	-	-	37.9	-	-	30.6	-	-	24.3	164		
177	49.4	42.5	-	45.2	36.6	-	40.6	31.1	-	36.8	-	-	29.8	-	-	23.8	177		
190	46.7	40.8	-	43.0	35.7	-	38.6	30.4	-	35.5	24.7	-	28.9	-	-	23.1	190		
203	44.5	37.0	30.4	40.8	34.8	-	36.8	29.5	-	34.4	24.3	-	28.0	19.4	-	22.5	14.8	203	
217	32.6	34.0	27.6	38.6	32.0	25.6	34.8	28.9	-	32.8	24.0	-	27.3	19.2	-	21.6	14.8	217	
230	-	31.3	25.1	36.2	29.3	23.1	33.1	27.3	21.2	31.3	23.6	-	26.2	19.2	-	20.9	14.8	230	
243	-	28.9	22.9	-	26.7	20.9	32.2	24.9	19.0	29.5	23.1	18.3	25.4	19.0	-	20.3	14.8	243	
256	-	-	20.9	-	24.7	19.0	20.9	22.7	17.0	28.7	22.3	16.5	24.5	18.7	13.9	19.4	14.8	256	
269	-	-	-	-	-	17.2	-	20.7	15.2	25.1	20.3	14.8	23.8	18.5	13.7	18.7	14.8	9.7	269
282	-	-	-	-	-	15.7	-	19.0	13.7	-	18.5	13.2	23.4	18.1	12.8	18.1	14.8	9.7	282
295	-	-	-	-	-	-	-	-	12.3	-	16.8	11.7	14.3	16.3	11.2	17.6	14.8	9.7	295
308	-	-	-	-	-	-	-	-	-	-	-	10.4	-	15.0	9.9	17.2	13.9	9.0	308
322	-	-	-	-	-	-	-	-	-	-	-	9.3	-	13.7	8.8	-	12.6	7.7	322
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	7.7	-	11.5	6.8	335
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	5.7	348
361	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4.9	361

Remarks

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



TEREX | DEMAG

LIFTING CAPACITIES LUFFING FLY JIB, MAIN BOOM 83° TO 65°

360°																				85 %
169.9 ft + 13.1 ft Main boom + adapter																				
Fly jib																				
78.7 ft		98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft						
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft	1,000 lb																		ft	
66	71.0	-	-	62.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	66	
72	67.7	-	-	60.0	-	-	53.6	-	-	-	-	-	-	-	-	-	-	-	72	
79	65.0	-	-	57.5	-	-	52.0	-	-	45.0	-	-	-	-	-	-	-	-	79	
85	62.4	-	-	55.8	-	-	50.5	-	-	43.9	-	-	41.0	-	-	-	-	-	85	
92	60.4	-	-	54.2	-	-	48.9	-	-	42.5	-	-	39.9	-	-	35.1	-	-	92	
98	58.9	-	-	52.5	-	-	47.6	-	-	41.4	-	-	39.0	-	-	34.4	-	-	98	
105	-	-	-	51.4	-	-	46.3	-	-	40.3	-	-	37.9	-	-	33.5	-	-	105	
112	-	-	-	50.3	-	-	45.0	-	-	39.2	-	-	37.0	-	-	32.8	-	-	112	
118	-	41.2	-	49.4	39.2	-	43.9	-	-	38.4	-	-	36.2	-	-	32.2	-	-	118	
125	-	38.8	-	-	37.3	-	42.5	-	-	37.3	-	-	35.3	-	-	31.3	-	-	125	
131	-	37.3	-	-	35.3	-	41.7	32.6	-	36.4	-	-	34.4	-	-	30.6	-	-	131	
138	-	-	-	-	33.3	-	40.6	31.1	-	35.7	29.1	-	33.7	-	-	30.2	-	-	138	
144	-	-	-	-	31.7	-	-	29.5	-	34.8	27.6	-	33.1	-	-	29.5	-	-	144	
151	-	-	-	-	30.4	-	-	28.0	-	34.2	26.0	-	32.4	26.9	-	28.9	-	-	151	
158	-	-	-	-	-	24.5	-	26.7	-	33.7	24.7	-	31.7	25.6	-	28.2	23.6	-	158	
164	-	-	-	-	-	23.1	-	25.6	20.9	-	23.4	-	31.1	24.3	-	27.8	22.5	-	164	
177	-	-	-	-	-	-	-	-	18.7	-	21.2	17.0	30.6	22.0	-	26.9	20.1	-	177	
190	-	-	-	-	-	-	-	-	17.0	-	19.8	15.0	-	20.3	16.1	26.0	18.1	-	190	
203	-	-	-	-	-	-	-	-	-	-	-	13.4	-	19.0	14.3	-	16.5	12.6	203	
217	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.0	-	15.2	11.0	217	
230	-	-	-	-	-	-	-	-	-	-	-	-	-	-	12.1	-	14.6	9.9	230	
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	8.8	243	
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256	

196.9 ft		216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft					
ft	1,000 lb																		ft
98	30.0	-	-	23.8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	98
105	29.3	-	-	23.4	-	-	19.0	-	-	-	-	-	-	-	-	-	-	-	105
112	28.9	-	-	23.1	-	-	18.7	-	-	14.8	-	-	-	-	-	-	-	-	112
118	28.4	-	-	22.7	-	-	18.3	-	-	14.6	-	-	11.2	-	-	-	-	-	118
125	27.8	-	-	22.3	-	-	18.1	-	-	14.3	-	-	11.0	-	-	7.9	-	-	125
131	27.3	-	-	22.0	-	-	17.9	-	-	14.1	-	-	11.0	-	-	7.9	-	-	131
138	26.9	-	-	21.6	-	-	17.4	-	-	13.9	-	-	10.8	-	-	7.7	-	-	138
144	26.2	-	-	21.2	-	-	17.2	-	-	13.7	-	-	10.6	-	-	7.7	-	-	144
151	25.8	-	-	20.9	-	-	17.0	-	-	13.4	-	-	10.6	-	-	7.7	-	-	151
158	25.4	-	-	20.5	-	-	16.5	-	-	13.2	-	-	10.4	-	-	7.7	-	-	158
164	24.9	20.9	-	20.3	-	-	16.3	-	-	13.2	-	-	10.4	-	-	7.7	-	-	164
177	24.0	19.2	-	19.4	16.1	-	15.7	-	-	12.8	-	-	9.9	-	-	7.5	-	-	177
190	23.4	17.2	-	19.2	14.6	-	15.2	12.1	-	12.3	-	-	9.7	-	-	7.5	-	-	190
203	22.7	15.7	-	18.7	13.2	-	14.8	10.8	-	12.1	-	-	9.5	-	-	7.3	-	-	203
217	22.5	14.3	10.6	18.3	11.9	-	14.6	9.7	-	11.9	-	-	9.3	-	-	7.3	-	-	217
230	-	13.0	9.3	18.3	10.8	-	14.1	8.6	-	11.7	-	-	9.3	-	-	7.3	-	-	230
243	-	12.3	8.2	-	9.7	-	13.9	7.7	-	11.7	-	-	9.0	-	-	7.1	-	-	243
256	-	-	7.1	-	8.8	-	13.7	6.8	-	11.5	-	-	8.8	-	-	7.1	-	-	256
269	-	-	6.6	-	8.4	-	-	6.0	-	11.2	-	-	8.8	-	-	6.8	-	-	269
282	-	-	-	-	-	-	-	5.5	-	-	-	-	8.6	-	-	6.8	-	-	282
295	-	-	-	-	-	-	-	-	-	-	-	-	8.6	-	-	6.6	-	-	295
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.6	-	-	308
322	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	322

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**ALL TERRAIN CRANE**
AC 500-2**LIFTING CAPACITIES LUFFING FLY JIB WITH SSL, MAIN BOOM 83°-65°**

360°85%																
169.9 ft + 13.1 ft Main boom + adapter																
Fly jib																
98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft	
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°		65°
ft	1,000 lb															ft
66	110.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	66
72	106.5	-	-	92.4	-	-	-	-	-	-	-	-	-	-	-	72
79	102.5	-	-	92.8	-	-	78.3	-	-	-	-	-	-	-	-	79
85	99.2	-	-	86.4	-	-	83.8	-	-	68.6	-	-	-	-	-	85
92	96.1	-	-	83.6	-	-	78.3	-	-	77.4	-	-	70.5	-	-	92
98	93.0	-	-	81.1	-	-	73.0	-	-	73.2	-	-	67.5	-	-	98
105	90.8	-	-	78.7	-	-	69.2	-	-	68.8	-	-	64.4	-	-	105
112	88.8	-	-	76.5	-	-	67.2	-	-	64.4	-	-	61.5	-	-	112
118	86.6	73.2	-	75.0	-	-	65.5	-	-	61.7	-	-	58.4	-	-	118
125	-	69.0	-	73.4	66.1	-	63.5	-	-	58.9	-	-	55.6	-	-	125
131	-	65.5	-	72.1	63.1	-	62.4	-	-	56.9	-	-	53.4	-	-	131
138	-	62.2	-	70.8	59.7	-	61.3	55.6	-	55.6	-	-	50.9	-	-	138
144	-	59.5	-	-	57.1	-	60.2	53.6	-	54.7	49.8	-	48.7	-	-	144
151	-	56.9	48.1	-	54.5	-	59.1	51.6	-	53.8	48.7	-	46.7	42.5	-	151
158	-	-	45.6	-	52.5	-	58.2	49.8	-	52.9	47.6	-	45.9	41.7	-	158
164	-	-	43.4	-	50.5	41.4	-	48.1	-	52.0	46.3	-	45.2	40.8	-	164
177	-	-	-	-	-	37.7	-	44.5	36.4	50.7	43.9	-	43.9	38.8	-	177
190	-	-	-	-	-	35.1	-	40.6	33.1	-	41.2	34.4	42.8	37.3	-	190
203	-	-	-	-	-	-	-	-	30.4	-	38.4	31.3	-	35.7	30.0	203
217	-	-	-	-	-	-	-	-	-	-	-	29.1	-	34.0	27.3	217
230	-	-	-	-	-	-	-	-	-	-	-	26.9	-	31.3	24.9	230
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	22.7	243
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			ft	
ft	1,000 lb																		ft
92	50.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92		
98	60.6	-	-	40.8	-	-	-	-	-	-	-	-	-	-	-	-	98		
105	58.9	-	-	50.7	-	-	33.3	-	-	-	-	-	-	-	-	-	105		
112	56.9	-	-	49.4	-	-	42.5	-	-	25.1	-	-	-	-	-	-	112		
118	54.9	-	-	47.8	-	-	41.7	-	-	35.1	-	-	19.8	-	-	-	118		
125	53.1	-	-	46.3	-	-	40.8	-	-	34.6	-	-	28.4	-	-	13.4	125		
131	51.1	-	-	44.8	-	-	39.9	-	-	34.2	-	-	28.2	-	-	22.5	131		
138	49.2	-	-	43.2	-	-	38.8	-	-	33.7	-	-	27.8	-	-	22.3	138		
144	47.2	-	-	41.9	-	-	37.9	-	-	33.1	-	-	27.6	-	-	22.0	144		
151	45.2	-	-	40.3	-	-	37.0	-	-	32.6	-	-	27.3	-	-	21.8	151		
158	43.2	-	-	38.8	-	-	35.7	-	-	32.0	-	-	27.1	-	-	21.6	158		
164	41.4	35.9	-	37.5	-	-	34.6	-	-	31.5	-	-	26.9	-	-	21.4	164		
177	38.8	34.4	-	34.6	29.3	-	32.2	-	-	29.5	-	-	26.0	-	-	20.7	177		
190	36.8	32.8	-	32.6	28.0	-	29.8	24.0	-	27.8	19.4	-	25.1	-	-	20.3	190		
203	35.9	31.7	-	30.6	26.9	-	27.8	22.9	-	26.0	19.0	-	24.0	15.0	-	19.4	203		
217	35.3	30.9	26.5	29.5	25.8	-	26.2	21.8	-	24.5	18.5	-	22.9	14.8	-	18.7	217		
230	-	29.8	24.0	29.1	25.1	22.0	24.5	20.9	-	22.9	17.9	-	21.6	14.6	-	18.1	230		
243	-	28.0	21.8	-	24.3	19.8	23.8	20.3	17.4	21.6	17.4	-	20.5	14.3	-	17.4	243		
256	-	-	20.1	-	23.6	18.1	23.6	19.6	15.9	20.5	16.8	13.0	19.2	14.1	9.7	16.8	256		
269	-	-	18.3	-	22.0	16.3	-	19.2	14.1	20.1	16.3	12.6	18.1	13.7	9.7	16.1	269		
282	-	-	-	-	-	14.8	-	18.3	12.6	-	15.7	12.1	17.6	13.4	9.5	15.4	282		
295	-	-	-	-	-	-	-	-	11.2	-	15.4	10.8	17.2	13.2	9.3	15.0	295		
308	-	-	-	-	-	-	-	-	10.1	-	14.8	9.5	-	13.0	9.0	14.8	308		
322	-	-	-	-	-	-	-	-	-	-	-	8.4	-	13.0	7.9	-	322		
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.8	-	335		
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.0	-	348		
361	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9.7	361		

Remarks

Counterweight 176,400 lb 220,500 lb 264,600 lb 308,600 lb 352,700 lb 396,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

**TEREX | DEMAG****TECHNICAL DESCRIPTION****CARRIER**

Drive / Steering	16 x 8 x 14.
Frame	Demag-built special main frame of high-strength fine-grain structural steel, with pot-shaped centre section and foldaway outrigger boxes.
Outriggers	4-point outrigger system, folding outrigger beams, fully hydraulic horizontal and vertical extension, providing 360° continuous rotation. Outrigger loading indicator.
Engine	Water-cooled 8-cylinder DaimlerChrysler diesel engine OM 502 LA, output 448 kW (610 hp) at 1800 ¹ /min, torque 2700 Nm at 1200 ¹ /min. Fuel tank capacity: 156 gallons.
Transmission	Allison type CLBT 755 with electronic transmission control (ATEC), torque converter and hydraulic retarder.
Axles	1 + 2 + 5 driving, connectable drive of axle 3. 1-4 and 6-8 steering, all axles hydropneumatically suspended and hydraulically blockable.
Wheels and tires	16 wheels, 14.00 R 25.
Steering	Dual-circuit semiblock mechanical steering with hydraulic booster.
Brakes	In conformity with EC directives. Sustained action brake: constant decompression valve, exhaust brake, hydraulic retarder integrated into gearbox.
Electrical equipment	24 V system, lighting in compliance with EC standards.
Driver's cab	Rubber-mounted low-line steel cab, ergonomic design, with pneumatically suspended driver's seat and one passenger's seat; vertically adjustable steering wheel; heated outside mirrors, mirror electrically adjustable; dashboard with clearly arranged instrumentation and carrier controls.

SUPERSTRUCTURE

Engine	Water-cooled 6-cylinder DaimlerChrysler diesel engine OM 906 LA, output: 205 kW (279 hp) at 2300 ¹ /min, torque 1100 Nm at 1300 ¹ /min. Fuel tank capacity: 79 gallons.
Hydraulic system	Powered via 5 hydraulic circuits, 4 main pumps for independent control movements, 1 pump for auxiliary circuits, one control pump for the servo control.
Hoist I	Axial-piston variable displacement motor, hoist drum with integrated planetary gear reducer, and brake.
Slew unit	Axial piston motor with planetary gearing, spring-applied automatic holding brake.
Boom elevation	2 differential cylinders with pilot-controlled lowering brake valves.
Control	Electric pilot-control by two self-centering servo levers.
Crane cab	Spacious all-steel comfortable cab (tiltable) with sliding door and large hinged windscreen, roof window with armoured glass, full instrumentation and crane controls, comfortable seat with ergonomic armrest mounted joystick controls, working light. Self-contained hot water heater with timer and 'Heizmatic' for sensitive heat flow control. Intermittent control window wiper and washer, air-conditioning.
Main boom	Boom base and four telescopic sections fabricated from fine grain structural steel, telescoping with partial load. Buckling-resistant Demag ovaloid design with diagonally arranged self-centering slider shoes.
Counterweight	220,500 lb, divisible.
Safety devices	Electronic safe load indicator with large graphic display and sealed touch-type keyboard, digital read-out for hook load, nominal load, boom length, angle, and radius. Analog display to indicate the capacity utilization, and monitoring code to assist in trouble shooting. Integrated control system for boom telescoping, display for load charts and both theoretical and measured outrigger loadings. In addition, provision has been made for: limit switches on hoist and lowering motions, pressure relief and safety holding valves, hoist rotation indicator and anemometer.

OPTIONAL EQUIPMENT

Superlift attachment	This attachment used to increase the crane's load moment consists of both the boom suspension system folding out, as required, at 0°, 30° or 60°. The boom suspension system provides for an automatic rope length adjustment for boom telescoping, and is lowered to the main boom when not needed (axle loads to be observed).
Main boom extension	Lattice extension consisting of components of the 295.3 ft luffing jib, 19.7 – 98.4 ft long, 0°, 20° and 40° offset from 39.3 ft length.
Fixed fly jib	Fixed lattice jib, comprising of parts of the luffing jib, 27.6 – 204.7 ft m long (LF system).
Luffing jib	78.7 – 295.3 ft, plus 13.1 ft adapter, with two luffing masts, pendant bars, electrical equipment, safety devices (hoist II is required when using the luffing jib).
Additional counterweight	176,400 lb, integrated into the standard counterweight, installed by the crane itself.
Additional jack leg	For special duties with 48.2 ft main boom.
Hoist II	Axial piston variable displacement motor, hoist drum with integrated planetary reduction, spring-applied multi-disk brake, hoist rope.
Independent rear axle steering	

ALL TERRAIN CRANE

AC 500-2

NOTES TO LIFTING CAPACITY

Ratings are in compliance with ISO 4305 and DIN 15019.2 (test load = 1.25 x suspended load + 0.1 x dead weight of boom head).
Weight of hook blocks and slings is part of the load, and is to be deducted from the capacity ratings.

Crane operation with main boom is permissible up to a

wind pressure of: 1.25 lb/ft²
wind speed of: 21.9 mph

Consult operation manual for further details.

Note: Data published herein is intended as a guide only and shall not be construed to warrant applicability for lifting purposes.
Crane operation is subject to the computer charts and operation manual both supplied with the crane.


KEY



Counterweight



Lifting capacities on outriggers 360°



"D"

SL

Superlift



OVERVIEW OF STANDARD DUTY CHARTS



31.6 ft x 31.5 ft



26.4 ft x 24.0 ft

Main boom

Main boom		0 lb	44,100 lb	88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		360°	360°	360°	360°	360°	360°	360°	360°	360°	360°
48.2 ft		x	x	x	x	x	x	x	x	x	-
63.3 ft		x	x	x	x	x	x	x	x	x	-
78.7 ft		x	x	x	x	x	x	x	x	x	-
93.8 ft		x	x	x	x	x	x	x	x	x	-
108.9 ft		x	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL
124.3 ft		x	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL
139.4 ft		x	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL
154.9 ft		x	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL
169.9 ft		x	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL
183.7 ft		x	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL

Main boom											
		0 lb	44,100 lb	88,200 lb	132,300 lb	176,400 lb	220,500 lb				
48.2 ft		x	x	x	x	x	x				
63.3 ft		x	x	x	x	x	x				
78.7 ft		x	x	x	x	x	x				
93.8 ft		x	x	x	x	x	x				
108.9 ft		x	x	x	x	x	x				
124.3 ft		x	x	x	x	x	x				
139.4 ft		x	x	x	x	x	x				
154.9 ft		-	x	x	x	x	x				
169.9 ft		-	x	x	x	x	x				
183.7 ft		-	x	x	x	x	x				



31.6 ft x 31.5 ft



26.4 ft x 24.0 ft

Main boom extension

Main boom	Extension										
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb		
183.7 ft	19.7 ft – 0°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	39.4 ft – 0°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	59.1 ft – 0°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	78.7 ft – 0°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	98.4 ft – 0°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	39.4 ft – 0°	SSL = 30°	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	59.1 ft – 0°	SSL = 30°	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	78.7 ft – 0°	SSL = 30°	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	98.4 ft – 0°	SSL = 30°	x	x	x/+SSL	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	39.4 ft – 20°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	59.1 ft – 20°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	78.7 ft – 20°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
183.7 ft	98.4 ft – 20°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	39.4 ft – 40°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	
	59.1 ft – 40°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	
	78.7 ft – 40°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	
	98.4 ft – 40°	SSL = 0°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	
	39.4 ft – 20°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	59.1 ft – 20°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	78.7 ft – 20°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	98.4 ft – 20°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL	+SSL	
	39.4 ft – 40°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	
	59.1 ft – 40°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	
	78.7 ft – 40°	SSL = 30°	x	x	x	x/+SSL	x/+SSL	+SSL	+SSL	-	

Main boom	Extension										
		88,200 lb	132,300 lb	176,400 lb	220,500 lb						
183.7 ft	19.7 ft – 0°	x	x	x	x						
	39.4 ft – 0°	x	x	x	x						
	59.1 ft – 0°	x	x	x	x						
	78.7 ft – 0°	x	x	x	x						
	98.4 ft – 0°	x	x	x	x						
	39.4 ft – 20°	x	x	x	x						
	59.1 ft – 20°	x	x	x	x						
	78.7 ft – 20°	x	x	x	x						
	98.4 ft – 20°	x	x	x	x						
	39.4 ft – 40°	x	x	x	x						
	59.1 ft – 40°	x	x	x	x						
	78.7 ft – 40°	x	x	x	x						



31.6 ft x 31.5 ft

Fixed fly jib

Main boom	Extension										
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb		
139.4 ft	27.6 ft – 0°	x	x	x	x	x	x	x	-	-	
	47.2 ft – 0°	x	x	x	x	x	x	x	-	-	
	66.9 ft – 0°	x	x	x	x	x	x	x	-	-	
	86.6 ft – 0°	x	x	x	x	x	x	x	-	-	
	106.3 ft – 0°	x	x	x	x	x	x	x	-	-	
	126.0 ft – 0°	x	x	x	x	x	x	x	-	-	
	145.7 ft – 0°	x	x	x	x	x	x	x	-	-	
	165.4 ft – 0°	x	x	x	x	x	x	x	-	-	
	185.0 ft – 0°	x	x	x	x	x	x	x	-	-	
	204.7 ft – 0°	x	x	x	x	x	x	x	-	-	
	86.6 ft – 20°	x	x	x	x	x	x	-	-	-	
	106.3 ft – 20°	x	x	x	x	x	x	-	-	-	
139.4 ft	126.0 ft – 20°	x	x	x	x	x	x	-	-	-	
	145.7 ft – 20°	x	x	x	x	x	x	-	-	-	
	165.4 ft – 20°	x	x	x	x	x	x	-	-	-	
	185.0 ft – 20°	x	x	x	x	x	x	-	-	-	
	204.7 ft – 20°	x	x	x	x	x	x	-	-	-	
	86.6 ft – 40°	x	x	x	x	x	-	-	-	-	
	106.3 ft – 40°	x	x	x	x	x	-	-	-	-	
	126.0 ft – 40°	x	x	x	x	x	-	-	-	-	
	145.7 ft – 40°	x	x	x	x	x	-	-	-	-	
	165.4 ft – 40°	x	x	x	x	x	-	-	-	-	
	185.0 ft – 40°	x	x	x	x	x	-	-	-	-	
	204.7 ft – 40°	x	x	x	x	x	-	-	-	-	

Main boom	Extension									
		88,200 lb	132,300 lb	176,400 lb**	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb	
		SSL 0° + 30°								
	27.6 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL+	
	47.2 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	SSL	
	66.9 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL	
	86.6 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL	
	106.3 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL	
	126.0 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL	
	145.7 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL	
	165.4 ft – 0°	x	x	x/4SSL	x/4SSL	x/4SSL	x/4SSL	x/4SSL	+SSL	
	169.9 ft		SSL 0°							
86.6 ft – 20°		x	x	x	x/4SSL	x/4SSL	x/4SSL	+SSL	-	
106.3 ft – 20°		x	x	x	x/4SSL	x/4SSL	x/4SSL	+SSL	-	
126.0 ft – 20°		x	x	x	x/4SSL	x/4SSL	x/4SSL	+SSL	-	
145.7 ft – 20°		x	x	x	x/4SSL	x/4SSL	x/4SSL	+SSL	-	
165.4 ft – 20°		x	x	x	x/4SSL	x/4SSL	x/4SSL	+SSL	-	
		SSL 0°								
86.6 ft – 40°		x	x	x	x/4SSL	x/4SSL	+SSL	-	-	
106.3 ft – 40°		x	x	x	x/4SSL	x/4SSL	+SSL	-	-	
126.0 ft – 40°		x	x	x	x/4SSL	x/4SSL	+SSL	-	-	
				</						

** 176,400 lb:
only SSL 30°



ALL TERRAIN CRANE
AC 500-2

OVERVIEW OF STANDARD DUTY CHARTS

 31.6 ft x 31.5 ft

Luffing fly jib

Main boom	Jib								
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83° / 73° / 65°							
48.2 ft + 13.1 ft 63.3 ft + 13.1 ft 78.7 ft + 13.1 ft 93.8 ft + 13.1 ft 108.9 ft + 13.1 ft	78.7 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	98.4 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	118.1 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	137.8 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	157.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	177.2 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	196.9 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	216.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	236.2 ft	-	-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	255.9 ft	-	-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	275.6 ft	-	-	-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	295.3 ft	-	-	-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x

Main boom	Jib								
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83° / 73° / 65°							
154.9 ft + 13.1 ft	78.7 ft	-	x/-/-	x/-/-	x/x/-	x/x/-	x/x/-	-	-
	98.4 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-	-
	118.1 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-	-
	137.8 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-	-
	157.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-	-
	177.2 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-	-
	196.9 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-	-
	216.5 ft	-	x/-/-	x/-/-	x/x/-	x/x/-	x/x/-	-	-
	236.2 ft	-	-	x/-/-	x/x/-	x/x/-	x/x/-	-	-
	255.9 ft	-	-	x/-/-	x/-/-	x/-/-	x/-/-	-	-
	275.6 ft	-	-	-	x/-/-	x/-/-	x/-/-	-	-
	295.3 ft	-	-	-	x/-/-	x/-/-	x/-/-	-	-

Main boom	Jib								
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83° / 73° / 65°							
124.3 ft + 13.1 ft	78.7 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	98.4 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	118.1 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	137.8 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	157.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	177.2 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	196.9 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	216.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	236.2 ft	-	-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	255.9 ft	-	-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	275.6 ft	-	-	-	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	295.3 ft	-	-	-	x/x/-	x/x/-	x/x/-	x/x/-	x/x/-

Main boom		Jib								
			88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
			83° / 73° / 65°							
169.9 ft + 13.1 ft	78.7 ft	-	x/-/-	x/-/-	x/x/-	x/x/-	-	-	-	
	98.4 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-	-	
	118.1 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-	-	
	137.8 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-	-	
	157.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-	-	
	177.2 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-	-	
	196.9 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-	-	
	216.5 ft	-	x/-/-	x/-/-	x/x/-	x/x/-	-	-	-	
	236.2 ft	-	-	x/-/-	x/x/-	x/x/-	-	-	-	
	255.9 ft	-	-	x/-/-	x/-/-	x/-/-	-	-	-	
	275.6 ft	-	-	-	x/-/-	x/-/-	-	-	-	
	295.3 ft	-	-	-	x/-/-	x/-/-	-	-	-	

Main boom	Jib								
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83° / 73° / 65°							
139.4 ft + 13.1 ft	78.7 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	98.4 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	118.1 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	137.8 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	157.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	177.2 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	196.9 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	216.5 ft	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	236.2 ft	-	-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	255.9 ft	-	-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x	-
	275.6 ft	-	-	-	x/x/x	x/x/x	x/x/x	x/x/x	-
	295.3 ft	-	-	-	x/x/-	x/x/-	x/x/-	x/x/-	-

with SSL 0°

	Jib	Main boom 108.9 ft + 13.1 ft				Main boom 139.4 ft + 13.1 ft			
		264,600 lb	308,600 lb	352,700 lb	396,800 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83° / 73° / 65°							
	98.4 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	118.1 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	137.8 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	157.5 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	177.2 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	196.9 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	216.5 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	236.2 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/-	x/x/x	x/x/x	x/x/x
	255.9 ft	x/x/-	x/x/x	x/x/x	x/x/x	x/x/-	x/x/-	x/x/x	x/x/x
	275.6 ft	x/x/-	x/x/x	x/x/x	x/x/x	x/x/-	x/x/-	x/x/x	x/x/x
	295.3 ft	x/x/-	x/x/-	x/x/x	x/x/x	x/x/-	x/x/-	x/x/x	x/x/x

	Jib	Main boom 154.9 ft + 13.1 ft				Main boom 169.9 ft + 13.1 ft			
		264,600 lb	308,600 lb	352,700 lb	396,800 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83° / 73° / 65°							
	98.4 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	118.1 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	137.8 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	157.5 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	177.2 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	196.9 ft	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
	216.5 ft	x/x/-	x/x/x	x/x/x	x/x/x	x/x/-	x/x/x	x/x/x	x/x/x
	236.2 ft	x/x/-	x/x/x	x/x/x	x/x/x	x/x/-	x/x/-	x/x/x	x/x/x
	255.9 ft	x/x/-	x/x/-	x/x/x	x/x/x	x/x/-	x/x/-	x/x/x	x/x/x
	275.6 ft	x/x/-	x/x/-	x/x/x	x/x/x	x/x/-	x/x/-	x/x/x	x/x/x
	295.3 ft	-	-	-	-	-	-	-	-

with SSL 60°

Main boom	Jib								
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
		83°							
108.9 ft + 13.1 ft 124.3 ft + 13.1 ft 139.4 ft + 13.1 ft 154.9 ft + 13.1 ft 169.9 ft + 13.1 ft	98.4 ft	-	-	X	X	X	X	X	X
	118.1 ft	-	-	X	X	X	X	X	X
	137.8 ft	-	-	X	X	X	X	X	X
	157.5 ft	-	-	X	X	X	X	X	X
	177.2 ft	-	-	X	X	X	X	X	X
	196.9 ft	-	-	X	X	X	X	X	X
	216.5 ft	-	-	X	X	X	X	X	X
	236.2 ft	-	-	X	X	X	X	X	X
	255.9 ft	-	-	X	X	X	X	X	X
	275.6 ft	-	-	-	X	X	X	X	X
295.3 ft	-	-	-	X	X	X	X	X	

26.4 ft x 24.0 ft

Main boom	Jib								
		88,200 lb	132,300 lb	176,400 lb	220,500 lb	264,600 lb	308,600 lb	352,700 lb	396,800 lb
48.2 ft + 13.1 ft	78.7 ft	-	X	X	X	-	-	-	-
63.3 ft + 13.1 ft	98.4 ft	-	X	X	X	-	-	-	-
78.7 ft + 13.1 ft	118.1 ft	-	X	X	X	-	-	-	-
93.8 ft + 13.1 ft	137.8 ft	-	X	X	X	-	-	-	-
108.9 ft + 13.1 ft	157.5 ft	-	X	X	X	-	-	-	-
124.3 ft + 13.1 ft	177.2 ft	-	X	X	X	-	-	-	-
139.4 ft + 13.1 ft	196.9 ft	-	X	X	X	-	-	-	-
154.9 ft + 13.1 ft	216.5 ft	-	-	X	X	-	-	-	-
169.9 ft + 13.1 ft	236.2 ft	-	-	-	X	-	-	-	-
	255.9 ft	-	-	-	X	-	-	-	-





ALL TERRAIN CRANE AC 500-2

NOTES



TEREX | DEMAG

ALL TERRAIN CRANE
AC 500-2

The information contained in this brochure merely consists of general descriptions and a broad compilation of performance features which might not apply precisely as described under specific application conditions or which may change as a result of further product development.
The desired performance features only become binding once expressly agreed in the final contract.

Note: Data published herein is intended as a guide only and shall not be construed to warrant applicability for lifting purposes.
Crane operation is subject to the computer charts and operation manual both supplied with the crane.

Subject to change without notice.

08 / 05



TEREX | DEMAG

Terex Cranes Wilmington Operations

Mobile hydraulic and lattice-boom cranes
202 Raleigh St. · Wilmington, NC 28412 USA
Phone +1 910 395 8500 · Fax +1 910 395 8538
Email: american@american-crane.com