




AC 700






800t



HIGHLIFTS

Demag AC 700

- ▶ Most powerful telescopic crane in the world roadable with full main boom
- ▶ Superior boom technology provides exceptional lifting capacities
- ▶ Exceptional capacity enhancements due to new Sideways Superlift
- ▶ Star-type outriggers giving enhanced stability
- ▶ Fast rigging and optimized transport weights for all configurations



WWW. terex-cranes.com



Contents

		Page:
Specifications		
Dimensions		4
Specifications		6
Main boom		
Working ranges		7
Lifting capacities		8
Lifting capacities with SSL 0°		11
Main boom extension		
Working ranges		13
Lifting capacities		14
Lifting capacities with SSL 0° + 30°		15
Fixed fly jib		
Working ranges		17
Lifting capacities		18
Lifting capacities with SSL 0° + 30°		19
Working ranges with SSL 0° + 30°		20
Luffing fly jib		
Working ranges		21
Lifting capacities		22
Working ranges with SSL		31
Lifting capacities with SSL		32
Technical description		
Carrier · Superstructure · Optional equipment		37
Overview of standard duty charts		
.....		38

1

2

3

4


5


6

7




Dimensions





* Tail swing above ground



*)Duties with reduced outrigger base on request



Specifications

Axle loads and weights

Crane with main boom, rear outriggers and hook block	
Axles	9 x 26,500 lb
Total weight	238,500 lb

Working speeds (infinitely variable)

Mechanisms	Line speed	Max. permissible line pull	Rope length
Hoist I	max. 469 ft / min	30,150 lb	1 640 ft
Hoist II	max. 495 ft / min	30,150 lb	2 530 ft
Slewing			max. 1.0 rpm
Telescoping speed			50.9 – 196.6 ft: approx. 480 s
Boom elevation			-0.5° – +83°: 120 s


Carrier performance

Travel speed	0 to 39 mph
--------------	-------------

Hook block / Heavy-lift attachment

Type	Possible load	Number of sheaves	Weight	„D”	max. reeving	Heavy-lift attachment
320	689,000 lb	13	8,800 lb	13 ft	26	2 add. sheaves
250	518,100 lb	9	6,200 lb	13 ft	19	
200	417,000 lb	7	5,700 lb	10 ft	15	
160	311,000 lb	5	4,900 lb	10 ft	11	
100	203,000 lb	3	4,000 lb	10 ft	7	
40	88,200 lb	1	2,700 lb	9 ft	3	
13.5	30,000 lb	Single line hook	1,400 lb	7 ft	1	

Working ranges main boom



Lifting capacities main boom

308,700 lb



 360°

DIN/ISO

		Main boom													
Radius	ft	50.9*	50.9	67.3*	67.3	83.7*	83.7	100.0	116.5	132.9	149.3	165.7	182.1	196.9	Radius
ft	1,000 lb														ft
10	1543.5 ¹⁾	-	687.8	-	-	-	-	-	-	-	-	-	-	-	10
10	1255.1 ²⁾	687.8	687.8	687.8	687.8	-	-	-	-	-	-	-	-	-	10
11	1147.6 ²⁾	687.8	687.8	687.8	687.8	-	-	-	-	-	-	-	-	-	11
13	1014.1 ²⁾	687.8	687.8	687.8	661.3	661.3	-	-	-	-	-	-	-	-	13
15	923.3 ²⁾	685.3	687.8	684.6	661.3	661.3	-	-	-	-	-	-	-	-	15
16	884.3 ²⁾	674.5	687.8	671.2	661.3	661.3	510.3	437.0	-	-	-	-	-	-	16
19	784.9 ²⁾	614.4	659.9	611.7	610.8	610.8	486.1	416.8	353.8	-	-	-	-	-	19
23	680.5	544.0	585.8	539.6	535.2	535.2	453.9	387.7	321.6	271.0	-	-	-	-	23
26	618.0	499.7	533.4	497.3	488.8	488.8	431.7	367.6	299.4	256.9	-	-	-	-	26
29	562.9	462.7	490.2	458.6	448.0	448.0	407.7	347.4	279.1	244.6	227.0	-	-	-	29
33	497.4	419.4	441.2	415.0	401.7	401.7	377.7	320.7	254.7	228.5	211.0	183.5	-	-	33
39	402.7	367.0	382.8	364.6	347.2	347.2	333.4	284.4	224.5	205.3	190.8	165.3	144.0	-	39
46	-	-	330.3	314.9	301.6	301.6	288.4	253.2	197.0	181.6	168.4	148.6	129.9	-	46
52	-	-	296.0	282.6	269.4	269.4	256.1	231.1	176.9	164.5	153.3	136.5	120.9	-	52
59	-	-	216.7	206.7	240.5	240.5	225.1	211.7	156.6	146.7	136.8	124.6	110.3	-	59
65	-	-	-	-	220.3	220.3	204.9	195.6	142.5	133.6	125.7	116.5	103.2	-	65
72	-	-	-	-	188.2	179.6	185.6	177.9	128.2	120.4	113.8	107.1	95.0	-	72
79	-	-	-	-	-	-	170.2	162.6	115.3	108.7	104.4	98.9	87.9	-	79
85	-	-	-	-	-	-	155.0	150.5	106.2	100.7	97.3	92.9	82.9	-	85
92	-	-	-	-	-	-	-	138.6	97.9	91.3	89.1	85.8	77.0	-	92
98	-	-	-	-	-	-	-	129.6	90.8	85.3	83.1	80.8	72.0	-	98
105	-	-	-	-	-	-	-	110.2	84.8	79.3	77.1	74.9	67.2	-	105
111	-	-	-	-	-	-	-	-	78.8	74.3	72.1	69.9	63.8	-	111
118	-	-	-	-	-	-	-	-	73.9	68.4	66.2	65.7	59.5	-	118
124	-	-	-	-	-	-	-	-	-	65.1	62.7	62.1	56.1	-	124
131	-	-	-	-	-	-	-	-	-	60.9	58.5	58.1	52.5	-	131
138	-	-	-	-	-	-	-	-	-	56.9	54.5	54.5	49.5	-	138
144	-	-	-	-	-	-	-	-	-	-	51.7	51.7	46.8	-	144
151	-	-	-	-	-	-	-	-	-	-	48.6	48.6	44.0	-	151
157	-	-	-	-	-	-	-	-	-	-	-	46.2	42.0	-	157
164	-	-	-	-	-	-	-	-	-	-	-	43.4	39.6	-	164
177	-	-	-	-	-	-	-	-	-	-	-	-	35.7	-	177
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	190

Remarks

- * central jack leg + 352,800 lb counterweight
- 1) over rear, special attachment required, on request
- 2) over rear, heavy-lift attachment required



220,500 lb



360°

DIN/ISO

Main boom												Radius ft
Radius	ft	50.9	67.3	83.7	100.0	116.5	132.9	149.3	165.7	182.1	196.9	
ft						1,000 lb						ft
10		687.8	687.8	-	-	-	-	-	-	-	-	10
11		687.8	687.8	-	-	-	-	-	-	-	-	11
13		687.8	687.8	661.3	-	-	-	-	-	-	-	13
15		682.7	682.1	659.7	-	-	-	-	-	-	-	15
16		661.2	657.9	653.0	510.3	437.0	-	-	-	-	-	16
19		598.5	595.8	596.3	486.1	416.8	353.8	-	-	-	-	19
23		528.6	524.2	526.4	453.9	387.7	321.6	271.0	-	-	-	23
26		486.3	481.8	484.1	431.7	367.6	299.4	256.9	-	-	-	26
29		449.5	446.9	447.3	407.7	347.4	279.1	244.6	227.0	-	-	29
33		408.4	404.0	401.7	377.7	320.7	254.7	228.5	211.0	183.5	-	33
39		358.0	353.6	347.2	333.4	284.4	224.5	205.3	190.8	165.3	144.0	39
46		-	297.1	299.3	288.4	253.2	197.0	181.6	168.4	148.6	129.9	46
52		-	256.8	259.0	256.1	231.1	176.9	164.5	153.3	136.5	120.9	52
59		-	206.5	220.7	225.1	211.7	156.6	146.7	136.8	124.6	110.3	59
65		-	-	186.5	190.9	194.6	142.5	133.6	125.7	116.5	103.2	65
72		-	-	156.1	159.5	163.9	128.2	120.4	113.8	107.1	95.0	72
79		-	-	-	144.8	140.4	115.3	108.7	104.4	98.9	87.9	79
85		-	-	-	129.7	124.2	106.2	100.7	97.3	92.9	82.9	85
92		-	-	-	-	108.8	97.9	91.3	89.1	85.8	77.0	92
98		-	-	-	-	97.7	90.8	85.3	83.1	80.8	72.0	98
105		-	-	-	-	88.1	83.7	79.3	77.1	74.9	67.2	105
111		-	-	-	-	-	76.7	74.3	72.1	69.9	63.8	111
118		-	-	-	-	-	68.4	68.4	66.2	65.7	59.5	118
124		-	-	-	-	-	-	63.0	62.7	62.1	56.1	124
131		-	-	-	-	-	-	56.8	58.1	58.1	52.5	131
138		-	-	-	-	-	-	51.4	52.5	54.5	49.5	138
144		-	-	-	-	-	-	-	48.3	50.5	46.8	144
151		-	-	-	-	-	-	-	43.8	46.0	44.0	151
157		-	-	-	-	-	-	-	-	42.6	42.0	157
164		-	-	-	-	-	-	-	-	38.8	39.0	164
177		-	-	-	-	-	-	-	-	-	32.9	177

2



Lifting capacities main boom

132,300 lb  360° **DIN/ISO**

Main boom												Radius
Radius	ft	50.9	67.3	83.7	100.0	116.5	132.9	149.3	165.7	182.1	196.9	
ft												ft
						1,000 lb						
10		687.8	687.8	-	-	-	-	-	-	-	-	10
11		687.8	687.8	-	-	-	-	-	-	-	-	11
13		687.8	687.8	661.3	-	-	-	-	-	-	-	13
15		667.0	662.6	657.2	-	-	-	-	-	-	-	15
16		644.1	639.7	639.7	510.3	437.0	-	-	-	-	-	16
19		582.6	578.2	580.4	486.1	416.8	353.8	-	-	-	-	19
23		513.2	511.0	511.0	453.9	387.7	321.6	271.0	-	-	-	23
26		472.9	468.6	470.7	431.7	367.6	299.4	256.9	-	-	-	26
29		436.2	433.7	434.0	407.7	347.4	279.1	244.6	227.0	-	-	29
33		383.6	379.2	381.4	377.3	320.7	254.7	228.5	211.0	183.5	-	33
39		317.1	312.7	314.9	318.8	284.4	224.5	205.3	190.8	165.3	144.0	39
46		-	241.9	246.3	246.3	242.0	197.0	181.6	168.4	148.6	129.9	46
52		-	189.5	191.8	207.0	200.7	176.9	164.5	153.3	136.5	120.9	52
59		-	146.9	149.1	164.6	159.0	155.5	146.7	136.8	124.6	110.3	59
65		-	-	123.8	138.2	132.7	129.4	129.6	125.7	116.5	103.2	65
72		-	-	101.9	115.2	109.7	106.4	107.5	108.4	107.1	95.0	72
79		-	-	-	97.6	92.1	93.3	89.8	92.0	94.2	87.9	79
85		-	-	-	86.5	81.0	86.3	81.8	79.9	82.1	82.9	85
92		-	-	-	-	69.2	74.7	75.9	68.1	71.4	71.4	92
98		-	-	-	-	62.4	66.7	69.8	61.8 **	63.6	64.2	98
105		-	-	-	-	54.8	59.7	61.9	57.3 **	55.5	56.2	105
111		-	-	-	-	-	53.8	56.0	53.4 **	49.5	50.1	111
118		-	-	-	-	-	48.1	50.1	49.8 **	43.3	43.7	118
124		-	-	-	-	-	-	45.6	46.2 **	38.6	39.1	124
131		-	-	-	-	-	-	40.9	41.6 **	33.8	34.3	131
138		-	-	-	-	-	-	36.9	37.3 **	29.6	30.0	138
144		-	-	-	-	-	-	-	32.4 **	26.4	26.8	144
151		-	-	-	-	-	-	-	21.1	23.1	23.5	151
157		-	-	-	-	-	-	-	-	20.6	20.9	157
164		-	-	-	-	-	-	-	-	18.0	18.3	164
177		-	-	-	-	-	-	-	-	-	13.9	177

0 lb  360° **DIN/ISO**

		Main boom											
Radius	ft	50.9	67.3	83.7	100.0	116.5	132.9	149.3	159.1	165.7	182.1	196.9	Radius
	ft	1,000 lb											ft
10		687.8	687.8	-	-	-	-	-	-	-	-	-	10
11		687.8	687.8	-	-	-	-	-	-	-	-	-	11
13		683.7	681.7	662.8	-	-	-	-	-	-	-	-	13
15		638.3	634.2	636.1	-	-	-	-	-	-	-	-	15
16		615.5	612.7	613.3	510.3	437.0	-	-	-	-	-	-	16
19		548.7	544.7	546.5	486.1	416.8	364.9	-	-	-	-	-	19
23		448.8	443.8	380.2	360.5	310.0	268.3	241.9	-	-	-	-	23
26		366.1	308.7	273.3	271.8	237.4	218.0	192.5	153.7	-	-	-	26
29		274.2	230.1	210.0	215.5	189.8	183.8	170.6	147.6	147.2	-	-	29
33		179.6	165.5	154.9	165.0	146.4	144.3	140.0	135.6	118.0	114.8	-	33
39		110.1	102.0	104.5	119.6	120.5	113.1 *	105.7	102.3	87.8	86.6	82.6	39
46		-	63.0	65.4	82.4	90.1	89.0 *	79.1	77.0	64.2	64.6	62.0	46
52		-	44.5	46.3	61.8	68.9	69.9 *	63.8	62.6	50.1	51.1	49.3	52
59		-	30.0	31.2	45.5	52.6	53.4 *	49.2	49.4	37.5	39.1	37.7	59
65		-	-	22.5	35.8	42.4	43.3 *	39.3	40.2	29.6	31.4	30.3	65
72		-	-	13.6	27.3	33.5	34.3 *	30.6	31.3	21.8	23.9	23.1	72
79		-	-	-	20.9	26.9	27.5 *	23.8	24.7	14.7	17.8	17.4	79
85		-	-	-	16.7	22.2	22.9 *	19.4	20.0	9.5	12.6	13.2	85
92		-	-	-	-	18.0	18.4 *	15.1	15.7	4.5	7.6	8.5	92
98		-	-	-	-	14.9	15.4 *	11.5	12.3	-	-	4.8	98
105		-	-	-	-	-	12.3 *	7.9	8.5	-	-	-	105
111		-	-	-	-	-	9.7 *	5.3	5.9	-	-	-	111
118		-	-	-	-	-	-	-	-	-	-	-	118

Remarks

- * Length of main boom 121.4 ft
- ** Length of main boom 159.1 ft



Lifting capacities main boom with SSL 0°

352,800 lb   360° DIN/ISO

		Main boom						
Radius	ft	116.5	132.9	149.3	165.7	182.1	196.9	Radius
ft				1,000 lb				ft
16		429.8	-	-	-	-	-	16
19		429.8	363.3	-	-	-	-	19
23		423.2	352.6	306.3	-	-	-	23
26		417.1	346.6	298.2	251.4	-	-	26
29		407.4	340.5	292.0	249.4	207.7	160.1	29
33		389.0	330.1	286.2	246.7	203.7	157.5	33
39		352.7	314.0	276.1	240.6	197.6	153.4	39
46		310.4	290.7	266.6	231.4	189.5	147.6	46
52		278.2	268.5	256.5	225.3	181.4	141.5	52
59		244.9	242.7	231.6	216.1	172.0	134.5	59
65		222.7	221.5	215.5	204.0	163.9	128.4	65
72		201.1	201.1	197.7	189.9	155.6	122.5	72
79		182.2	183.4	182.4	175.8	147.4	116.6	79
85		165.1	169.3	169.3	164.8	140.3	111.5	85
92		147.2	151.8	155.1	151.8	132.1	106.8	92
98		127.1	139.7	143.0	141.8	126.0	102.8	98
105		98.0	125.6	130.0	131.1	119.0	98.1	105
111		-	110.5	119.9	122.0	112.9	95.0	111
118		-	90.7	109.3	112.5	105.9	90.4	118
124		-	-	98.2	105.5	99.8	87.4	124
131		-	-	83.1	98.3	93.8	83.8	131
138		-	-	-	86.7	88.0	80.4	138
144		-	-	-	76.6	84.0	78.3	144
151		-	-	-	62.4	78.1	74.9	151
157		-	-	-	-	71.1	71.8	157
164		-	-	-	-	60.0	68.3	164
177		-	-	-	-	-	53.5	177

308,700 lb   360° DIN/ISO

		Main boom						
Radius	ft	116.5	132.9	149.3	165.7	182.1	196.9	Radius
ft				1,000 lb				ft
16		429.8	-	-	-	-	-	16
19		429.8	363.3	-	-	-	-	19
23		423.2	352.6	306.3	-	-	-	23
26		417.1	346.6	298.2	251.4	-	-	26
29		407.4	340.5	292.0	249.4	207.7	160.1	29
33		389.0	330.1	286.2	246.7	203.7	157.5	33
39		352.7	314.0	276.1	240.6	197.6	153.4	39
46		306.0	290.7	266.6	231.4	189.5	147.6	46
52		273.8	268.5	256.5	225.3	181.4	141.5	52
59		242.7	242.7	231.6	216.1	172.0	134.5	59
65		218.5	221.5	215.5	204.0	163.9	128.4	65
72		192.4	195.7	197.7	189.9	155.6	122.5	72
79		170.1	174.5	176.8	175.8	147.4	116.6	79
85		154.0	158.4	161.7	164.8	140.3	111.5	85
92		138.6	141.9	145.2	148.5	132.1	106.8	92
98		126.5	130.8	133.1	136.4	126.0	102.8	98
105		98.0	116.8	120.1	123.4	119.0	98.1	105
111		-	106.7	109.0	113.3	112.9	95.0	111
118		-	90.6	98.2	102.6	104.8	90.4	118
124		-	-	90.1	94.6	96.8	87.4	124
131		-	-	82.9	86.2	88.4	83.8	131
138		-	-	-	78.0	81.3	80.3	138
144		-	-	-	73.0	75.3	76.3	144
151		-	-	-	62.4	69.3	70.4	151
157		-	-	-	-	65.5	66.2	157
164		-	-	-	-	60.0	61.3	164
177		-	-	-	-	-	53.2	177



Lifting capacities main boom with SSL 0°


220,500 lb



360°


DIN/ISO

		Main boom						
Radius	ft	116.5	132.9	149.3	165.7	182.1	196.9	Radius
ft				1,000 lb				ft
16		429.8	-	-	-	-	-	16
19		429.8	363.3	-	-	-	-	19
23		423.2	352.6	306.3	-	-	-	23
26		417.1	346.6	298.2	251.4	-	-	26
29		407.4	340.5	292.0	249.4	207.7	160.1	29
33		388.8	330.1	286.2	246.7	203.7	157.5	33
39		344.4	314.0	276.1	240.6	197.6	153.4	39
46		292.7	290.6	266.6	231.4	189.5	147.6	46
52		252.4	256.3	256.5	225.3	181.4	141.5	52
59		216.3	219.6	222.9	216.1	172.0	134.5	59
65		188.1	192.4	196.7	196.0	163.9	128.4	65
72		156.2	160.6	165.0	169.3	155.6	122.5	72
79		131.5	135.9	139.3	144.7	147.0	116.6	79
85		115.4	119.8	123.1	127.6	130.8	111.5	85
92		100.0	103.3	106.6	111.0	114.3	106.8	92
98		88.9	92.2	95.5	98.9	102.2	102.8	98
105		77.1	80.4	83.7	88.1	90.3	91.4	105
111		-	72.3	75.7	79.1	82.3	83.4	111
118		-	64.5	67.3	70.6	73.9	75.0	118
124		-	-	60.9	64.8	67.9	68.0	124
131		-	-	54.2	57.9	61.2	62.1	131
138		-	-	-	52.1	55.4	56.2	138
144		-	-	-	47.6	50.7	51.4	144
151		-	-	-	42.9	45.8	46.6	151
157		-	-	-	-	42.1	42.8	157
164		-	-	-	-	38.1	38.8	164
177		-	-	-	-	-	32.4	177





Working ranges main boom extension





Lifting capacities main boom extension

220,500 lb  360° DIN/ISO

196.9 ft Main boom												
Radius ft	19.6 ft	39.3 ft		59.0 ft		Extension 78.7 ft		98.4 ft		118.1 ft		Radius ft
	0°	0°	20°	0°	20°	0°	20°	0°	20°	0°	20°	
46	102.2	-	-	-	-	-	-	-	-	-	-	46
52	95.3	82.2	-	69.5	-	-	-	-	-	-	-	52
59	88.0	75.6	-	64.6	-	52.9	-	-	-	-	-	59
65	82.3	70.8	62.2	61.0	-	50.1	-	41.6	-	34.9	-	65
72	76.2	65.6	58.9	56.9	48.1	47.2	-	39.9	-	33.3	-	72
79	70.8	61.1	55.8	53.4	45.7	44.6	-	38.2	-	31.9	-	79
85	66.5	57.7	53.4	50.6	43.9	42.6	33.5	36.8	-	30.4	-	85
92	61.8	54.1	50.8	47.5	41.8	40.3	32.3	35.2	-	29.0	-	92
98	58.4	51.5	48.6	45.3	40.2	38.4	31.5	33.8	27.4	27.8	-	98
105	54.6	48.7	46.2	42.9	38.5	36.5	30.6	32.1	26.4	26.4	21.3	105
111	51.6	46.2	44.2	40.9	37.1	34.9	29.8	30.9	25.4	25.2	20.5	111
118	48.5	43.9	42.1	38.8	35.5	33.3	28.8	29.3	24.4	24.0	19.8	118
124	45.7	41.6	40.3	37.0	34.3	31.7	28.0	28.1	23.4	22.8	19.0	124
131	43.0	39.5	38.4	35.1	32.8	30.2	27.3	26.5	22.5	21.6	18.3	131
138	40.2	37.1	36.5	33.2	31.4	28.6	26.4	25.0	21.3	20.4	17.3	138
144	38.2	35.3	34.9	31.8	30.4	27.4	25.6	23.8	20.3	19.4	16.7	144
151	36.1	33.4	33.0	30.1	29.0	26.0	24.6	22.4	19.3	18.2	16.0	151
157	34.3	31.8	31.6	28.7	27.8	24.9	23.8	21.4	18.3	17.2	15.2	157
164	32.4	29.9	29.9	27.1	26.4	23.5	22.9	20.0	17.4	16.3	14.5	164
177	29.1	26.9	27.1	24.5	24.0	21.1	20.9	17.8	15.6	14.1	13.0	177
190	26.2	24.3	24.5	22.1	21.8	19.0	19.0	15.9	14.1	12.3	11.7	190
203	-	21.9	22.1	19.6	19.6	17.0	17.2	13.9	12.6	10.6	10.4	203
216	-	-	-	17.7	17.7	15.0	15.2	12.1	11.0	8.8	9.0	216
229	-	-	-	-	16.1	13.3	13.5	10.4	9.7	7.5	7.7	229
243	-	-	-	-	-	11.4	11.8	8.7	8.5	5.9	6.3	243
256	-	-	-	-	-	-	-	7.2	7.4	4.8	5.2	256
269	-	-	-	-	-	-	-	-	6.6	-	-	269

132,300 lb  360° DIN/ISO

196.9 ft Main boom																	
Radius ft	19.6 ft	39.3 ft			59.0 ft			Extension 78.7 ft			98.4 ft			118.1 ft			Radius ft
	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
									1,000 lb								
46	102.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	46
52	95.3	82.2	-	-	69.5	-	-	-	-	-	-	-	-	-	-	-	52
59	88.0	75.6	-	-	64.6	-	-	52.9	-	-	-	-	-	-	-	-	59
65	82.3	70.8	62.2	-	61.0	-	-	50.1	-	-	41.6	-	-	34.9	-	-	65
72	76.2	65.6	58.9	53.8	56.9	48.1	-	47.2	-	-	39.9	-	-	33.3	-	-	72
79	70.8	61.1	55.8	51.7	53.4	45.7	-	44.6	-	-	38.2	-	-	31.9	-	-	79
85	66.5	57.7	53.4	50.1	50.6	43.9	39.0	42.6	33.5	-	36.8	-	-	30.4	-	-	85
92	61.8	54.1	50.8	48.0	47.5	41.8	37.6	40.3	32.3	-	35.2	-	-	29.0	-	-	92
98	58.4	51.5	48.6	46.4	45.3	40.2	36.4	38.4	31.5	-	33.8	27.4	-	27.8	-	-	98
105	53.1	48.7	46.2	44.5	42.9	38.5	35.2	36.5	30.6	25.7	32.1	26.4	-	26.4	21.3	-	105
111	47.6	46.2	44.2	43.1	40.9	37.1	34.2	34.9	29.8	25.5	30.9	25.4	-	25.2	20.5	-	111
118	41.9	41.9	42.1	41.2	38.8	35.5	33.0	33.3	28.8	25.3	29.3	24.4	20.7	24.0	19.8	-	118
124	37.7	37.7	40.3	39.8	37.0	34.3	32.0	31.7	28.0	24.9	28.1	23.4	20.1	22.8	19.0	-	124
131	33.2	33.2	36.0	37.9	34.4	32.8	30.9	30.2	27.3	24.6	26.5	22.5	19.4	21.6	18.3	-	131
138	29.0	29.2	31.8	33.6	30.5	31.4	29.7	28.6	26.4	24.2	25.0	21.3	18.7	20.4	17.3	15.1	138
144	25.9	26.1	28.6	30.1	27.5	30.4	28.9	27.4	25.6	23.8	23.8	20.3	18.1	19.4	16.7	14.5	144
151	22.6	22.8	25.0	26.4	24.2	27.7	27.7	25.5	24.6	23.3	22.4	19.3	17.4	18.2	16.0	14.1	151
157	20.0	20.2	22.2	23.3	21.8	25.1	26.9	23.1	23.8	22.9	21.4	18.3	16.8	17.2	15.2	13.7	157
164	17.2	17.4	19.2	20.3	18.9	22.0	24.0	20.3	22.9	22.4	20.0	17.4	16.0	16.3	14.5	13.2	164
177	12.6	12.8	14.3	-	14.3	17.0	18.5	15.9	19.4	21.1	16.7	15.6	15.0	14.1	13.0	12.3	177
190	8.6	9.1	10.0	-	10.6	12.6	13.7	11.9	15.0	17.2	13.0	14.1	13.9	12.3	11.7	11.2	190
203	-	5.6	6.2	-	7.1	8.9	-	8.7	11.3	12.9	9.8	12.6	12.6	10.2	10.4	10.3	203
216	-	-	-	-	-	5.4	-	5.6	7.8	-	6.7	9.8	11.5	7.3	9.0	9.3	216
229	-	-	-	-	-	-	-	-	4.7	-	-	6.9	-	4.7	7.7	8.2	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	5.2	7.0	243



Lifting capacities main boom extension with SSL 0° + 30°

352,800 lb  360° DIN/ISO 220,500 lb  360° DIN/ISO

196.9 ft Main boom + SSL 0°					
Radius ft	19.6 ft	Extension 39.3 ft		59.0 ft	
	0°	0°	20°	0°	20°
		1,000 lb			
33	117.9	-	-	-	-
39	116.9	95.2	-	77.2	-
46	112.8	91.6	-	74.7	-
52	109.6	88.6	85.0	72.2	-
59	105.8	85.1	82.0	69.6	-
65	102.6	82.3	79.6	67.4	59.1
72	99.2	79.0	76.7	64.8	56.7
79	96.0	75.9	73.9	62.2	54.3
85	93.1	73.3	71.7	60.0	52.7
92	90.1	70.4	69.4	57.7	50.8
98	87.4	68.2	67.3	55.7	49.6
105	84.4	65.9	65.0	53.7	48.2
111	81.8	63.8	63.2	51.9	47.0
118	78.9	61.7	61.1	50.2	46.0
124	76.5	59.9	59.4	48.6	45.0
131	73.9	58.2	57.8	47.2	44.1
138	71.3	56.3	55.9	45.8	43.1
144	69.1	55.1	54.7	44.8	42.3
151	66.7	53.5	53.1	43.6	41.4
157	64.7	52.5	51.9	42.8	40.8
164	62.6	51.1	50.7	41.8	40.1
177	58.9	49.1	48.5	40.3	38.6
190	-	47.2	46.5	39.0	37.5
203	-	44.8	44.8	37.7	36.1
216	-	-	-	36.4	35.0

196.9 ft		Main boom + SSL 0°					
Radius ft	19.6 ft 0°	Extension					
		39.3 ft			59.0 ft		
		0°	20°	40°	0°	20°	40°
		1,000 lb					
33	117.9	-	-	-	-	-	-
39	116.9	95.2	-	-	77.2	-	-
46	112.8	91.6	-	-	74.7	-	-
52	109.6	88.6	85.0	-	72.2	-	-
59	105.8	85.1	82.0	-	69.6	-	-
65	102.6	82.3	79.6	67.9	67.4	59.1	-
72	99.2	79.0	76.7	67.0	64.8	56.7	-
79	96.0	75.9	73.9	66.0	62.2	54.3	45.1
85	93.1	73.3	71.7	65.0	60.0	52.7	44.1
92	90.1	70.4	69.4	63.9	57.7	50.8	43.1
98	87.4	68.2	67.3	62.9	55.7	49.6	42.3
105	84.4	65.9	65.0	61.5	53.7	48.2	41.6
111	81.8	63.8	63.2	60.4	51.9	47.0	41.0
118	77.0	61.7	61.1	59.1	50.2	46.0	40.3
124	70.6	59.9	59.4	57.8	48.6	45.0	39.9
131	63.9	58.2	57.8	56.4	47.2	44.1	39.4
138	58.0	56.3	55.9	55.0	45.8	43.1	39.0
144	53.4	53.9	54.7	53.8	44.8	42.3	38.6
151	48.2	48.8	51.3	52.4	43.6	41.4	38.1
157	44.4	45.0	47.0	48.3	42.8	40.8	37.9
164	40.1	40.8	42.7	43.6	41.8	40.1	37.4
177	33.5	34.0	35.5	-	35.7	38.3	36.8
190	-	28.3	29.4	-	30.1	32.3	-
203	-	23.5	24.4	-	25.0	26.8	-
216	-	-	-	-	20.8	22.2	-

352,800 lb  360° DIN/ISO 220,500 lb  360° DIN/ISO

196.9 ft Main boom + SSL 30°					
Radius ft	39.3 ft	59.0 ft	Extension 78.7 ft		118.1 ft
	0°	0°	0°	0°	0°
			1,000 lb		
46	113.4	88.7	64.9	-	-
52	106.6	83.7	60.9	52.7	-
59	98.6	78.0	56.9	49.1	41.4
65	92.1	73.6	53.8	46.5	39.2
72	84.8	68.6	50.5	43.7	36.6
79	77.8	64.2	47.7	41.1	34.5
85	72.1	60.3	45.7	39.3	32.7
92	66.0	56.3	43.3	37.2	30.8
98	61.1	53.1	41.7	35.6	29.4
105	56.4	49.8	40.1	33.9	27.9
111	52.1	46.9	38.5	32.7	26.7
118	48.1	44.1	37.0	31.3	25.3
124	44.8	41.5	35.6	30.3	24.3
131	41.7	39.1	34.2	29.1	23.4
138	38.9	36.7	32.8	27.9	22.4
144	36.9	34.9	31.3	26.9	21.6
151	34.5	32.8	29.9	26.0	20.9
157	32.9	31.2	28.7	24.9	20.1
164	31.0	29.3	27.3	24.0	19.4
177	28.2	26.4	24.7	22.2	18.3
190	25.4	23.8	22.3	20.5	17.2
203	22.5	21.6	20.1	18.7	16.1
216	-	19.2	18.1	17.0	15.0
229	-	-	16.1	15.5	13.9
243	-	-	-	13.6	12.7
256	-	-	-	11.8	11.4
269	-	-	-	-	9.7

196.9 ft Main boom + SSL 30°					
Radius ft	39.3 ft	59.0 ft	Extension 78.7 ft		118.1 ft
	0°	0°	0°	0°	0°
			1,000 lb		
46	113.4	88.7	64.9	-	-
52	106.6	83.7	60.9	52.7	-
59	98.6	78.0	56.9	49.1	41.4
65	92.1	73.6	53.8	46.5	39.2
72	84.8	68.6	50.5	43.7	36.6
79	77.8	64.2	47.7	41.1	34.5
85	72.1	60.3	45.7	39.3	32.7
92	66.0	56.3	43.3	37.2	30.8
98	61.1	53.1	41.7	35.6	29.4
105	56.4	49.8	40.1	33.9	27.9
111	52.1	46.9	38.5	32.7	26.7
118	48.1	44.1	37.0	31.3	25.3
124	44.8	41.5	35.6	30.3	24.3
131	41.7	39.1	34.2	29.1	23.4
138	38.9	36.7	32.8	27.9	22.4
144	36.9	34.9	31.3	26.9	21.6
151	34.5	32.8	29.9	26.0	20.9
157	32.9	31.2	28.7	24.9	20.1
164	31.0	29.3	27.3	24.0	19.4
177	28.2	26.4	24.7	22.2	18.3
190	25.4	23.8	22.3	20.5	17.2
203	22.5	21.6	20.1	18.7	16.1
216	-	19.2	18.1	17.0	15.0
229	-	-	16.1	15.5	13.9
243	-	-	-	13.6	12.7
256	-	-	-	11.8	11.4
269	-	-	-	-	9.7

Notes to lifting capacity


Ratings are in compliance with ISO 4305 and DIN 15019.2 (test load = 1.25 x suspended load + 0.1 x dead weight of boom, reduced to boom point).
Weight of hook blocks and slings is part of the load, and is to be deducted from the capacity ratings.

Crane operation is permissible up to a
wind pressure of 1.25 lb/sq ft
wind speed of 32 ft/s

Consult operation manual for further details.

Note: Data published herein is intended as a guide only and shall not be construed to warrant applicability for lifting purposes.
Crane operation is subject to the computer charts and operation manual both supplied with the crane.

Working ranges fixed fly jib





Lifting capacities fixed fly jib



360°

DIN/ISO

165.7 ft Main boom

Radius ft	65.6 ft	85.3 ft			105.0 ft			Fly jib 124.7 ft			144.4 ft			164.0 ft			Radius ft
	0°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
46	104.1	-	-	-	-	-	-	1,000 lb			-	-	-	-	-	-	46
52	96.7	83.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	52
59	89.1	77.8	-	-	69.4	-	-	-	-	-	-	-	-	-	-	-	59
65	83.2	73.0	66.6	-	65.0	-	-	53.3	-	-	43.3	-	-	-	-	-	65
72	76.8	68.0	62.9	58.7	60.5	-	-	50.9	-	-	41.2	-	-	36.2	-	-	72
79	71.4	63.3	59.3	56.1	56.3	50.8	-	48.6	-	-	39.1	-	-	34.3	-	-	79
85	67.4	59.7	56.3	53.9	53.0	49.0	-	46.6	35.0	-	37.5	-	-	32.7	-	-	85
92	62.9	55.7	53.2	51.3	49.5	46.6	42.0	44.2	34.3	-	35.6	-	-	31.0	-	-	92
98	59.7	52.8	50.8	49.3	46.9	44.6	40.8	42.2	33.5	-	34.2	25.6	-	29.4	-	-	98
105	56.2	49.6	48.0	46.9	44.0	42.5	39.6	39.9	32.8	27.1	32.4	24.6	-	27.7	-	-	105
111	53.5	47.1	45.8	44.9	41.8	40.7	38.4	38.0	32.0	26.7	30.9	23.8	-	26.5	21.2	-	111
118	50.5	44.5	43.4	43.0	39.7	38.6	37.0	35.9	31.3	26.2	29.5	22.9	19.6	24.9	20.5	-	118
124	48.3	42.5	41.6	41.2	37.9	36.9	35.6	34.1	30.5	26.0	28.1	22.3	19.2	23.7	19.9	-	124
131	45.9	40.4	39.7	39.3	35.7	35.1	34.2	32.0	29.5	25.5	26.7	21.4	18.7	22.3	19.2	-	131
138	43.5	38.5	37.8	37.6	34.1	33.2	32.5	30.1	28.4	25.1	25.3	20.7	18.5	21.1	18.4	15.4	138
144	41.7	37.1	36.4	36.2	32.5	31.8	31.3	28.7	27.6	24.7	24.3	20.3	18.1	19.9	17.6	15.2	144
151	39.6	35.4	35.0	34.5	30.8	30.1	29.7	26.8	26.4	24.2	22.9	19.6	17.6	18.7	16.9	14.7	151
157	38.0	34.2	33.8	33.3	29.6	28.9	28.5	25.6	25.6	23.6	21.9	19.0	17.2	17.7	16.1	14.3	157
164	36.3	32.8	32.4	31.9	28.0	27.5	27.1	24.0	24.4	23.1	20.5	18.3	16.9	16.5	15.4	14.1	164
177	33.1	30.4	30.0	29.7	25.6	24.9	24.7	21.4	22.0	21.8	18.3	17.2	16.3	14.5	13.6	13.0	177
190	30.2	28.2	27.8	-	23.2	22.9	22.5	19.2	19.8	20.3	16.3	15.9	15.4	12.8	12.1	11.9	190
203	27.2	25.8	25.6	-	21.2	21.0	-	17.2	17.4	18.3	14.3	14.5	14.5	11.0	10.6	10.6	203
216	-	23.2	23.2	-	19.2	19.0	-	15.2	15.5	15.7	12.6	13.0	13.2	9.5	9.3	9.3	216
229	-	-	-	-	17.2	17.4	-	13.7	13.5	-	11.1	11.7	11.9	8.2	8.0	8.2	229
243	-	-	-	-	-	15.6	-	12.1	11.8	-	9.6	10.3	-	7.0	6.8	7.0	243
256	-	-	-	-	-	-	-	10.7	10.7	-	8.5	9.0	-	5.9	5.9	6.1	256
269	-	-	-	-	-	-	-	-	-	-	7.7	8.1	-	5.0	5.0	-	269
282	-	-	-	-	-	-	-	-	-	-	-	7.2	-	4.4	4.6	-	282
295	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	295

182.1 ft Main boom

ft	1,000 lb																ft
52	81.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	52
59	76.1	63.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59
65	71.8	59.8	-	-	52.3	-	-	-	-	-	-	-	-	-	-	-	65
72	67.1	55.8	50.9	-	49.2	-	-	44.1	-	-	38.8	-	-	-	-	-	72
79	62.9	52.3	48.6	46.2	46.1	-	-	41.7	-	-	36.2	-	-	30.7	-	-	79
85	59.4	49.5	46.6	44.1	43.7	39.1	-	39.5	-	-	34.2	-	-	29.1	-	-	85
92	55.9	46.4	44.2	42.0	41.4	37.0	-	37.2	-	-	31.9	-	-	27.0	-	-	92
98	53.3	44.0	42.2	40.2	39.3	35.1	32.3	35.4	32.0	-	30.1	-	-	25.4	-	-	98
105	50.4	41.4	39.9	38.1	37.2	33.2	30.6	33.2	30.6	-	28.2	24.2	-	23.8	-	-	105
111	48.2	39.4	38.0	36.3	35.4	31.6	29.2	31.4	29.4	26.9	26.6	23.2	-	22.1	-	-	111
118	45.6	37.2	35.9	34.4	33.5	30.0	27.5	29.3	28.0	25.8	24.7	21.8	-	20.7	18.9	-	118
124	43.8	35.4	34.1	32.8	31.9	28.5	26.3	27.7	26.8	24.8	23.3	20.8	18.5	19.3	17.9	-	124
131	41.7	33.5	32.2	30.9	30.2	26.9	24.9	25.8	25.1	23.6	21.6	19.6	17.8	17.9	17.0	-	131
138	39.6	31.9	30.3	29.2	28.6	25.5	23.7	24.2	23.7	22.2	20.2	18.4	16.9	16.7	16.0	-	138
144	38.2	30.5	28.9	27.8	27.4	24.3	22.5	22.7	22.5	21.2	19.0	17.6	16.3	15.5	15.2	14.3	144
151	36.3	28.8	27.5	26.2	25.7	23.1	21.3	21.1	21.1	20.0	17.6	16.5	15.4	14.3	14.3	13.4	151
157	34.9	27.6	26.3	25.0	24.5	22.1	20.5	19.9	19.9	19.0	16.6	15.7	14.6	13.5	13.3	12.6	157
164	33.3	26.2	24.9	23.5	23.1	20.9	19.4	18.5	18.5	17.8	15.4	14.7	13.8	12.3	12.3	11.6	164
177	30.6	23.8	22.5	21.4	20.5	18.7	17.6	16.1	16.3	15.6	13.2	13.0	12.3	10.6	10.6	10.1	177
190	28.0	21.6	20.5	19.4	18.1	17.0	15.9	14.1	14.1	13.7	11.5	11.2	10.8	9.0	9.0	8.8	190
203	25.4	19.4	18.7	-	15.9	15.2	14.1	12.6	12.4	11.9	9.9	9.7	9.3	7.5	7.5	7.5	203
216	23.0	17.7	17.2	-	14.1	13.7	-	11.0	11.0	10.4	8.4	8.2	8.0	6.2	6.2	6.4	216
229	-	15.7	15.7	-	12.4	12.4	-	9.7	9.7	9.3	7.1	6.9	6.8	4.9	5.1	5.3	229
243	-	-	-	-	11.0	11.2	-	8.3	8.3	-	5.9	5.7	5.7	-	-	4.3	243
256	-	-	-	-	9.9	10.1	-	7.4	7.4	-	4.8	4.8	-	-	-	-	256
269	-	-	-	-	-	-	-	6.3	6.6	-	-	-	-	-	-	-	269
282	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	282

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight · Further counterweight configurations on request



Lifting capacities fixed fly jib with SSL 0° + 30°



360°

DIN/ISO

182.1 ft Main boom

Radius ft	65.6 ft		85.3 ft		105.0 ft			Fly jib 124.7 ft			144.4 ft			164.0 ft			Radius ft	
	0°		0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°		40°
									1,000 lb									
39	93.1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	39
46	90.3	69.4	-	-	57.9	-	-	-	-	-	-	-	-	-	-	-	-	46
52	88.1	68.2	-	-	57.5	-	-	48.9	-	-	-	-	-	-	-	-	-	52
59	85.3	67.0	62.4	-	56.8	-	-	48.5	-	-	40.7	-	-	31.7	-	-	-	59
65	82.9	65.6	60.9	-	56.0	-	-	47.9	-	-	39.9	-	-	31.1	-	-	-	65
72	80.3	64.1	59.3	57.7	54.9	49.1	-	46.9	-	-	39.0	-	-	30.2	-	-	-	72
79	77.5	62.5	57.7	56.1	53.7	48.2	-	46.0	37.2	-	38.1	-	-	29.5	-	-	-	79
85	75.2	60.9	56.2	54.7	52.7	47.4	43.9	45.0	36.2	-	37.2	-	-	28.7	-	-	-	85
92	72.7	59.2	54.4	53.0	51.3	46.2	42.9	43.8	35.0	-	36.1	28.6	-	27.9	-	-	-	92
98	70.4	57.6	53.0	51.6	50.1	45.2	41.9	42.8	34.2	28.2	35.3	27.8	-	27.1	-	-	-	98
105	67.8	55.9	51.3	50.0	48.4	43.8	40.5	41.4	33.0	27.7	34.1	26.8	-	26.2	21.6	-	-	105
111	65.6	54.3	49.7	48.4	47.2	42.8	39.5	40.4	32.2	27.3	33.1	26.2	-	25.6	20.9	-	-	111
118	63.3	52.5	48.0	46.7	45.6	41.4	38.3	39.0	31.3	26.6	31.9	25.5	21.8	24.7	20.5	-	-	118
124	61.0	50.8	46.6	45.3	44.2	40.2	37.1	37.8	30.7	26.2	31.1	24.9	21.4	24.0	19.9	-	-	124
131	58.7	49.0	45.0	43.7	42.6	38.8	35.9	36.4	29.7	25.5	30.0	24.2	21.1	23.1	19.4	15.4	-	131
138	56.3	47.3	43.3	42.0	40.9	37.4	34.5	35.2	29.0	25.1	29.0	23.7	20.7	22.4	18.9	14.9	-	138
144	54.5	45.7	42.1	40.8	39.7	36.2	33.5	34.0	28.4	24.7	28.2	23.1	20.3	21.8	18.3	14.7	-	144
151	52.2	44.0	40.7	39.4	38.1	35.0	32.1	32.8	27.7	24.0	27.3	22.7	19.8	20.9	17.8	14.5	-	151
157	50.4	42.4	39.7	38.2	36.9	33.8	31.1	31.8	27.1	23.6	26.5	22.2	19.4	20.3	17.4	14.1	-	157
164	48.5	40.7	38.3	37.0	35.5	32.6	29.9	30.6	26.4	23.1	25.5	21.8	18.9	19.6	16.9	13.8	-	164
177	45.0	37.9	36.1	34.2	33.1	30.6	28.0	28.6	25.1	22.0	24.2	20.9	18.0	18.5	16.1	13.2	-	177
190	41.9	35.3	34.2	-	30.6	28.7	26.2	26.9	23.8	20.9	22.9	19.8	17.4	17.6	15.4	12.7	-	190
203	39.3	32.9	32.2	-	28.7	26.9	24.7	25.4	22.7	19.8	21.8	18.9	16.5	16.7	14.5	12.1	-	203
216	34.5	30.7	30.7	-	26.7	25.4	-	24.0	21.6	18.7	20.9	18.1	15.6	15.9	13.9	11.6	-	216
229	-	29.1	29.1	-	25.0	23.8	-	22.7	20.3	-	19.8	17.2	14.8	15.2	13.2	11.0	-	229
243	-	-	-	-	23.5	22.4	-	21.3	19.1	-	18.9	16.2	14.0	14.5	12.5	10.5	-	243
256	-	-	-	-	-	21.1	-	20.4	17.8	-	18.0	15.2	-	14.1	12.1	9.9	-	256
269	-	-	-	-	-	-	-	19.6	16.5	-	17.1	14.3	-	13.4	11.4	-	-	269
282	-	-	-	-	-	-	-	-	-	-	16.3	13.4	-	13.0	11.0	-	-	282
295	-	-	-	-	-	-	-	-	-	-	-	12.8	-	12.5	10.3	-	-	295
308	-	-	-	-	-	-	-	-	-	-	-	-	-	10.4	9.7	-	-	308


182.1 ft Main boom + SSL 30°

Radius ft	65.6 ft		85.3 ft		Fly jib 105.0 ft		124.7 ft		144.4 ft		164.0 ft	
	0°	0°	0°	0°	0°	0°	0°	0°	0°	0°	0°	0°
	1,000 lb											
46	106.8	-	-	-	-	-	-	-	-	-	-	-
52	99.5	88.9	75.9	-	-	-	-	-	-	-	-	-
59	91.5	82.2	71.0	57.3	48.0	-	-	-	-	-	-	-
65	85.3	76.6	66.9	54.9	45.8	37.2	-	-	-	-	-	-
72	78.4	70.7	62.2	52.1	43.4	35.1	-	-	-	-	-	-
79	71.8	65.2	58.0	49.2	41.1	33.2	-	-	-	-	-	-
85	66.8	60.8	54.8	47.0	39.3	31.8	-	-	-	-	-	-
92	61.4	56.1	51.0	44.4	37.4	30.1	-	-	-	-	-	-
98	57.1	52.3	48.0	42.4	35.8	28.7	-	-	-	-	-	-
105	52.6	48.4	44.9	40.1	33.9	27.3	-	-	-	-	-	-
111	48.8	45.2	42.1	38.1	32.5	26.1	-	-	-	-	-	-
118	45.2	41.9	39.5	35.9	30.8	24.9	-	-	-	-	-	-
124	42.0	39.1	37.0	34.3	29.6	23.7	-	-	-	-	-	-
131	38.9	36.4	34.6	32.2	28.2	22.5	-	-	-	-	-	-
138	36.0	33.8	32.3	30.3	26.8	21.5	-	-	-	-	-	-
144	34.0	32.0	30.5	28.9	25.6	20.5	-	-	-	-	-	-
151	31.5	29.9	28.6	27.0	24.2	19.6	-	-	-	-	-	-
157	29.8	28.3	27.0	25.6	23.2	18.6	-	-	-	-	-	-
164	28.0	26.6	25.3	24.0	21.8	17.6	-	-	-	-	-	-
177	25.1	24.0	22.5	21.4	19.4	15.8	-	-	-	-	-	-
190	22.7	21.6	20.3	18.7	17.2	14.3	-	-	-	-	-	-
203	20.5	19.6	18.1	16.6	15.2	12.6	-	-	-	-	-	-
216	-	17.7	16.1	14.6	13.3	11.2	-	-	-	-	-	-
229	-	15.7	14.4	12.8	11.5	9.7	-	-	-	-	-	-
243	-	-	12.5	11.4	9.8	8.5	-	-	-	-	-	-
256	-	-	-	10.1	8.5	7.4	-	-	-	-	-	-
269	-	-	-	-	7.4	6.3	-	-	-	-	-	-
282	-	-	-	-	6.8	5.5	-	-	-	-	-	-
295	-	-	-	-	-	4.8	-	-	-	-	-	-

196.9 ft Main boom + SSL 30°


Radius ft	65.6 ft		85.3 ft		Fly jib 105.0 ft		124.7 ft		144.4 ft		164.0 ft	
	0°	0°	0°	0°	0°	0°	0°	0°	0°	0°	0°	0°
	1,000 lb											
46	97.3	-	-	-	-	-	-	-	-	-	-	-
52	90.7	81.5	76.1	59.5	54.4	-	-	-	-	-	-	-
59	83.8	76.1	66.4	57.8	49.0	41.5	32.4	-	-	-	-	-
65	78.1	71.4	66.4	57.8	49.0	41.5	32.4	-	-	-	-	-
72	72.0	66.4	61.7	54.3	46.4	39.1	31.0	-	-	-	-	-
79	66.6	61.7	57.9	51.3	44.2	37.3	29.6	-	-	-	-	-
85	62.1	57.9	53.7	48.0	41.8	35.4	28.1	-	-	-	-	-
92	57.6	53.7	49.7	45.3	39.8	33.8	27.1	-	-	-	-	-
98	53.8	50.2	46.7	42.3	37.4	31.9	25.7	-	-	-	-	-
105	50.0	46.7	43.7	39.7	35.6	30.5	24.7	-	-	-	-	-
111	46.8	43.7	40.3	37.0	33.7	28.9	23.6	-	-	-	-	-
118	43.4	40.3	37.7	34.8	31.9	27.4	22.4	-	-	-	-	-
124	40.6	37.7	35.1	32.4	30.0	26.0	21.4	-	-	-	-	-
131	37.7	35.1	32.5	30.1	28.3	24.6	20.2	-	-	-	-	-
138	34.9	32.5	30.5	28.3	26.7	23.6	19.2	-	-	-	-	-
144	32.9	30.5	28.4	26.4	25.1	22.2	18.2	-	-	-	-	-
151	30.6	28.4	26.4	25.1	23.9	21.2	17.2	-	-	-	-	-
157	28.8	27.0	25.0	23.9	22.2	19.8	16.3	-	-	-	-	-
164	26.6	25.1	23.1	22.2	20.5	18.6	15.5	-	-	-	-	-
177	23.4	22.3	20.5	19.6	17.6	15.4	12.8	-	-	-	-	-
190	20.7	19.8	18.3	17.0	15.4	12.8	10.5	-	-	-	-	-
203	18.5	17.9	16.3	14.8	13.5	11.0	9.5	-	-	-	-	-
216	16.6	16.1	14.6	12.8	11.5	9.5	8.2	-	-	-	-	-
229	-	14.1	13.0	11.1	9.9	8.2	6.8	-	-	-	-	-
243	-	12.0	11.4	9.4	8.3	6.8	5.5	-	-	-	-	-
256	-	-	9.9	8.1	7.0	5.5	4.4	-	-	-	-	-
269	-	-	-	7.0	6.1	4.4	3.5	-	-	-	-	-
282	-	-	-	-	5.3	3.5	2.8	-	-	-	-	-
295	-	-	-	-	4.8	2.8	2.2	-	-	-	-	-

Working ranges fixed fly jib with SSL 30°





Working ranges luffing fly jib, main boom 83° to 65°





Lifting capacities luffing fly jib, main boom 83° to 65°



360°

DIN/ISO

50.9 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
1,000 lb																			
39	271.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	39
46	260.0	-	-	227.0	-	-	196.1	-	-	-	-	-	-	-	-	-	-	-	46
52	249.9	-	-	222.9	-	-	194.1	-	-	160.9	-	-	-	-	-	-	-	-	52
59	240.3	-	-	222.6	-	-	191.8	-	-	160.9	-	-	133.3	-	-	114.6	-	-	59
65	226.1	223.4	-	220.6	203.4	-	189.8	-	-	159.9	-	-	133.3	-	-	114.6	-	-	65
72	198.0	206.5	-	210.8	196.3	-	188.5	-	-	158.7	-	-	133.3	-	-	114.6	-	-	72
79	-	191.2	186.8	194.5	189.0	-	187.1	169.6	-	157.5	-	-	133.2	-	-	114.6	-	-	79
85	-	179.1	174.7	182.4	176.9	172.5	181.0	167.6	-	156.5	147.7	-	131.2	-	-	114.6	-	-	85
92	-	-	160.7	155.9	163.9	159.5	167.1	162.8	-	154.2	147.6	-	128.9	124.5	-	113.4	-	-	92
98	-	-	150.6	130.7	152.9	148.5	147.9	151.7	147.3	153.2	146.6	-	126.9	124.5	-	111.4	-	-	98
105	-	-	-	-	142.1	137.7	127.8	141.0	136.6	142.1	138.8	-	125.6	123.4	-	108.0	108.0	-	105
111	-	-	-	-	-	129.7	110.7	132.0	128.6	128.0	130.8	127.5	123.6	122.4	-	106.0	107.0	-	111
118	-	-	-	-	-	121.3	90.7	123.5	120.2	112.6	122.4	119.1	115.8	121.2	111.3	102.5	104.7	-	118
124	-	-	-	-	-	-	-	116.5	114.2	100.5	116.4	112.1	109.8	115.3	110.3	99.5	102.7	-	124
131	-	-	-	-	-	-	-	-	107.1	86.4	109.3	106.0	98.5	108.2	104.9	94.9	100.3	100.4	131
138	-	-	-	-	-	-	-	-	101.2	71.2	102.2	100.1	87.8	101.2	99.0	90.2	98.0	96.8	138
144	-	-	-	-	-	-	-	-	-	-	94.1	95.1	78.8	97.2	94.0	86.2	94.9	92.8	144
151	-	-	-	-	-	-	-	-	-	-	-	90.3	68.2	91.4	88.1	77.0	90.3	87.0	151
157	-	-	-	-	-	-	-	-	-	-	-	85.2	-	86.3	84.1	70.0	85.2	83.0	157
164	-	-	-	-	-	-	-	-	-	-	-	-	-	75.0	79.3	62.4	80.5	78.2	164
177	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	69.5	70.6	177
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	64.7	190
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	203

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft				
ft									1,000 lb												ft	
65	92.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	65	
72	92.5	-	-	78.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72	
79	92.5	-	-	77.1	-	-	66.1	-	-	-	-	-	-	-	-	-	-	-	-	-	79	
85	92.5	-	-	76.1	-	-	66.1	-	-	53.6	-	-	-	-	-	-	-	-	-	-	85	
92	92.5	-	-	74.9	-	-	66.1	-	-	52.6	-	-	43.4	-	-	35.2	-	-	-	-	92	
98	92.5	-	-	73.9	-	-	66.1	-	-	51.8	-	-	42.6	-	-	34.4	-	-	28.7	-	98	
105	92.5	-	-	72.7	-	-	66.1	-	-	50.9	-	-	41.8	-	-	33.7	-	-	27.5	-	105	
111	92.5	88.1	-	71.7	-	-	65.9	-	-	50.3	-	-	41.0	-	-	32.9	-	-	26.5	-	111	
118	92.5	88.1	-	71.6	71.6	-	65.4	-	-	49.3	-	-	40.3	-	-	32.1	-	-	25.5	-	118	
124	92.5	87.1	-	70.6	71.6	-	64.8	65.0	-	48.7	-	-	39.5	-	-	31.5	-	-	24.7	-	124	
131	92.5	87.0	-	69.4	70.5	-	64.1	65.0	-	48.0	-	-	38.6	-	-	30.8	-	-	24.0	-	131	
138	92.4	85.9	-	68.3	69.4	-	63.4	65.0	-	47.3	48.4	-	37.8	-	-	30.1	-	-	23.3	-	138	
144	89.4	84.8	82.6	67.3	69.4	-	62.8	65.0	-	46.7	47.8	-	37.0	38.4	-	29.5	-	-	22.7	-	144	
151	83.6	83.7	81.5	66.1	68.3	68.3	62.1	65.0	-	46.0	47.1	-	36.1	37.4	-	28.8	-	-	22.0	-	151	
157	76.6	81.7	80.5	64.7	67.3	67.3	61.5	65.0	-	45.2	46.5	-	35.5	36.6	-	28.2	29.3	-	21.4	-	157	
164	69.4	79.3	78.2	63.0	66.1	66.1	60.8	65.0	61.5	44.5	45.8	-	34.6	35.7	-	27.5	28.6	-	20.9	21.8	-	164
177	57.4	72.8	70.6	59.3	63.5	63.9	56.7	65.0	60.8	43.2	44.5	44.9	33.0	34.1	-	26.4	27.3	-	19.8	20.9	-	177
190	45.2	64.1	64.5	50.6	60.6	61.9	52.1	61.1	60.2	41.7	43.2	43.4	31.5	32.6	33.9	25.3	26.2	-	19.1	20.0	-	190
203	-	51.7	59.0	40.8	56.7	57.2	44.7	57.2	56.1	40.1	41.9	41.9	30.2	31.3	32.4	24.4	25.3	27.1	18.5	19.2	-	203
216	-	-	-	-	47.1	52.6	36.5	50.5	51.3	38.4	40.6	40.6	28.9	30.0	31.1	23.6	24.2	25.8	17.8	18.5	19.0	216
229	-	-	-	-	-	48.7	28.4	42.5	47.1	32.9	39.1	39.3	27.8	28.9	29.8	22.7	23.4	24.5	17.2	17.6	17.7	229
243	-	-	-	-	-	-	-	33.3	43.3	25.8	37.6	37.9	26.6	27.7	28.4	22.0	22.4	23.3	16.5	16.9	16.5	243
256	-	-	-	-	-	-	-	-	-	-	31.2	36.7	23.7	26.8	27.5	21.1	21.8	22.4	16.0	16.3	15.6	256
269	-	-	-	-	-	-	-	-	-	-	-	33.7	18.0	26.0	26.4	20.7	21.1	21.6	15.4	15.4	14.7	269
282	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25.8	16.3	20.5	20.9	14.7	14.7	14.1	282
295	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	20.0	20.3	14.1	14.3	13.6	295
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.6	13.4	308
321	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.2	321
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	335

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



360°

DIN/ISO

67.3 ft + 13.1 ft Main boom + adapter

		Fly jib																			
		78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft				
Radius		83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft		1,000 lb																		ft	
46		251.2	-	-	217.0	-	-	173.0	-	-	-	-	-	-	-	-	-	-	-	46	
52		243.1	-	-	212.0	-	-	171.0	-	-	139.9	-	-	-	-	-	-	-	-	52	
59		229.3	-	-	207.2	-	-	169.7	-	-	139.9	-	-	114.6	-	-	-	-	-	59	
65		218.2	205.0	-	203.2	-	-	169.7	-	-	138.9	-	-	114.6	-	-	97.0	-	-	65	
72		204.2	192.1	-	197.4	176.5	-	168.6	-	-	138.8	-	-	114.6	-	-	97.0	-	-	72	
79		191.3	180.3	-	190.2	168.3	-	167.4	146.4	-	137.7	-	-	114.5	-	-	97.0	-	-	79	
85		-	171.3	160.1	180.1	161.2	-	164.3	143.4	-	136.7	-	-	113.5	-	-	97.0	-	-	85	
92		-	161.8	151.9	165.9	154.1	145.3	158.5	139.9	-	135.5	125.6	-	112.4	-	-	97.0	-	-	92	
98		-	-	144.9	142.7	147.1	138.2	151.5	135.8	-	134.5	123.6	-	112.4	110.3	-	97.0	-	-	98	
105		-	-	134.4	-	138.8	132.2	136.6	131.1	123.4	127.8	120.1	-	111.3	108.0	-	95.8	94.7	-	105	
111		-	-	-	-	130.8	125.2	119.5	127.1	119.4	122.8	118.1	-	110.3	106.0	-	94.8	93.7	-	111	
118		-	-	-	-	-	116.9	99.5	120.2	115.7	112.5	113.6	105.8	105.8	103.6	-	93.7	91.5	-	118	
124		-	-	-	-	-	110.9	-	114.2	109.8	103.5	110.5	102.8	101.8	101.6	-	91.7	90.5	-	124	
131		-	-	-	-	-	-	-	107.1	102.7	91.8	105.9	99.3	95.0	99.2	90.4	88.3	88.2	-	131	
138		-	-	-	-	-	-	-	96.8	77.8	100.1	95.7	87.9	95.8	89.2	85.8	85.9	83.7	-	138	
144		-	-	-	-	-	-	-	92.8	-	95.1	91.7	81.9	92.7	87.2	81.8	83.8	81.6	-	144	
151		-	-	-	-	-	-	-	-	-	90.3	85.9	72.6	88.1	84.8	77.1	81.5	79.3	-	151	
157		-	-	-	-	-	-	-	-	-	-	81.8	63.5	84.1	80.7	73.0	79.5	78.3	-	157	
164		-	-	-	-	-	-	-	-	-	-	77.1	-	79.3	76.0	66.1	77.1	74.9	-	164	
177		-	-	-	-	-	-	-	-	-	-	-	-	-	68.4	50.4	70.6	67.3	-	177	
190		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	60.6	61.6	-	190	

		196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft					
ft									1,000 lb																ft
65	81.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	65			
72	81.5	-	-	-	66.1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72			
79	81.5	-	-	-	66.1	-	-	57.0	-	-	-	-	-	-	-	-	-	-	-	-	-	79			
85	81.5	-	-	-	65.9	-	-	56.8	-	-	47.8	-	-	-	-	-	-	-	-	-	-	85			
92	81.5	-	-	-	65.4	-	-	56.6	-	-	47.3	-	-	38.5	-	-	-	-	-	-	-	92			
98	81.5	-	-	-	65.0	-	-	56.6	-	-	46.9	-	-	38.3	-	-	30.4	-	-	-	-	98			
105	81.5	-	-	-	64.3	-	-	56.4	-	-	46.7	-	-	37.9	-	-	29.9	-	-	24.0	-	105			
111	81.5	-	-	-	63.9	-	-	56.4	-	-	46.3	-	-	37.5	-	-	29.3	-	-	23.4	-	111			
118	81.5	77.1	-	-	63.2	-	-	56.4	-	-	45.8	-	-	37.0	-	-	28.8	-	-	22.9	-	118			
124	81.5	77.1	-	-	62.8	65.3	-	56.4	-	-	45.4	-	-	36.6	-	-	28.2	-	-	22.3	-	124			
131	81.5	77.1	-	-	62.1	64.6	-	56.2	55.5	-	44.7	-	-	35.9	-	-	27.7	-	-	21.6	-	131			
138	81.5	76.0	-	-	61.7	63.9	-	55.9	55.5	-	44.2	-	-	35.2	-	-	27.1	-	-	21.1	-	138			
144	79.4	76.0	-	-	61.1	63.3	-	55.7	55.5	-	43.8	44.8	-	34.6	-	-	26.7	-	-	20.5	-	144			
151	77.1	74.9	69.4	-	60.3	62.6	-	55.5	55.5	-	43.2	44.3	-	33.9	35.2	-	26.2	-	-	20.0	-	151			
157	73.0	72.9	68.4	-	59.1	61.9	-	54.9	55.5	-	42.5	43.7	-	33.3	34.6	-	25.6	-	-	19.6	-	157			
164	69.4	71.6	67.2	-	57.7	61.2	59.7	54.4	55.5	-	42.1	43.2	-	32.6	33.9	-	25.1	26.2	-	19.1	-	164			
177	60.7	68.3	64.6	-	53.8	59.5	57.1	52.9	55.5	52.9	40.8	42.1	-	31.3	32.4	-	24.2	25.1	-	18.3	19.1	177			
190	48.3	64.4	61.5	49.9	57.1	54.5	50.7	54.2	52.0	39.4	40.8	41.4	30.0	31.1	-	23.1	24.2	-	17.4	18.5	-	190			
203	-	57.3	56.1	43.4	54.7	52.7	46.8	52.0	50.7	37.9	39.7	40.1	28.4	30.0	31.1	22.2	23.3	-	16.7	17.6	-	203			
216	-	-	51.7	-	51.2	49.9	38.7	49.9	48.5	36.6	38.6	38.8	27.3	28.7	29.8	21.6	22.5	23.8	16.1	16.7	17.9	216			
229	-	-	-	-	41.3	46.0	30.4	45.8	44.7	34.7	37.3	37.7	26.2	27.6	28.7	20.7	21.6	22.7	15.4	16.1	16.8	229			
243	-	-	-	-	-	-	-	37.3	40.9	27.6	36.1	36.5	25.3	26.6	27.5	20.0	20.7	21.5	14.7	15.4	15.6	243			
256	-	-	-	-	-	-	-	-	38.1	-	34.5	35.4	24.4	25.7	26.4	19.3	20.0	20.7	14.1	14.7	14.7	256			
269	-	-	-	-	-	-	-	-	-	-	-	34.3	19.4	24.9	25.5	18.7	19.4	20.0	13.4	14.1	13.8	269			
282	-	-	-	-	-	-	-	-	-	-	-	-	-	24.2	24.9	17.4	18.7	19.1	12.7	13.4	13.2	282			
295	-	-	-	-	-	-	-	-	-	-	-	-	-	-	24.2	-	18.3	18.7	12.3	12.8	12.7	295			
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	18.1	11.0	12.1	12.1	308			
321	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11.7	11.9	321			
335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	335			

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



Lifting capacities luffing fly jib, main boom 83° to 65°



360°

DIN/ISO

83.7 ft + 13.1 ft Main boom + adapter

Fly jib																				
78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft					
Radius	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	Radius	
ft																				ft
46	244.5	-	-	203.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	46	
52	234.5	-	-	201.8	-	-	167.5	-	-	-	-	-	-	-	-	-	-	-	52	
59	219.4	-	-	196.2	-	-	167.5	-	-	133.3	-	-	108.0	-	-	-	-	-	59	
65	203.3	-	-	190.2	-	-	167.5	-	-	133.3	-	-	108.0	-	-	90.3	-	-	65	
72	183.5	167.8	-	181.0	-	-	166.4	-	-	133.3	-	-	108.0	-	-	90.3	-	-	72	
79	168.0	156.1	-	171.6	149.5	-	162.9	-	-	132.2	-	-	108.0	-	-	90.3	-	-	79	
85	-	148.1	-	163.5	141.5	-	157.8	135.9	-	131.2	-	-	108.0	-	-	90.3	-	-	85	
92	-	141.0	-	153.0	133.2	-	151.9	127.7	-	130.0	-	-	108.0	-	-	90.3	-	-	92	
98	-	137.9	121.6	144.9	127.1	-	144.9	122.7	-	128.9	117.1	-	108.0	-	-	90.3	-	-	98	
105	-	-	115.7	-	122.3	110.2	134.4	117.9	-	125.6	111.3	-	108.0	105.8	-	90.3	-	-	105	
111	-	-	111.7	-	118.3	105.1	125.3	113.9	103.9	122.6	107.2	-	108.0	101.7	-	90.3	89.3	-	111	
118	-	-	-	-	115.7	100.3	106.1	111.3	99.2	114.7	103.6	-	105.8	97.0	-	90.3	88.2	-	118	
124	-	-	-	-	-	97.3	-	108.3	94.2	107.7	99.6	90.7	103.8	94.0	-	90.3	86.2	-	124	
131	-	-	-	-	-	94.8	-	104.8	90.5	97.3	96.0	87.2	98.3	90.5	-	88.2	84.9	-	131	
138	-	-	-	-	-	-	-	99.0	87.0	83.3	93.6	82.6	92.4	87.0	79.2	86.9	82.6	-	138	
144	-	-	-	-	-	-	-	-	86.0	-	91.6	80.5	87.3	84.9	76.2	82.9	81.6	-	144	
151	-	-	-	-	-	-	-	-	83.7	-	87.0	77.1	77.0	83.7	72.7	78.2	79.3	72.7	151	
157	-	-	-	-	-	-	-	-	-	-	83.0	75.1	66.9	81.7	70.7	74.1	78.3	70.7	157	
164	-	-	-	-	-	-	-	-	-	-	-	73.8	-	77.1	68.3	69.4	76.0	67.2	164	
177	-	-	-	-	-	-	-	-	-	-	-	-	-	69.5	65.7	53.5	68.4	63.7	177	
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	60.0	-	62.5	58.5	190	
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	53.5	203	
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	216	

196.9 ft				216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			
ft										1,000 lb												ft
72	79.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72	
79	79.3	-	-	61.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79	
85	79.3	-	-	61.7	-	-	52.9	-	-	46.2	-	-	-	-	-	-	-	-	-	-	85	
92	79.3	-	-	61.7	-	-	52.9	-	-	46.2	-	-	37.4	-	-	-	-	-	-	-	92	
98	79.3	-	-	61.7	-	-	52.9	-	-	46.2	-	-	37.2	-	-	29.7	-	-	-	-	98	
105	79.3	-	-	61.7	-	-	52.9	-	-	46.2	-	-	37.2	-	-	29.3	-	-	22.9	-	105	
111	79.3	-	-	61.7	-	-	52.9	-	-	46.2	-	-	37.0	-	-	28.9	-	-	22.7	-	111	
118	79.3	-	-	61.5	-	-	52.9	-	-	46.2	-	-	36.8	-	-	28.4	-	-	22.2	-	118	
124	79.3	76.0	-	61.5	-	-	52.9	-	-	46.2	-	-	36.6	-	-	28.0	-	-	21.8	-	124	
131	79.3	74.9	-	61.2	65.0	-	52.9	-	-	45.8	-	-	36.5	-	-	27.5	-	-	21.4	-	131	
138	79.3	74.9	-	61.0	64.5	-	52.9	51.8	-	45.6	-	-	36.3	-	-	27.1	-	-	20.9	-	138	
144	78.3	74.9	-	61.0	64.3	-	52.9	51.8	-	45.2	-	-	35.7	-	-	26.7	-	-	20.5	-	144	
151	77.1	73.8	-	60.8	63.9	-	52.9	51.8	-	44.5	45.8	-	35.0	-	-	26.2	-	-	20.0	-	151	
157	74.1	72.8	63.7	60.2	63.5	-	52.9	51.8	-	44.1	45.4	-	34.4	36.2	-	25.8	-	-	19.8	-	157	
164	70.5	72.7	62.6	59.5	62.8	-	52.9	51.8	-	43.4	44.9	-	33.7	35.4	-	25.3	26.4	-	19.4	-	164	
177	63.1	68.4	60.4	56.6	61.7	56.7	52.0	51.8	-	42.3	43.8	-	32.4	33.9	-	24.4	25.5	-	18.5	19.6	-	177
190	50.9	62.5	58.0	53.8	60.2	53.4	49.4	51.8	49.4	41.2	42.7	-	31.1	32.6	-	23.6	24.4	-	17.6	18.7	-	190
203	-	57.2	53.5	45.2	55.4	50.5	46.8	50.9	47.8	40.1	41.7	42.1	30.0	31.5	33.1	22.7	23.6	-	16.7	17.8	-	203
216	-	49.2	49.1	35.0	50.8	47.1	40.3	49.4	45.7	39.0	40.6	41.0	29.1	30.4	31.8	21.8	22.9	24.0	15.9	17.0	-	216
229	-	-	45.3	-	45.2	43.4	32.1	45.6	42.0	36.0	39.3	39.9	28.0	29.3	30.4	20.9	22.0	22.9	15.2	16.1	17.2	229
243	-	-	-	-	-	40.0	-	40.6	38.5	28.9	38.1	38.7	27.1	28.4	29.3	20.0	21.1	22.0	14.3	15.4	16.3	243
256	-	-	-	-	-	-	-	-	35.6	21.7	36.9	35.9	26.1	27.3	28.2	19.3	20.4	21.1	13.6	14.7	15.4	256
269	-	-	-	-	-	-	-	-	-	-	30.2	33.0	20.5	26.6	27.3	18.7	19.8	20.5	13.0	13.8	14.5	269
282	-	-	-	-	-	-	-	-	-	-	-	30.6	-	25.8	26.4	18.0	18.9	19.6	12.3	13.2	13.8	282
295	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25.8	-	18.3	18.9	11.6	12.5	13.2	295
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	17.6	18.3	11.2	11.9	12.5	308
321	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	17.6	-	11.4	11.9	321
334	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11.2	334
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	348

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



360°

DIN/ISO

100.0 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
1,000 lb																			
52	206.1	-	-	177.4	-	-	136.6	-	-	-	-	-	-	-	-	-	-	-	52
59	191.9	-	-	173.1	-	-	136.6	-	-	110.2	-	-	-	-	-	-	-	-	59
65	180.8	-	-	168.0	-	-	136.6	-	-	110.2	-	-	88.1	-	-	-	-	-	65
72	170.0	-	-	160.0	-	-	135.6	-	-	110.2	-	-	88.1	-	-	73.8	-	-	72
79	161.8	136.3	-	150.6	-	-	133.2	-	-	110.1	-	-	88.1	-	-	73.8	-	-	79
85	156.7	128.2	-	143.6	124.8	-	130.2	-	-	109.1	-	-	88.1	-	-	73.8	-	-	85
92	-	121.1	-	136.5	117.8	-	126.6	107.9	-	108.0	-	-	88.1	-	-	73.8	-	-	92
98	-	116.1	-	131.5	113.8	-	122.6	102.8	-	108.0	-	-	88.1	-	-	73.8	-	-	98
105	-	112.4	99.2	130.0	109.1	-	117.9	96.9	-	106.9	93.6	-	88.1	-	-	73.8	-	-	105
111	-	-	95.1	-	105.0	92.9	112.8	92.9	-	105.9	89.6	-	88.1	85.1	-	73.8	-	-	111
118	-	-	91.5	-	101.4	88.2	107.0	90.4	-	101.4	86.0	-	88.1	81.6	-	73.8	73.8	-	118
124	-	-	-	-	98.4	85.2	93.9	87.3	77.6	97.4	83.0	-	88.1	78.6	-	73.8	71.8	-	124
131	-	-	-	-	-	81.6	-	86.0	73.9	92.7	79.4	71.8	84.9	75.0	-	73.8	69.5	-	131
138	-	-	-	-	-	79.2	-	85.9	70.5	87.7	77.1	67.1	81.4	72.6	-	73.7	68.2	-	138
144	-	-	-	-	-	-	-	85.9	69.5	74.6	76.1	65.5	78.4	70.6	62.9	71.7	66.2	-	144
151	-	-	-	-	-	-	-	-	67.2	-	73.8	62.8	75.9	68.3	59.9	69.4	65.4	-	151
157	-	-	-	-	-	-	-	-	66.2	-	72.8	61.1	70.9	67.3	57.7	67.4	64.2	56.6	157
164	-	-	-	-	-	-	-	-	-	-	72.7	59.3	59.3	66.1	55.3	65.0	62.8	54.2	164
177	-	-	-	-	-	-	-	-	-	-	-	58.2	-	65.2	52.2	56.3	60.6	50.3	177
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50.5	-	58.9	47.4	190
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	55.8	45.4	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	44.3	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	229

		196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			
ft											1,000 lb										ft		
72	66.1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72		
79	66.1	-	-	51.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79		
85	66.1	-	-	51.3	-	-	44.5	-	-	-	-	-	-	-	-	-	-	-	-	-	85		
92	66.1	-	-	51.3	-	-	44.5	-	-	38.8	-	-	-	-	-	-	-	-	-	-	92		
98	66.1	-	-	51.3	-	-	44.5	-	-	38.8	-	-	31.3	-	-	-	-	-	-	-	98		
105	66.1	-	-	51.3	-	-	44.5	-	-	38.8	-	-	31.3	-	-	25.5	-	-	-	-	105		
111	66.1	-	-	51.3	-	-	44.5	-	-	38.8	-	-	31.3	-	-	25.1	-	-	19.6	-	111		
118	66.1	-	-	51.3	-	-	44.5	-	-	38.8	-	-	31.0	-	-	24.9	-	-	19.4	-	118		
124	66.1	-	-	51.1	-	-	44.5	-	-	38.8	-	-	31.0	-	-	24.7	-	-	19.0	-	124		
131	66.1	61.5	-	51.1	-	-	44.5	-	-	38.5	-	-	31.0	-	-	24.4	-	-	18.7	-	131		
138	66.1	61.0	-	51.1	56.6	-	44.5	-	-	38.5	-	-	30.8	-	-	24.0	-	-	18.2	-	138		
144	65.9	60.2	-	50.9	55.6	-	44.5	43.4	-	38.3	-	-	30.6	-	-	23.8	-	-	18.0	-	144		
151	65.8	59.5	-	50.9	54.6	-	44.5	43.4	-	38.1	-	-	30.4	-	-	23.5	-	-	17.6	-	151		
157	64.2	58.9	-	50.7	53.6	-	44.5	43.2	-	37.9	37.9	-	30.2	-	-	23.1	-	-	17.4	-	157		
164	62.6	57.9	50.2	50.7	52.6	-	44.5	43.2	-	37.7	37.7	-	29.9	30.2	-	22.9	-	-	16.9	-	164		
177	59.3	56.2	47.8	49.1	50.7	46.5	44.3	42.9	-	37.0	37.2	-	29.3	29.5	-	22.2	23.3	-	16.3	-	177		
190	52.8	54.2	45.6	47.6	48.9	43.5	43.2	42.7	40.1	36.6	36.8	-	28.6	28.8	-	21.6	22.7	-	15.6	16.7	-	190	
203	-	52.3	43.5	46.1	47.4	40.4	41.9	42.3	38.2	35.9	36.1	34.4	28.0	28.4	-	20.9	22.0	-	15.0	15.9	-	203	
216	-	49.9	41.7	36.7	46.1	38.4	40.6	41.4	36.2	35.3	35.5	32.9	27.3	27.8	26.7	20.5	21.4	-	14.3	15.2	-	216	
229	-	-	39.9	-	44.6	37.3	33.2	40.6	34.6	34.6	34.8	31.3	26.7	27.3	25.6	19.8	20.7	20.9	13.7	14.5	-	229	
243	-	-	-	-	-	36.1	-	39.6	33.4	29.8	33.9	30.1	26.0	26.8	24.2	19.1	20.0	20.0	12.9	13.8	14.9	243	
256	-	-	-	-	-	35.0	-	35.2	32.3	22.8	33.0	29.0	25.1	26.4	23.1	18.5	19.6	19.1	12.3	13.2	14.3	256	
269	-	-	-	-	-	-	-	-	31.0	-	31.9	28.2	21.3	26.0	22.0	17.8	18.9	18.3	11.9	12.7	13.6	269	
282	-	-	-	-	-	-	-	-	-	-	-	27.3	-	25.5	21.1	17.4	18.3	17.6	11.2	12.1	13.0	282	
295	-	-	-	-	-	-	-	-	-	-	-	-	-	24.0	20.3	13.9	17.6	16.7	11.0	11.6	12.3	295	
308	-	-	-	-	-	-	-	-	-	-	-	-	-	-	19.6	-	17.2	16.1	10.5	11.2	11.7	308	
321	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	15.2	-	10.8	11.2	321	
334	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	10.5	10.6	334	
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	10.1	348	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



Lifting capacities luffing fly jib, main boom 83° to 65°



360°

DIN/ISO

116.5 ft + 13.1 ft Main boom + adapter

Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
	Fly jib																		
	1,000 lb																		
52	180.4	-	-	148.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	52
59	169.8	-	-	146.6	-	-	120.1	-	-	-	-	-	-	-	-	-	-	-	59
65	160.7	-	-	143.6	-	-	120.1	-	-	99.2	-	-	78.2	-	-	-	-	-	65
72	150.1	-	-	137.9	-	-	120.1	-	-	99.2	-	-	78.2	-	-	66.1	-	-	72
79	141.9	-	-	132.0	-	-	117.8	-	-	99.2	-	-	78.2	-	-	66.1	-	-	79
85	136.9	111.5	-	127.0	-	-	115.8	-	-	99.2	-	-	78.2	-	-	66.1	-	-	85
92	-	105.7	-	122.2	100.1	-	112.3	-	-	98.1	-	-	78.2	-	-	66.1	-	-	92
98	-	100.6	-	119.2	95.1	-	110.3	91.7	-	98.1	-	-	78.2	-	-	66.1	-	-	98
105	-	96.9	-	117.9	90.3	-	109.1	87.0	-	96.9	-	-	78.2	-	-	66.1	-	-	105
111	-	-	80.7	-	87.3	-	107.1	83.0	-	95.9	80.8	-	78.2	-	-	66.1	-	-	111
118	-	-	77.2	-	83.8	71.6	105.8	79.4	-	94.8	77.2	-	78.2	72.7	-	66.1	-	-	118
124	-	-	73.2	-	81.7	69.6	100.8	76.4	-	93.8	74.1	-	78.2	70.7	-	66.1	66.3	-	124
131	-	-	-	-	-	66.2	-	73.9	64.7	91.5	70.6	-	77.2	67.3	-	66.1	63.8	-	131
138	-	-	-	-	-	64.5	-	72.7	61.4	89.9	68.2	-	77.1	65.4	-	66.1	61.4	-	138
144	-	-	-	-	-	63.1	-	72.7	59.4	78.8	66.2	56.5	76.1	63.6	-	65.9	59.8	-	144
151	-	-	-	-	-	-	-	-	57.0	-	65.0	53.7	74.9	61.2	51.7	65.6	57.7	-	151
157	-	-	-	-	-	-	-	-	55.8	-	63.8	51.9	73.9	60.0	49.5	65.2	56.3	-	157
164	-	-	-	-	-	-	-	-	54.6	-	62.6	49.8	63.1	58.4	47.1	65.0	54.6	45.2	164
177	-	-	-	-	-	-	-	-	-	-	-	47.8	-	56.8	43.6	58.7	52.2	41.4	177
190	-	-	-	-	-	-	-	-	-	-	-	-	-	-	41.7	-	50.7	38.6	190
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	40.8	-	49.6	36.4	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	35.1	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	229

ft	196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
	1,000 lb																					
79	59.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79
85	59.5	-	-	46.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85
92	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	-	-	-	-	-	-	-	-	-	92
98	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	-	-	-	-	-	-	98
105	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	24.2	-	-	-	-	-	105
111	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	24.0	-	-	18.7	-	-	111
118	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	24.0	-	-	18.5	-	-	118
124	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	23.8	-	-	18.3	-	-	124
131	59.5	-	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	23.8	-	-	17.8	-	-	131
138	59.5	54.1	-	46.2	-	-	40.7	-	-	35.2	-	-	28.6	-	-	23.5	-	-	17.6	-	-	138
144	59.5	52.9	-	46.2	54.3	-	40.7	-	-	35.2	-	-	28.6	-	-	23.3	-	-	17.4	-	-	144
151	59.5	51.7	-	46.2	52.2	-	40.7	39.6	-	35.2	-	-	28.6	-	-	23.1	-	-	17.1	-	-	151
157	59.3	50.7	-	46.2	50.6	-	40.7	39.6	-	35.2	-	-	28.6	-	-	23.1	-	-	16.7	-	-	157
164	58.8	49.6	-	46.2	48.7	-	40.7	39.4	-	35.2	33.7	-	28.6	-	-	22.9	-	-	16.5	-	-	164
177	58.2	47.6	41.0	46.2	45.6	-	40.7	39.2	-	35.2	33.7	-	28.6	27.5	-	22.4	-	-	15.8	-	-	177
190	54.5	45.8	38.4	46.2	43.2	37.3	40.7	38.8	-	35.2	33.7	-	28.6	27.5	-	22.0	22.7	-	15.2	16.3	-	190
203	41.6	44.3	36.0	46.2	41.0	34.0	40.7	38.1	32.9	35.2	33.7	-	28.6	27.5	-	21.6	22.2	-	14.5	15.6	-	203
216	-	43.2	34.0	38.2	39.5	31.4	40.7	37.5	30.3	35.0	33.7	28.5	28.2	27.5	-	21.1	21.8	-	13.9	15.0	-	216
229	-	-	32.4	-	38.4	29.4	34.2	36.6	27.9	35.0	33.1	26.7	27.6	27.5	23.2	20.5	21.4	-	13.4	14.3	-	229
243	-	-	31.0	-	37.6	28.2	24.7	35.4	25.9	30.7	32.3	24.8	26.6	27.1	21.8	20.0	20.9	20.2	12.7	13.6	-	243
256	-	-	-	-	27.5	-	34.3	24.6	23.7	31.7	23.5	25.9	26.4	20.4	19.6	20.5	19.3	12.3	13.2	14.3	-	256
269	-	-	-	-	-	-	-	23.8	-	31.0	22.4	21.8	25.7	19.4	18.9	20.0	18.3	11.9	12.7	13.8	-	269
282	-	-	-	-	-	-	-	23.3	-	27.8	21.6	-	25.3	18.3	18.5	19.4	17.4	11.4	12.3	13.2	-	282
295	-	-	-	-	-	-	-	-	-	-	20.9	-	24.7	17.2	14.4	18.9	16.5	11.2	11.9	12.7	-	295
308	-	-	-	-	-	-	-	-	-	-	-	-	-	16.3	-	18.3	15.6	11.0	11.6	12.1	-	308
321	-	-	-	-	-	-	-	-	-	-	-	-	-	15.4	-	17.8	14.5	-	11.4	11.7	-	321
334	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.7	-	11.2	11.0	-	334
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	10.3	-	348
361	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	361

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



360°

DIN/ISO

132.9 ft + 13.1 ft Main boom + adapter

Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
	Fly jib																		
	1,000 lb																		
59	144.4	-	-	123.4	-	-	94.7	-	-	-	-	-	-	-	-	-	-	-	59
65	139.4	-	-	123.4	-	-	94.7	-	-	78.2	-	-	-	-	-	-	-	-	65
72	132.4	-	-	121.3	-	-	94.7	-	-	78.2	-	-	64.3	-	-	-	-	-	72
79	124.3	-	-	114.4	-	-	94.7	-	-	78.2	-	-	64.3	-	-	55.5	-	-	79
85	118.2	-	-	109.3	-	-	92.6	-	-	78.2	-	-	64.3	-	-	55.5	-	-	85
92	-	91.3	-	104.6	-	-	90.3	-	-	78.2	-	-	64.3	-	-	55.5	-	-	92
98	-	86.3	-	101.5	85.3	-	89.3	-	-	78.2	-	-	64.3	-	-	55.5	-	-	98
105	-	82.6	-	100.3	80.4	-	88.1	71.6	-	77.1	-	-	64.3	-	-	55.5	-	-	105
111	-	78.6	-	-	76.4	-	87.1	68.6	-	77.1	-	-	64.3	-	-	55.5	-	-	111
118	-	-	65.9	-	72.8	-	85.9	65.5	-	76.0	63.3	-	64.3	-	-	55.3	-	-	118
124	-	-	61.7	-	69.7	-	84.9	62.7	-	76.0	60.7	-	64.1	58.0	-	55.3	-	-	124
131	-	-	58.9	-	68.3	58.0	-	60.6	-	74.9	58.0	-	63.9	55.4	-	55.3	-	-	131
138	-	-	-	-	-	55.0	-	58.6	49.9	73.8	55.5	-	63.4	52.8	-	55.3	50.2	-	138
144	-	-	-	-	-	53.0	-	57.8	47.9	72.8	53.8	-	63.2	51.0	-	55.1	48.5	-	144
151	-	-	-	-	-	50.6	-	57.0	45.6	-	52.0	43.6	62.8	48.9	-	55.1	46.4	-	151
157	-	-	-	-	-	-	-	-	44.4	-	51.0	42.0	62.2	47.5	-	54.9	45.0	-	157
164	-	-	-	-	-	-	-	-	42.7	-	50.0	40.1	61.7	45.8	37.9	54.4	43.4	-	164
177	-	-	-	-	-	-	-	-	-	-	-	37.5	-	43.8	34.6	54.0	41.0	33.5	177
190	-	-	-	-	-	-	-	-	-	-	-	36.1	-	42.7	32.2	-	39.2	30.7	190
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	30.6	-	38.1	28.5	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	26.9	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	26.0	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	243

ft	196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
	1,000 lb																					
79	48.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79
85	48.2	-	-	37.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85
92	48.2	-	-	37.4	-	-	31.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92
98	48.2	-	-	37.4	-	-	31.5	-	-	27.7	-	-	-	-	-	-	-	-	-	-	-	98
105	48.2	-	-	37.4	-	-	31.5	-	-	27.7	-	-	22.0	-	-	-	-	-	-	-	-	105
111	48.2	-	-	37.4	-	-	31.5	-	-	27.5	-	-	22.0	-	-	18.2	-	-	-	-	-	111
118	48.2	-	-	37.4	-	-	31.5	-	-	27.5	-	-	22.0	-	-	18.2	-	-	13.8	-	-	118
124	48.2	-	-	37.4	-	-	31.5	-	-	27.3	-	-	22.0	-	-	18.1	-	-	13.6	-	-	124
131	48.2	-	-	37.4	-	-	31.5	-	-	27.3	-	-	22.0	-	-	18.0	-	-	13.4	-	-	131
138	48.2	-	-	37.4	-	-	31.5	-	-	27.3	-	-	22.0	-	-	18.0	-	-	13.0	-	-	138
144	48.2	43.2	-	37.4	-	-	31.5	-	-	27.3	-	-	22.0	-	-	17.8	-	-	12.7	-	-	144
151	48.2	42.0	-	37.4	42.0	-	31.5	-	-	27.3	-	-	22.0	-	-	17.8	-	-	12.5	-	-	151
157	48.2	41.0	-	37.4	40.8	-	31.5	-	-	27.3	-	-	22.0	-	-	17.8	-	-	12.3	-	-	157
164	48.0	39.9	-	37.4	39.4	-	31.5	30.2	-	27.3	-	-	22.0	-	-	17.6	-	-	12.1	-	-	164
177	47.6	37.9	-	37.4	37.0	-	31.5	29.7	-	27.3	27.5	-	22.0	20.9	-	17.6	-	-	11.6	-	-	177
190	47.1	36.4	30.0	37.4	34.4	-	31.5	29.3	-	27.3	26.9	-	22.0	20.9	-	17.4	-	-	11.2	-	-	190
203	43.3	35.0	27.8	37.4	32.6	26.9	31.5	28.8	-	27.1	26.4	-	22.0	20.9	-	17.2	17.1	-	10.8	11.6	-	203
216	-	33.9	26.0	37.4	31.5	24.5	31.5	28.2	23.0	27.1	25.8	-	21.8	20.9	-	16.9	16.9	-	10.3	11.2	-	216
229	-	33.1	24.5	-	30.4	22.3	31.5	27.3	21.0	27.1	25.1	18.5	21.6	20.9	17.0	16.7	16.7	-	10.1	10.8	-	229
243	-	-	23.3	-	29.3	21.3	26.1	26.4	18.7	27.0	24.4	16.9	21.1	20.9	15.6	16.3	16.5	15.1	9.6	10.5	-	243
256	-	-	-	-	-	20.4	-	25.7	18.0	24.4	23.8	15.8	20.9	20.5	14.5	16.0	16.0	13.8	9.4	10.1	-	256
269	-	-	-	-	-	19.6	-	24.9	17.1	-	23.1	14.9	20.5	20.2	13.4	15.8	15.8	13.0	9.2	9.9	-	269
282	-	-	-	-	-	-	-	-	16.5	-	22.2	14.1	16.1	20.0	12.3	15.6	15.4	11.9	9.0	9.4	-	282
295	-	-	-	-	-	-	-	-	-	-	-	13.6	-	19.8	11.6	14.7	15.0	11.0	8.8	9.2	-	295
308	-	-	-	-	-	-	-	-	-	-	-	13.4	-	19.4	11.0	-	14.5	10.3	8.6	9.0	-	308
321	-	-	-	-	-	-	-	-	-	-	-	-	-	-	10.6	-	14.1	9.5	8.3	8.8	-	321
334	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9.0	-	8.6	-	334
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	8.3	-	8.3	-	348
361	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	361

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



Lifting capacities luffing fly jib, main boom 83° to 65°



360°

DIN/ISO

149.3 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
1,000 lb																			
65	113.7	-	-	99.2	-	-	79.3	-	-	-	-	-	-	-	-	-	-	-	65
72	109.2	-	-	99.2	-	-	79.3	-	-	66.1	-	-	57.3	-	-	-	-	-	72
79	103.4	-	-	95.7	-	-	79.3	-	-	66.1	-	-	57.3	-	-	50.7	-	-	79
85	98.3	-	-	91.6	-	-	79.3	-	-	66.1	-	-	57.3	-	-	50.7	-	-	85
92	93.6	-	-	88.1	-	-	77.1	-	-	66.1	-	-	57.3	-	-	50.7	-	-	92
98	-	-	-	86.1	-	-	77.1	-	-	66.1	-	-	57.3	-	-	50.7	-	-	98
105	-	71.6	-	84.8	67.2	-	76.0	-	-	66.1	-	-	57.0	-	-	50.7	-	-	105
111	-	67.6	-	82.8	64.2	-	75.0	60.8	-	66.1	-	-	57.0	-	-	50.7	-	-	111
118	-	65.2	-	-	61.1	-	74.9	57.5	-	66.1	-	-	56.8	-	-	50.7	-	-	118
124	-	-	-	-	58.6	-	73.9	54.9	-	66.1	52.7	-	56.6	-	-	50.5	-	-	124
131	-	-	49.2	-	56.7	-	73.8	52.5	-	65.7	50.1	-	56.4	47.9	-	50.4	-	-	131
138	-	-	46.4	-	54.8	44.9	-	50.4	-	65.4	47.5	-	56.2	45.3	-	50.4	-	-	138
144	-	-	-	-	-	43.3	-	49.2	-	65.0	45.9	-	55.8	43.5	-	50.2	42.2	-	144
151	-	-	-	-	-	41.4	-	48.0	38.3	64.8	43.8	-	55.5	41.4	-	50.2	40.1	-	151
157	-	-	-	-	-	40.2	-	47.6	36.9	-	42.8	-	55.1	39.8	-	50.0	38.6	-	157
164	-	-	-	-	-	-	-	-	35.2	-	41.4	33.7	54.8	38.1	-	49.8	36.8	-	164
177	-	-	-	-	-	-	-	-	33.5	-	39.9	31.3	-	35.7	28.7	49.1	34.2	-	177
190	-	-	-	-	-	-	-	-	-	-	-	29.3	-	34.2	26.2	45.9	32.2	25.6	190
203	-	-	-	-	-	-	-	-	-	-	-	-	-	-	24.3	-	30.6	23.4	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	22.9	-	30.0	21.8	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	20.5	229

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft				
ft										1,000 lb										ft		
85	41.8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85		
92	41.8	-	-	32.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92		
98	41.8	-	-	32.4	-	-	25.3	-	-	23.3	-	-	-	-	-	-	-	-	-	98		
105	41.8	-	-	32.4	-	-	25.3	-	-	23.1	-	-	-	-	-	-	-	-	-	105		
111	41.8	-	-	32.4	-	-	25.3	-	-	22.9	-	-	17.6	-	-	-	-	-	-	111		
118	41.8	-	-	32.4	-	-	25.3	-	-	22.7	-	-	17.6	-	-	14.3	-	-	10.8	-	118	
124	41.8	-	-	32.4	-	-	25.3	-	-	22.5	-	-	17.6	-	-	14.3	-	-	10.6	-	124	
131	41.8	-	-	32.4	-	-	25.3	-	-	22.4	-	-	17.6	-	-	14.3	-	-	10.1	-	131	
138	41.8	-	-	32.4	-	-	25.3	-	-	22.2	-	-	17.6	-	-	14.3	-	-	9.9	-	138	
144	41.8	-	-	32.4	-	-	25.3	-	-	22.0	-	-	17.6	-	-	14.3	-	-	9.7	-	144	
151	41.8	37.0	-	32.4	-	-	25.3	-	-	22.0	-	-	17.6	-	-	14.3	-	-	9.4	-	151	
157	41.8	36.0	-	32.4	-	-	25.3	-	-	22.0	-	-	17.6	-	-	14.3	-	-	9.2	-	157	
164	41.8	34.8	-	32.4	32.8	-	25.3	-	-	22.0	-	-	17.6	-	-	14.3	-	-	9.0	-	164	
177	41.8	32.8	-	32.4	30.4	-	25.3	23.8	-	22.0	24.9	-	17.6	-	-	14.3	-	-	8.6	-	177	
190	41.8	31.1	-	32.4	28.4	-	25.3	23.3	-	22.0	23.6	-	17.6	16.5	-	14.3	-	-	8.3	-	190	
203	41.8	29.5	22.7	32.4	26.7	-	25.3	22.7	-	22.0	22.3	-	17.6	16.5	-	14.3	13.2	-	8.1	8.8	-	203
216	-	28.2	20.8	32.4	25.1	19.0	25.3	22.0	17.5	22.0	20.9	-	17.6	16.5	-	14.3	13.2	-	7.9	8.6	-	216
229	-	27.3	19.2	29.0	23.8	17.0	25.3	21.4	15.3	22.0	19.8	11.9	17.6	16.5	-	14.3	13.2	-	7.7	8.3	-	229
243	-	-	18.0	-	22.9	15.6	25.3	20.7	13.4	22.0	18.7	10.5	17.6	16.5	11.2	14.3	13.2	-	7.7	8.1	-	243
256	-	-	16.9	-	22.2	14.5	-	19.8	12.1	22.0	17.8	9.4	17.6	16.0	9.9	14.3	13.0	10.5	7.4	7.9	-	256
269	-	-	-	-	-	13.6	-	18.7	11.0	17.2	16.9	8.6	17.6	15.4	8.6	14.3	12.7	9.0	7.4	7.7	-	269
282	-	-	-	-	-	-	-	-	10.3	-	16.3	8.1	16.7	14.9	7.7	14.3	12.5	7.9	7.2	7.4	-	282
295	-	-	-	-	-	-	-	-	9.9	-	15.6	7.5	-	14.3	7.0	14.3	12.3	6.8	7.2	7.4	-	295
308	-	-	-	-	-	-	-	-	-	-	-	7.2	-	13.6	6.4	9.4	12.1	5.9	7.0	7.2	-	308
321	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.1	-	11.9	5.3	6.6	7.0	-	321
334	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6.1	-	-	4.8	-	6.8	-	334
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4.4	-	6.6	-	348

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



360°

DIN/ISO

165.7 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
1,000 lb																			
65	83.7	-	-	71.8	-	-	58.6	-	-	-	-	-	-	-	-	-	-	-	65
72	82.7	-	-	69.5	-	-	58.6	-	-	48.7	-	-	-	-	-	-	-	-	72
79	80.4	-	-	68.3	-	-	58.6	-	-	48.7	-	-	44.5	-	-	-	-	-	79
85	79.4	-	-	68.3	-	-	58.6	-	-	48.7	-	-	44.5	-	-	37.6	-	-	85
92	77.1	-	-	68.3	-	-	58.1	-	-	48.7	-	-	44.5	-	-	37.6	-	-	92
98	-	-	-	68.3	-	-	57.7	-	-	48.7	-	-	44.5	-	-	37.6	-	-	98
105	-	59.2	-	67.2	-	-	57.5	-	-	48.7	-	-	44.3	-	-	37.6	-	-	105
111	-	56.4	-	66.2	54.4	-	57.1	-	-	48.7	-	-	44.1	-	-	37.6	-	-	111
118	-	53.8	-	-	51.8	-	56.8	-	-	48.7	-	-	43.6	-	-	37.4	-	-	118
124	-	51.8	-	-	49.6	-	56.7	43.6	-	48.7	-	-	43.2	-	-	37.4	-	-	124
131	-	-	-	-	47.4	-	56.4	41.7	-	48.7	39.5	-	42.9	-	-	37.4	-	-	131
138	-	-	-	-	45.3	-	-	39.8	-	48.4	37.4	-	42.5	35.4	-	37.4	-	-	138
144	-	-	-	-	44.1	37.6	-	38.6	-	48.2	36.0	-	42.1	33.8	-	37.4	-	-	144
151	-	-	-	-	-	35.2	-	37.2	-	48.2	34.3	-	41.8	31.9	-	37.4	30.6	-	151
157	-	-	-	-	-	33.8	-	36.6	29.6	-	33.3	-	41.4	30.7	-	37.2	29.4	-	157
164	-	-	-	-	-	31.9	-	35.9	28.2	-	31.9	-	41.2	29.1	-	37.0	28.0	-	164
177	-	-	-	-	-	-	-	-	26.2	-	30.6	24.2	-	27.1	-	36.6	25.8	-	177
190	-	-	-	-	-	-	-	-	-	-	-	22.5	-	25.6	20.1	36.3	24.0	-	190
203	-	-	-	-	-	-	-	-	-	-	-	21.2	-	24.7	18.3	-	22.7	17.4	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	17.0	-	21.8	15.9	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	14.6	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	13.8	243
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256

196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			
ft							1,000 lb									ft		
85	29.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85	
92	29.7	-	-	22.7	-	-	-	-	-	-	-	-	-	-	-	-	92	
98	29.7	-	-	22.7	-	-	17.1	-	-	-	-	-	-	-	-	-	98	
105	29.7	-	-	22.7	-	-	17.1	-	-	14.5	-	-	-	-	-	-	105	
111	29.7	-	-	22.7	-	-	17.1	-	-	14.3	-	-	10.5	-	-	-	111	
118	29.7	-	-	22.7	-	-	17.1	-	-	14.3	-	-	10.5	-	-	-	118	
124	29.7	-	-	22.7	-	-	17.1	-	-	14.3	-	-	10.5	-	-	-	124	
131	29.7	-	-	22.7	-	-	17.1	-	-	14.1	-	-	10.5	-	-	-	131	
138	29.7	-	-	22.7	-	-	17.1	-	-	14.1	-	-	10.5	-	-	-	138	
144	29.7	-	-	22.7	-	-	17.1	-	-	13.9	-	-	10.5	-	-	-	144	
151	29.7	-	-	22.7	-	-	17.1	-	-	13.8	-	-	10.5	-	-	-	151	
157	29.7	26.7	-	22.7	-	-	17.1	-	-	13.8	-	-	10.5	-	-	-	157	
164	29.7	25.8	-	22.7	-	-	17.1	-	-	13.8	-	-	10.5	-	-	-	164	
177	29.7	24.0	-	22.7	21.6	-	17.1	16.5	-	13.8	-	-	10.5	-	-	-	177	
190	29.7	22.3	-	22.7	19.8	-	17.1	15.8	-	13.8	-	-	10.5	-	-	-	190	
203	29.7	20.9	16.3	22.7	18.3	-	17.1	15.4	-	13.8	-	-	10.5	-	-	-	203	
216	-	20.0	14.8	22.7	17.0	-	17.1	14.7	-	13.8	-	-	10.5	-	-	-	216	
229	-	19.2	13.5	22.7	16.1	-	17.1	14.1	-	13.8	-	-	10.5	-	-	-	229	
243	-	18.5	12.3	-	15.2	-	17.1	13.6	-	13.8	-	-	10.5	-	-	-	243	
256	-	-	11.6	-	14.5	-	-	13.0	-	13.8	-	-	10.5	-	-	-	256	
269	-	-	-	-	-	-	-	12.5	-	13.8	-	-	10.5	-	-	-	269	
282	-	-	-	-	-	-	-	11.9	-	-	-	-	10.5	-	-	-	282	
295	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	295	

Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



Lifting capacities luffing fly jib, main boom 83° to 65°

360°

DIN/ISO

182.1 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius ft	78.7 ft			98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			Radius ft
	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	83°	73°	65°	
	1,000 lb																		
72	68.3	-	-	56.2	-	-	44.0	-	-	-	-	-	-	-	-	-	-	-	72
79	66.0	-	-	56.1	-	-	44.0	-	-	36.5	-	-	-	-	-	-	-	-	79
85	65.0	-	-	55.5	-	-	44.0	-	-	36.5	-	-	36.3	-	-	-	-	-	85
92	63.4	-	-	54.4	-	-	44.0	-	-	36.5	-	-	36.3	-	-	28.4	-	-	92
98	-	-	-	53.6	-	-	44.0	-	-	36.5	-	-	36.3	-	-	28.4	-	-	98
105	-	-	-	52.6	-	-	44.0	-	-	36.5	-	-	36.1	-	-	28.4	-	-	105
111	-	-	-	51.8	-	-	44.0	-	-	36.5	-	-	35.9	-	-	28.4	-	-	111
118	-	44.7	-	-	40.3	-	44.0	-	-	36.5	-	-	35.2	-	-	28.4	-	-	118
124	-	42.7	-	-	38.5	-	44.0	-	-	36.5	-	-	34.6	-	-	28.4	-	-	124
131	-	-	-	-	36.8	-	44.0	34.2	-	36.5	-	-	34.1	-	-	28.4	-	-	131
138	-	-	-	-	35.2	-	-	32.5	-	36.5	30.3	-	33.4	-	-	28.4	-	-	138
144	-	-	-	-	34.2	-	-	31.5	-	36.5	29.1	-	33.0	-	-	28.4	-	-	144
151	-	-	-	-	-	-	-	30.4	-	36.5	27.7	-	32.6	25.1	-	28.4	-	-	151
157	-	-	-	-	-	26.9	-	29.7	-	-	26.7	-	32.2	24.1	-	28.4	22.5	-	157
164	-	-	-	-	-	25.5	-	28.8	-	-	25.8	-	31.9	22.7	-	28.2	21.3	-	164
177	-	-	-	-	-	-	-	-	21.6	-	24.2	-	-	20.9	-	27.9	19.4	-	177
190	-	-	-	-	-	-	-	-	20.0	-	-	17.6	-	19.4	-	27.7	17.8	-	190
203	-	-	-	-	-	-	-	-	-	-	-	16.3	-	18.5	13.6	-	16.7	12.6	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	12.6	-	15.9	11.2	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11.7	-	-	10.1	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9.2	243

	196.9 ft			216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft				
ft	1,000 lb																			ft
92	20.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92		
98	20.9	-	-	15.4	-	-	-	-	-	-	-	-	-	-	-	-	-	98		
105	20.9	-	-	14.4	-	-	11.0	-	-	-	-	-	-	-	-	-	-	105		
111	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	-	-	-	-	-	111		
118	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	118		
124	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	124		
131	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	131		
138	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	138		
144	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	144		
151	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	151		
157	20.9	-	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	157		
164	20.9	19.4	-	15.4	-	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	164		
177	20.9	17.6	-	15.4	13.6	-	11.0	-	-	7.2	-	-	4.4	-	-	-	-	177		
190	20.9	16.3	-	15.4	12.3	-	11.0	10.3	-	7.2	-	-	4.4	-	-	-	-	190		
203	20.9	15.0	-	15.4	11.2	-	11.0	9.5	-	7.2	-	-	4.4	-	-	-	-	203		
216	-	13.9	10.1	15.4	10.1	-	11.0	8.8	-	7.2	-	-	4.4	-	-	-	-	216		
229	-	13.2	8.8	15.4	9.0	-	11.0	8.3	-	7.2	-	-	4.4	-	-	-	-	229		
243	-	12.5	7.9	-	8.1	-	11.0	7.7	-	7.2	-	-	4.4	-	-	-	-	243		
256	-	-	7.2	-	7.4	-	-	7.2	-	7.2	-	-	4.4	-	-	-	-	256		
269	-	-	6.6	-	-	-	-	6.8	-	7.2	-	-	4.4	-	-	-	-	269		
282	-	-	-	-	-	-	-	6.6	-	-	-	-	4.4	-	-	-	-	282		


Remarks

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

Working ranges luffing fly jib with SSL, main boom 83° to 65°





Lifting capacities luffing fly jib with SSL, main boom 83°–65°

	360°	DIN/ISO
--	------	---------

116.5 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius	98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			196.9 ft			Radius
	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	
ft	1,000 lb																		ft
52	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	52
59	202.8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59
65	194.8	-	-	174.1	-	-	146.6	-	-	-	-	-	-	-	-	-	-	-	65
72	182.2	-	-	170.9	-	-	146.6	-	-	129.0	-	-	-	-	-	-	-	-	72
79	171.5	-	-	163.9	-	-	146.5	-	-	126.5	-	-	107.9	-	-	-	-	-	79
85	161.4	-	-	156.9	-	-	144.5	-	-	123.5	-	-	105.9	-	-	89.2	-	-	85
92	151.9	136.5	-	148.6	-	-	139.8	-	-	121.1	-	-	103.5	-	-	88.1	-	-	92
98	143.8	132.5	-	140.5	114.7	-	134.8	-	-	118.1	-	-	101.5	-	-	86.1	-	-	98
105	133.3	126.7	-	133.3	112.4	-	128.9	99.2	-	115.7	-	-	100.3	-	-	84.8	-	-	105
111	-	120.7	-	126.3	109.4	-	123.9	98.1	-	112.7	-	-	98.2	-	-	83.8	-	-	111
118	-	113.6	104.8	118.0	105.8	-	118.0	98.1	-	109.1	78.2	-	95.9	-	-	82.6	-	-	118
124	-	106.6	98.7	102.1	102.8	-	113.0	97.1	-	107.1	78.2	-	93.9	66.1	-	81.6	-	-	124
131	-	-	92.7	-	97.1	91.6	106.0	95.9	-	102.6	78.2	-	92.6	66.1	-	79.4	59.5	-	131
138	-	-	88.0	-	92.4	85.8	93.2	91.3	83.6	99.0	78.2	-	90.2	66.1	-	78.2	59.5	-	138
144	-	-	84.0	-	87.3	81.8	80.1	87.3	79.6	94.0	77.2	-	87.2	66.1	-	77.2	59.5	-	144
151	-	-	-	-	-	77.1	-	82.6	74.9	83.6	76.0	72.7	84.8	66.1	-	76.0	59.5	-	151
157	-	-	-	-	-	74.1	-	78.5	71.8	74.5	74.0	69.6	80.7	65.5	-	74.0	59.5	-	157
164	-	-	-	-	-	70.5	-	74.9	68.3	63.5	70.5	66.1	71.7	65.0	64.3	71.6	59.5	-	164
177	-	-	-	-	-	-	-	-	62.6	-	65.9	60.2	56.8	61.5	58.5	67.2	58.6	58.4	177
190	-	-	-	-	-	-	-	-	-	-	-	55.2	-	57.8	53.2	55.1	55.8	53.2	190
203	-	-	-	-	-	-	-	-	-	-	-	50.4	-	54.3	48.8	42.0	52.7	48.8	203
216	-	-	-	-	-	-	-	-	-	-	-	-	-	-	44.9	-	49.9	44.7	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	40.9	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	37.6	243
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256

216.5 ft				236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			
ft							1,000 lb												ft
92	70.5	-	-	61.2	-	-	-	-	-	-	-	-	-	-	-	-	-	92	
98	69.5	-	-	60.2	-	-	50.3	-	-	-	-	-	-	-	-	-	-	98	
105	68.3	-	-	59.3	-	-	49.3	-	-	39.6	-	-	-	-	-	-	-	105	
111	67.3	-	-	58.2	-	-	48.5	-	-	39.0	-	-	31.1	-	-	-	-	111	
118	66.1	-	-	57.3	-	-	47.6	-	-	38.1	-	-	30.4	-	-	24.6	-	118	
124	65.9	-	-	56.3	-	-	46.8	-	-	37.5	-	-	30.0	-	-	24.2	-	124	
131	65.2	-	-	55.5	-	-	45.8	-	-	36.6	-	-	29.3	-	-	23.8	-	131	
138	64.3	46.2	-	54.6	-	-	44.7	-	-	35.9	-	-	28.8	-	-	23.1	-	138	
144	63.7	46.2	-	54.0	-	-	44.3	-	-	35.1	-	-	28.2	-	-	22.7	-	144	
151	62.8	46.2	-	35.5	40.7	-	43.6	-	-	34.3	-	-	27.5	-	-	22.2	-	151	
157	62.2	46.2	-	52.9	40.7	-	43.2	35.2	-	33.7	-	-	27.1	-	-	21.6	-	157	
164	61.5	46.2	-	52.2	40.7	-	42.5	35.2	-	33.0	-	-	26.4	-	-	21.1	-	164	
177	59.5	46.2	-	50.9	40.7	-	41.6	35.2	-	31.9	28.6	-	25.3	23.1	-	20.2	-	177	
190	57.8	46.0	46.2	49.4	40.7	-	40.3	35.2	-	30.6	28.6	-	24.2	22.9	-	19.2	-	190	
203	48.7	45.0	46.2	47.6	40.5	40.7	39.0	35.2	-	29.5	28.6	-	22.9	22.7	-	18.3	-	203	
216	38.7	44.1	42.4	42.9	39.7	40.3	37.7	35.0	35.2	28.4	28.6	28.6	22.0	22.4	-	17.4	-	216	
229	-	43.2	38.7	34.8	38.8	36.7	36.2	34.6	35.2	27.3	28.4	28.0	21.2	22.2	23.1	16.5	-	229	
243	-	40.5	35.2	25.2	37.8	33.2	31.1	33.9	33.6	26.0	27.7	27.3	20.2	22.0	22.4	15.8	-	243	
256	-	-	32.3	-	35.9	30.4	24.2	33.2	30.6	25.3	26.8	26.6	19.3	21.3	21.8	15.2	-	256	
269	-	-	-	-	-	27.7	-	32.6	28.0	22.4	26.2	26.2	18.7	20.9	21.1	14.5	-	269	
282	-	-	-	-	-	-	-	28.4	25.8	16.1	25.3	25.3	18.0	20.2	20.7	13.8	-	282	
295	-	-	-	-	-	-	-	-	23.8	-	24.7	23.1	15.0	19.8	20.2	13.4	-	295	
308	-	-	-	-	-	-	-	-	-	-	-	21.4	-	19.2	19.8	13.0	-	308	
321	-	-	-	-	-	-	-	-	-	-	-	-	-	18.7	19.4	8.7	-	321	
334	-	-	-	-	-	-	-	-	-	-	-	-	-	-	18.3	-	-	334	

Remarks

* SSL 0°

** SSL 60°

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



360°

DIN/ISO

149.3 ft + 13.1 ft Main boom + adapter

Fly jib																			
Radius	98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			196.9 ft			Radius
	83°***	73°*	65°*	83°***	73°*	65°*	83°***	73°*	65°*	83°***	73°*	65°*	83°***	73°*	65°*	83°***	73°*	65°*	
ft	1,000 lb																		ft
52	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	52
59	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	59
65	146.6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	65
72	139.0	-	-	132.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72
79	130.8	-	-	124.3	-	-	118.7	-	-	-	-	-	-	-	-	-	-	-	79
85	123.7	-	-	118.2	-	-	112.7	-	-	104.9	-	-	93.8	-	-	-	-	-	85
92	116.7	-	-	112.3	-	-	106.8	-	-	100.2	-	-	90.3	-	-	76.0	-	-	92
98	110.6	98.3	-	107.2	-	-	102.8	-	-	96.1	-	-	87.2	-	-	75.0	-	-	98
105	103.6	94.7	-	101.4	-	-	98.0	-	-	91.4	-	-	84.8	-	-	73.8	-	-	105
111	97.5	91.7	-	96.3	78.2	-	94.0	-	-	88.4	-	-	81.8	-	-	72.8	-	-	111
118	-	88.2	-	90.4	77.1	-	89.3	65.9	-	84.9	-	-	79.4	-	-	71.6	-	-	118
124	-	84.2	-	85.4	76.1	-	85.3	65.7	-	81.9	57.3	-	76.4	-	-	70.6	-	-	124
131	-	79.5	76.1	79.5	73.9	-	80.6	65.2	-	78.3	57.3	-	73.9	-	-	68.4	-	-	131
138	-	74.8	73.7	-	71.5	-	76.9	64.9	-	74.8	57.3	-	71.5	50.7	-	67.1	-	-	138
144	-	-	70.7	-	68.5	69.5	71.9	63.7	-	71.8	57.3	-	68.5	50.7	-	65.7	39.9	-	144
151	-	-	67.2	-	65.2	67.2	67.1	62.3	-	68.3	57.3	-	66.1	50.7	-	63.9	39.9	-	151
157	-	-	64.9	-	62.1	64.7	-	60.1	62.9	65.0	56.5	-	63.8	50.7	-	62.0	39.9	-	157
164	-	-	-	-	-	61.9	-	57.3	60.6	61.3	55.3	-	61.0	50.7	-	59.9	39.9	-	164
177	-	-	-	-	-	56.2	-	52.5	56.0	-	50.7	53.1	55.6	49.1	50.5	55.1	39.9	-	177
190	-	-	-	-	-	-	-	-	51.2	-	45.9	48.3	43.9	45.7	47.4	50.5	39.2	39.9	190
203	-	-	-	-	-	-	-	-	-	-	-	44.4	-	42.2	44.4	45.5	37.5	39.4	203
216	-	-	-	-	-	-	-	-	-	-	-	40.5	-	38.5	40.7	-	35.9	38.8	216
229	-	-	-	-	-	-	-	-	-	-	-	-	-	-	37.4	-	34.2	36.9	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	33.9	243
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	31.2	256

	216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			
ft							1,000 lb												ft
85	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	85	
92	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	92	
98	63.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	98	
105	62.6	-	-	52.9	-	-	-	-	-	-	-	-	-	-	-	-	-	105	
111	62.4	-	-	52.7	-	-	43.2	-	-	-	-	-	-	-	-	-	-	111	
118	61.9	-	-	52.2	-	-	42.9	-	-	35.0	-	-	27.5	-	-	-	-	118	
124	61.5	-	-	52.0	-	-	42.5	-	-	34.6	-	-	27.1	-	-	21.4	-	124	
131	60.8	-	-	51.8	-	-	42.3	-	-	34.1	-	-	26.9	-	-	21.1	-	131	
138	60.3	-	-	51.3	-	-	42.1	-	-	33.9	-	-	26.6	-	-	20.9	-	138	
144	59.3	-	-	51.1	-	-	41.8	-	-	33.5	-	-	26.4	-	-	20.7	-	144	
151	58.4	32.4	-	50.7	-	-	41.4	-	-	33.0	-	-	26.2	-	-	20.5	-	151	
157	57.4	32.4	-	50.2	-	-	41.2	-	-	32.6	-	-	26.0	-	-	20.5	-	157	
164	56.4	32.4	-	49.8	25.3	-	40.7	-	-	32.1	-	-	25.7	-	-	20.2	-	164	
177	53.8	32.4	-	48.9	25.3	-	40.1	20.5	-	31.3	14.3	-	24.9	-	-	19.8	-	177	
190	49.6	32.4	-	47.2	25.3	-	39.2	20.5	-	30.2	14.3	-	24.0	9.9	-	19.1	-	190	
203	45.5	32.1	32.4	43.7	25.3	-	38.3	20.5	-	29.3	14.3	-	22.9	9.9	-	18.3	-	203	
216	40.9	31.7	32.4	40.2	25.3	25.3	36.8	20.5	-	28.2	14.3	-	22.0	9.9	-	17.4	-	216	
229	29.9	31.3	32.4	36.5	25.3	25.3	35.3	20.5	19.8	27.3	14.3	-	21.2	9.9	-	16.5	-	229	
243	-	30.8	31.2	27.4	25.3	25.3	32.5	20.5	19.8	26.2	14.3	14.3	20.2	9.9	-	15.8	-	243	
256	-	30.1	28.8	-	25.3	24.9	25.5	20.5	19.8	25.3	14.3	14.3	19.6	9.9	9.9	15.2	-	256	
269	-	-	26.4	-	25.3	24.4	17.6	20.5	19.8	23.3	14.3	14.3	18.7	9.9	9.9	14.5	-	269	
282	-	-	-	-	-	22.2	-	20.5	19.8	17.2	14.3	14.3	18.0	9.9	9.9	13.8	-	282	
295	-	-	-	-	-	20.5	-	20.5	19.8	-	14.3	14.3	15.7	9.9	9.9	13.4	-	295	
308	-	-	-	-	-	-	-	-	18.9	-	14.3	14.3	10.1	9.9	9.9	13.0	-	308	
321	-	-	-	-	-	-	-	-	-	-	-	14.3	-	9.9	9.9	9.2	-	321	
334	-	-	-	-	-	-	-	-	-	-	-	14.3	-	-	9.9	-	-	334	
348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9.9	-	-	348	

Remarks

* SSL 0°

** SSL 60°

Counterweight 132,300 lb 176,400 lb 220,500 lb 264,600 lb 308,700 lb 352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request

Lifting capacities luffing fly jib with SSL, main boom 83°–65°

360°

DIN/ISO

182.1 ft + 13.1 ft Main boom + adapter

Fly jib																			
98.4 ft			118.1 ft			137.8 ft			157.5 ft			177.2 ft			196.9 ft				
Radius	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	83°**	73°*	65°*	Radius
ft	1,000 lb																		ft
72	87.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	72
79	81.3	-	-	76.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	79
85	77.3	-	-	72.9	-	-	69.6	-	-	-	-	-	-	-	-	-	-	-	85
92	73.7	-	-	68.2	-	-	66.0	-	-	62.0	-	-	-	-	-	-	-	-	92
98	69.7	-	-	66.0	-	-	63.0	-	-	59.0	-	-	53.2	-	-	48.3	-	-	98
105	67.2	-	-	63.2	-	-	60.1	-	-	55.7	-	-	50.9	-	-	46.7	-	-	105
111	65.8	53.8	-	60.8	-	-	57.5	-	-	52.9	-	-	48.7	-	-	45.1	-	-	111
118	-	53.1	-	59.1	41.8	-	55.1	-	-	50.7	-	-	46.5	-	-	43.2	-	-	118
124	-	52.5	-	57.6	41.8	-	52.9	-	-	49.1	-	-	44.5	-	-	41.6	-	-	124
131	-	50.9	-	56.4	41.8	-	51.4	34.6	-	47.0	-	-	42.8	-	-	39.9	-	-	131
138	-	49.0	-	-	41.8	-	50.0	34.6	-	44.9	30.8	-	41.1	-	-	38.5	-	-	138
144	-	47.0	-	-	41.2	-	49.0	34.6	-	43.9	30.4	-	39.7	-	-	37.3	-	-	144
151	-	-	44.9	-	40.5	-	47.6	34.6	-	42.9	30.1	-	38.1	25.3	-	35.9	-	-	151
157	-	-	43.3	-	39.3	-	-	34.2	-	41.9	29.7	-	37.3	25.3	-	34.7	19.4	-	157
164	-	-	41.2	-	38.1	38.3	-	33.7	-	41.0	29.5	-	36.3	25.3	-	33.5	19.4	-	164
177	-	-	-	-	-	35.5	-	32.4	32.6	-	28.6	-	34.8	25.3	-	31.7	19.4	-	177
190	-	-	-	-	-	32.6	-	-	30.9	-	27.5	27.8	33.5	24.9	-	30.0	19.4	-	190
203	-	-	-	-	-	-	-	-	28.7	-	26.2	26.2	-	24.0	24.0	28.4	19.4	-	203
216	-	-	-	-	-	-	-	-	-	-	-	24.5	-	23.1	22.5	-	19.4	19.4	216
229	-	-	-	-	-	-	-	-	-	-	-	22.5	-	-	21.0	-	19.4	19.4	229
243	-	-	-	-	-	-	-	-	-	-	-	-	-	-	19.3	-	19.4	18.7	243
256	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	17.4	256
269	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	16.0	269

216.5 ft			236.2 ft			255.9 ft			275.6 ft			295.3 ft			315.0 ft			
ft							1,000 lb									ft		
98	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	98	
105	41.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	105	
111	40.0	-	-	35.1	-	-	-	-	-	-	-	-	-	-	-	-	111	
118	38.3	-	-	33.9	-	-	30.2	-	-	-	-	-	-	-	-	-	118	
124	37.1	-	-	32.7	-	-	29.4	-	-	24.0	-	-	-	-	-	-	124	
131	35.5	-	-	31.5	-	-	28.4	-	-	23.6	-	-	17.8	-	-	-	131	
138	34.1	-	-	30.3	-	-	27.3	-	-	22.9	-	-	17.8	-	-	-	138	
144	33.1	-	-	29.1	-	-	26.5	-	-	22.5	-	-	17.6	-	-	-	144	
151	31.9	-	-	27.9	-	-	25.5	-	-	22.0	-	-	17.4	-	-	-	151	
157	31.1	-	-	27.3	-	-	24.7	-	-	21.6	-	-	17.4	-	-	-	157	
164	29.9	14.3	-	26.4	-	-	24.0	-	-	20.9	-	-	17.1	-	-	-	164	
177	28.2	14.3	-	25.1	11.0	-	22.7	-	-	20.2	-	-	16.9	-	-	-	177	
190	26.9	14.3	-	23.6	11.0	-	21.4	7.2	-	19.4	-	-	16.5	-	-	-	190	
203	25.6	14.3	-	22.5	11.0	-	20.3	7.2	-	18.5	-	-	16.1	-	-	-	203	
216	24.5	14.3	14.3	21.4	11.0	-	19.4	7.2	-	17.8	-	-	15.4	-	-	-	216	
229	23.0	14.3	13.9	20.3	11.0	8.8	18.3	7.2	-	17.0	-	-	15.0	-	-	-	229	
243	-	14.3	13.4	19.1	11.0	8.8	17.4	7.2	7.2	16.0	-	-	14.3	-	-	-	243	
256	-	14.3	13.0	-	11.0	8.8	16.5	7.2	7.2	15.2	-	-	13.6	-	-	-	256	
269	-	-	12.3	-	11.0	8.8	15.6	7.2	7.2	14.5	-	-	12.7	-	-	-	269	
282	-	-	11.6	-	11.0	8.8	-	7.2	7.2	13.6	-	-	12.1	-	-	-	282	
295	-	-	-	-	-	8.8	-	7.2	7.0	-	-	-	11.4	-	-	-	295	
308	-	-	-	-	-	8.8	-	-	6.8	-	-	-	10.8	-	-	-	308	
321	-	-	-	-	-	-	-	-	6.6	-	-	-	-	-	-	-	321	

Remarks

* SSL 0°

** SSL 60°

Counterweight

132,300 lb

176,400 lb

220,500 lb

264,600 lb

308,700 lb

352,800 lb

Max. capacities with minimum counterweight

Further counterweight configurations on request



Technical description

Carrier

Drive / steering	18 x 8 x 16.
Frame	Demag-built special main frame of high-strength fine-grain structural steel, with pot-shaped centre section to accommodate the outrigger beams.
Outriggers	4-point outrigger system, folding outrigger beams, fully hydraulic horizontal and vertical extension, providing 360° continuous rotation. Outrigger loading indicator.
Engine	Water-cooled 8-cylinder DaimlerChrysler diesel engine OM 502 LA, output 420 kW (571 hp) at 1800 1/min, torque 2700 Nm at 1100 1/min. Fuel tank capacity: 171.700 gallons.
Transmission	Allison type CLBT 755 with electronic transmission control (ATEC), torque converter and hydraulic retarder. Dual-range transfer case with differential lockout control.
Axles	3 + 4, 8 + 9 driving, 1-5 and 7-9 steering, all axles hydropneumatically suspended and hydraulically blockable.
Wheels and tyres	18 wheels, 14.00-R 25.
Steering	Dual-circuit semiblock mechanical steering with hydraulic booster.
Brakes	In conformity with EC-directives. Sustained action brake: constant decompression valve, exhaust brake, hydr. retarder integrated into gearbox.
Electrical equipment	24 V system, lighting in compliance with German StVZO.
Driver's cab	Rubber-mounted low-line steel cab, ergonomic design, with pneumatically suspended driver's seat and one passenger's seat; vertically adjustable steering wheel; heated outside mirrors, right-hand mirror electrically adjustable; dashboard with clearly arranged instrumentation and carrier controls.

Superstructure

Engine	Water-cooled 6-cylinder DaimlerChrysler diesel engine OM 906 LA, output: 205 kW (279 hp) at 2300 1/min, torque 1100 Nm at 1300 1/min. Fuel tank capacity: 79.300 gallons.
Hydraulic system	Powered via five hydraulic circuits, three main pumps for independent control movements, one pump for auxiliary circuits, one control pump for the servo control.
Hoist I	Axial-piston variable displacement motor, hoist drum with integrated planetary gear reducer, and brake.
Slew unit	Axial piston motor with planetary gearing, foot-operated brake, and spring-applied holding brake.
Boom elevation	Two differential cylinders with pilot-controlled lowering brake valves.
Control	Electrical pilot-control by two self-centering servo levers.
Crane cab	Spacious all-steel comfortable cab (tiltable) with sliding door and large hinged windscreen, roof window with armoured glass, full instrumentation and crane controls, comfortable seat with ergonomic armrest mounted joystick controls, working light. Self-contained hot water heater with timer and 'Heizmatic' for sensitive heat flow control. Intermittent control window wiper and washer, air-conditioning.
Main boom	Boom base and four telescopic sections fabricated from fine grain structural steel, telescoping with partial load. Buckling-resistant Demag ovaloid design with diagonally arranged self-centering slider shoes.
Counterweight	220,500 lb, divisible.
Safety devices	Electronic safe load indicator with large graphic display and sealed touch-type keyboard, digital read-out for hook load, nominal load, boom length, angle, and radius. Analog display to indicate the capacity utilization, and monitoring code to assist in trouble shooting. Integrated guide system for boom telescoping, display for load charts, display and calculation of outrigger loadings. Other features include: limit switches on hoist and lowering motions, pressure relief and safety holding valves, hoist rotation indicator and anemometer.

Optional equipment

Superlift attachment	This attachment used to increase the crane's load moment consists of both the boom suspension system folding out, as required, at 0°, 30° or 60°. The boom suspension system provides for an automatic rope length adjustment for boom telescoping, and is lowered to the main boom when not needed (axle loads to be observed).
Main boom extension	Lattice extension consisting of components of the 315.0 ft luffing jib, 19.7 – 118.1 ft long, 0°, 20° and 40° offset.
Fixed jib	Fixed lattice jib, comprising of parts of the luffing jib, 65.6 – 164.0 ft long (LF-system).
Luffing jib	78.7 – 315.0 ft, plus 13.1 ft adapter, with two luffing masts, pendant bars, electrical equipment, safety devices (hoist II is required when using the luffing jib).
Additional counterweight	132,300 lb, integrated into the standard counterweight, installed by the crane itself.
Additional jack leg	For special duties with 50.9 ft main boom.
Hoist II	Axial piston variable displacement motor, hoist drum with integrated planetary reduction, spring-applied multi-disk brake, hoist rope.
Independent rear axle steering	



Overview of standard duty charts

 40.0 x 39.4 ft

Main boom

Main boom	0 klb 360°	88.2 klb 360°	132.3 klb 360°	176.4 klb 360°	220.5 klb 360°	264.6 klb 360°	308.7 klb 360°	352.8 klb 360°
50.9 ft	x	x	x	x	x	x	x	x
67.3 ft	x	x	x	x	x	x	x	x
83.7 ft	x	x	x	x	x	x	x	x
100.0 ft	x	x	x	x	x	x	x	-
116.5 ft	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL
132.9 ft	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL
149.3 ft	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL
165.7 ft	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL
182.1 ft	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL
196.9 ft	x	x	x	x	x/+SSL	x/+SSL	x/+SSL	+SSL

 29.6 x 27.7 ft

Main boom	0 klb 360°	88.2 klb 360°	132.3 klb 360°	176.4 klb 360°	220.5 klb 360°	264.6 klb 360°	308.7 klb 360°	352.8 klb 360°
50.9 ft	x	x	x	x	x	-	-	-
67.3 ft	x	x	x	x	x	-	-	-
83.7 ft	x	x	x	x	x	-	-	-
100.0 ft	x	x	x	x	x	-	-	-
116.5 ft	x	x	x	x	x	-	-	-
132.9 ft	x	x	x	x	x	-	-	-
149.3 ft	x	x	x	x	x	-	-	-
165.7 ft	-	x	x	x	x	-	-	-
182.1 ft	-	x	x	x	x	-	-	-
196.9 ft	-	x	x	x	x	-	-	-

 40.0 x 39.4 ft

Lattice extension

Main boom	Extension	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
196.9 ft	19.7 ft - 0°	SSL 0°	x	x	x	x/+SSL	+SSL	+SSL
	39.3 ft - 0°	SSL 0°	x	x	x	x/+SSL	+SSL	+SSL
	59.0 ft - 0°	SSL 0°	x	x	x	x/+SSL	+SSL	+SSL
	78.7 ft - 0°	SSL 30°	x	x	x	x/+SSL	+SSL	+SSL
	98.4 ft - 0°	SSL 30°	x	x	x	x/+SSL	+SSL	+SSL
	118.1 ft - 0°	SSL 30°	x	x	x	x/+SSL	+SSL	+SSL
	39.3 ft - 20°	SSL 0°	x	x	x	x/+SSL	+SSL	+SSL
	59.0 ft - 20°	SSL 0°	x	x	x	x/+SSL	+SSL	+SSL
	78.7 ft - 20°		x	x	x	-	-	-
	98.4 ft - 20°		x	x	x	-	-	-
	118.1 ft - 20°		x	x	x	-	-	-
	39.3 ft - 40°	SSL 0°	x	x	x	+SSL	+SSL	-
	59.0 ft - 40°	SSL 0°	x	x	x	+SSL	+SSL	-
	78.7 ft - 40°		x	x	x	-	-	-
	98.4 ft - 40°		x	x	x	-	-	-
	118.1 ft - 40°		x	x	x	-	-	-

* SSL 0° + 30°

 29.6 x 27.7 ft

Main boom	Extension	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
196.9 ft	19.7 ft - 0°	x	x	x	x	-	-	-
	39.3 ft - 0°/20°	x	x	x	x	-	-	-
	59.0 ft - 0°/20°	x	x	x	x	-	-	-
	78.7 ft - 0°/20°	x	x	x	x	-	-	-
	98.4 ft - 0°/20°	x	x	x	x	-	-	-
	118.1 ft - 0°/20°	x	x	x	x	-	-	-
	39.3 ft - 40°	x	x	x	x	-	-	-
	59.0 ft - 40°	x	x	x	x	-	-	-
	78.7 ft - 40°	x	x	x	x	-	-	-
	98.4 ft - 40°	x	x	x	x	-	-	-

 40.0 x 39.4 ft

Fixed fly jib

Main boom	Jib	0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
165.7 ft	65.6 ft - 0°			x	x	x	x		
	65.6 ft - 20°			-	-	-	-		
	65.6 ft - 40°			-	-	-	-		
	85.3 ft - 0°			x	x	x	x		
	85.3 ft - 20°			x	x	x	x		
	85.3 ft - 40°			x	x	x	-		
	105.0 ft - 0°			x	x	x	x		
	105.0 ft - 20°			x	x	x	x		
	105.0 ft - 40°			x	x	x	-		
	124.7 ft - 0°			x	x	x	x		
	124.7 ft - 20°			x	x	x	x		
	124.7 ft - 40°			x	x	x	-		
	144.4 ft - 0°			x	x	x	x		
	144.4 ft - 20°			x	x	x	x		
	144.4 ft - 40°			x	x	x	-		
	164.0 ft - 0°			x	x	x	x		
	164.0 ft - 20°			x	x	x	x		
	164.0 ft - 40°			x	x	x	-		

Jib	Main boom							
	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb	220.5/264.6	308.7/352.8 klb
65.6 ft - 0°	x	x	x/+SSL	x/+SSL	+SSL	+SSL	+ SSL	
65.6 ft - 20°	-	-	-	-	-	-	-	
65.6 ft - 40°	-	-	-	-	-	-	-	
85.3 ft - 0°	x	x	x/+SSL	x/+SSL	+SSL	+SSL	+ SSL	
85.3 ft - 20°	x	x	x/+SSL	x/+SSL	+SSL	-	-	
85.3 ft - 40°	x	x	x/+SSL	+SSL	-	-	-	
105.0 ft - 0°	x	x	x/+SSL	x/+SSL	+SSL	+SSL	+ SSL	
105.0 ft - 20°	x	x	x/+SSL	x/+SSL	+SSL	-	-	
105.0 ft - 40°	x	x	x/+SSL	+SSL	-	-	-	
124.7 ft - 0°	x	x	x/+SSL	x/+SSL	+SSL	+SSL	+ SSL	
124.7 ft - 20°	x	x	x/+SSL	x/+SSL	+SSL	-	-	
124.7 ft - 40°	x	x	x/+SSL	+SSL	-	-	-	
144.4 ft - 0°	x	x	x/+SSL	x/+SSL	+SSL	+SSL	+ SSL	
144.4 ft - 20°	x	x	x/+SSL	x/+SSL	+SSL	-	-	
144.4 ft - 40°	x	x	x/+SSL	+SSL	-	-	-	
164.0 ft - 0°	x	x	x/+SSL	x/+SSL	+SSL	+SSL	+ SSL	
164.0 ft - 20°	x	x	x/+SSL	x/+SSL	+SSL	-	-	
164.0 ft - 40°	x	x	x/+SSL	+SSL	-	-	-	

 29.6 x 27.7 ft

Luffing fly jib

Main boom	Jib	0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
50.9 ft + 13.1 ft* 67.3 ft + 13.1 ft* 83.7 ft + 13.1 ft* 100.0 ft + 13.1 ft* 116.5 ft + 13.1 ft* 132.9 ft + 13.1 ft*	78.7 ft	-	-	x	x	x	-	-	-
	98.4 ft	-	-	x	x	x	-	-	-
	118.1 ft	-	-	x	x	x	-	-	-
	137.8 ft	-	-	x	x	x	-	-	-
	157.5 ft	-	-	x	x	x	-	-	-
	177.2 ft	-	-	x	x	x	-	-	-
	196.9 ft	-	-	x	x	x	-	-	-
	216.5 ft	-	-	x	x	x	-	-	-
	236.2 ft	-	-	x	x	x	-	-	-
	255.9 ft	-	-	-	x	x	-	-	-
	275.6 ft	-	-	-	x	x	-	-	-
	295.3 ft	-	-	-	x	x	-	-	-

* adapter

Main boom	Jib	0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
165.7 ft + 13.1 ft* 182.1 ft + 13.1 ft*	78.7 ft	-	-	x	x	x	-	-	-
	98.4 ft	-	-	x	x	x	-	-	-
	118.1 ft	-	-	x	x	x	-	-	-
	137.8 ft	-	-	x	x	x	-	-	-
	157.5 ft	-	-	x	x	x	-	-	-
	177.2 ft	-	-	x	x	x	-	-	-
	196.9 ft	-	-	x	x	x	-	-	-
	216.5 ft	-	-	x	x	x	-	-	-
	236.2 ft	-	-	x	x	x	-	-	-
	255.9 ft	-	-	-	x	x	-	-	-
	275.6 ft	-	-	-	x	x	-	-	-
	295.3 ft	-	-	-	-	-	-	-	-

 40.0 x 39.4 ft

Luffing fly jib

Main boom	Jib								
		0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
50.9 ft + 13.1 ft* 67.3 ft + 13.1 ft* 83.7 ft + 13.1 ft* 100.0 ft + 13.1 ft*	78.7 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	98.4 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	118.1 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	137.8 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	157.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	177.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	196.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	216.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	236.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	255.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x
	275.6 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	x/x/x

Main boom	Jib								
		0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
165.7 ft + 13.1 ft*	78.7 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	98.4 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	118.1 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	137.8 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	157.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	177.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	196.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	216.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	236.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	255.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	275.6 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-

Main boom	Jib								
		0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
132.9 ft + 13.1 ft*	78.7 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	98.4 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	118.1 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	137.8 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	157.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	177.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	196.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	216.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	236.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	255.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-
	275.6 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	x/x/x	-

Main boom	Jib								
		0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
182.1 ft + 13.1 ft*	78.7 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	98.4 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	118.1 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	137.8 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	157.5 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	177.2 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	196.9 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	216.5 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	236.2 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	255.9 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-
	275.6 ft	-	-	x/-/-	x/-/-	x/x/x	-	-	-

Main boom	Jib								
		0 klb	88.2 klb	132.3 klb	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
149.3 ft + 13.1 ft*	78.7 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	98.4 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	118.1 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	137.8 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	157.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	177.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	196.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	216.5 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	236.2 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	255.9 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-
	275.6 ft	-	-	x/-/-	x/-/-	x/x/x	x/x/x	-	-

 40.0 x 39.4 ft

Luffing fly jib + SSL

Jib	Main boom / SSL 0°							
	116.5 ft + 13.1 ft* / 149.3 ft + 13.1 ft*				182.1 ft + 13.1 ft*			
	220.5 klb	264.6 klb	308.7 klb	352.8 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb
	83°		83°/73°/65°		83°		83°/73°/65°	
98.4 ft	x	x	x	x	x	x	x	x
118.1 ft	x	x	x	x	x	x	x	x
137.8 ft	x	x	x	x	x	x	x	x
157.5 ft	x	x	x	x	x	x	x	x
177.2 ft	x	x	x	x	x	x	x	x
196.9 ft	x	x	x	x	x	x	x	x
216.5 ft	x	x	x	x	x	x	x	x
236.2 ft	x	x	x	x	x	x	x	x
255.9 ft	x	x	x	x	x	x	x	x
275.6 ft	x	x	x	x	-	-	-	-
295.3 ft	x	x	x	x	-	-	-	-
315.0 ft	-	-	-	-	-	-	-	-

* adapter

Jib	Main boom / SSL 60°							
	116.5 ft + 13.1 ft* / 132.9 ft + 13.1 ft* / 149.3 ft + 13.1 ft*				165.7 ft + 13.1 ft* / 182.1 ft + 13.1 ft*			
	176.4 klb	220.5 klb	264.6 klb	308.7 klb	352.8 klb	176.4 klb	220.5 klb	264.6 klb
	83°		83°		83°		83°	
98.4 ft	x	x	x	x	x	x	x	x
118.1 ft	x	x	x	x	x	x	x	x
137.8 ft	x	x	x	x	x	x	x	x
157.5 ft	x	x	x	x	x	x	x	x
177.2 ft	x	x	x	x	x	x	x	x
196.9 ft	x	x	x	x	x	x	x	x
216.5 ft	x	x	x	x	x	x	x	x
236.2 ft	x	x	x	x	x	x	x	x
255.9 ft	x	x	x	x	x	x	x	x
275.6 ft	x	x	x	x	x	x	x	x
295.3 ft	x	x	x	x	x	x	x	x
315.0 ft	x	x	x	x	x	-	-	-



Key






Counterweight



Lifting capacities on outriggers 360°

„D“



SSL: Sideways Superlift



This image shows a full page of white paper with horizontal ruling lines. The lines are evenly spaced and extend across the width of the page. There is a dark red or maroon header bar at the top edge. The overall appearance is that of a clean, unused sheet of stationery.



The information contained in this brochure merely consists of general descriptions and a broad compilation of performance features which might not apply precisely as described under specific application conditions or which may change as a result of further product development.
The desired performance features only become binding once expressly agreed in the final contract.

Subject to change without notice. · Machine operation is subject to computer charts only.

03/03

Demag Mobile Cranes Inc.

9871 Highway 78 · Ladson, SC 29456

Telephone: 843-572-9311

Telefax: 843-824-0793