







VG//G	
OUT REACH (mm)	CAPACITY (kg)
3.000	7.500
5.000	4.000
7.000	3.000





## **TECHNICAL DATA**

CRANE FRAME: Six-wheel frame fabricated from preformed and welded steel plate with built-in counterweight.

**TRACTION**: by DC 20 kw 96V reversible electric motor, controlled by chopper.

Boom movements: 20 kW - 96 V service motor pump

**BATTERY**: 96V 1036Ah battery, battery meter on dashboard.

**BRAKES:** foot hydraulically operated brakes (disc on front, drums on rear wheels). Parking hand brake mechanically operated.

**SUSPENSION:** oscillating rear axle with mechanical lock.

**STEERING:** power steering operated through own hydraulic circuit by a hydraulic cylinder fitted between the articulated power unit and the crane frame allowing steering fitted with safety valves and filters. 6 kW – 96 V motor driven pump.

WHEELS: Nr. 2 rear superelastic 3.55/65-15" - Nr. 4 front superelastic 3.55/65-15"

**BOOM**: boom fabricated from preformed and welded quality steel plate. Nr.4 telescoping sections: 1 fixed; 3 hydraulically telescoping. Fitted with nylon wear pads adjustable wear pads on the sides.

**BOOM CONTROL:** Distributor by proportional levers. Motor driven pump 20kW

LMI: Electronic Load Moment Indicator. Display showing lifted load, max allowed load, tilting percentage, operating radius, angle, telescope and light indicators on the operative mode.

TOTAL WEIGHT: approx. kg. 20.000 **MAX. CAPACITY**: kg. 18.000

Options on request: hydraulic winch; chain hoists; carry-deck; battery charger (on board and stand-alone); manual and hydraulic jibs; cable remote control; radio remote control; working light; fire extinguisher.




R4480







- The crane applies to the following std.:
- -2006/42/CE
- -UNIEN13000
- -I.S.P.E.S.L.





Valla – division of CVS Ferrari Srl

Via Piacenza, 45 - 29010 Calendasco - Piacenza - ITALIA Tel. 0039 0523 762025 - 762004 - Fax 0039 0523 760531

Internet: www.valla.com - email: info@valla.com