



Electric battery operated Mobile Crane Max. Capacity Lbs. 19,800





OUTREACH (Ft) (Lbs.) 6 13,000 9 9,000 15 5,000

Valla 90 E



TECHNICAL DATA

CRANE FRAME: six-wheelers frame fabricated from preformed and welded steel plate with built-in counterweight.

DRIVE: by AC 14 kw 48V reversible electric motor, controlled by inverter, electro magnetic control on disk brake.

BATTERY: 48V-700Ah battery, battery meter on dashboard.

BRAKES: foot hydraulically operated drum brakes. Parking hand brake mechanically operated.

SUSPENSION: oscillating rear axle with mechanical lock.

STEERING: power steering with hydraulic cylinder and 140° articulation. Safety valves and filter.

WHEELS: nr. 2 rear superelastic 23 x 10-12 - nr. 4 front superelastic 23 x 10-12

BOOM: boom fabricated from preformed and welded quality steel plate. Nr.4 telescoping sections: 1 fixed; 3 hydraulically telescoping. Fitted with nylon wear pads adjustable wear pads on the sides.

BOOM CONTROL: distributor by proportional levers. Motor driven pump 5kW 48V.


LMI: electronic Load Moment Indicator. Display showing lifted load, max allowed load, tilting percentage, operating radius, angle, telescope and light indicators on the operative mode.


TOTAL WEIGHT: approx. Lbs. 20,200 MAX. CAPACITY: Lbs. 19,800


Options on request: hydraulic winch; chain hoists; carry-deck; battery charger (on board and stand-alone); manual and hydraulic jibs; cable remote control; radio remote control; non marking tires; man bucket and relevant certification as aerial platform; full set of road lights.

SINCE 1945 LEADER IN PICK & CARRY

- VALLA mobile crane mod. 90E complies with the following standards:
- -2006/42/CE
- -UNIEN13000 -I.S.P.E.S.L.







Lbs./ft



Valla a division of CVS Ferrari Srl Via Piacenza, 45 - 29010 Calendasco (Piacenza) - ITALIA Tel. +39 0523 762025 / 752004 - Fax +39 0523 760531 e-mail: info@valla.com - www.valla.com