

**25/35 Versa-Lift with 0 Counterweight Slabs**Slab Weight (lbs)**1900**Number of Slabs**0**Standard Wheel Base (in)**76**

Lift Capacities w/Forks Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Fork Face (in)	24	16300	18900	21400	24000
	36	13000	15100	17100	19200
	48	10800	12500	14200	16000
	60	9300	10700	12200	13700
	72	8100	9400	10700	11900
	84	7200	8300	9500	10600

Lift Capacities w/Boom Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	12	15500	18100	20700	23200
	24	12400	14400	16500	18500
	36	10300	12000	13700	15400
	48	8800	10300	11800	13200
	60	7700	9000	10300	11600
	72	6900	8000	9100	10300
	84	6200	7200	8200	9200
	96	5600	6500	7500	8400

Lift Capacities w/Forks & Boom (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	24	11400	13500	15500	17600
	36	9500	11200	12900	14600
	48	8100	9600	11100	12500
	60	7100	8400	9700	11000
	72	6300	7500	8600	9700
	84	5700	6700	7700	8800
	96	5200	6100	7000	8000

***All Load Capacities are rated with the mast vertical.

**25/35 Versa-Lift with 1 Counterweight Slabs**Slab Weight (lbs)**1900**Number of Slabs**1**Standard Wheel Base (in)**76**

Lift Capacities w/Forks Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Fork Face (in)	24	19000	22000	25000	28000
	36	15100	17500	19900	22300
	48	12600	14600	16600	18600
	60	10800	12500	14200	15900
	72	9400	10900	12400	13900
	84	8400	9700	11000	12400

Lift Capacities w/Boom Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	12	18200	21200	24200	27200
	24	14500	16900	19300	21700
	36	12100	14100	16100	18100
	48	10300	12000	13800	15500
	60	9000	10500	12000	13500
	72	8000	9400	10700	12000
	84	7200	8400	9600	10800
	96	6600	7700	8700	9800

Lift Capacities w/Forks & Boom (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	24	13600	15900	18300	20700
	36	11300	13300	15300	17200
	48	9700	11400	13100	14800
	60	8400	9900	11400	12900
	72	7500	8800	10100	11500
	84	6700	7900	9100	10300
	96	6100	7200	8300	9400

***All Load Capacities are rated with the mast vertical.

**25/35 Versa-Lift with 2 Counterweight Slabs**Slab Weight (lbs)**1900**Number of Slabs**2**Standard Wheel Base (in)**76**

Lift Capacities w/Forks Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Fork Face (in)	24	21600	25100	28500	31900
	36	17300	20000	22700	25500
	48	14400	16600	18900	21200
	60	12300	14300	16200	18100
	72	10800	12500	14200	15900
	84	9600	11100	12600	14100

Lift Capacities w/Boom Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	12	20900	24300	27700	31100
	24	16700	19400	22100	24800
	36	13900	16100	18400	20700
	48	11900	13800	15800	17700
	60	10400	12100	13800	15500
	72	9200	10700	12200	13700
	84	8300	9700	11000	12400
	96	7500	8800	10000	11200

Lift Capacities w/Forks & Boom (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	24	15700	18400	21100	23900
	36	13100	15300	17600	19900
	48	11200	13100	15100	17000
	60	9800	11500	13200	14900
	72	8700	10200	11700	13200
	84	7800	9200	10500	11900
	96	7100	8300	9600	10800

***All Load Capacities are rated with the mast vertical.

**25/35 Versa-Lift with 3 Counterweight Slabs**Slab Weight (lbs)**1900**Number of Slabs**3**Standard Wheel Base (in)**76**

Lift Capacities w/Forks Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Fork Face (in)	24	24300	28200	32000	35800
	36	19400	22500	25500	28600
	48	16200	18700	21300	23800
	60	13800	16000	18200	20400
	72	12100	14000	15900	17800
	84	10700	12400	14100	15800

Lift Capacities w/Boom Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	12	23500	27400	31200	35100
	24	18800	21900	24900	28000
	36	15600	18200	20700	23300
	48	13400	15600	17800	19900
	60	11700	13600	15500	17400
	72	10400	12100	13800	15500
	84	9400	10900	12400	13900
	96	8500	9900	11300	12700

Lift Capacities w/Forks & Boom (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	24	17800	20900	24000	27000
	36	14800	17400	19900	22500
	48	12700	14900	17100	19300
	60	11100	13000	14900	16800
	72	9900	11600	13300	15000
	84	8900	10400	11900	13500
	96	8100	9500	10800	12200

***All Load Capacities are rated with the mast vertical.