



## **Model 58XRB**

### **Hi-Performance Multi-Purpose Lift**



**TOTAL HYDRAULIC  
JOYSTICK BASKET CONTROLS  
PROPORTIONAL BASE CONTROLS  
5000# LIFT WINCH  
400# JIB WINCH  
ROTATING BASKET  
POWER LEVELED BASKET**



### **Standard Features:**

Power Leveling and Rotating 2 man aluminum 24" X 60" basket

All functions pressure relieved for a balanced system

Joystick proportional controls in basket

Hydraulic powered self-leveling basket

Remote engine throttle, and engine start and stop from the base and basket

Tandem Hydraulic cylinders for extension (no cables)

All hydraulic for smooth three function control at the same time

Rotation motor direct coupled to gearbox

PTO powered hydraulic pump with electric shift on.

All operations can run at the same time

Power retract by tandem hydraulic cylinders

360 degree working radius

Heavy Duty lift capacity

All Hydraulic powered extension and retraction

Quick connect load line to convert from service to crane lifting

Rotation drive with adjustment collar for exacting mesh to bull gear

Single stage elevation cylinder, double acting

5000 lb. rated load line

### **Options:**

110 Volt in basket

Welding leads in basket

Auxiliary hydraulic jib winch in the basket 400 Lbs. rated

Air or power washer leads in basket

### **Minimum Truck Specifications:**

10,000 Lb. Front Axle, 17,000 Rear Axle

25,950 G.V.W.:120" CA: 194"WB

Truck Frame - 2,000,000 RBM

Front and Rear outrigger stabilizers required

*NON INSULATED - ELECTROCUTION HAZARD*

*STATE & FEDERAL REGULATIONS REQUIRE CERTAIN CLEARANCES OF ELECTRICAL POWER LINES.*