



Model 65XRB

**Hi-Performance Multi-Purpose Lift
65' Work Reach with 55' Hook Reach**



**TOTAL HYDRAULIC
JOYSTICK BASKET CONTROLS
PROPORTIONAL BASE CONTROLS
5000# LIFT WINCH
400# JIB WINCH
ROTATING BASKET
POWER LEVELED BASKET**



Standard Features:

- Power Leveling and Rating 2 man basket
- All functions pressure relieved for a balanced system.
- Joystick proportional controls in basket
- Hydraulic powered self-leveling basket
- Remote engine throttle, and engine start and stop from the base and basket
- Tandem Hydraulic cylinders for extension (no cables)
- All hydraulic for smooth three function control at the same time
- Rotation motor direct coupled to gearbox
- PTO powered hydraulic pump with electric shift on.
- All operations can run at the same time
- Power retract by tandem hydraulic cylinders
- 360 degree working radius
- Heavy Duty lift capacity
- All Hydraulic powered extension and retraction
- Quick connect load line to convert from service to crane lifting
- Rotation drive with adjustment collar for exacting mesh to bull gear
- Single stage elevation cylinder, double acting
- 5000 lb. rated load line

Options:

- 110 Volt in basket
- Welding leads in basket
- Auxiliary hydraulic jib winch in the basket 400 Lbs. rated
- Air or power washer leads in basket

Minimum Truck Specifications:

- 10,000 Lb. Front Axle, 17,000 Rear Axle
- 27,000 G.V.W.:138" CA: 206"WB
- Reinforced Truck Frame
- Front and Rear outrigger stabilizers required

NON INSULATED - ELECTROCUTION HAZARD

STATE & FEDERAL REGULATIONS REQUIRE CERTAIN CLEARANCES OF ELECTRICAL POWER LINES.